

Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that A/C system has been properly cleaned, and new accumulator / filter drier has been installed. Specs are for total system capacities. Always refer to under hood decal as the primary source for refrigerant and lubricant information.

Year	Model	Lubricant
CL		
03-01	All Eng. - 23.00 Oz. R-134a; 5.50 Oz. PAG-46	59007
99-97	All Eng. - 26.00 Oz. R-134a; 5.50 Oz. PAG-46	59007
INTEGRA		
01-94	All Eng. - 24.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
93-89	All Eng. - 34.00 Oz. R-12; 5.00 Oz. Mineral Oil	59000 ⁵⁹
88-86	All Eng. - 33.00 Oz. R-12; 5.00 Oz. Mineral Oil	59000 ⁵⁹
LEGEND		
95-94	All Eng. - 24.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
93	All Eng. - 24.00 Oz. R-134a; 6.50 Oz. PAG-46	59007
92-91	All Eng. - 27.00 Oz. R-12; 6.50 Oz. Mineral Oil	59000 ⁵⁹
90-89	All Eng. - 30.00 Oz. R-12; 6.50 Oz. Mineral Oil	59000 ⁵⁹
88-86	All Eng. - 33.00 Oz. R-12; 6.50 Oz. Mineral Oil	59000 ⁵⁹
MDX		
13	6 Cyl. 3.7 Eng. - 23.00 Oz. R-134a; 4.23-4.63 Oz. PAG-46	59007
12-10	6 Cyl. 3.7 Eng.; w/o Rear AC - 22.00 Oz. R-134a; 7.60 Oz. PAG-46	59007
	6 Cyl. 3.7 Eng.; w/ Rear AC - 22.00 Oz. R-134a; 8.60 Oz. PAG-46	59007
09-07	All Eng.; w/o Rear AC - 22.00 Oz. R-134a; 7.60 Oz. PAG-46	59007
	All Eng.; w/ Rear AC - 22.00 Oz. R-134a; 8.60 Oz. PAG-46	59007
06-02	All Eng. - 25.50 Oz. R-134a; 5.00 Oz. PAG-46	59007
01	All Eng. - 27.00 Oz. R-134a; 5.50 Oz. PAG-46	59007
NSX		
05-97	All Eng. - 30.00 Oz. R-134a; 5.50 Oz. PAG-46	59007
96-93	All Eng. - 30.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
92-91	All Eng. - 34.00 Oz. R-12; 5.00 Oz. Mineral Oil	59000 ⁵⁹
RDX		
12-09	4 Cyl. 2.3 Eng.; w/o Rear AC - 15.90 Oz. R-134a; 6.50 Oz. PAG-46	59007
	4 Cyl. 2.3 Eng.; w/ Rear AC - 17.60 Oz. R-134a; 6.50 Oz. PAG-46	59007
08-07	All Eng.; w/o Rear AC - 15.90 Oz. R-134a; 6.50 Oz. PAG-46	59007
	All Eng.; w/ Rear AC - 17.60 Oz. R-134a; 6.50 Oz. PAG-46	59007
RL		
12-10	6 Cyl. 3.7 Eng. - 15.80-17.60 Oz. R-134a; 8.00-8.50 Oz. PAG-46	59007
09-06	All Eng. - 17.50 Oz. R-134a; 7.00 Oz. PAG-46	59007
05	All Eng. - 19.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
04	All Eng. - 26.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
03-02	All Eng. - 25.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
01-96	All Eng. - 26.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
RSX		
06	All Eng. - 17.60-19.40 Oz. R-134a; 7.40-8.10 Oz. PAG-46	59007
05-02	All Eng. - 18.00 Oz. R-134a; 5.50 Oz. PAG-46	59007
SLX		
99-98	All Eng. - 21.00 Oz. R-134a; 5.00 Oz. PAG-46; w/ Denso Compressor	59007
	All Eng. - 21.00 Oz. R-134a; 5.00 Oz. PAG-46; w/ OE Harrison Compressor	59007
97-96	All Eng. - 28.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
TL		
13	6 Cyl. 3.5 Eng. - 20.00 Oz. R-134a; 2.37-2.77 Oz. PAG-46	59007
	6 Cyl. 3.7 Eng. - 20.00 Oz. R-134a; 2.37-2.77 Oz. PAG-46	59007
12-10	6 Cyl. 3.5 Eng. - 17.60-19.40 Oz. R-134a; 5.81 Oz. PAG-46	59007
	6 Cyl. 3.7 Eng. - 17.60-19.40 Oz. R-134a; 6.15 Oz. PAG-46	59007
09	All Eng. - 17.60-19.40 Oz. R-134a; 6.15 Oz. PAG-46	59007
08-04	All Eng. - 17.60-19.40 Oz. R-134a; 7.00 Oz. PAG-46	59007
03-99	All Eng. - 21.00-23.00 Oz. R-134a; 8.80-9.40 Oz. PAG-46	59007
98-95	All Eng. - 26.50 Oz. R-134a; 5.33 Oz. PAG-46	59007
TSX		
12-11	4 Cyl. 2.4 Eng. - 15.90-17.60 Oz. R-134a; 6.42-6.83 Oz. PAG-46	59007
	6 Cyl. 3.5 Eng. - 15.90-17.60 Oz. R-134a; 6.11 Oz. PAG-46	59007
10	4 Cyl. 2.4 Eng. - 15.90-17.60 Oz. R-134a; 6.42-6.83 Oz. PAG-46	59007
	6 Cyl. 3.5 Eng. - 15.90-17.60 Oz. R-134a; 6.42-6.83 Oz. PAG-46	59007
09	All Eng. - 15.80-17.60 Oz. R-134a; 6.50-6.90 Oz. PAG-46	59007
08	4 Cyl. 2.4 Eng. - 17.60-19.40 Oz. R-134a; 8.11 Oz. PAG-46	59007
07-04	All Eng. - 17.60-19.40 Oz. R-134a; 8.11 Oz. PAG-46	59007
VIGOR		
94-92	All Eng. - 30.00 Oz. R-12; 7.00 Oz. Mineral Oil	59000 ⁵⁹

Continued on Next Page

⁵⁹ When retrofitting to R134a PAG Oil must be used.

ACURA

Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that A/C system has been properly cleaned, and new accumulator / filter drier has been installed. Specs are for total system capacities. Always refer to under hood decal as the primary source for refrigerant and lubricant information.

Year	Model	Lubricant
	ZDX	
13-12	6 Cyl. 3.7 Eng. - 19.00 Oz. R-134a; 3.45 Oz. PAG-46	59007
11	6 Cyl. 3.7 Eng. - 17.00 Oz. R-134a; 5.40 Oz. PAG-46	59007
10	6 Cyl. 3.7 Eng. - 17.00 Oz. R-134a; 3.40-6.00 Oz. PAG-46	59007

AMERICAN MOTORS

Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that A/C system has been properly cleaned, and new accumulator / filter drier has been installed. Specs are for total system capacities. Always refer to under hood decal as the primary source for refrigerant and lubricant information.

Year	Model	Lubricant
	AMX	
80	6 Cyl. 4.2 Eng. - See Under Hood Decal	59000 ⁵⁹
79	6 Cyl. 4.2 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.0 Eng. - See Under Hood Decal	59000 ⁵⁹
	CONCORD	
83	6 Cyl. 4.2 Eng. - See Under Hood Decal	59000 ⁵⁹
82-80	4 Cyl. 2.5 Eng. - See Under Hood Decal	59000 ⁵⁹
	6 Cyl. 4.2 Eng. - See Under Hood Decal	59000 ⁵⁹
	EAGLE	
88-85	6 Cyl. 4.2 Eng. - See Under Hood Decal	59000 ⁵⁹
84	4 Cyl. 2.5 Eng. - See Under Hood Decal	59000 ⁵⁹
	6 Cyl. 4.2 Eng. - See Under Hood Decal	59000 ⁵⁹
83	4 Cyl. 2.5 Eng. - See Under Hood Decal	59000 ⁵⁹
82-81	4 Cyl. 2.5 Eng. - See Under Hood Decal	59000 ⁵⁹
	6 Cyl. 4.2 Eng. - See Under Hood Decal	59000 ⁵⁹
80	6 Cyl. 4.2 Eng. - See Under Hood Decal	59000 ⁵⁹
	SPIRIT	
83	6 Cyl. 4.2 Eng. - See Under Hood Decal	59000 ⁵⁹
82-80	4 Cyl. 2.5 Eng. - See Under Hood Decal	59000 ⁵⁹
	6 Cyl. 4.2 Eng. - See Under Hood Decal	59000 ⁵⁹
79	4 Cyl. 2.0 Eng. - See Under Hood Decal	59000 ⁵⁹
	6 Cyl. 3.8 Eng. - See Under Hood Decal	59000 ⁵⁹
	6 Cyl. 4.2 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.0 Eng. - See Under Hood Decal	59000 ⁵⁹

AUDI

Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that A/C system has been properly cleaned, and new accumulator / filter drier has been installed. Specs are for total system capacities. Always refer to under hood decal as the primary source for refrigerant and lubricant information.

Year	Model	Lubricant
	100 SERIES	
94	All Eng. - 26.50 Oz. R-134a; 8.50 Oz. PAG-46	59007
93	All Eng. - 26.50 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
	All Eng. - 26.50 Oz. R-134a; 8.50 Oz. PAG-46	59007
92-89	All Eng. - 38.00 Oz. R-12; 10.00 Oz. Mineral Oil	59000 ⁵⁹
	200 SERIES	
91-89	All Eng. - 38.00 Oz. R-12; 10.00 Oz. Mineral Oil	59000 ⁵⁹
	5000 SERIES	
88-87	5 Cyl. 2.2 Eng. - See Under Hood Decal	59000 ⁵⁹
	5 Cyl. 2.3 Eng. - See Under Hood Decal	59000 ⁵⁹
86-84	5 Cyl. 2.2 Eng. - See Under Hood Decal	59000 ⁵⁹
	80 SERIES	
92-88	All Eng. - 37.00 Oz. R-12; 10.00 Oz. Mineral Oil	59000 ⁵⁹
	90 SERIES	
95-93	All Eng. - 23.00 Oz. R-134a; 8.50 Oz. PAG-46	59007
91-88	All Eng. - 37.00 Oz. R-12; 10.00 Oz. Mineral Oil	59000 ⁵⁹
	A3 SERIES	
13-10	4 Cyl. 2.0 Eng. - 19.00 Oz. R-134a; 4.50 Oz. PAG-46	59007
09	6 Cyl. 3.2 Eng. - 19.00 Oz. R-134a; See Under Hood Decal	59007
08	4 Cyl. 2.0 Eng. - See Under Hood Decal	59007

Continued on Next Page

⁵⁹ When retrofitting to R134a PAG Oil must be used.

Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that A/C system has been properly cleaned, and new accumulator / filter drier has been installed. Specs are for total system capacities. Always refer to under hood decal as the primary source for refrigerant and lubricant information.

Year	Model	Lubricant
A3 SERIES (Cont'd)		
08	6 Cyl. 3.2 Eng. - 19.00 Oz. R-134a; See Under Hood Decal	59007
07-06	4 Cyl. 2.0 Eng. - 18.00 Oz. R-134a; 3.71 Oz. PAG-46; w/ Sanden Compressor	59007
	4 Cyl. 2.0 Eng. - 18.00 Oz. R-134a; 4.72 Oz. PAG-46; w/ Zexel Compressor	59007
	6 Cyl. 3.2 Eng. - 18.00 Oz. R-134a; 3.71 Oz. PAG-46; w/ Sanden Compressor	59007
	6 Cyl. 3.2 Eng. - 18.00 Oz. R-134a; 4.72 Oz. PAG-46; w/ Zexel Compressor	59007
A4 SERIES		
13	4 Cyl. 2.0 Eng. - 22.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
12	4 Cyl. 1.8 Eng. - See Under Hood Decal	59007
11-10	4 Cyl. 2.0 Eng. - 22.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
09	4 Cyl. 2.0 Eng. - 22.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
	6 Cyl. 3.2 Eng. - 19.00 Oz. R-134a; 4.50 Oz. PAG-46	59007
08-06	All Eng. - 19.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
05	All Eng. - 20.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
04-02	All Eng. - 17.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
01-00	All Eng. - 24.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
99-96	All Eng. - 23.00 Oz. R-134a; 8.50 Oz. PAG-46	59007
A5 SERIES		
13	4 Cyl. 2.0 Eng. - 22.00 Oz. R-134a; 4.70-5.30 Oz. PAG-46	59007
12-11	4 Cyl. 2.0 Eng. - See Under Hood Decal	59007
10	4 Cyl. 2.0 Eng. - See Under Hood Decal	59007
09-08	6 Cyl. 3.2 Eng. - See Under Hood Decal	59007
	6 Cyl. 3.2 Eng. - See Under Hood Decal	59007
A6 SERIES		
13	4 Cyl. 2.0 Eng. - 20.00 Oz. R-134a; 3.70-4.30 Oz. PAG-46	59007
	6 Cyl. 3.0 Eng. - 20.00 Oz. R-134a; 4.38 Oz. PAG-46	59007
12	4 Cyl. 2.0 Eng. - 22.00 Oz. R-134a; 4.70-5.30 Oz. PAG-46	59007
	6 Cyl. 3.0 Eng. - 20.00 Oz. R-134a; 4.38 Oz. PAG-46	59007
11	6 Cyl. 3.0 Eng. - 19.00 Oz. R-134a; 4.38 Oz. PAG-46	59007
	6 Cyl. 3.2 Eng. - 19.00 Oz. R-134a; 4.38 Oz. PAG-46	59007
	8 Cyl. 4.2 Eng.; Single Evaporator - 28.00 Oz. R-134a; 4.40 Oz. PAG-46	59007
10	8 Cyl. 4.2 Eng.; Dual Evaporator - 33.00 Oz. R-134a; 4.40 Oz. PAG-46	59007
	6 Cyl. 3.0 Eng. - 19.00 Oz. R-134a; 4.38 Oz. PAG-46	59007
09	6 Cyl. 3.2 Eng. - 19.00 Oz. R-134a; 4.38 Oz. PAG-46	59007
	6 Cyl. 2.8 Eng. - 19.00 Oz. R-134a; 4.38 Oz. PAG-46	59007
08	6 Cyl. 3.0 Eng. - 19.00 Oz. R-134a; 4.38 Oz. PAG-46	59007
	6 Cyl. 3.2 Eng. - 19.00 Oz. R-134a; 4.38 Oz. PAG-46	59007
	8 Cyl. 4.2 Eng. - 22.00 Oz. R-134a; 5.10 Oz. PAG-46	59007
	6 Cyl. 3.2 Eng. - 19.00 Oz. R-134a; 4.38 Oz. PAG-46	59007
07-06	8 Cyl. 4.2 Eng. - 22.00 Oz. R-134a; 5.10 Oz. PAG-46	59007
05	All Eng. - 28.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
04-03	All Eng. - 24.00 Oz. R-134a; 10.00 Oz. PAG-46	59007
02-01	All Eng. - 30.00 Oz. R-134a; 10.00 Oz. PAG-46	59007
00-98	All Eng. - 24.00 Oz. R-134a; 8.50 Oz. PAG-46	59007
97-96	All Eng. - 28.00 Oz. R-134a; 8.50 Oz. PAG-46	59007
95	All Eng. - 21.00 Oz. R-134a; 8.50 Oz. PAG-46	59007
95	All Eng. - 26.50 Oz. R-134a; 8.50 Oz. PAG-46	59007
A7 SERIES		
13-12	6 Cyl. 3.0 Eng. - 21.00 Oz. R-134a; 3.70-4.30 Oz. PAG-46	59007
A8 SERIES		
13	6 Cyl. 3.0 Eng.; Single Evaporator - 28.00 Oz. R-134a; 4.10-4.70 Oz. PAG-46	59007
	6 Cyl. 3.0 Eng.; Dual Evaporator - 34.00 Oz. R-134a; 4.10-4.70 Oz. PAG-46	59007
12	12 Cyl. 6.3 Eng.; Single Evaporator - 28.00 Oz. R-134a; 4.10-4.70 Oz. PAG-46	59007
	12 Cyl. 6.3 Eng.; Dual Evaporator - 33.00 Oz. R-134a; 4.10-4.70 Oz. PAG-46	59007
11-10	8 Cyl. 4.2 Eng.; Single Evaporator - 27.00 Oz. R-134a; 4.40 Oz. PAG-46	59007
	8 Cyl. 4.2 Eng.; Dual Evaporator - 33.00 Oz. R-134a; 4.40 Oz. PAG-46	59007
	8 Cyl. 4.2 Eng.; Single Evaporator - 27.00 Oz. R-134a; 4.40 Oz. PAG-46	59007
09-08	8 Cyl. 4.2 Eng.; Dual Evaporator - 33.00 Oz. R-134a; 4.40 Oz. PAG-46	59007
	12 Cyl. 6.0 Eng. - 22.00 Oz. R-134a; 5.10 Oz. PAG-46	59007
07	8 Cyl. 4.2 Eng. - 19.00 Oz. R-134a; 4.40 Oz. PAG-46	59007
	12 Cyl. 6.0 Eng. - 22.00 Oz. R-134a; 5.10 Oz. PAG-46	59007
06	8 Cyl. 4.2 Eng. - 21.00 Oz. R-134a; 5.06 Oz. PAG-46	59007
	All Eng. - 28.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
05	All Eng. - 23.00 Oz. R-134a; 7.00 Oz. PAG-46	59007

Continued on Next Page

Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that A/C system has been properly cleaned, and new accumulator / filter drier has been installed. Specs are for total system capacities. Always refer to under hood decal as the primary source for refrigerant and lubricant information.

Year	Model	Lubricant
A8 SERIES (Cont'd)		
04	All Eng. - 21.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
03-00	All Eng. - 25.00 Oz. R-134a; 8.50 Oz. PAG-46; w/o Restrictor	59007
	All Eng. - 29.00 Oz. R-134a; 8.50 Oz. PAG-46; w/ Yellow Restrictor	59007
99	All Eng. - 21.00 Oz. R-134a; 8.50 Oz. PAG-46	59007
98-97	All Eng. - 21.00 Oz. R-134a; 8.50 Oz. PAG-46	59007
ALLROAD QUATTRO		
13	4 Cyl. 2.0 Eng. - 22.00 Oz. R-134a; 4.70-5.30 Oz. PAG-46	59007
05	All Eng. - 23.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
04-03	All Eng. - 30.00 Oz. R-134a; 9.25 Oz. PAG-46	59007
02-01	All Eng. - 24.50 Oz. R-134a; 9.25 Oz. PAG-46	59007
CABRIOLET		
05-03	All Eng. - 19.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
98-94	All Eng. - 23.00 Oz. R-134a; 8.50 Oz. PAG-46	59007
COUPE QUATTRO		
91-90	All Eng. - 37.00 Oz. R-12; 10.00 Oz. Mineral Oil	59000 ⁵⁹
Q SERIES		
13	4 Cyl. 2.0 Eng. - 21.00 Oz. R-134a; 4.70-5.30 Oz. PAG-46	59007
	6 Cyl. 3.0 Eng. - 21.00 Oz. R-134a; 4.70-5.30 Oz. PAG-46	59007
10-09	6 Cyl. 3.6 Eng. - See Under Hood Decal	59007
08	6 Cyl. 3.6 Eng. - 19.00 Oz. R-134a; 3.70 Oz. PAG-46; w/ Sanden Compressor	59007
	6 Cyl. 3.6 Eng. - 19.00 Oz. R-134a; 4.10 Oz. PAG-46; w/ Zexel Compressor	59007
	6 Cyl. 3.6 Eng. - 19.00 Oz. R-134a; 4.70 Oz. PAG-46; w/ Denso Compressor	59007
07	6 Cyl. 3.6 Eng. - 19.00 Oz. R-134a; 4.90 Oz. PAG-46	59007
	6 Cyl. 3.6 Eng. - 37.00 Oz. R-134a; 8.28 Oz. PAG-46	59007
	8 Cyl. 4.2 Eng.; w/o Rear AC - 19.00 Oz. R-134a; 4.90 Oz. PAG-46	59007
	8 Cyl. 4.2 Eng.; w/ Rear AC - 37.00 Oz. R-134a; 8.28 Oz. PAG-46	59007
R8		
12-10	10 Cyl. 5.2 Eng. - 22.00 Oz. R-134a; 4.80-5.40 Oz. PAG-46	59007
	8 Cyl. 4.2 Eng. - 22.00 Oz. R-134a; 4.80-5.40 Oz. PAG-46	59007
09-08	8 Cyl. 4.2 Eng. - See Under Hood Decal	59007
RS4		
08	8 Cyl. 4.2 Eng. - 19.00 Oz. R-134a; 3.70 Oz. PAG-46; w/ Sanden Compressor	59007
	8 Cyl. 4.2 Eng. - 19.00 Oz. R-134a; 4.10 Oz. PAG-46; w/ Zexel Compressor	59007
	8 Cyl. 4.2 Eng. - 19.00 Oz. R-134a; 4.70 Oz. PAG-46; w/ Denso Compressor	59007
07	All Eng. - 16.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
RS6		
04-03	8 Cyl. 4.2 Eng. - 19.00 Oz. R-134a; 8.50 Oz. PAG-46	59007
S SERIES		
13	6 Cyl. 3.0 Eng. - 22.00 Oz. R-134a; 5.10 Oz. PAG-46	59007
	8 Cyl. 4.0 Eng. - 22.00 Oz. R-134a; 5.10 Oz. PAG-46	59007
12	6 Cyl. 3.0 Eng. - 22.00 Oz. R-134a; 5.10 Oz. PAG-46	59007
	8 Cyl. 4.2 Eng. - 22.00 Oz. R-134a; 5.10 Oz. PAG-46	59007
11-10	10 Cyl. 5.2 Eng. - 22.00 Oz. R-134a; 5.10 Oz. PAG-46	59007
	6 Cyl. 3.0 Eng. - 22.00 Oz. R-134a; 5.10 Oz. PAG-46	59007
	8 Cyl. 4.2 Eng. - 22.00 Oz. R-134a; 5.10 Oz. PAG-46	59007
09	10 Cyl. 5.2 Eng. - 22.00 Oz. R-134a; 5.10 Oz. PAG-46	59007
	8 Cyl. 4.2 Eng. - 22.00 Oz. R-134a; 5.10 Oz. PAG-46	59007
08	10 Cyl. 5.2 Eng. - 22.00 Oz. R-134a; 4.40 Oz. PAG-46	59007
	8 Cyl. 4.2 Eng. - 22.00 Oz. R-134a; 4.40 Oz. PAG-46	59007
07	10 Cyl. 5.2 Eng. - 17.00 Oz. R-134a; 4.40 Oz. PAG-46	59007
	8 Cyl. 4.2 Eng. - 17.00 Oz. R-134a; 4.40 Oz. PAG-46	59007
06-05	8 Cyl. 4.2 Eng. - 19.00 Oz. R-134a; 4.40 Oz. PAG-46	59007
04	All Eng. - 19.00 Oz. R-134a; 4.40 Oz. PAG-46	59007
	All Eng. - 19.00 Oz. R-134a; 4.40 Oz. PAG-46	59007
03-01	All Eng. - 25.00 Oz. R-134a; 6.07 Oz. PAG-46	59007
00	6 Cyl. 2.7 Eng. - 25.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
96-94	All Eng. - 26.50 Oz. R-134a; 8.50 Oz. PAG-46	59007
93	All Eng. - 26.50 Oz. R-134a; 8.50 Oz. PAG-46	59007
	All Eng. - w/ R-12	59000 ⁵⁹
92	All Eng. - 38.00 Oz. R-12; 10.00 Oz. Mineral Oil	59000 ⁵⁹
TT SERIES		
13-12	4 Cyl. 2.0 Eng. - 18.00 Oz. R-134a; 2.70-3.30 Oz. PAG-46; w/ Denso Compressor	59007
	4 Cyl. 2.0 Eng. - 18.00 Oz. R-134a; 3.40-4.00 Oz. PAG-46; w/ Sanden Compressor	59007

Continued on Next Page

⁵⁹ When retrofitting to R134a PAG Oil must be used.

Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that A/C system has been properly cleaned, and new accumulator / filter drier has been installed. Specs are for total system capacities. Always refer to under hood decal as the primary source for refrigerant and lubricant information.

Year	Model	Lubricant
TT SERIES (Cont'd)		
13-12	5 Cyl. 2.5 Eng. - 18.00 Oz. R-134a; 2.70-3.30 Oz. PAG-46; w/ Denso Compressor	59007
	5 Cyl. 2.5 Eng. - 18.00 Oz. R-134a; 3.40-4.00 Oz. PAG-46; w/ Sanden Compressor	59007
11	4 Cyl. 2.0 Eng. - 18.00 Oz. R-134a; 3.00 Oz. PAG-46; w/ Denso Compressor	59007
	4 Cyl. 2.0 Eng. - 18.00 Oz. R-134a; 3.70 Oz. PAG-46; w/ Sanden Compressor	59007
10	4 Cyl. 2.0 Eng. - 18.00 Oz. R-134a; 3.70 Oz. PAG-46	59007
09	4 Cyl. 2.0 Eng. - 18.00 Oz. R-134a; 3.70 Oz. PAG-46; w/ Sanden Compressor	59007
	4 Cyl. 2.0 Eng. - 18.00 Oz. R-134a; 4.10 Oz. PAG-46; w/ Zexel Compressor	59007
	4 Cyl. 2.0 Eng. - 18.00 Oz. R-134a; 4.70 Oz. PAG-46; w/ Denso Compressor	59007
	6 Cyl. 3.2 Eng. - 18.00 Oz. R-134a; 3.70 Oz. PAG-46; w/ Sanden Compressor	59007
	6 Cyl. 3.2 Eng. - 18.00 Oz. R-134a; 4.10 Oz. PAG-46; w/ Zexel Compressor	59007
	6 Cyl. 3.2 Eng. - 18.00 Oz. R-134a; 4.70 Oz. PAG-46; w/ Denso Compressor	59007
08	6 Cyl. 3.2 Eng. - 18.00 Oz. R-134a; 3.70 Oz. PAG-46; w/ Sanden Compressor	59007
	6 Cyl. 3.2 Eng. - 18.00 Oz. R-134a; 4.10 Oz. PAG-46; w/ Zexel Compressor	59007
	6 Cyl. 3.2 Eng. - 18.00 Oz. R-134a; 4.70 Oz. PAG-46; w/ Denso Compressor	59007
06-02	All Eng. - 26.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
01-00	All Eng. - 28.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
V8 QUATTRO		
94-93	All Eng. - 30.00 Oz. R-134a; 8.50 Oz. PAG-46	59007
92-90	All Eng. - 39.00 Oz. R-12; 10.00 Oz. Mineral Oil	59000 ⁵⁹

Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that A/C system has been properly cleaned, and new accumulator / filter drier has been installed. Specs are for total system capacities. Always refer to under hood decal as the primary source for refrigerant and lubricant information.

Year	Model	Lubricant
128 SERIES		
13-12	6 Cyl. 3.0 Eng. - 21.00 Oz. R-134a; 5.40-6.00 Oz. PAG-46	59007
11	6 Cyl. 3.0 Eng. - 21.87 Oz. R-134a; 6.08 Oz. PAG-46	59007
10	6 Cyl. 3.0 Eng. - 20.81 Oz. R-134a; 6.08 Oz. PAG-46	59007
09	6 Cyl. 3.0 Eng. - 21.00 Oz. R-134a; 6.30 Oz. PAG-46	59007
08	6 Cyl. 3.0 Eng. - 20.81 Oz. R-134a; 6.08 Oz. PAG-46	59007
135 SERIES		
13	6 Cyl. 3.0 Eng. - 21.00 Oz. R-134a; See Under Hood Decal PAG-46	59007
12-11	6 Cyl. 3.0 Eng. - 21.87 Oz. R-134a; 6.34 Oz. PAG-46	59007
10-08	6 Cyl. 3.0 Eng. - 20.81 Oz. R-134a; 6.34 Oz. PAG-46	59007
318 SERIES		
99-93	All Eng. - 29.00 Oz. R-134a; 6.00 Oz. PAG-100; Flat Tube Condenser	59002
	All Eng. - 36.00 Oz. R-134a; 6.00 Oz. PAG-100; Round Tube Condenser	59002
92-91	All Eng. - 42.50 Oz. R-12; 10.00 Oz. Mineral Oil; w/ Bosch Compressor	59000 ⁵⁹
	All Eng. - 42.50 Oz. R-12; 6.75 Oz. Mineral Oil; w/ Behr Compressor	59000 ⁵⁹
85-84	4 Cyl. 1.8 Eng. - See Under Hood Decal	59000 ⁵⁹
320 SERIES		
13	4 Cyl. 2.0 Eng. - 20.00 Oz. R-134a; 5.40-6.00 Oz. PAG-46	59007
05-01	6 Cyl. 2.2 Eng. - 26.10+/-0.88 Oz. R-134a; 5.41 Oz. PAG-46	59007
83-80	4 Cyl. 1.8 Eng. - 45.00 Oz. R-12; See Under Hood Decal	59000 ⁵⁹
323 SERIES		
00	All Eng. From 9/98 - 29.50 Oz. R-134a; 5.50 Oz. PAG-100	59002
99-98	All Eng. - 29.00 Oz. R-134a; 6.00 Oz. PAG-100; Flat Tube Condenser	59002
	All Eng. - 36.00 Oz. R-134a; 6.00 Oz. PAG-100; Round Tube Condenser	59002
325 SERIES		
06-01	All Eng. - 25.50 Oz. R-134a; 5.00 Oz. PAG-46	59007
95-94	All Eng. - 36.00 Oz. R-134a; 6.00 Oz. PAG-100	59002
93	All Eng. - 36.00 Oz. R-12; 6.00 Oz. Mineral Oil	59000 ⁵⁹
	All Eng. - 36.00 Oz. R-134a; 6.00 Oz. PAG-100	59002
92-91	All Eng. - 42.00 Oz. R-12; 10.00 Oz. Mineral Oil; w/ Bosch Compressor	59000 ⁵⁹
	All Eng. - 42.50 Oz. R-12; 6.75 Oz. Mineral Oil; w/ Behr Compressor	59000 ⁵⁹
90-89	All Eng. - 34.50 Oz. R-12; 10.00 Oz. Mineral Oil; w/ Bosch Compressor	59000 ⁵⁹
	All Eng. - 34.50 Oz. R-12; 6.75 Oz. Mineral Oil; w/ Behr Compressor	59000 ⁵⁹
88-86	All Eng. - 33.50 Oz. R-12; 5.75 Oz. Mineral Oil	59000 ⁵⁹
85	6 Cyl. 2.7 Eng. - See Under Hood Decal	59000 ⁵⁹

Continued on Next Page

⁵⁹ When retrofitting to R134a PAG Oil must be used.



Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that A/C system has been properly cleaned, and new accumulator / filter drier has been installed. Specs are for total system capacities. Always refer to under hood decal as the primary source for refrigerant and lubricant information.

Year	Model	Lubricant
328 SERIES		
13-12	4 Cyl. 2.0 Eng. - 20.00 Oz. R-134a; 5.40-6.00 Oz. PAG-46	59007
	6 Cyl. 3.0 Eng. - 21.00 Oz. R-134a; 5.40-6.00 Oz. PAG-46	59007
11-07	6 Cyl. 3.0 Eng. - 21.00 Oz. R-134a; 5.40-6.80 Oz. PAG-46	59007
00-96	All Eng. - 36.00 Oz. R-134a; 6.00 Oz. PAG-100	59002
330 SERIES		
06	6 Cyl. 3.0 Eng. - 26.00 Oz. R-134a; 5.10-5.70 Oz. PAG-46	59007
05-01	6 Cyl. 3.0 Eng. - 26.00 Oz. R-134a; 5.10-5.70 Oz. PAG-100	59002
335 SERIES		
13	6 Cyl. 3.0 Eng. - 20.00 Oz. R-134a; See Under Hood Decal PAG-46	59007
12	6 Cyl. 3.0 Eng. - 21.87 Oz. R-134a; 6.34 Oz. PAG-46	59007
11	6 Cyl. 3.0 Eng. - 21.00 Oz. R-134a; 5.40-6.80 Oz. PAG-46	59007
10-07	6 Cyl. 3.0 Eng. - 20.81 Oz. R-134a; 6.34 Oz. PAG-46	59007
525 SERIES		
07	6 Cyl. 3.0 Eng. - 28.00 Oz. R-134a; 4.90-5.90 Oz. PAG-46; w/ Denso Compressor	59007
	6 Cyl. 3.0 Eng. - 28.00 Oz. R-134a; 5.40-6.80-5.90 Oz. PAG-46; w/ Seiko Seiki Compressor	59007
06-04	All Eng. - 29.00 Oz. R-134a; 6.75 Oz. PAG-46	59007
03-01	All Eng. - 27.00 Oz. R-134a; 6.00 Oz. PAG-46	59007
95-94	All Eng. - 51.00 Oz. R-134a; 6.00 Oz. PAG-100; Flat Tube Condenser	59002
	All Eng. - 53.00 Oz. R-134a; 6.00 Oz. PAG-100; Round Tube Condenser	59002
93	All Eng. - 51.00 Oz. R-134a; 6.00 Oz. PAG-100; Flat Tube Condenser	59002
	All Eng. - 53.00 Oz. R-134a; 6.00 Oz. PAG-100; Round Tube Condenser	59002
	6 Cyl. 2.5 Eng. - w/ R-12	59000 ⁵⁹
92-89	All Eng. - 68.00 Oz. R-12; 10.00 Oz. Mineral Oil; w/ Bosch Compressor	59000 ⁵⁹
	All Eng. - 68.00 Oz. R-12; 6.75 Oz. Mineral Oil; w/ Behr Compressor	59000 ⁵⁹
528 SERIES		
13	4 Cyl. 2.0 Eng. - 30.00 Oz. R-134a; See Under Hood Decal PAG-46	59007
12	4 Cyl. 2.0 Eng. - 30.00 Oz. R-134a; See Under Hood Decal	59007
11-10	6 Cyl. 3.0 Eng. - 28.00 Oz. R-134a; 5.40-6.80 Oz. PAG-46	59007
09-08	6 Cyl. 3.0 Eng. - 29.00 Oz. R-134a; 6.30 Oz. PAG-46	59007
00-98	All Eng. - 26.40 Oz. R-134a; 4.90-5.90 Oz. PAG-100; w/ Denso Compressor	59002
	All Eng. - 26.40 Oz. R-134a; 5.40-6.80 Oz. PAG-46; w/ Seiko Seiki Compressor	59007
97	All Eng. - 43.00 Oz. R-134a; 4.90-5.90 Oz. PAG-100; w/ Denso Compressor	59002
	All Eng. - 43.00 Oz. R-134a; 5.40-6.80 Oz. PAG-46; w/ Seiko Seiki Compressor	59007
82	6 Cyl. 2.7 Eng. - See Under Hood Decal	59000 ⁵⁹
81-79	6 Cyl. 2.8 Eng. - See Under Hood Decal	59000 ⁵⁹
530 SERIES		
07	6 Cyl. 3.0 Eng. - 28.00 Oz. R-134a; 4.90-5.90 Oz. PAG-46; w/ Denso Compressor	59007
	6 Cyl. 3.0 Eng. - 28.00 Oz. R-134a; 5.40-6.80 Oz. PAG-46; w/ Seiko Seiki Compressor	59007
06-04	All Eng. - 29.00 Oz. R-134a; 6.75 Oz. PAG-46	59007
03-02	6 Cyl. 3.0 Eng. - 27.00 Oz. R-134a; 4.90-5.40 Oz. PAG-100; w/ Denso Compressor	59002
	6 Cyl. 3.0 Eng. - 27.00 Oz. R-134a; 5.40-6.80 Oz. PAG-46; w/ Seiko Seiki Compressor	59007
01	6 Cyl. 3.0 Eng. - 27.00 Oz. R-134a; 4.90-5.90 Oz. PAG-100; w/ Denso Compressor	59002
	6 Cyl. 3.0 Eng. - 27.00 Oz. R-134a; 5.40-6.80 Oz. PAG-46; w/ Seiko Seiki Compressor	59007
95-94	All Eng. - 51.00 Oz. R-134a; 6.00 Oz. PAG-100; Flat Tube Condenser	59002
	All Eng. - 53.00 Oz. R-134a; 6.00 Oz. PAG-100; Round Tube Condenser	59002
533 SERIES		
84-83	6 Cyl. 3.2 Eng. - See Under Hood Decal	59000 ⁵⁹
535 SERIES		
13-12	6 Cyl. 3.0 Eng. - 30.00 Oz. R-134a; See Under Hood Decal PAG-46	59007
11	6 Cyl. 3.0 Eng. - 25.00 Oz. R-134a; 5.40-6.80 Oz. PAG-46	59007
10	6 Cyl. 3.0 Eng. - 25.00 Oz. R-134a; 6.10 Oz. PAG-46	59007
09-08	6 Cyl. 3.0 Eng. - 25.00 Oz. R-134a; 6.30 Oz. PAG-46	59007
93	All Eng. - 51.00 Oz. R-134a; 6.00 Oz. PAG-100; Flat Tube Condenser	59002
	All Eng. - 53.00 Oz. R-134a; 6.00 Oz. PAG-100; Round Tube Condenser	59002
92-89	All Eng. - 68.00 Oz. R-12; 10.00 Oz. Mineral Oil; w/ Bosch Compressor	59000 ⁵⁹
	All Eng. - 68.00 Oz. R-12; 6.75 Oz. Mineral Oil; w/ Behr Compressor	59000 ⁵⁹
540 SERIES		
03-01	All Eng. - 26.00 Oz. R-134a; 6.00 Oz. PAG-100	59002
00-99	All Eng. - 44.00 Oz. R-134a; 6.00 Oz. PAG-100	59002
98-97	All Eng. - 43.00 Oz. R-134a; 6.00 Oz. PAG-100	59002
95-94	All Eng. - 51.00 Oz. R-134a; 6.00 Oz. PAG-100; Flat Tube Condenser	59002
	All Eng. - 53.00 Oz. R-134a; 6.00 Oz. PAG-100; Round Tube Condenser	59002

Continued on Next Page

⁵⁹ When retrofitting to R134a PAG Oil must be used.

Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that A/C system has been properly cleaned, and new accumulator / filter drier has been installed. Specs are for total system capacities. Always refer to under hood decal as the primary source for refrigerant and lubricant information.

Year	Model	Lubricant
545 SERIES		
05-04	All Eng. - 29.00 Oz. R-134a; 6.75 Oz. PAG-46	59007
550 SERIES		
13-12	8 Cyl. 4.4 Eng. - 30.00 Oz. R-134a; See Under Hood Decal PAG-46	59007
11	8 Cyl. 4.4 Eng. - 28.00 Oz. R-134a; 5.40-6.80 Oz. PAG-46	59007
10	8 Cyl. 4.4 Eng. - 28.00 Oz. R-134a; 6.10 Oz. PAG-46	59007
	8 Cyl. 4.8 Eng. - 28.00 Oz. R-134a; 6.10 Oz. PAG-46	59007
09-08	8 Cyl. 4.8 Eng. - 29.00 Oz. R-134a; 6.30 Oz. PAG-46	59007
07-06	8 Cyl. 4.8 Eng. - 27.00 Oz. R-134a; 4.90-5.90 Oz. PAG-46; w/ Denso Compressor	59007
	8 Cyl. 4.8 Eng. - 27.00 Oz. R-134a; 5.40-6.80 Oz. PAG-46; w/ Seiko Seiki Compressor	59007
633 SERIES		
82-78	6 Cyl. 3.2 Eng. - See Under Hood Decal	59000⁵⁹
635 SERIES		
89	All Eng.; w/o Rear AC - 39.00 Oz. R-12; 5.75 Oz. Mineral Oil	59000⁵⁹
	All Eng.; w/ Rear AC - 63.50 Oz. R-12; 5.75 Oz. Mineral Oil	59000⁵⁹
640 SERIES		
13-12	6 Cyl. 3.0 Eng. - 30.00 Oz. R-134a; See Under Hood Decal PAG-46	59007
645 SERIES		
05-04	8 Cyl. 4.4 Eng. - 28.00 Oz. R-134a; See Under Hood Decal PAG-46	59007
650 SERIES		
12	8 Cyl. 4.4 Eng. - 28.48 Oz. R-134a; 6.34 Oz. PAG-46	59007
11-06	8 Cyl. 4.8 Eng. - 28.48 Oz. R-134a; 6.34 Oz. PAG-46	59007
733 SERIES		
84-78	6 Cyl. 3.2 Eng. - See Under Hood Decal	59000⁵⁹
735 SERIES		
92	All Eng.; w/o Rear AC 4/92-12/92 - 55.00 Oz. R-134a; 5.50 Oz. PAG-100; w/ Denso Compressor	59002
	All Eng.; w/o Rear AC 4/92-12/92 - 55.00 Oz. R-134a; 6.00 Oz. PAG-46; w/ Seiko Seiki Compressor	59007
	All Eng.; w/ Rear AC 4/92-12/92 - 60.00 Oz. R-134a; 6.00 Oz. PAG-100	59002
	All Eng.; w/o Rear AC To 3/92 - 68.00 Oz. R-12; 10.00 Oz. Mineral Oil; w/ Bosch Compressor	59000⁵⁹
	All Eng.; w/o Rear AC To 3/92 - 68.00 Oz. R-12; 6.75 Oz. Mineral Oil; w/ Behr Compressor	59000⁵⁹
	All Eng.; w/ Rear AC To 3/92 - 73.00 Oz. R-12; 10.00 Oz. Mineral Oil; w/ Bosch Compressor	59000⁵⁹
	All Eng.; w/ Rear AC To 3/92 - 73.00 Oz. R-12; 6.75 Oz. Mineral Oil; w/ Behr Compressor	59000⁵⁹
	6 Cyl. 3.5 Eng. - w/ R-12	59000⁵⁹
91-89	All Eng.; w/o Rear AC - 68.00 Oz. R-12; 10.00 Oz. Mineral Oil; w/ Bosch Compressor	59000⁵⁹
	All Eng.; w/o Rear AC - 68.00 Oz. R-12; 6.75 Oz. Mineral Oil; w/ Behr Compressor	59000⁵⁹
	All Eng.; w/ Rear AC - 73.00 Oz. R-12; 10.00 Oz. Mineral Oil; w/ Bosch Compressor	59000⁵⁹
	All Eng.; w/ Rear AC - 73.00 Oz. R-12; 6.75 Oz. Mineral Oil; w/ Behr Compressor	59000⁵⁹
88-85	6 Cyl. 3.5 Eng. - See Under Hood Decal	59000⁵⁹
740 SERIES		
13	6 Cyl. 3.0 Eng. - 30.00 Oz. R-134a; See Under Hood Decal PAG-46	59007
01	All Eng. - 24.00 Oz. R-134a; 6.50 Oz. PAG-100	59002
00-99	All Eng. - 55.00 Oz. R-134a; 6.00 Oz. PAG-100	59002
98-95	All Eng. - 42.50 Oz. R-134a; 5.50 Oz. PAG-100; w/ Denso Compressor	59002
	All Eng. - 42.50 Oz. R-134a; 6.00 Oz. PAG-46; w/ Seiko Seiki Compressor	59007
94-93	All Eng.; w/o Rear AC - 55.00 Oz. R-134a; 6.00 Oz. PAG-100	59002
	All Eng.; w/ Rear AC - 60.00 Oz. R-134a; 6.00 Oz. PAG-100	59002
745 SERIES		
05-04	All Eng. - 29.00 Oz. R-134a; 6.75 Oz. PAG-46	59007
03-02	8 Cyl. 4.4 Eng. - 28.00 Oz. R-134a; 5.40-6.80 Oz. PAG-46	59007
750 SERIES		
13-12	8 Cyl. 4.4 Eng. - 30.00 Oz. R-134a; See Under Hood Decal	59007
11-10	All Eng. - 30.00 Oz. R-134a; See Under Hood Decal	59007
09	8 Cyl. 4.4 Eng. - 30.00 Oz. R-134a; See Under Hood Decal	59007
	8 Cyl. 4.8 Eng. - 30.00 Oz. R-134a; See Under Hood Decal	59007
	8 Cyl. 4.8 Eng.; w/ Rear AC - 41.00 Oz. R-134a; See Under Hood Decal	59007
08-06	8 Cyl. 4.8 Eng.; w/o Rear AC - 28.00 Oz. R-134a; 6.34 Oz. PAG-46	59007
	8 Cyl. 4.8 Eng.; w/ Rear AC - 37.87 Oz. R-134a; 8.46 Oz. PAG-46	59007
01	All Eng. - 24.00 Oz. R-134a; 6.50 Oz. PAG-100	59002
00-99	All Eng. - 43.00 Oz. R-134a; 6.50 Oz. PAG-100	59002
98-95	All Eng.; w/o Rear AC - 42.50 Oz. R-134a; 5.50 Oz. PAG-100; w/ Denso Compressor	59002
	All Eng.; w/ Rear AC - 42.50 Oz. R-134a; 6.00 Oz. PAG-100	59002
	All Eng.; w/o Rear AC - 42.50 Oz. R-134a; 6.00 Oz. PAG-46; w/ Seiko Seiki Compressor	59007
94-93	All Eng.; w/o Rear AC - 55.00 Oz. R-134a; 5.50 Oz. PAG-100; w/ Denso Compressor	59002
	All Eng.; w/o Rear AC - 55.00 Oz. R-134a; 6.00 Oz. PAG-46; w/ Seiko Seiki Compressor	59007

Continued on Next Page

⁵⁹ When retrofitting to R134a PAG Oil must be used.



Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that A/C system has been properly cleaned, and new accumulator / filter drier has been installed. Specs are for total system capacities. Always refer to under hood decal as the primary source for refrigerant and lubricant information.

Year	Model	Lubricant
750 SERIES (Cont'd)		
94-93	All Eng.; w/ Rear AC - 60.00 Oz. R-134a; 6.00 Oz. PAG-100	59002
91-89	All Eng.; w/o Rear AC - 68.00 Oz. R-12; 10.00 Oz. Mineral Oil; w/ Bosch Compressor	59000 ⁵⁹
	All Eng.; w/o Rear AC - 68.00 Oz. R-12; 6.75 Oz. Mineral Oil; w/ Behr Compressor	59000 ⁵⁹
	All Eng.; w/ Rear AC - 73.00 Oz. R-12; 10.00 Oz. Mineral Oil; w/ Bosch Compressor	59000 ⁵⁹
	All Eng.; w/ Rear AC - 73.00 Oz. R-12; 6.75 Oz. Mineral Oil; w/ Behr Compressor	59000 ⁵⁹
760 SERIES		
13-10	12 Cyl. 6.0 Eng. - 30.00 Oz. R-134a; See Under Hood Decal PAG-46	59007
08-07	12 Cyl. 6.0 Eng.; w/o Rear AC - 29.00 Oz. R-134a; 6.35 Oz. PAG-46	59007
	12 Cyl. 6.0 Eng.; w/ Rear AC - 40.00 Oz. R-134a; 8.50 Oz. PAG-46	59007
06-04	All Eng. - 29.00 Oz. R-134a; 6.75 Oz. PAG-46	59007
840 SERIES		
97-94	All Eng. - 55.00 Oz. R-134a; 5.50 Oz. PAG-100; w/ Denso Compressor	59002
	All Eng. - 55.00 Oz. R-134a; 6.00 Oz. PAG-46; w/ Seiko Seiki Compressor	59007
850 SERIES		
97-93	All Eng. - 55.00 Oz. R-134a; 5.50 Oz. PAG-100; w/ Denso Compressor	59002
	All Eng. - 55.00 Oz. R-134a; 6.00 Oz. PAG-46; w/ Seiko Seiki Compressor	59007
92-91	All Eng. - 68.00 Oz. R-12; 10.00 Oz. Mineral Oil; w/ Bosch Compressor	59000 ⁵⁹
	All Eng. - 68.00 Oz. R-12; 6.75 Oz. Mineral Oil; w/ Behr Compressor	59000 ⁵⁹
ACTIVEHYBRID 5		
12	6 Cyl. 3.0 Eng. - 30.00 Oz. R-134a; See Under Hood Decal PAG-46	59007
L SERIES		
87-86	6 Cyl. 3.5 Eng. - See Under Hood Decal	59000 ⁵⁹
M SERIES		
13	8 Cyl. 4.0 Eng. - 21.00 Oz. R-134a; 5.40-6.00 Oz. PAG-46	59007
	8 Cyl. 4.4 Eng. - 30.00 Oz. R-134a; See Under Hood Decal PAG-46	59007
12	8 Cyl. 4.0 Eng. - 21.00 Oz. R-134a; 4.70-5.40 Oz. PAG-46	59007
	8 Cyl. 4.4 Eng. - 30.00 Oz. R-134a; See Under Hood Decal PAG-46	59007
11	10 Cyl. 5.0 Eng. - 21.00 Oz. R-134a; 4.70-5.40 Oz. PAG-46	59007
	8 Cyl. 4.0 Eng. - 21.00 Oz. R-134a; 4.70-5.40 PAG-46	59007
10	10 Cyl. 5.0 Eng. - 28.00 Oz. R-134a; 6.10 Oz. PAG-46	59007
	8 Cyl. 4.0 Eng. - 21.00 Oz. R-134a; 4.07-5.40 Oz. PAG-46	59007
09-08	10 Cyl. 5.0 Eng. - 29.00 Oz. R-134a; 6.34 Oz. PAG-46	59007
	8 Cyl. 4.0 Eng. - 29.00 Oz. R-134a; 6.34 Oz. PAG-46	59007
07	10 Cyl. 5.0 Eng. - 28.57 Oz. R-134a; 6.34 Oz. PAG-46	59007
06	10 Cyl. 5.0 Eng. - 28.00 Oz. R-134a; 6.34 Oz. PAG-46	59007
	6 Cyl. 3.2 Eng. - 26.10 Oz. R-134a; 5.40+/-0.30 Oz. PAG-46	59007
05-04	6 Cyl. 3.2 Eng. - 26.00 Oz. R-134a; 5.10-5.70 Oz. PAG-46	59007
03-02	6 Cyl. 3.2 Eng. - 26.00 Oz. R-134a; 5.10-5.70 Oz. PAG-46	59007
	8 Cyl. 5.0 Eng. - 43.00 Oz. R-134a; 4.90-5.90 Oz. PAG-46; w/ Denso Compressor	59007
	8 Cyl. 5.0 Eng. - 43.00 Oz. R-134a; 5.40-6.80 Oz. PAG-46; w/ Seiko Seiki Compressor	59007
01	6 Cyl. 3.2 Eng. - 36.00 Oz. R-134a; 3.30-4.70 Oz. PAG-46; w/ Denso Compressor	59007
	8 Cyl. 3.2 Eng. - 36.00 Oz. R-134a; 4.70-5.40 Oz. PAG-46; w/ Seiko Seiki Compressor	59007
	8 Cyl. 5.0 Eng. - 43.00 Oz. R-134a; 4.90-5.90 Oz. PAG-46; w/ Denso Compressor	59007
00	8 Cyl. 5.0 Eng. - 31.74 Oz. R-134a; 5.40-6.80 Oz. PAG-46; w/ Denso Compressor	59007
	8 Cyl. 5.0 Eng. - 33.51 Oz. R-134a; 5.40-6.80 Oz. PAG-46; w/ Seiko Seiki Compressor	59007
	8 Cyl. 5.0 Eng. - 43.00 Oz. R-134a; 5.40-6.80 Oz. PAG-46; w/ Seiko Seiki Compressor	59007
99-95	All Eng. - 29.00 Oz. R-134a; 5.00 Oz. PAG-100; Flat Tube Condenser	59002
	All Eng. - 36.00 Oz. R-134a; 5.00 Oz. PAG-100; Round Tube Condenser	59002
93	All Eng. - 51.00 Oz. R-134a; 6.00 Oz. PAG-100; Flat Tube Condenser	59002
	All Eng. - 51.14 Oz. R-12; 5.41 Oz. Mineral Oil	59000 ⁵⁹
	All Eng. - 53.00 Oz. R-134a; 6.00 Oz. PAG-100; Round Tube Condenser	59002
92	All Eng. - 53.00 Oz. R-12; 6.75 Oz. Mineral Oil	59000 ⁵⁹
91	4 Cyl. - 31.00 Oz. R-12; 10.00 Oz. Mineral Oil; w/ Bosch Compressor	59000 ⁵⁹
	4 Cyl. - 31.00 Oz. R-12; 6.75 Oz. Mineral Oil; w/ Behr Compressor	59000 ⁵⁹
	6 Cyl. - 53.00 Oz. R-12; 6.75 Oz. Mineral Oil	59000 ⁵⁹
90-89	All Eng. - 31.00 Oz. R-12; 10.00 Oz. Mineral Oil; w/ Bosch Compressor	59000 ⁵⁹
	All Eng. - 31.00 Oz. R-12; 6.75 Oz. Mineral Oil; w/ Behr Compressor	59000 ⁵⁹
88	4 Cyl. 2.3 Eng. - See Under Hood Decal	59000 ⁵⁹
X SERIES		
13	4 Cyl. 2.0 Eng. - 21.00 Oz. R-134a; See Under Hood Decal PAG-46	59007
	6 Cyl. 3.0 Eng. - 25.00 Oz. R-134a; 4.40-5.10 Oz. PAG-46	59007
	8 Cyl. 4.4 Eng. - 25.00 Oz. R-134a; 4.40-5.10 Oz. PAG-46	59007
12	6 Cyl. 3.0 Eng. - 18.00 Oz. R-134a; 5.40-6.00 Oz. PAG-46	59007

Continued on Next Page

⁵⁹ When retrofitting to R134a PAG Oil must be used.

Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that A/C system has been properly cleaned, and new accumulator / filter drier has been installed. Specs are for total system capacities. Always refer to under hood decal as the primary source for refrigerant and lubricant information.

Year	Model	Lubricant
X SERIES (Cont'd)		
12	8 Cyl. 4.4 Eng. - 25.00 Oz. R-134a; 4.40-5.10 Oz. PAG-46	59007
11	6 Cyl. 3.0 Eng. - 26.00 Oz. R-134a; 5.40-6.80 Oz. PAG-46	59007
	8 Cyl. 4.4 Eng. - 25.00 Oz. R-134a; 4.90-5.60 Oz. PAG-46	59007
10	6 Cyl. 3.0 Eng. - 25.00 Oz. R-134a; 5.10 Oz. PAG-46	59007
	8 Cyl. 4.4 Eng. - 25.00 Oz. R-134a; 5.10 Oz. PAG-46	59007
09	6 Cyl. 3.0 Eng. - 26.00 Oz. R-134a; 6.30 Oz. PAG-46	59007
	8 Cyl. 4.4 Eng. - 25.00 Oz. R-134a; 5.30 Oz. PAG-46	59007
08	6 Cyl. 2.5 Eng. - See Under Hood Decal	59007
	6 Cyl. 3.0 Eng. - 26.00 Oz. R-134a; 6.30 Oz. PAG-46	59007
	8 Cyl. 4.4 Eng. - 24.70 Oz. R-134a; 5.30 Oz. PAG-46	59007
07	6 Cyl. 2.5 Eng. - See Under Hood Decal	59007
	6 Cyl. 3.0 Eng. - 26.00 Oz. R-134a; See Under Hood Decal PAG-46	59007
	8 Cyl. 4.8 Eng. - 25.00 Oz. R-134a; See Under Hood Decal PAG-46	59007
06	6 Cyl. 2.5 Eng. - 26.00 Oz. R-134a; See Under Hood Decal PAG-46	59007
	6 Cyl. 3.0 Eng. - 16.00 Oz. R-134a; See Under Hood Decal PAG-46	59007
	8 Cyl. 4.4 Eng. - 16.00 Oz. R-134a; See Under Hood Decal PAG-46	59007
	8 Cyl. 4.8 Eng. - 16.00 Oz. R-134a; See Under Hood Decal PAG-46	59007
05-04	All Eng. - 16.00 Oz. R-134a; See Under Hood Decal PAG-46	59007
03-02	6 Cyl. 3.0 Eng. - 16.00 Oz. R-134a; See Under Hood Decal PAG-46	59007
	8 Cyl. 4.4 Eng. - 16.00 Oz. R-134a; See Under Hood Decal PAG-46	59007
	8 Cyl. 4.6 Eng. - 16.00 Oz. R-134a; See Under Hood Decal PAG-46	59007
01	X5 - 16.00 Oz. R-134a; See Under Hood Decal PAG-46	59007
00	8 Cyl. 4.4 Eng. - 16.00 Oz. R-134a; See Under Hood Decal PAG-46	59007
Z SERIES		
13	4 Cyl. 2.0 Eng. - 21.00 Oz. R-134a; See Under Hood Decal PAG-46	59007
	6 Cyl. 3.0 Eng. - 16.00 Oz. R-134a; 5.40-6.00 Oz. PAG-46	59007
12	4 Cyl. 2.0 Eng. - 20.00 Oz. R-134a; See Under Hood Decal PAG-46	59007
	6 Cyl. 3.0 Eng. - 20.46 Oz. R-134a; See Under Hood Decal PAG-46	59007
11-10	6 Cyl. 3.0 Eng. - 20.46 Oz. R-134a; See Under Hood Decal PAG-46	59007
08	6 Cyl. 3.0 Eng. - 26.00 Oz. R-134a; 5.10 Oz. PAG-46	59007
	6 Cyl. 3.2 Eng. - 26.00 Oz. R-134a; 5.30 Oz. PAG-46	59007
07-06	6 Cyl. 3.0 Eng. - 26.00 Oz. R-134a; 5.10 Oz. PAG-46	59007
	6 Cyl. 3.2 Eng. - 26.00 Oz. R-134a; 5.10 Oz. PAG-46	59007
05	6 Cyl. 2.5 Eng. - 26.00 Oz. R-134a; 5.10 Oz. PAG-46	59007
	6 Cyl. 3.0 Eng. - 26.00 Oz. R-134a; 5.10 Oz. PAG-46	59007
04	6 Cyl. 2.5 Eng. - 26.00 Oz. R-134a; 5.10 Oz. PAG-46	59007
	6 Cyl. 3.0 Eng. - 26.00 Oz. R-134a; 5.29+/-0.35 Oz. PAG-46	59007
03	8 Cyl. 5.0 Eng. - 25.00 Oz. R-134a; See Under Hood Decal	59007
02	6 Cyl. 2.5 Eng. - 36.00 Oz. R-134a; 3.30-4.70 Oz. PAG-46; w/ Denso Compressor	59007
	6 Cyl. 2.5 Eng. - 36.00 Oz. R-134a; 4.70-5.40 Oz. PAG-46; w/ Seiko Seiki Compressor	59007
	6 Cyl. 3.0 Eng. - 36.00 Oz. R-134a; 3.30-4.70 Oz. PAG-46; w/ Denso Compressor	59007
	6 Cyl. 3.0 Eng. - 36.00 Oz. R-134a; 4.70-5.40 Oz. PAG-46; w/ Seiko Seiki Compressor	59007
	6 Cyl. 3.2 Eng. - 36.00 Oz. R-134a; 3.30-4.70 Oz. PAG-46; w/ Denso Compressor	59007
	6 Cyl. 3.2 Eng. - 36.00 Oz. R-134a; 4.70-5.40 Oz. PAG-46; w/ Seiko Seiki Compressor	59007
	8 Cyl. 5.0 Eng. - 25.00 Oz. R-134a; See Under Hood Decal PAG-46	59007
01	4 Cyl. 3.0 Eng. - 36.00 Oz. R-134a; 4.70-5.40 Oz. PAG-46; w/ Seiko Seiki Compressor	59007
	6 Cyl. 2.5 Eng. - 36.00 Oz. R-134a; 3.30-4.70 Oz. PAG-46; w/ Denso Compressor	59007
	6 Cyl. 2.5 Eng. - 36.00 Oz. R-134a; 4.70-5.40 Oz. PAG-46; w/ Seiko Seiki Compressor	59007
	6 Cyl. 3.0 Eng. - 36.00 Oz. R-134a; 3.30-4.70 Oz. PAG-46; w/ Denso Compressor	59007
	6 Cyl. 3.2 Eng. - 36.00 Oz. R-134a; 3.30-4.70 Oz. PAG-46	59007
	6 Cyl. 3.2 Eng. - 36.00 Oz. R-134a; 4.70-5.40 Oz. PAG-46; w/ Seiko Seiki Compressor	59007
00	Z8 - 26.00 Oz. R-134a;	59007
	Z3 - 29.00 Oz. R-134a; 6.00 Oz. PAG-100; Flat Tube Condenser	59002
	Z3 - 36.00 Oz. R-134a; 6.00 Oz. PAG-100; Round Tube Condenser	59002
99	Z3 - 29.00 Oz. R-134a; 6.00 Oz. PAG-100; Flat Tube Condenser	59002
	Z3 - 36.00 Oz. R-134a; 6.00 Oz. PAG-100; Round Tube Condenser	59002
98	4 Cyl. 1.9 Eng. - 29.10 Oz. R-134a; 5.29 Oz. PAG-100; w/ Seiko Seiki Compressor	59002
	4 Cyl. 1.9 Eng. - 36.00 Oz. R-134a; 3.30-4.70 Oz. PAG-46; w/ Denso Compressor	59007
	6 Cyl. 2.8 Eng. - 29.10 Oz. R-134a; 4.23 Oz. PAG-46; w/ Denso Compressor	59007
	6 Cyl. 2.8 Eng. - 29.10 Oz. R-134a; 5.29 Oz. PAG-100; w/ Seiko Seiki Compressor	59002
	6 Cyl. 3.2 Eng. - See Under Hood Decal	59007
97	4 Cyl. 1.9 Eng. - 36.00 Oz. R-134a; 3.30-4.70 Oz. PAG-46; w/ Denso Compressor	59007
	4 Cyl. 1.9 Eng. - 36.00 Oz. R-134a; 4.70-5.40 Oz. PAG-46; w/ Seiko Seiki Compressor	59007

Continued on Next Page

BMW

Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that A/C system has been properly cleaned, and new accumulator / filter drier has been installed. Specs are for total system capacities. Always refer to under hood decal as the primary source for refrigerant and lubricant information.

Year	Model	Lubricant
Z SERIES (Cont'd)		
97	6 Cyl. 2.8 Eng. - 36.00 Oz. R-134a; 3.30-4.70 Oz. PAG-46; w/ Denso Compressor	59007
	6 Cyl. 2.8 Eng. - 36.00 Oz. R-134a; 4.70-5.40 Oz. PAG-46; w/ Seiko Seiki Compressor	59007
96	4 Cyl. 1.9 Eng. - 36.00 Oz. R-134a; 3.30-4.70 Oz. PAG-46; w/ Denso Compressor	59007
	4 Cyl. 1.9 Eng. - 36.00 Oz. R-134a; 4.70-5.40 Oz. PAG-46; w/ Seiko Seiki Compressor	59007

BUICK

Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that A/C system has been properly cleaned, and new accumulator / filter drier has been installed. Specs are for total system capacities. Always refer to under hood decal as the primary source for refrigerant and lubricant information.

Year	Model	Lubricant
ALLURE		
10	6 Cyl. 3.0 Eng. - 20.16 Oz. R-134a; 3.70 Oz. PAG-46	59007
	6 Cyl. 3.6 Eng. - 20.16 Oz. R-134a; 3.70 Oz. PAG-46	59007
09	6 Cyl. 3.8 Eng. - 21.60-19.20 Oz. R-134a; 5.00 Oz. PAG-46	59007
	8 Cyl. 5.3 Eng. - 21.60-19.20 Oz. R-134a; 5.00 Oz. PAG-46	59007
08	6 Cyl. 3.8 Eng. - 21.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
	8 Cyl. 5.3 Eng. - 17.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
07-06	6 Cyl. 3.6 Eng. - 21.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
	6 Cyl. 3.8 Eng. - 21.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
05	6 Cyl. 3.6 Eng. - 35.00 Oz. R-134a; 6.60 Oz. PAG-46	59007
	6 Cyl. 3.8 Eng. - 35.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
APOLLO		
73	6 Cyl. 4.1 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.7 Eng. - See Under Hood Decal	59000 ⁵⁹
CENTURY SEDAN / COUPE		
05	All Eng. - 38.00 Oz. R-134a; 9.00 Oz. PAG-150	59003
04-03	All Eng. - 36.00 Oz. R-134a; 9.00 Oz. PAG-150	59003
02-97	All Eng. - 36.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
96-94	All Eng. - 28.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
93	All Eng. - 38.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
92	All Eng. - 40.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
91-85	All Eng. - 44.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
84	4 Cyl. 2.5 Eng. - See Under Hood Decal	59000 ⁵⁹
	6 Cyl. 2.8 Eng. - See Under Hood Decal	59000 ⁵⁹
	6 Cyl. 3.0 Eng. - See Under Hood Decal	59000 ⁵⁹
	6 Cyl. 3.8 Eng. - See Under Hood Decal	59000 ⁵⁹
83-82	4 Cyl. 2.5 Eng. - See Under Hood Decal	59000 ⁵⁹
	6 Cyl. 2.8 Eng. - See Under Hood Decal	59000 ⁵⁹
	6 Cyl. 3.0 Eng. - See Under Hood Decal	59000 ⁵⁹
ELECTRA SEDAN / COUPE		
90-89	All Eng. - 38.50 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
88	All Eng. - 36.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
87-86	All Eng. - 46.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
85	All Eng. - 56.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
84	6 Cyl. 4.1 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.0 Eng. - See Under Hood Decal	59000 ⁵⁹
72-70	8 Cyl. 7.5 Eng. - See Under Hood Decal	59000 ⁵⁹
69-67	8 Cyl. 7.0 Eng. - See Under Hood Decal	59000 ⁵⁹
66-64	8 Cyl. 6.6 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 7.0 Eng. - See Under Hood Decal	59000 ⁵⁹
63	8 Cyl. 6.6 Eng. - See Under Hood Decal	59000 ⁵⁹
ENCLAVE		
13	6 Cyl. 3.6 Eng. - See Under Hood Decal; 7.80 Oz. PAG-46	59007
12-10	6 Cyl. 3.6 Eng. - 36.80 Oz. R-134a; 6.50 Oz. PAG-46	59007
09-08	All Eng. - 36.80 Oz. R-134a; 6.50 Oz. PAG-46	59007
ESTATE WAGON		
96-94	8 Cyl. 5.7 Eng. - w/ Denso Compressor	59007
	8 Cyl. 5.7 Eng. - w/ OE Harrison Compressor	59003
93	8 Cyl. 5.7 Eng. - 50.00 Oz. R-12; Mineral	59000 ⁵⁹
92	8 Cyl. 5.7 Eng. - See Under Hood Decal	59000 ⁵⁹
91-90	8 Cyl. 5.0 Eng. - See Under Hood Decal	59000 ⁵⁹

Continued on Next Page

⁵⁹ When retrofitting to R134a PAG Oil must be used.

Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that A/C system has been properly cleaned, and new accumulator / filter drier has been installed. Specs are for total system capacities. Always refer to under hood decal as the primary source for refrigerant and lubricant information.

Year	Model	Lubricant
ESTATE WAGON (Cont'd)		
89	4 Cyl. 2.5 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.0 Eng. - See Under Hood Decal	59000
88-86	4 Cyl. 2.5 Eng. - See Under Hood Decal	59000 ⁵⁹
	6 Cyl. 2.8 Eng. - See Under Hood Decal	59000 ⁵⁹
	6 Cyl. 3.8 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.0 Eng. - See Under Hood Decal	59000 ⁵⁹
85	4 Cyl. 2.5 Eng. - See Under Hood Decal	59000
	6 Cyl. 2.8 Eng. - See Under Hood Decal	59000 ⁵⁹
	6 Cyl. 3.0 Eng. - See Under Hood Decal	59000 ⁵⁹
	6 Cyl. 3.8 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.0 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.7 Eng. - See Under Hood Decal	59000
84	8 Cyl. 5.0 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.7 Eng. - See Under Hood Decal	59000 ⁵⁹
72-70	8 Cyl. 5.7 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 7.5 Eng. - See Under Hood Decal	59000 ⁵⁹
LACROSSE		
13	4 Cyl. 2.4 Eng. - 24.00 Oz. R-134a; 3.70 Oz. PAG-46	59007
	6 Cyl. 3.6 Eng. - 24.00 Oz. R-134a; 3.70 Oz. PAG-46	59007
12-11	4 Cyl. 2.4 Eng. - 21.00 Oz. R-134a; 3.70 Oz. PAG-46	59007
	6 Cyl. 3.6 Eng. - 21.60 Oz. R-134a; 5.00 Oz. PAG-46	59007
10	4 Cyl. 2.4 Eng. - 19.00 Oz. R-134a; 3.70 Oz. PAG-46	59007
	6 Cyl. 3.0 Eng. - 19.00 Oz. R-134a; 3.70 Oz. PAG-46	59007
	6 Cyl. 3.6 Eng. - 21.60 Oz. R-134a; 5.00 Oz. PAG-46	59007
09-06	All Eng. - 21.60 Oz. R-134a; 5.00 Oz. PAG-46	59007
05	All Eng. - 36.96 Oz. R-134a; 6.50 Oz. PAG-46	59007
LESABRE SEDAN / COUPE		
05	All Eng. - 38.00 Oz. R-134a; 9.00 Oz. PAG-150	59003
04-03	All Eng. - 35.00 Oz. R-134a; 9.00 Oz. PAG-150	59003
02-98	All Eng. - 32.00 Oz. R-134a; 9.00 Oz. PAG-150	59003
97-96	All Eng. - 32.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
95-94	All Eng. - 39.00 Oz. R-134a; 8.00 Oz. PAG-150; w/ OE Harrison Compressor	59003
	All Eng. - 39.00 Oz. R-134a; 8.00 Oz. PAG-46; w/ Denso Compressor	59007
93-89	All Eng. - 38.50 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
88	All Eng. - 53.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
87-86	All Eng. - 38.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
85	All Eng. - 56.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000
84	6 Cyl. 3.8 Eng. - See Under Hood Decal	59000 ⁵⁹
	6 Cyl. 4.1 Eng. - See Under Hood Decal	59000 ⁵⁹
72-70	8 Cyl. 7.5 Eng. - See Under Hood Decal	59000 ⁵⁹
64-63	8 Cyl. 6.6 Eng. - See Under Hood Decal	59000 ⁵⁹
LUCERNE		
11	6 Cyl. 3.9 Eng. - 23.00 Oz. R-134a; 4.70 Oz. PAG-46	59007
	8 Cyl. 4.6 Eng. - 23.00 Oz. R-134a; 4.70 Oz. PAG-46	59007
10	6 Cyl. 3.9 Eng. - 21.00 Oz. R-134a; 4.70 Oz. PAG-46	59007
	8 Cyl. 4.6 Eng. - 21.00 Oz. R-134a; 4.70 Oz. PAG-46	59007
09-06	All Eng. - 23.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
PARK AVENUE		
05	All Eng. - 38.00 Oz. R-134a; 9.00 Oz. PAG-150	59003
04-00	All Eng. - 35.00 Oz. R-134a; 9.00 Oz. PAG-150	59003
99-97	All Eng. - 32.00 Oz. R-134a; 9.00 Oz. PAG-150	59003
96	All Eng. - 32.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
95-94	All Eng. - 39.00 Oz. R-134a; 8.00 Oz. PAG-150; w/ OE Harrison Compressor	59003
	All Eng. - 39.00 Oz. R-134a; 8.00 Oz. PAG-46; w/ Denso Compressor	59007
93-92	All Eng. - 38.50 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
91	All Eng. - 39.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
RAINIER		
07-04	All Eng.; w/o Rear AC - 30.40 Oz. R-134a; 8.00 Oz. PAG-46	59007
	All Eng.; w/ Rear AC - 42.40 Oz. R-134a; 8.00 Oz. PAG-46	59007
REATTA		
91-89	All Eng. - 38.50 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
88	6 Cyl. 3.8 Eng. - See Under Hood Decal	59000

Continued on Next Page

⁵⁹ When retrofitting to R134a PAG Oil must be used.

BUICK

Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that A/C system has been properly cleaned, and new accumulator / filter drier has been installed. Specs are for total system capacities. Always refer to under hood decal as the primary source for refrigerant and lubricant information.

Year	Model	Lubricant
REGAL SEDAN / COUPE		
13	4 Cyl. 2.0 Eng. - 20.80-24.00 Oz. R-134a; 3.70 Oz. PAG-46	59007
	4 Cyl. 2.4 Eng. - 24.00 Oz. R-134a; 3.70 Oz. PAG-46	59007
12-11	4 Cyl. 2.0 Eng. - 21.00 Oz. R-134a; 3.70 Oz. PAG-46	59007
	4 Cyl. 2.4 Eng. - 24.00 Oz. R-134a; 3.70 Oz. PAG-46	59007
04-97	All Eng. - 36.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
96	All Eng. - 32.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
95-94	All Eng. - 32.00 Oz. R-134a; 8.00 Oz. PAG-150; w/ OE Harrison Compressor	59003
	All Eng. - 32.00 Oz. R-134a; 8.00 Oz. PAG-46; w/ Denso Compressor	59007
93-88	All Eng. - 36.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
87-85	All Eng. - 52.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
84	6 Cyl. 3.8 Eng. - See Under Hood Decal	59000 ⁵⁹
	6 Cyl. 4.1 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.0 Eng. - See Under Hood Decal	59000 ⁵⁹
74-73	8 Cyl. 5.7 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 7.5 Eng. - See Under Hood Decal	59000 ⁵⁹
RENDEZVOUS		
07-02	All Eng. - 27.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
RIVIERA		
99-97	All Eng. - 32.00 Oz. R-134a; 9.00 Oz. PAG-150	59003
96-95	All Eng. - 32.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
93-89	All Eng. - 38.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
88-86	All Eng. - 46.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
85	All Eng. - 52.00 Oz. R-12; 7.00 Oz. Mineral Oil	59000 ⁵⁹
84	6 Cyl. 4.1 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.0 Eng. - See Under Hood Decal	59000 ⁵⁹
71-70	8 Cyl. 7.5 Eng. - See Under Hood Decal	59000 ⁵⁹
69-67	8 Cyl. 7.0 Eng. - See Under Hood Decal	59000 ⁵⁹
66-65	8 Cyl. 6.6 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 7.0 Eng. - See Under Hood Decal	59000 ⁵⁹
ROADMASTER		
96-94	All Eng. - 28.00 Oz. R-134a; 8.00 Oz. PAG-150; w/ OE Harrison Compressor	59003
	All Eng. - 28.00 Oz. R-134a; 8.00 Oz. PAG-46; w/ Denso Compressor	59007
93-91	All Eng. - 50.00 Oz. R-12; 6.00 Oz. Mineral Oil	59000 ⁵⁹
SKYHAWK		
89	All Eng. - 36.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
88-87	4 Cyl. 2.0 Eng. - See Under Hood Decal	59000 ⁵⁹
86-85	4 Cyl. 1.8 Eng. - See Under Hood Decal	59000 ⁵⁹
	4 Cyl. 2.0 Eng. - See Under Hood Decal	59000 ⁵⁹
SKYLARK		
98-95	All Eng. - 36.00 Oz. R-134a; 9.00 Oz. PAG-150	59003
94	All Eng. - 36.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
93	All Eng. - 42.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
	All Eng. - 42.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
92	All Eng. - 42.50 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
91-89	All Eng. - 36.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
88	4 Cyl. 2.3 Eng. - See Under Hood Decal	59000 ⁵⁹
	4 Cyl. 2.5 Eng. - See Under Hood Decal	59000 ⁵⁹
	6 Cyl. 3.0 Eng. - See Under Hood Decal	59000 ⁵⁹
87-86	4 Cyl. 2.5 Eng. - See Under Hood Decal	59000 ⁵⁹
	6 Cyl. 3.0 Eng. - See Under Hood Decal	59000 ⁵⁹
85-82	4 Cyl. 2.5 Eng. - See Under Hood Decal	59000 ⁵⁹
	6 Cyl. 2.8 Eng. - See Under Hood Decal	59000 ⁵⁹
SOMERSET		
87-85	4 Cyl. 2.5 Eng. - See Under Hood Decal	59000 ⁵⁹
	6 Cyl. 3.0 Eng. - See Under Hood Decal	59000 ⁵⁹
TERRAZA		
07	All Eng.; w/o Rear AC - 22.88 Oz. R-134a; 7.00 Oz. PAG-46	59007
	All Eng.; w/ Rear AC - 31.66 Oz. R-134a; 7.77 Oz. PAG-46	59007
06	All Eng.; w/o Rear AC - 22.88 Oz. R-134a; 7.10 Oz. PAG-46	59007
	All Eng.; w/ Rear AC - 31.66 Oz. R-134a; 7.77 Oz. PAG-46	59007
05	All Eng.; w/o Rear AC - 26.88 Oz. R-134a; 7.10 Oz. PAG-46	59007
	All Eng.; w/ Rear AC - 35.60 Oz. R-134a; 7.77 Oz. PAG-46	59007

Continued on Next Page

⁵⁹ When retrofitting to R134a PAG Oil must be used.

Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that A/C system has been properly cleaned, and new accumulator / filter drier has been installed. Specs are for total system capacities. Always refer to under hood decal as the primary source for refrigerant and lubricant information.

Year	Model	Lubricant
	VERANO	
13	4 Cyl. 2.0 Eng. - 22.73 Oz. R-134a; 4.23 Oz. PAG-46	59007
	4 Cyl. 2.4 Eng. - 22.73 Oz. R-134a; 4.23 Oz. PAG-46	59007
12	4 Cyl. 2.4 Eng. - 20.80-24.00 Oz. R-134a; 3.70 Oz. PAG-46	59007

CADILLAC

Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that A/C system has been properly cleaned, and new accumulator / filter drier has been installed. Specs are for total system capacities. Always refer to under hood decal as the primary source for refrigerant and lubricant information.

Year	Model	Lubricant
	ALLANTE	
93-87	All Eng. - 36.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
	CALAIS	
73-70	8 Cyl. 7.7 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 8.2 Eng. - See Under Hood Decal	59000 ⁵⁹
69-68	8 Cyl. 7.7 Eng. - See Under Hood Decal	59000 ⁵⁹
67-65	8 Cyl. 7.0 Eng. - See Under Hood Decal	59000 ⁵⁹
	CATERA	
01-99	All Eng. - 41.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
98-97	All Eng. - 41.50 Oz. R-134a; 9.00 Oz. PAG-150	59003
	CIMARRON	
88-86	All Eng. - 36.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
85	4 Cyl. 2.0 Eng. - See Under Hood Decal	59000 ⁵⁹
	6 Cyl. 2.8 Eng. - See Under Hood Decal	59000 ⁵⁹
84-83	4 Cyl. 2.0 Eng. - See Under Hood Decal	59000 ⁵⁹
82	4 Cyl. 1.8 Eng. - See Under Hood Decal	59000 ⁵⁹
	CTS	
13	6 Cyl. 3.0 Eng. - 19.00 Oz. R-134a; 3.70 Oz. PAG-46	59007
	6 Cyl. 3.6 Eng. - 19.00 Oz. R-134a; 3.70 Oz. PAG-46	59007
	8 Cyl. 6.2 Eng. - 19.00 Oz. R-134a; 3.70 Oz. PAG-46	59007
12	6 Cyl. 3.0 Eng. - 19.00 Oz. R-134a; 3.70 Oz. PAG-46	59007
	6 Cyl. 3.6 Eng. - 19.00 Oz. R-134a; 3.70 Oz. PAG-46	59007
	8 Cyl. 6.2 Eng. - 18.20.00 Oz. R-134a; 3.72 Oz. PAG-46	59007
11-10	6 Cyl. 3.0 Eng. - 18.20.00 Oz. R-134a; 3.72 Oz. PAG-46	59007
	6 Cyl. 3.6 Eng. - 18.20.00 Oz. R-134a; 3.72 Oz. PAG-46	59007
	8 Cyl. 6.2 Eng. - 18.20.00 Oz. R-134a; 3.72 Oz. PAG-46	59007
09-08	All Eng. - 19.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
07-03	All Eng. - 21.00 Oz. R-134a; 4.75 Oz. PAG-46	59007
	DEVILLE	
05-02	All Eng. - 35.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
01-00	All Eng. - 32.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
99-98	All Eng. - 32.00 Oz. R-134a; 9.00 Oz. PAG-150; w/ OE Harrison Compressor	59003
	All Eng. - 32.00 Oz. R-134a; 9.00 Oz. PAG-46; w/ Denso Compressor	59007
97-94	All Eng. - 32.00 Oz. R-134a; 8.00 Oz. PAG-150; w/ OE Harrison Compressor	59003
	All Eng. - 32.00 Oz. R-134a; 8.00 Oz. PAG-46; w/ Denso Compressor	59007
93-91	All Eng. - 39.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
90-89	All Eng. - 46.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
88	All Eng. - 38.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
87-85	All Eng. - 46.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
73-68	8 Cyl. 7.7 Eng. - See Under Hood Decal	59000 ⁵⁹
67-64	8 Cyl. 7.0 Eng. - See Under Hood Decal	59000 ⁵⁹
63	8 Cyl. 6.4 Eng. - See Under Hood Decal	59000 ⁵⁹
	DTS	
11	8 Cyl. 4.6 Eng. - 22.88 Oz. R-134a; 4.75 Oz. PAG-46	59007
10-06	All Eng. - 22.88 Oz. R-134a; 4.75 Oz. PAG-46	59007
	ELDORADO	
02-98	All Eng. - 32.00 Oz. R-134a; 9.00 Oz. PAG-150; w/ OE Harrison Compressor	59003
	All Eng. - 32.00 Oz. R-134a; 9.00 Oz. PAG-46; w/ Denso Compressor	59007
97-94	All Eng. - 32.00 Oz. R-134a; 8.00 Oz. PAG-150; w/ OE Harrison Compressor	59003
	All Eng. - 32.00 Oz. R-134a; 8.00 Oz. PAG-46; w/ Denso Compressor	59007
93-91	All Eng. - 38.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
90-89	All Eng. - 38.50 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹

Continued on Next Page

⁵⁹ When retrofitting to R134a PAG Oil must be used.

CADILLAC

Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that A/C system has been properly cleaned, and new accumulator / filter drier has been installed. Specs are for total system capacities. Always refer to under hood decal as the primary source for refrigerant and lubricant information.

Year	Model	Lubricant
ELDORADO (Cont'd)		
88-86	All Eng. - 44.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
85	All Eng. - 56.00 Oz. R-12; 7.00 Oz. Mineral Oil	59000 ⁵⁹
84	8 Cyl. 4.1 Eng. - See Under Hood Decal	59000 ⁵⁹
73-70	8 Cyl. 8.2 Eng. - See Under Hood Decal	59000 ⁵⁹
69-68	8 Cyl. 7.7 Eng. - See Under Hood Decal	59000 ⁵⁹
67-65	8 Cyl. 7.0 Eng. - See Under Hood Decal	59000 ⁵⁹
ESCALADE		
13	8 Cyl. 6.2 Eng. - 25.60 Oz. R-134a; 7.10 Oz. PAG-46	59007
	8 Cyl. 6.2 Eng.; w/ Rear AC - 40.00 Oz. R-134a; 11.00 Oz. PAG-46	59007
	8 Cyl. 6.2 Eng. EXT; w/ Rear AC - 48.00 Oz. R-134a; 11.00 Oz. PAG-46	59007
12	8 Cyl. 6.0 Eng.; w/ Rear AC - 48.00 Oz. R-134a; 11.00 Oz. PAG-46	59007
	8 Cyl. 6.2 Eng.; w/o Rear AC - 25.60 Oz. R-134a; 7.10 Oz. PAG-46	59007
	8 Cyl. 6.2 Eng.; w/ Rear AC - 40.00 Oz. R-134a; 11.00 Oz. PAG-46	59007
	8 Cyl. 6.2 Eng. EXT; w/ Rear AC - 48.00 Oz. R-134a; 11.00 Oz. PAG-46	59007
11-10	8 Cyl. 6.0 Eng.; w/o Rear AC - 25.60 Oz. R-134a; 7.10 Oz. PAG-46	59007
	8 Cyl. 6.0 Eng.; w/ Rear AC - 40.00 Oz. R-134a; 11.00 Oz. PAG-46	59007
	8 Cyl. 6.0 Eng.; Hybrid; w/ Rear AC - 48.00 Oz. R-134a; 11.00 Oz. PAG-46	59007
	8 Cyl. 6.2 Eng.; w/o Rear AC - 25.60 Oz. R-134a; 7.10 Oz. PAG-46	59007
	8 Cyl. 6.2 Eng.; w/ Rear AC - 40.00 Oz. R-134a; 11.00 Oz. PAG-46	59007
	8 Cyl. 6.2 Eng. EXT; w/ Rear AC - 48.00 Oz. R-134a; 11.00 Oz. PAG-46	59007
09	All Eng.; w/o Rear AC - 26.00 Oz. R-134a; 7.10 Oz. PAG-46	59007
	All Eng.; w/ Rear AC - 40.00 Oz. R-134a; 11.00 Oz. PAG-46	59007
08-07	ExT - 25.50 Oz. R-134a; 8.00 Oz. PAG-46	59007
	All Eng.; w/o Rear AC - 26.00 Oz. R-134a; 7.10 Oz. PAG-46	59007
	Excl. ESV & EXT; w/ Rear AC - 40.00 Oz. R-134a; 10.00 Oz. PAG-46	59007
	All Eng.; w/ Rear AC - 40.00 Oz. R-134a; 11.00 Oz. PAG-46	59007
	EsV; w/ Rear AC - 48.00 Oz. R-134a; 11.00 Oz. PAG-46	59007
06-03	ExT - 25.50 Oz. R-134a; 8.00 Oz. PAG-46	59007
	Excl. ESV & EXT; w/ Rear AC - 43.00 Oz. R-134a; 11.00 Oz. PAG-46	59007
	EsV; w/ Rear AC - 48.00 Oz. R-134a; 11.00 Oz. PAG-46	59007
02	All Eng.; w/o Rear AC - 28.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
	All Eng.; w/ Rear AC - 42.00 Oz. R-134a; 11.00 Oz. PAG-46	59007
00-99	All Eng.; w/o Rear AC - 36.00 Oz. R-134a; 8.00 Oz. PAG-150; w/ HT6 Compressor; w/ OE Harrison Compressor	59003
	All Eng.; w/o Rear AC - 36.00 Oz. R-134a; 8.00 Oz. PAG-46; w/ Denso Compressor	59007
	All Eng.; w/ Rear AC - 64.00 Oz. R-134a; 11.00 Oz. PAG-150; w/ HT6 Compressor; w/ OE Harrison Compressor	59003
	All Eng.; w/ Rear AC - 64.00 Oz. R-134a; 11.00 Oz. PAG-46; w/ Denso Compressor	59007
FLEETWOOD / BROUGHAM		
96-94	All Eng.; RWD - 28.00 Oz. R-134a; 8.00 Oz. PAG-150; w/ OE Harrison Compressor	59003
	All Eng.; RWD - 28.00 Oz. R-134a; 8.00 Oz. PAG-46; w/ Denso Compressor	59007
93	All Eng.; RWD - 50.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
92-91	FLEETWOOD; FWD - 39.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
	BROUGHAM - 49.50 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
90-87	FLEETWOOD; FWD - 46.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
	BROUGHAM - 56.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
86	FLEETWOOD; FWD - 46.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
	BROUGHAM - 56.00 Oz. R-12; 7.00 Oz. Mineral Oil	59000 ⁵⁹
85	BROUGHAM - 56.00 Oz. R-12; 7.00 Oz. Mineral Oil	59000 ⁵⁹
73-70	8 Cyl. 7.7 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 8.2 Eng. - See Under Hood Decal	59000 ⁵⁹
69-68	8 Cyl. 7.7 Eng. - See Under Hood Decal	59000 ⁵⁹
67-65	8 Cyl. 7.0 Eng. - See Under Hood Decal	59000 ⁵⁹
SEVILLE		
04-01	All Eng. - 35.00 Oz. R-134a; 9.00 Oz. PAG-46; w/ Mitsubishi Compressor	59007
00-99	All Eng. - 32.00 Oz. R-134a; 9.00 Oz. PAG-46; w/ Mitsubishi Compressor	59007
98	All Eng. - 32.00 Oz. R-134a; 9.00 Oz. PAG-150; w/ HD6 Compressor; w/ OE Harrison Compressor	59003
	All Eng. - 32.00 Oz. R-134a; 9.00 Oz. PAG-46; w/ HD6 Compressor; w/ OE Harrison Compressor	59007
	All Eng. - 32.00 Oz. R-134a; 9.00 Oz. PAG-46; w/ Mitsubishi Compressor	59007
	All Eng. - 32.00 Oz. R-134a; 9.00 Oz. PAG-46; w/ Mitsubishi Compressor	59007
97-94	All Eng. - 32.00 Oz. R-134a; 8.00 Oz. PAG-150; w/ OE Harrison Compressor	59003
	All Eng. - 32.00 Oz. R-134a; 8.00 Oz. PAG-46; w/ Denso Compressor	59007
93-91	All Eng. - 38.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
90-89	All Eng. - 38.50 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
88	8 Cyl. 4.5 Eng. - w/ OE Harrison Compressor	59000 ⁵⁹

Continued on Next Page

⁵⁹ When retrofitting to R134a PAG Oil must be used.

Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that A/C system has been properly cleaned, and new accumulator / filter drier has been installed. Specs are for total system capacities. Always refer to under hood decal as the primary source for refrigerant and lubricant information.

Year	Model	Lubricant
SEVILLE (Cont'd)		
87-86	8 Cyl. 4.1 Eng. - w/ OE Harrison Compressor	59000 ⁵⁹
85	8 Cyl. 4.1 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.7 Eng. - See Under Hood Decal	59000 ⁵⁹
84	8 Cyl. 4.1 Eng. - See Under Hood Decal	59000 ⁵⁹
SRX		
12	6 Cyl. 3.6 Eng. - 26.00 Oz. R-134a; 3.70 Oz. PAG-46	59007
11	6 Cyl. 2.8 Eng. - 26.00 Oz. R-134a; 3.70 Oz. PAG-46	59007
	6 Cyl. 3.0 Eng. - 26.00 Oz. R-134a; 3.70 Oz. PAG-46	59007
10	6 Cyl. 2.8 Eng. - 25.60 Oz. R-134a; 3.70 Oz. PAG-46	59007
	6 Cyl. 3.0 Eng. - 25.75 Oz. R-134a; 3.70 Oz. PAG-46	59007
09	6 Cyl. 3.6 Eng.; w/o Rear AC - 20.16 Oz. R-134a; 6.09 Oz. PAG-46	59007
	8 Cyl. 4.6 Eng.; w/ Rear AC - 28.16 Oz. R-134a; 7.44 Oz. PAG-46	59007
08-04	All Eng.; w/o Rear AC - 20.16 Oz. R-134a; 6.09 Oz. PAG-46	59007
	All Eng.; w/ Rear AC - 28.16 Oz. R-134a; 7.44 Oz. PAG-46	59007
STS		
11	6 Cyl. 3.6 Eng. - 22.00 Oz. R-134a; 4.73 Oz. PAG-46	59007
10	6 Cyl. 3.6 Eng. - 22.00 Oz. R-134a; 4.73 Oz. PAG-46	59007
	8 Cyl. 4.6 Eng. - 22.00 Oz. R-134a; 4.73 Oz. PAG-46	59007
09-08	6 Cyl. 3.6 Eng. - 22.00 Oz. R-134a; 4.73 Oz. PAG-46	59007
	8 Cyl. 4.4 Eng. - 22.00 Oz. R-134a; 4.73 Oz. PAG-46	59007
	8 Cyl. 4.6 Eng. - 22.00 Oz. R-134a; 4.73 Oz. PAG-46	59007
07	All Eng. - 22.00 Oz. R-134a; 4.73 Oz. PAG-46	59007
06	6 Cyl. 3.6 Eng. - 22.00 Oz. R-134a; 4.73 Oz. PAG-46	59007
	8 Cyl. 4.4 Eng. - 22.00 Oz. R-134a; 4.73 Oz. PAG-46	59007
	8 Cyl. 4.6 Eng. - 22.00 Oz. R-134a; 4.73 Oz. PAG-46	59007
05	6 Cyl. 3.6 Eng. - 22.00 Oz. R-134a; 4.73 Oz. PAG-46	59007
	8 Cyl. 4.6 Eng. - 22.00 Oz. R-134a; 4.73 Oz. PAG-46	59007
XLR		
09-06	All Eng. - 18.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
05-04	All Eng. - 22.00 Oz. R-134a; 6.00 Oz. PAG-46	59007

CHEVROLET

Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that A/C system has been properly cleaned, and new accumulator / filter drier has been installed. Specs are for total system capacities. Always refer to under hood decal as the primary source for refrigerant and lubricant information.

Year	Model	Lubricant
AVEO		
11-10	4 Cyl. 1.2 Eng. - 18.00+/-1 Oz. R-134a; 5.00 Oz. PAG-46	59007
	4 Cyl. 1.6 Eng. - 18.00+/-1 Oz. R-134a; 6.80 Oz. PAG-46	59007
09	4 Cyl. 1.6 Eng. - 18.00+/-1 Oz. R-134a; 6.80 Oz. PAG-46	59007
08	All Eng. - 18.00+/-1 Oz. R-134a; 6.80 Oz. PAG-46	59007
07	All Eng. - 21.00+/-1 Oz. R-134a; 7.40 Oz. PAG-46	59007
06	All Eng. - 23.68 Oz. R-134a; 7.40 Oz. PAG-46	59007
05	All Eng. - 24.00 Oz. R-134a; 8.00 Oz. PAG-150; w/ OE Harrison Compressor V5	59003
04	All Eng. - 24.00 Oz. R-134a; 8.00 Oz. PAG-150; w/ OE Harrison Compressor V5	59003
	All Eng. - 35.00 Oz. R-134a; 8.75 Oz. PAG-46; w/ Mitsubishi Compressor	59007
BERETTA		
96-94	All Eng. - 36.00 Oz. R-134a; 9.00 Oz. PAG-150	59003
93	All Eng. - 42.00 Oz. R-12; 8.00 Oz. PAG-150	59003
	4 Cyl. 2.2 Eng. - 42.00 Oz. R-12; 8.00 Oz. PAG-150	59003
	4 Cyl. 2.3 Eng. - 42.00 Oz. R-12; 8.00 Oz. PAG-150	59003
	6 Cyl. 3.1 Eng. - 42.00 Oz. R-12; 8.00 Oz. PAG-150	59003
92	All Eng. - 42.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
	4 Cyl. 2.2 Eng. - 42.00 Oz. R-12; 8.00 Oz. PAG-150	59003
	4 Cyl. 2.3 Eng. - 42.00 Oz. R-12; 8.00 Oz. PAG-150	59003
	6 Cyl. 3.1 Eng. - 42.00 Oz. R-12; 8.00 Oz. PAG-150	59003
91	All Eng. - 36.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
90-88	All Eng. - 44.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
87	4 Cyl. 2.0 Eng. - 36.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
	6 Cyl. 2.8 Eng. - 26.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹

Continued on Next Page

⁵⁹ When retrofitting to R134a PAG Oil must be used.

CHEVROLET

Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that A/C system has been properly cleaned, and new accumulator / filter drier has been installed. Specs are for total system capacities. Always refer to under hood decal as the primary source for refrigerant and lubricant information.

Year	Model	Lubricant
CAMARO		
13	6 Cyl. 3.6 Eng. - 18.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
	8 Cyl. 6.2 Eng. - 18.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
12	6 Cyl. 3.6 Eng. - 16.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
	8 Cyl. 6.2 Eng. - 16.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
11	6 Cyl. 3.6 Eng. - 21.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
	8 Cyl. 6.2 Eng. - 21.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
10	6 Cyl. 3.6 Eng. - 21.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
	8 Cyl. 6.2 Eng. - 21.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
02-98	All Eng. - 24.00 Oz. R-134a; 9.00 Oz. PAG-150	59003
97	6 Cyl. 3.8 Eng. - 26.00 Oz. R-134a; 8.00 Oz. PAG-150; w/ OE Harrison Compressor	59003
	6 Cyl. 3.8 Eng. - 26.00 Oz. R-134a; 8.00 Oz. PAG-46; w/ Denso Compressor	59007
	8 Cyl. 5.7 Eng. - 32.00 Oz. R-134a; 8.00 Oz. PAG-150; w/ OE Harrison Compressor	59003
	8 Cyl. 5.7 Eng. - 32.00 Oz. R-134a; 8.00 Oz. PAG-46; w/ Denso Compressor	59007
96	6 Cyl. 3.8 Eng. - 28.00 Oz. R-134a; 8.00 Oz. PAG-150; w/ OE Harrison Compressor	59003
	6 Cyl. 3.8 Eng. - 28.00 Oz. R-134a; 8.00 Oz. PAG-46; w/ Denso Compressor	59007
	8 Cyl. 5.7 Eng. - 32.00 Oz. R-134a; 8.00 Oz. PAG-150; w/ OE Harrison Compressor	59003
	8 Cyl. 5.7 Eng. - 32.00 Oz. R-134a; 8.00 Oz. PAG-46; w/ Denso Compressor	59007
95-94	All Eng. - 32.00 Oz. R-134a; 8.00 Oz. PAG-150; w/ OE Harrison Compressor	59003
	All Eng. - 32.00 Oz. R-134a; 8.00 Oz. PAG-46; w/ Denso Compressor	59007
93	All Eng. - 32.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
	All Eng. - 32.00 Oz. R-134a; 8.00 Oz. PAG-150; w/ OE Harrison Compressor	59003
	All Eng. - 32.00 Oz. R-134a; 8.00 Oz. PAG-46; w/ Denso Compressor	59007
92-89	All Eng. - 36.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
88	6 Cyl. 2.8 Eng. - 54.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
	8 Cyl. 5.0 Eng. - 54.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
	8 Cyl. 5.7 Eng. - 54.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
87-85	All Eng. - 48.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
84-82	4 Cyl. 2.5 Eng. - See Under Hood Decal	59000 ⁵⁹
	6 Cyl. 2.8 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.0 Eng. - See Under Hood Decal	59000 ⁵⁹
73	6 Cyl. 4.1 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.0 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.7 Eng. - See Under Hood Decal	59000 ⁵⁹
72-71	6 Cyl. 4.1 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.0 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.7 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 6.6 Eng. - See Under Hood Decal	59000 ⁵⁹
70	6 Cyl. 3.8 Eng. - See Under Hood Decal	59000 ⁵⁹
	6 Cyl. 4.1 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.0 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.7 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 6.5 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 6.6 Eng. - See Under Hood Decal	59000 ⁵⁹
69	6 Cyl. 3.8 Eng. - See Under Hood Decal	59000 ⁵⁹
	6 Cyl. 4.1 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.0 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.4 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.7 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 6.5 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 7.0 Eng. - See Under Hood Decal	59000 ⁵⁹
68	6 Cyl. 3.8 Eng. - See Under Hood Decal	59000 ⁵⁹
	6 Cyl. 4.1 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.0 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.4 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.7 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 6.5 Eng. - See Under Hood Decal	59000 ⁵⁹
67	6 Cyl. 3.8 Eng. - See Under Hood Decal	59000 ⁵⁹
	6 Cyl. 4.1 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 4.6 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.0 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.4 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.7 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 6.5 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 6.5 Eng. - See Under Hood Decal	59000 ⁵⁹

Continued on Next Page

⁵⁹ When retrofitting to R134a PAG Oil must be used.

Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that A/C system has been properly cleaned, and new accumulator / filter drier has been installed. Specs are for total system capacities. Always refer to under hood decal as the primary source for refrigerant and lubricant information.

Year	Model	Lubricant
CAPRICE		
13-12	6 Cyl. 3.6 Eng. - 17.00 Oz. R-134a; 3.30-4.70 Oz. PAG-46	59007
	8 Cyl. 6.0 Eng. - 17.00 Oz. R-134a; 3.30-4.70 Oz. PAG-46	59007
11	8 Cyl. 6.0 Eng. - 20.00 Oz. R-134a; 3.30-4.70 Oz. PAG-46	59007
96-95	All Eng. - 28.00 Oz. R-134a; 8.00 Oz. PAG-150; w/ OE Harrison Compressor	59003
	All Eng. - 28.00 Oz. R-134a; 8.00 Oz. PAG-46; w/ Denso Compressor	59007
94	All Eng. - 28.00 Oz. R-134a; 8.00 Oz. PAG-150; w/ OE Harrison Compressor	59003
	All Eng. - 28.00 Oz. R-134a; 8.00 Oz. PAG-46; w/ Denso Compressor	59007
	8 Cyl. 5.7 Eng. - 28.00 Oz. R-134a; 8.00 Oz. PAG-150; w/ OE Harrison Compressor	59003
93-91	All Eng. - 50.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
90-89	All Eng. - 44.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
88-85	All Eng. - 56.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
84	6 Cyl. 3.8 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.0 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.7 Eng. - See Under Hood Decal	59000 ⁵⁹
72-70	8 Cyl. 5.0 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.7 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 6.6 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 7.4 Eng. - See Under Hood Decal	59000 ⁵⁹
69	6 Cyl. 4.1 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.0 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.4 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.7 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 6.5 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 7.0 Eng. - See Under Hood Decal	59000 ⁵⁹
68	6 Cyl. 4.1 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.0 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.4 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 6.5 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 7.0 Eng. - See Under Hood Decal	59000 ⁵⁹
67-66	6 Cyl. 4.1 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 4.6 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.4 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 6.5 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 7.0 Eng. - See Under Hood Decal	59000 ⁵⁹
CAVALIER		
05-03	All Eng. - 24.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
02	4 Cyl. 2.2 Eng. - 21.00 Oz. R-134a; 5.00 Oz. PAG-46; w/ CVC Compressor	59007
	4 Cyl. 2.2 Eng. - 24.00 Oz. R-134a; 9.00 Oz. PAG-150; w/ V5 Compressor	59003
	4 Cyl. 2.4 Eng. - 21.00 Oz. R-134a; 9.00 Oz. PAG-150	59003
01-95	All Eng. - 24.00 Oz. R-134a; 9.00 Oz. PAG-150	59003
94	All Eng. - 36.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
	4 Cyl. 2.2 Eng. - 36.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
	6 Cyl. 3.1 Eng. - 36.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
93-86	All Eng. - 36.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
85	All Eng. - 40.00 Oz. R-12; 7.00 Oz. Mineral Oil	59000 ⁵⁹
84-83	4 Cyl. 2.0 Eng. - See Under Hood Decal	59000 ⁵⁹
CELEBRITY		
90-85	All Eng. - 44.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
84-82	4 Cyl. 2.5 Eng. - See Under Hood Decal	59000 ⁵⁹
	6 Cyl. 2.8 Eng. - See Under Hood Decal	59000 ⁵⁹
CHEVELLE		
73-71	6 Cyl. 4.1 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.0 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.7 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 6.6 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 7.4 Eng. - See Under Hood Decal	59000 ⁵⁹
70	6 Cyl. 4.1 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.0 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.7 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 6.5 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 6.6 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 7.4 Eng. - See Under Hood Decal	59000 ⁵⁹
69	6 Cyl. 3.8 Eng. - See Under Hood Decal	59000 ⁵⁹

Continued on Next Page

⁵⁹ When retrofitting to R134a PAG Oil must be used.

CHEVROLET

Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that A/C system has been properly cleaned, and new accumulator / filter drier has been installed. Specs are for total system capacities. Always refer to under hood decal as the primary source for refrigerant and lubricant information.

Year	Model	Lubricant
CHEVELLE (Cont'd)		
69	6 Cyl. 4.1 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.0 Eng. - See Under Hood Decal	59000 ⁵⁹
68	8 Cyl. 5.7 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 6.5 Eng. - See Under Hood Decal	59000 ⁵⁹
	6 Cyl. 3.8 Eng. - See Under Hood Decal	59000 ⁵⁹
	6 Cyl. 4.1 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.0 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.3 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.4 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.7 Eng. - See Under Hood Decal	59000 ⁵⁹
67	8 Cyl. 6.5 Eng. - See Under Hood Decal	59000 ⁵⁹
	6 Cyl. 3.8 Eng. - See Under Hood Decal	59000 ⁵⁹
	6 Cyl. 4.1 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 4.6 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.3 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.4 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 6.5 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 6.5 Eng. - See Under Hood Decal	59000 ⁵⁹
66	6 Cyl. 3.2 Eng. - See Under Hood Decal	59000 ⁵⁹
	6 Cyl. 3.8 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 4.6 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.3 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.4 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 6.5 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 6.5 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 6.5 Eng. - See Under Hood Decal	59000 ⁵⁹
65	6 Cyl. 3.2 Eng. - See Under Hood Decal	59000 ⁵⁹
	6 Cyl. 3.8 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 4.6 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.4 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 6.5 Eng. - See Under Hood Decal	59000 ⁵⁹
CHEVY II		
67	6 Cyl. 4.1 Eng. - See Under Hood Decal	59000 ⁵⁹
66-63	6 Cyl. 3.2 Eng. - See Under Hood Decal	59000 ⁵⁹
62	6 Cyl. 3.8 Eng. - See Under Hood Decal	59000 ⁵⁹
	6 Cyl. 3.2 Eng. - See Under Hood Decal	59000 ⁵⁹
CITATION		
85-82	4 Cyl. 2.5 Eng. - See Under Hood Decal	59000 ⁵⁹
	6 Cyl. 2.8 Eng. - See Under Hood Decal	59000 ⁵⁹
CLASSIC		
05-04	4 Cyl. 2.2 Eng. - 22.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
COBALT		
10-09	4 Cyl. 2.0 Eng. - 14.50 Oz. R-134a; 4.00 Oz. PAG-46	59007
	4 Cyl. 2.2 Eng. - 14.50 Oz. R-134a; 4.00 Oz. PAG-46	59007
08-07	All Eng. - 14.50 Oz. R-134a; 4.00 Oz. PAG-46	59007
	4 Cyl. 2.4 Eng. - 14.50 Oz. R-134a; 4.00 Oz. PAG-46	59007
06	All Eng. - 14.50 Oz. R-134a; 5.00 Oz. PAG-46	59007
05	4 Cyl. 2.0 Eng. - 14.50 Oz. R-134a; 5.00 Oz. PAG-46	59007
	4 Cyl. 2.2 Eng. - 16.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
CORSICA		
96-94	All Eng. - 36.00 Oz. R-134a; 9.00 Oz. PAG-150	59003
93	All Eng. - 42.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
	4 Cyl. 2.2 Eng. - 42.00 Oz. R-134; 8.00 Oz. PAG-150	59003
	6 Cyl. 3.1 Eng. - 42.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
92	All Eng. - 42.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
	4 Cyl. 2.2 Eng. - 42.00 Oz. R-12; 8.00 Oz. PAG-150	59003
	6 Cyl. 3.1 Eng. - 42.00 Oz. R-12; 8.00 Oz. PAG-150	59003
91	All Eng. - 36.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
90-88	All Eng. - 44.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
87	4 Cyl. 2.0 Eng. - 36.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
	6 Cyl. 2.8 Eng. - 36.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
CORVETTE		
13	8 Cyl. 6.2 Eng. - 17.60 Oz. R-134a; 5.00 Oz. PAG-46	59007
	8 Cyl. 7.0 Eng. - 17.60 Oz. R-134a; 5.00 Oz. PAG-46	59007
12	8 Cyl. 6.2 Eng. - 17.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
	8 Cyl. 7.0 Eng. - 17.00 Oz. R-134a; 5.00 Oz. PAG-46	59007

Continued on Next Page

⁵⁹ When retrofitting to R134a PAG Oil must be used.

Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that A/C system has been properly cleaned, and new accumulator / filter drier has been installed. Specs are for total system capacities. Always refer to under hood decal as the primary source for refrigerant and lubricant information.

Year	Model	Lubricant
CORVETTE (Cont'd)		
11	8 Cyl. 6.2 Eng. - 17.60 Oz. R-134a; 5.00 Oz. PAG-46	59007
	8 Cyl. 7.0 Eng. - 17.60 Oz. R-134a; 5.00 Oz. PAG-46	59007
10-06	All Eng. - 17.60 Oz. R-134a; 5.00 Oz. PAG-46	59007
05	All Eng. - 22.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
04-02	All Eng. - 28.00 Oz. R-134a; 9.00 Oz. PAG-150	59003
01-00	All Eng. - 24.00 Oz. R-134a; 9.00 Oz. PAG-150	59003
99-97	All Eng. - 26.00 Oz. R-134a; 9.00 Oz. PAG-150	59003
96-94	All Eng. - 32.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
93-90	All Eng. - 36.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
89-88	All Eng. - 44.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
87-85	All Eng. - 52.00 Oz. R-12; 7.00 Oz. Mineral Oil	59000 ⁵⁹
84-69	8 Cyl. 5.7 Eng. - See Under Hood Decal	59000
68-66	8 Cyl. 5.4 Eng. - See Under Hood Decal	59000 ⁵⁹
65	8 Cyl. - See Under Hood Decal	59000 ⁵⁹
CRUZE		
13-11	4 Cyl. 1.4 Eng. - 22.08 Oz. R-134a; 4.23 Oz. PAG-46	59007
	4 Cyl. 1.8 Eng. - 22.08 Oz. R-134a; 4.23 Oz. PAG-46	59007
EL CAMINO		
87-85	6 Cyl. 4.3 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.0 Eng. - See Under Hood Decal	59000 ⁵⁹
84	6 Cyl. 3.8 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.0 Eng. - See Under Hood Decal	59000 ⁵⁹
73	6 Cyl. 4.1 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.0 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.7 Eng. - See Under Hood Decal	59000 ⁵⁹
72-70	6 Cyl. 4.1 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.0 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.7 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 6.6 Eng. - See Under Hood Decal	59000 ⁵⁹
69	6 Cyl. 3.8 Eng. - See Under Hood Decal	59000 ⁵⁹
	6 Cyl. 4.1 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.0 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.3 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.7 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 6.5 Eng. - See Under Hood Decal	59000 ⁵⁹
68	6 Cyl. 3.8 Eng. - See Under Hood Decal	59000 ⁵⁹
	6 Cyl. 4.1 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.0 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.4 Eng. - See Under Hood Decal	59000 ⁵⁹
67-66	6 Cyl. 3.8 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 4.6 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.4 Eng. - See Under Hood Decal	59000 ⁵⁹
65	6 Cyl. 3.8 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. - See Under Hood Decal	59000 ⁵⁹
IMPALA		
13-12	6 Cyl. 3.6 Eng. - 21.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
11	6 Cyl. 3.5 Eng. - 21.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
	6 Cyl. 3.9 Eng. - 20.40 Oz. R-134a; 5.00 Oz. PAG-46	59007
10	6 Cyl. 3.9 Eng. - 20.40 Oz. R-134a; 5.00 Oz. PAG-46	59007
09	6 Cyl. 3.5 Eng. - 20.40 Oz. R-134a; 5.00 Oz. PAG-46	59007
	6 Cyl. 3.9 Eng. - 20.40 Oz. R-134a; 5.00 Oz. PAG-46	59007
	8 Cyl. 5.3 Eng. - 20.40 Oz. R-134a; 5.00 Oz. PAG-46	59007
08	6 Cyl. - 20.40 Oz. R-134a; 5.00 Oz. PAG-46	59007
	6 Cyl. 3.9 Eng. - 20.40 Oz. R-134a; 5.00 Oz. PAG-46	59007
	8 Cyl. 5.3 Eng. - 22.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
07-06	All Eng. - 20.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
	6 Cyl. 3.9 Eng. - 21.60 Oz. R-134a; 5.00 Oz. PAG-46	59007
05-04	All Eng. - 37.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
03-00	All Eng. - 36.00 Oz. R-134a; 9.00 Oz. PAG-150	59003
85	6 Cyl. 3.8 Eng. - See Under Hood Decal	59000 ⁵⁹
	6 Cyl. 4.3 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.0 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.7 Eng. - See Under Hood Decal	59000 ⁵⁹

Continued on Next Page

⁵⁹ When retrofitting to R134a PAG Oil must be used.

CHEVROLET

Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that A/C system has been properly cleaned, and new accumulator / filter drier has been installed. Specs are for total system capacities. Always refer to under hood decal as the primary source for refrigerant and lubricant information.

Year	Model	Lubricant
IMPALA (Cont'd)		
84-83	6 Cyl. 3.8 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.0 Eng. - See Under Hood Decal	59000 ⁵⁹
82-80	8 Cyl. 5.7 Eng. - See Under Hood Decal	59000 ⁵⁹
	6 Cyl. 3.8 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 4.4 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.0 Eng. - See Under Hood Decal	59000 ⁵⁹
79-77	8 Cyl. 5.7 Eng. - See Under Hood Decal	59000 ⁵⁹
	6 Cyl. 4.1 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.0 Eng. - See Under Hood Decal	59000 ⁵⁹
76-74	8 Cyl. 5.7 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 6.6 Eng. - See Under Hood Decal	59000 ⁵⁹
73	8 Cyl. 7.4 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.0 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.7 Eng. - See Under Hood Decal	59000 ⁵⁹
67-66	8 Cyl. 6.6 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 7.4 Eng. - See Under Hood Decal	59000 ⁵⁹
	6 Cyl. 4.1 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 4.6 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.4 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 6.5 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 7.0 Eng. - See Under Hood Decal	59000 ⁵⁹
IMPALA SS		
13-12	6 Cyl. 3.6 Eng. - 21.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
11	6 Cyl. 3.5 Eng. - 21.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
	6 Cyl. 3.9 Eng. - 19.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
09	8 Cyl. 5.3 Eng. - 19.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
96-94	All Eng. - 28.00 Oz. R-134a; 8.00 Oz. PAG-150; w/ OE Harrison Compressor	59003
	All Eng. - 28.00 Oz. R-134a; 8.00 Oz. PAG-46; w/ Denso Compressor	59007
LUMINA		
01-98	All Eng. - 36.00 Oz. R-134a; 9.00 Oz. PAG-150	59003
97	All Eng. - 36.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
96-94	All Eng. - 32.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
93	All Eng. - 36.00 Oz. R-12; 9.00 Oz. Mineral Oil	59000 ⁵⁹
92-90	All Eng. - 36.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
LUMINA APV		
96	All Eng.; w/o Rear AC - 36.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
	All Eng.; w/ Rear AC - 48.00 Oz. R-134a; 11.00 Oz. PAG-150	59003
95-94	All Eng.; w/o Rear AC - 36.00 Oz. R-134a; 8.00 Oz. PAG-150; w/ OE Harrison Compressor	59003
	All Eng.; w/o Rear AC - 36.00 Oz. R-134a; 8.00 Oz. PAG-46; w/ Denso Compressor	59007
	All Eng.; w/ Rear AC - 48.00 Oz. R-134a; 11.00 Oz. PAG-150; w/ OE Harrison Compressor	59003
	All Eng.; w/ Rear AC - 48.00 Oz. R-134a; 11.00 Oz. PAG-46; w/ Denso Compressor	59007
93	All Eng.; w/o Rear AC - 42.00 Oz. R-134a; 8.00 Oz. PAG-150; w/ OE Harrison Compressor	59003
	All Eng.; w/o Rear AC - 42.00 Oz. R-134a; 8.00 Oz. PAG-46; w/ Denso Compressor	59007
	All Eng.; w/ Rear AC - 56.00 Oz. R-134a; 11.00 Oz. PAG-150; w/ OE Harrison Compressor	59003
	All Eng.; w/ Rear AC - 56.00 Oz. R-134a; 11.00 Oz. PAG-46; w/ Denso Compressor	59007
	6 Cyl. 3.1 Eng. - w/ R-12; w/ OE Harrison Compressor	59000 ⁵⁹
	6 Cyl. 3.8 Eng. - w/ R-12; w/ OE Harrison Compressor	59000 ⁵⁹
92	All Eng.; w/o Rear AC - 51.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
	All Eng.; w/ Rear AC - 67.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
91	All Eng.; w/o Rear AC - 51.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
90	All Eng.; w/o Rear AC - 44.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
MALIBU / MALIBU MAXX		
12	4 Cyl. 2.4 Eng. - 18.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
	6 Cyl. 3.6 Eng. - 18.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
11	4 Cyl. 2.4 Eng. - 17.60 Oz. R-134a; 5.00 Oz. PAG-46	59007
	6 Cyl. 3.6 Eng. - 17.60 Oz. R-134a; 5.00 Oz. PAG-46	59007
10	4 Cyl. 2.4 Eng. - 17.60 Oz. R-134a; 5.00 Oz. PAG-46	59007
	6 Cyl. 3.5 Eng. - 21.60 Oz. R-134a; 5.00 Oz. PAG-46	59007
	6 Cyl. 3.6 Eng. - 17.60 Oz. R-134a; 5.00 Oz. PAG-46	59007
09-04	All Eng. - 17.60 Oz. R-134a; 5.00 Oz. PAG-46	59007
03-02	All Eng. - 22.00 Oz. R-134a; 9.00 Oz. PAG-150	59003
01-97	All Eng. - 28.00 Oz. R-134a; 9.00 Oz. PAG-150	59003

Continued on Next Page

⁵⁹ When retrofitting to R134a PAG Oil must be used.

Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that A/C system has been properly cleaned, and new accumulator / filter drier has been installed. Specs are for total system capacities. Always refer to under hood decal as the primary source for refrigerant and lubricant information.

Year	Model	Lubricant
MALIBU / MALIBU MAXX (Cont'd)		
73-72	6 Cyl. 4.1 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.0 Eng. - See Under Hood Decal	59000
	8 Cyl. 5.7 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 6.6 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 7.4 Eng. - See Under Hood Decal	59000 ⁵⁹
67	6 Cyl. 3.8 Eng. - See Under Hood Decal	59000 ⁵⁹
	6 Cyl. 4.1 Eng. - See Under Hood Decal	59000
	8 Cyl. 4.6 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.4 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 6.5 Eng. - See Under Hood Decal	59000 ⁵⁹
METRO		
01	All Eng. - 21.00 Oz. R-134a; 5.00 Oz. PAG-100	59002
00	3 Cyl. 1.0 Eng. - 19.00 Oz. R-134a; 3.40 Oz. PAG-100	59002
	4 Cyl. 1.3 Eng. - 19.00 Oz. R-134a; 3.40 Oz. PAG-100	59002
99-98	All Eng. - 21.00 Oz. R-134a; 3.50 Oz. PAG-100	59002
92	4 Cyl. 1.3 Eng. - 18.00 Oz. R-12; See Under Hood Decal; Mineral Oil	59000 ⁵⁹
MONTE CARLO		
07-06	All Eng. - 21.60 Oz. R-134a; 5.00 Oz. PAG-46	59007
05-04	All Eng. - 37.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
03-98	All Eng. - 36.00 Oz. R-134a; 9.00 Oz. PAG-150	59003
97	All Eng. - 36.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
96-95	All Eng. - 32.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
88	6 Cyl. 4.3 Eng. - 60.00 Oz. R-12; See Under Hood Decal; Mineral Oil	59000 ⁵⁹
	8 Cyl. 5.0 Eng. - 60.00 Oz. R-12; See Under Hood Decal; Mineral Oil	59000 ⁵⁹
87-86	All Eng. - 56.00 Oz. R-12; 7.00 Oz. Mineral Oil	59000 ⁵⁹
85	All Eng. - 52.00 Oz. R-12; 7.00 Oz. Mineral Oil	59000 ⁵⁹
	All Eng. - 52.00 Oz. R-12; 7.00 Oz. Mineral Oil	59000 ⁵⁹
73-70	8 Cyl. 5.7 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 6.6 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 7.4 Eng. - See Under Hood Decal	59000 ⁵⁹
NOVA		
88-87	All Eng. - 26.00 Oz. R-12; 7.00 Oz. Mineral Oil	59000 ⁵⁹
86	All Eng. - 27.00 Oz. R-12; 7.00 Oz. Mineral Oil	59000 ⁵⁹
73-67	6 Cyl. 4.1 Eng. - See Under Hood Decal	59000 ⁵⁹
66-63	6 Cyl. 3.2 Eng. - See Under Hood Decal	59000 ⁵⁹
	6 Cyl. 3.8 Eng. - See Under Hood Decal	59000 ⁵⁹
62	6 Cyl. 3.2 Eng. - See Under Hood Decal	59000 ⁵⁹
PRIZM		
02-98	All Eng. - 26.50 Oz. R-134a; 8.00 Oz. PAG-150	59003
SONIC		
13-12	4 Cyl. 1.4 Eng. - 18.00 Oz. R-134a; 3.70 Oz. PAG-46	59007
	4 Cyl. 1.8 Eng. - 18.00 Oz. R-134a; 3.70 Oz. PAG-46	59007
SPRINT		
88-85	3 Cyl. 1.0 Eng. - See Under Hood Decal	59000 ⁵⁹
VENTURE		
05-01	All Eng.; w/o Rear AC - 27.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
	All Eng.; w/ Rear AC - 35.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
00-97	All Eng.; w/o Rear AC - 32.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
	All Eng.; w/ Rear AC - 46.00 Oz. R-134a; 11.00 Oz. PAG-150	59003
VOLT		
13-11	4 Cyl. 1.4 Eng.; Hybrid - 34.00 Oz. R-134a; 6.10 Oz. Hybrid Oil	59889

CHEVROLET LIGHT TRUCK

Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that A/C system has been properly cleaned, and new accumulator / filter drier has been installed. Specs are for total system capacities. Always refer to under hood decal as the primary source for refrigerant and lubricant information.

Year	Model	Lubricant
ASTRO		
05-94	All Eng.; w/o Rear AC - 32.00 Oz. R-134a; 8.00 Oz. PAG-150; w/ OE Harrison Compressor	59003
	All Eng.; w/o Rear AC - 32.00 Oz. R-134a; 8.00 Oz. PAG-46; w/ Denso Compressor	59007
	All Eng.; w/ Rear AC - 48.00 Oz. R-134a; 11.00 Oz. PAG-150; w/ OE Harrison Compressor	59003

Continued on Next Page

⁵⁹ When retrofitting to R134a PAG Oil must be used.

CHEVROLET LIGHT TRUCK

Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that A/C system has been properly cleaned, and new accumulator / filter drier has been installed. Specs are for total system capacities. Always refer to under hood decal as the primary source for refrigerant and lubricant information.

Year	Model	Lubricant
ASTRO (Cont'd)		
05-94	All Eng.; w/ Rear AC - 48.00 Oz. R-134a; 11.00 Oz. PAG-46; w/ Denso Compressor	59007
93-92	All Eng.; w/o Rear AC - 48.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
	All Eng.; w/ Rear AC - 60.00 Oz. R-12; 10.00 Oz. Mineral Oil	59000 ⁵⁹
91-90	All Eng.; w/o Rear AC - 36.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
	All Eng.; w/ Rear AC - 60.00 Oz. R-12; 10.00 Oz. Mineral Oil	59000 ⁵⁹
89	All Eng.; w/o Rear AC - 32.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
	All Eng.; w/ Rear AC - 60.00 Oz. R-12; 10.00 Oz. Mineral Oil	59000 ⁵⁹
88-85	All Eng.; w/o Rear AC - 32.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
	All Eng.; w/ Rear AC - 48.00 Oz. R-12; 9.00 Oz. Mineral Oil	59000 ⁵⁹
AVALANCHE		
13	8 Cyl. 5.3 Eng.; w/o Rear AC - 25.60 Oz. R-134a; 7.10 Oz. PAG-46	59007
	8 Cyl. 5.3 Eng.; w/ Rear AC - 40.00 Oz. R-134a; 11.00 Oz. PAG-46	59007
12	8 Cyl. 5.3 Eng. - 24.00 Oz. R-134a; 7.10 Oz. PAG-46	59007
	8 Cyl. 5.3 Eng. - 38.00 Oz. R-134a; 11.00 Oz. PAG-46	59007
11	8 Cyl. 5.3 Eng.; w/o Rear AC - 24.00 Oz. R-134a; 7.10 Oz. PAG-46	59007
	8 Cyl. 5.3 Eng.; w/ Rear AC - 38.00 Oz. R-134a; 11.00 Oz. PAG-46	59007
10	8 Cyl. 5.3 Eng.; w/o Rear AC - 24.00 Oz. R-134a; 7.10 Oz. PAG-46	59007
	8 Cyl. 5.3 Eng.; w/ Rear AC - 38.00 Oz. R-134a; 11.00 Oz. PAG-46	59007
09	8 Cyl. 5.3 Eng.; w/ Rear AC - 38.00 Oz. R-134a; 11.00 Oz. PAG-46	59007
	8 Cyl. 5.3 Eng.; w/o Rear AC - 24.00 Oz. R-134a; 7.10 Oz. PAG-46	59007
	8 Cyl. 5.3 Eng.; w/ Rear AC - 38.00 Oz. R-134a; 11.00 Oz. PAG-46	59007
	8 Cyl. 6.0 Eng.; w/o Rear AC - 24.00 Oz. R-134a; 7.10 Oz. PAG-46	59007
	8 Cyl. 6.0 Eng.; w/ Rear AC - 38.00 Oz. R-134a; 11.00 Oz. PAG-46	59007
08	All Eng.; w/o Rear AC - 24.00 Oz. R-134a; 7.10 Oz. PAG-46	59007
	All Eng.; w/ Rear AC - 38.00 Oz. R-134a; 11.00 Oz. PAG-46	59007
07	All Eng.; w/o Rear AC - 24.00 Oz. R-134a; 7.10 Oz. PAG-46	59007
	8 Cyl. 5.3 Eng.; w/ Rear AC - 38.00 Oz. R-134a; 11.00 Oz. PAG-46	59007
06-05	8 Cyl. 5.3 Eng.; w/o Rear AC - 26.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
	8 Cyl. 5.3 Eng.; w/ Rear AC - 43.00 Oz. R-134a; 11.00 Oz. PAG-46	59007
	8 Cyl. 8.1 Eng. - 26.00 Oz. R-134a; 7.10 Oz. PAG-46	59007
	8 Cyl. 8.1 Eng.; w/ Rear AC - 43.00 Oz. R-134a; 11.00 Oz. PAG-46	59007
04-03	8 Cyl. 5.3 Eng.; w/o Rear AC - 26.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
	8 Cyl. 5.3 Eng.; w/ Rear AC - 43.00 Oz. R-134a; 11.00 Oz. PAG-46	59007
	8 Cyl. 8.1 Eng. - 26.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
	8 Cyl. 8.1 Eng.; w/ Rear AC - 43.00 Oz. R-134a; 11.00 Oz. PAG-46	59007
02	8 Cyl. 5.3 Eng. - 29.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
	8 Cyl. 5.3 Eng.; w/ Rear AC - 43.00 Oz. R-134a; 11.00 Oz. PAG-46	59007
	8 Cyl. 8.1 Eng. - 29.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
	8 Cyl. 8.1 Eng.; w/ Rear AC - 43.00 Oz. R-134a; 11.00 Oz. PAG-46	59007
CAPTIVA / CAPTIVA SPORT		
13	4 Cyl. 2.4 Eng. - 22.00 Oz. R-134a; 5.30 Oz. PAG-46	59007
12	4 Cyl. 2.4 Eng. - 22.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
	6 Cyl. 3.0 Eng.; LAF - 22.00 Oz. R-134a; 5.30 Oz. PAG-46	59007
COLORADO		
12	4 Cyl. 2.9 Eng. - 21.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
	5 Cyl. 3.7 Eng. - 21.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
	8 Cyl. 5.3 Eng. - 19.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
11	4 Cyl. 2.9 Eng. - 21.20 Oz. R-134a; 4.00 Oz. PAG-46	59007
	5 Cyl. 3.7 Eng. - 21.20 Oz. R-134a; 4.00 Oz. PAG-46	59007
	8 Cyl. 5.3 Eng. - 19.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
10-09	4 Cyl. 2.9 Eng. - 21.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
	5 Cyl. 3.7 Eng. - 21.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
	8 Cyl. 5.3 Eng. - 19.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
08	All Eng. - 21.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
07	All Eng. - 26.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
06	All Eng. - 25.50 Oz. R-134a; 4.00 Oz. PAG-46	59007
05-04	All Eng. - 24.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
EQUINOX		
13	4 Cyl. 2.4 Eng. - 23.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
	6 Cyl. 3.6 Eng. - 23.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
12	4 Cyl. 2.4 Eng. - 22.88 Oz. R-134a; 5.00 Oz. PAG-46	59007
	6 Cyl. 3.0 Eng. - 22.88 Oz. R-134a; 5.00 Oz. PAG-46	59007
11-10	4 Cyl. 2.4 Eng. - 22.88 Oz. R-134a; 4.00 Oz. PAG-46	59007

Continued on Next Page

⁵⁹ When retrofitting to R134a PAG Oil must be used.

CHEVROLET LIGHT TRUCK

Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that A/C system has been properly cleaned, and new accumulator / filter drier has been installed. Specs are for total system capacities. Always refer to under hood decal as the primary source for refrigerant and lubricant information.

Year	Model	Lubricant	
EQUINOX (Cont'd)			
11-10 09	6 Cyl. 3.0 Eng. - 22.88 Oz. R-134a; 4.00 Oz. PAG-46	59007	
	6 Cyl. 3.4 Eng. - 20.80 Oz. R-134a; 4.40 Oz. PAG-46	59007	
	6 Cyl. 3.6 Eng. - 20.80 Oz. R-134a; 4.40 Oz. PAG-46	59007	
08-06 05	All Eng. - 20.80 Oz. R-134a; 4.40 Oz. PAG-46	59007	
	All Eng. - 28.00 Oz. R-134a; 7.00 Oz. PAG-46	59007	
FULLSIZE PICKUP			
13	6 Cyl. 4.3 Eng. - 24.69 Oz. R-134a; 7.10 Oz. PAG-46	59007	
	8 Cyl. 4.8 Eng. - 24.69 Oz. R-134a; 7.10 Oz. PAG-46	59007	
	8 Cyl. 5.3 Eng. - 24.69 Oz. R-134a; 7.10 Oz. PAG-46	59007	
	8 Cyl. 6.0 Eng. - 24.69 Oz. R-134a; 7.10 Oz. PAG-46	59007	
	8 Cyl. 6.2 Eng. - 24.69 Oz. R-134a; 7.10 Oz. PAG-46	59007	
	8 Cyl. 6.6 Eng. - 24.69 Oz. R-134a; 7.10 Oz. PAG-46	59007	
	12	6 Cyl. 4.3 Eng. - 26.00 Oz. R-134a; 7.10 Oz. PAG-46	59007
		6 Cyl. 4.3 Eng. - 40.00 Oz. R-134a; 11.00 Oz. PAG-46	59007
6 Cyl. 4.8 Eng. - 40.00 Oz. R-134a; 11.00 Oz. PAG-46		59007	
6 Cyl. 5.3 Eng. - 40.00 Oz. R-134a; 11.00 Oz. PAG-46		59007	
6 Cyl. 6.0 Eng. - 40.00 Oz. R-134a; 11.00 Oz. PAG-46		59007	
6 Cyl. 6.2 Eng. - 40.00 Oz. R-134a; 11.00 Oz. PAG-46		59007	
8 Cyl. 4.8 Eng. - 26.00 Oz. R-134a; 7.10 Oz. PAG-46		59007	
8 Cyl. 5.3 Eng. - 26.00 Oz. R-134a; 7.10 Oz. PAG-46		59007	
8 Cyl. 6.0 Eng. - 26.00 Oz. R-134a; 7.10 Oz. PAG-46		59007	
8 Cyl. 6.2 Eng. - 26.00 Oz. R-134a; 7.10 Oz. PAG-46		59007	
11	6 Cyl. 4.3 Eng.; w/o Rear AC - 25.60 Oz. R-134a; 8.00 Oz. PAG-46	59007	
	6 Cyl. 4.3 Eng.; w/ Rear AC - 40.00 Oz. R-134a; 11.00 Oz. PAG-46	59007	
	8 Cyl. 4.8 Eng.; w/o Rear AC - 25.60 Oz. R-134a; 7.10 Oz. PAG-46	59007	
	8 Cyl. 4.8 Eng.; w/ Rear AC - 40.00 Oz. R-134a; 11.00 Oz. PAG-46	59007	
	8 Cyl. 5.3 Eng. - 26.00 Oz. R-134a; 7.10 Oz. PAG-46	59007	
	8 Cyl. 5.3 Eng.; w/ Rear AC - 40.00 Oz. R-134a; 11.00 Oz. PAG-46	59007	
	8 Cyl. 6.0 Eng. - 26.00 Oz. R-134a; 7.10 Oz. PAG-46	59007	
	8 Cyl. 6.0 Eng.; w/ Rear AC - 40.00 Oz. R-134a; 11.00 Oz. PAG-46	59007	
	8 Cyl. 6.2 Eng. - 26.00 Oz. R-134a; 7.10 Oz. PAG-46	59007	
	8 Cyl. 6.2 Eng.; w/ Rear AC - 40.00 Oz. R-134a; 11.00 Oz. PAG-46	59007	
10	8 Cyl. 6.6 Eng. - 26.00 Oz. R-134a; 7.10 Oz. PAG-46	59007	
	8 Cyl. 6.6 Eng.; w/ Rear AC - 40.00 Oz. R-134a; 11.00 Oz. PAG-46	59007	
	6 Cyl. 4.3 Eng.; w/o Rear AC - 25.60 Oz. R-134a; 8.00 Oz. PAG-46	59007	
	6 Cyl. 4.3 Eng.; w/ Rear AC - 40.00 Oz. R-134a; 11.00 Oz. PAG-46	59007	
	8 Cyl. 4.8 Eng.; w/o Rear AC - 25.60 Oz. R-134a; 7.10 Oz. PAG-46	59007	
	8 Cyl. 4.8 Eng.; w/ Rear AC - 40.00 Oz. R-134a; 11.00 Oz. PAG-46	59007	
	8 Cyl. 5.3 Eng.; w/o Rear AC - 25.60 Oz. R-134a; 7.10 Oz. PAG-46	59007	
	8 Cyl. 5.3 Eng.; w/ Rear AC - 40.00 Oz. R-134a; 11.00 Oz. PAG-46	59007	
	8 Cyl. 6.0 Eng.; w/o Rear AC - 25.60 Oz. R-134a; 7.10 Oz. PAG-46	59007	
	8 Cyl. 6.0 Eng.; w/ Rear AC - 40.00 Oz. R-134a; 11.00 Oz. PAG-46	59007	
09	8 Cyl. 6.2 Eng.; w/o Rear AC - 25.60 Oz. R-134a; 7.10 Oz. PAG-46	59007	
	8 Cyl. 6.6 Eng.; w/o Rear AC - 25.60 Oz. R-134a; 7.10 Oz. PAG-46	59007	
	6 Cyl. 4.3 Eng.; w/o Rear AC - 25.60 Oz. R-134a; 8.00 Oz. PAG-46	59007	
	6 Cyl. 4.3 Eng.; w/ Rear AC - 40.00 Oz. R-134a; 11.00 Oz. PAG-46	59007	
	8 Cyl. 4.8 Eng.; w/o Rear AC - 25.60 Oz. R-134a; 7.10 Oz. PAG-46	59007	
	8 Cyl. 4.8 Eng.; w/ Rear AC - 40.00 Oz. R-134a; 11.00 Oz. PAG-46	59007	
	8 Cyl. 5.3 Eng.; w/o Rear AC - 25.60 Oz. R-134a; 7.10 Oz. PAG-46	59007	
	8 Cyl. 5.3 Eng.; w/ Rear AC - 40.00 Oz. R-134a; 11.00 Oz. PAG-46	59007	
	8 Cyl. 6.0 Eng.; w/o Rear AC - 25.60 Oz. R-134a; 7.10 Oz. PAG-46	59007	
	8 Cyl. 6.0 Eng.; w/ Rear AC - 40.00 Oz. R-134a; 11.00 Oz. PAG-46	59007	
08	8 Cyl. 6.6 Eng.; w/o Rear AC - 25.60 Oz. R-134a; 7.10 Oz. PAG-46	59007	
	6 Cyl. 4.3 Eng.; w/o Rear AC - 25.60 Oz. R-134a; 7.10 Oz. PAG-46	59007	
	6 Cyl. 4.3 Eng.; w/ Rear AC - 40.00 Oz. R-134a; 11.00 Oz. PAG-46	59007	
	8 Cyl. 5.3 Eng.; w/o Rear AC - 25.60 Oz. R-134a; 8.00 Oz. PAG-46	59007	
	8 Cyl. 5.3 Eng.; w/ Rear AC - 40.00 Oz. R-134a; 11.00 Oz. PAG-46	59007	
	8 Cyl. 6.0 Eng.; w/o Rear AC - 25.60 Oz. R-134a; 7.10 Oz. PAG-46	59007	
07	8 Cyl. 6.0 Eng.; w/ Rear AC - 40.00 Oz. R-134a; 11.00 Oz. PAG-46	59007	
	6 Cyl. 4.3 Eng.; w/o Rear AC - 25.60 Oz. R-134a; 8.00 Oz. PAG-46	59007	
	6 Cyl. 4.3 Eng.; w/ Rear AC - 40.00 Oz. R-134a; 11.00 Oz. PAG-46	59007	
	8 Cyl. 5.3 Eng.; w/o Rear AC - 25.60 Oz. R-134a; 8.00 Oz. PAG-46	59007	
	8 Cyl. 5.3 Eng.; w/ Rear AC - 40.00 Oz. R-134a; 11.00 Oz. PAG-46	59007	
	8 Cyl. 6.0 Eng.; w/o Rear AC - 25.60 Oz. R-134a; 7.10 Oz. PAG-46	59007	

Continued on Next Page

CHEVROLET LIGHT TRUCK

Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that A/C system has been properly cleaned, and new accumulator / filter drier has been installed. Specs are for total system capacities. Always refer to under hood decal as the primary source for refrigerant and lubricant information.

Year	Model	Lubricant
FULLSIZE PICKUP (Cont'd)		
07	8 Cyl. 5.3 Eng.; w/ Rear AC - 40.00 Oz. R-134a; 11.00 Oz. PAG-46	59007
	8 Cyl. 6.0 Eng.; w/o Rear AC - 25.60 Oz. R-134a; 7.10 Oz. PAG-46	59007
	8 Cyl. 6.0 Eng.; w/ Rear AC - 40.00 Oz. R-134a; 11.00 Oz. PAG-46	59007
	8 Cyl. 8.1 Eng.; w/o Rear AC - 25.60 Oz. R-134a; 7.10 Oz. PAG-46	59007
	8 Cyl. 8.1 Eng.; w/ Rear AC - 40.00 Oz. R-134a; 11.00 Oz. PAG-46	59007
06	All Eng.; w/o Rear AC - 26.00 Oz. R-134a; 7.10 Oz. PAG-46	59007
	All Eng.; w/o Rear AC - 28.20 Oz. R-134a; 8.00 Oz. PAG-46	59007
05	6 Cyl. 4.3 Eng.; w/o Rear AC - 26.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
	6 Cyl. 4.3 Eng.; w/ Rear AC - 43.20 Oz. R-134a; 11.00 Oz. PAG-46	59007
	8 Cyl. 5.3 Eng.; Flex Fuel; w/o Rear AC - 26.00 Oz. R-134a; 7.10 Oz. PAG-46	59007
	8 Cyl. 6.0 Eng.; w/ Rear AC - 43.20 Oz. R-134a; 11.00 Oz. PAG-46	59007
	All Eng.; w/o Rear AC - 26.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
04-03	All Eng. - 29.00 Oz. R-134a; 8.00 Oz. PAG-46; w/ Denso Compressor	59007
	All Eng. - 29.00 Oz. R-134a; 8.00 Oz. PAG-46; w/ Denso Compressor	59007
	All Eng. - 32.00 Oz. R-134a; 8.00 Oz. PAG-150; w/ HT6 Compressor; w/ OE Harrison Compressor	59003
02	All Eng. - 32.00 Oz. R-134a; 8.00 Oz. PAG-46; w/ Denso Compressor	59007
	All Eng. - 29.00 Oz. R-134a; 8.00 Oz. PAG-46; w/ Denso Compressor	59007
	All Eng. - 32.00 Oz. R-134a; 8.00 Oz. PAG-150; w/ HT6 Compressor; w/ OE Harrison Compressor	59003
01	All Eng. - 29.00 Oz. R-134a; 8.00 Oz. PAG-46; w/ Denso Compressor	59007
	All Eng. - 29.00 Oz. R-134a; 8.00 Oz. PAG-46; w/ Denso Compressor	59007
	All Eng. - 32.00 Oz. R-134a; 8.00 Oz. PAG-150; w/ HT6 Compressor; w/ OE Harrison Compressor	59003
00	All Eng. - 32.00 Oz. R-134a; 8.00 Oz. PAG-46; w/ Denso Compressor	59007
	All Eng. - 29.00 Oz. R-134a; 8.00 Oz. PAG-46; w/ Denso Compressor	59007
	All Eng. - 32.00 Oz. R-134a; 8.00 Oz. PAG-150; w/ HT6 Compressor; w/ OE Harrison Compressor	59003
99-98	All Eng. - 32.00 Oz. R-134a; 8.00 Oz. PAG-46; w/ Denso Compressor	59007
	All Eng. - 32.00 Oz. R-134a; 8.00 Oz. PAG-150; Standard Cab; w/ HT6 Compressor; w/ OE Harrison Compressor	59003
	All Eng. - 32.00 Oz. R-134a; 8.00 Oz. PAG-46; Standard Cab; w/ Denso Compressor	59007
97-96	Crew Cab - 36.00 Oz. R-134a; 8.00 Oz. PAG-150; w/ HT6 Compressor; w/ OE Harrison Compressor	59003
	Crew Cab - 36.00 Oz. R-134a; 8.00 Oz. PAG-46; w/ Denso Compressor	59007
	All Eng. - 32.00 Oz. R-134a; 8.00 Oz. PAG-150; Standard Cab; w/ HT6 Compressor; w/ OE Harrison Compressor	59003
95-94	All Eng. - 32.00 Oz. R-134a; 8.00 Oz. PAG-46; Standard Cab; w/ Denso Compressor	59007
	All Eng. - 32.00 Oz. R-134a; 8.00 Oz. PAG-150; Standard Cab	59003
	Crew Cab - 36.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
93	All Eng. - 40.00 Oz. R-12; 8.00 Oz. Mineral Oil; Standard Cab	59000 ⁵⁹
	All Eng. - 40.00 Oz. R-134a; 8.00 Oz. PAG-150; Standard Cab	59003
	Crew Cab - 48.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
92	Crew Cab - 48.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
	All Eng. - 44.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
	All Eng. - 44.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
91-90	C,K - 44.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
	R,V - 52.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
89	C,K - 40.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
	R,V - 52.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
88	C,K - 40.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
	R, V - 52.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
87	All Eng. - 48.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
86-85	All Eng. - 44.00 Oz. R-12; 10.00 Oz. Mineral Oil; w/ A6 Compressor	59000 ⁵⁹
	All Eng. - 44.00 Oz. R-12; 8.00 Oz. Mineral Oil; w/ R4 Compressor	59000 ⁵⁹
84	6 Cyl. 4.1 Eng. - See Under Hood Decal	59000 ⁵⁹
	6 Cyl. 4.8 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.0 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.7 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 6.2 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 7.4 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 7.4 Eng. - See Under Hood Decal	59000 ⁵⁹
72-70	6 Cyl. 4.1 Eng. - See Under Hood Decal	59000 ⁵⁹
	6 Cyl. 4.8 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.0 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.7 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 6.6 Eng. - See Under Hood Decal	59000 ⁵⁹
69	6 Cyl. 3.8 Eng. - See Under Hood Decal	59000 ⁵⁹
	6 Cyl. 4.1 Eng. - See Under Hood Decal	59000 ⁵⁹
	6 Cyl. 4.8 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.0 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.3 Eng. - See Under Hood Decal	59000 ⁵⁹

Continued on Next Page

⁵⁹ When retrofitting to R134a PAG Oil must be used.

CHEVROLET LIGHT TRUCK

Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that A/C system has been properly cleaned, and new accumulator / filter drier has been installed. Specs are for total system capacities. Always refer to under hood decal as the primary source for refrigerant and lubricant information.

Year	Model	Lubricant
FULLSIZE PICKUP (Cont'd)		
69	8 Cyl. 5.7 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 6.5 Eng. - See Under Hood Decal	59000
68	6 Cyl. 3.8 Eng. - See Under Hood Decal	59000 ⁵⁹
	6 Cyl. 4.1 Eng. - See Under Hood Decal	59000 ⁵⁹
	6 Cyl. 4.8 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.0 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.4 Eng. - See Under Hood Decal	59000
	8 Cyl. 6.5 Eng. - See Under Hood Decal	59000 ⁵⁹
67-66	6 Cyl. 3.8 Eng. - See Under Hood Decal	59000 ⁵⁹
	6 Cyl. 4.1 Eng. - See Under Hood Decal	59000 ⁵⁹
	6 Cyl. 4.8 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. - See Under Hood Decal	59000 ⁵⁹
65	6 Cyl. 3.8 Eng. - See Under Hood Decal	59000 ⁵⁹
	6 Cyl. 4.8 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. - See Under Hood Decal	59000 ⁵⁹
G SERIES FULLSIZE VAN / EXPRESS		
13	8 Cyl. 4.8 Eng.; w/o Rear AC - 32.10 Oz. R-134a; 8.00 Oz. PAG-46	59007
	8 Cyl. 4.8 Eng.; w/ Rear AC - 56.44 Oz. R-134a; 11.00 Oz. PAG-46	59007
	8 Cyl. 5.3 Eng.; w/o Rear AC - 32.10 Oz. R-134a; 8.00 Oz. PAG-46	59007
	8 Cyl. 5.3 Eng.; w/ Rear AC - 56.09 Oz. R-134a; 11.00 Oz. PAG-46	59007
	8 Cyl. 6.0 Eng.; w/o Rear AC - 32.10 Oz. R-134a; 8.00 Oz. PAG-46	59007
	8 Cyl. 6.0 Eng.; w/ Rear AC - 56.44 Oz. R-134a; 11.00 Oz. PAG-46	59007
	8 Cyl. 6.6 Eng.; w/o Rear AC - 32.10 Oz. R-134a; 8.00 Oz. PAG-46	59007
	8 Cyl. 6.6 Eng.; w/ Rear AC - 56.44 Oz. R-134a; 11.00 Oz. PAG-46	59007
12	6 Cyl. 4.3 Eng.; w/o Rear AC - 31.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
	6 Cyl. 4.3 Eng.; w/ Rear AC - 49.00 Oz. R-134a; 11.00 Oz. PAG-46	59007
	8 Cyl. 4.8 Eng. - 31.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
	8 Cyl. 4.8 Eng.; w/ Rear AC - 49.00 Oz. R-134a; 11.00 Oz. PAG-46	59007
	8 Cyl. 5.3 Eng. - 31.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
	8 Cyl. 5.3 Eng.; w/ Rear AC - 49.00 Oz. R-134a; 11.00 Oz. PAG-46	59007
	8 Cyl. 6.0 Eng. - 31.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
	8 Cyl. 6.0 Eng.; w/ Rear AC - 49.00 Oz. R-134a; 11.00 Oz. PAG-46	59007
	8 Cyl. 6.6 Eng. - 31.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
	8 Cyl. 6.6 Eng.; w/ Rear AC - 49.00 Oz. R-134a; 11.00 Oz. PAG-46	59007
11-10	6 Cyl. 4.3 Eng.; w/o Rear AC - 32.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
	6 Cyl. 4.3 Eng.; w/ Rear AC - 48.00 Oz. R-134a; 11.00 Oz. PAG-46	59007
	8 Cyl. 4.8 Eng.; w/o Rear AC - 32.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
	8 Cyl. 4.8 Eng.; w/ Rear AC - 48.00 Oz. R-134a; 11.00 Oz. PAG-46	59007
	8 Cyl. 5.3 Eng.; w/o Rear AC - 32.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
	8 Cyl. 5.3 Eng.; w/ Rear AC - 48.00 Oz. R-134a; 11.00 Oz. PAG-46	59007
	8 Cyl. 6.0 Eng.; w/o Rear AC - 32.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
	8 Cyl. 6.0 Eng.; w/ Rear AC - 48.00 Oz. R-134a; 11.00 Oz. PAG-46	59007
	8 Cyl. 6.6 Eng.; w/o Rear AC - 32.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
	8 Cyl. 6.6 Eng.; w/ Rear AC - 48.00 Oz. R-134a; 11.00 Oz. PAG-46	59007
09-07	All Eng.; w/o Rear AC - 32.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
	All Eng.; w/ Rear AC - 48.00 Oz. R-134a; 11.00 Oz. PAG-46	59007
06	All Eng.; w/o Rear AC - 32.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
	All Eng.; w/ Rear AC - 56.00 Oz. R-134a; 11.00 Oz. PAG-46	59007
05-03	All Eng.; w/o Rear AC - 32.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
	All Eng.; w/ Rear AC - 48.00 Oz. R-134a; 11.00 Oz. PAG-46	59007
02	All Eng.; w/o Rear AC - 32.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
	All Eng.; w/ Rear AC - 56.00 Oz. R-134a; 11.00 Oz. PAG-150	59003
01	All Eng.; w/o Rear AC - 48.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
	All Eng.; w/ Rear AC - 72.00 Oz. R-134a; 11.00 Oz. PAG-150	59003
00	All Eng.; w/o Rear AC - 48.00 Oz. R-134a; 8.00 Oz. PAG-150; w/ OE Harrison Compressor	59003
	All Eng.; w/o Rear AC - 48.00 Oz. R-134a; 8.00 Oz. PAG-46; w/ Denso Compressor	59007
	All Eng.; w/ Rear AC - 72.00 Oz. R-134a; 11.00 Oz. PAG-150; w/ OE Harrison Compressor	59003
	All Eng.; w/ Rear AC - 72.00 Oz. R-134a; 11.00 Oz. PAG-46; w/ Denso Compressor	59007
99-97	All Eng.; w/o Rear AC - 48.00 Oz. R-134a; 8.00 Oz. PAG-150; w/ OE Harrison Compressor	59003
	All Eng.; w/o Rear AC - 48.00 Oz. R-134a; 8.00 Oz. PAG-46; w/ Denso Compressor	59007
	All Eng.; w/ Rear AC - 78.00 Oz. R-134a; 11.00 Oz. PAG-150; w/ OE Harrison Compressor	59003
	All Eng.; w/ Rear AC - 78.00 Oz. R-134a; 11.00 Oz. PAG-46; w/ Denso Compressor	59007
96	All Eng.; w/o Rear AC - 36.00 Oz. R-134a; 8.00 Oz. PAG-150; w/ OE Harrison Compressor	59003

Continued on Next Page

⁵⁹ When retrofitting to R134a PAG Oil must be used.

CHEVROLET LIGHT TRUCK

Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that A/C system has been properly cleaned, and new accumulator / filter drier has been installed. Specs are for total system capacities. Always refer to under hood decal as the primary source for refrigerant and lubricant information.

Year	Model	Lubricant
G SERIES FULLSIZE VAN / EXPRESS (Cont'd)		
96	All Eng.; w/o Rear AC - 36.00 Oz. R-134a; 8.00 Oz. PAG-46; w/ Denso Compressor	59007
	All Eng.; w/ Rear AC - 78.00 Oz. R-134a; 11.00 Oz. PAG-150; w/ OE Harrison Compressor	59003
95-94	All Eng.; w/o Rear AC - 48.00 Oz. R-134a; 8.00 Oz. PAG-46; w/ Denso Compressor	59007
	All Eng.; w/ Rear AC - 78.00 Oz. R-134a; 11.00 Oz. PAG-46; w/ OE Harrison Compressor	59003
93	All Eng.; w/o Rear AC - 48.00 Oz. R-134a; 8.00 Oz. PAG-150; w/ OE Harrison Compressor	59003
	All Eng.; w/ Rear AC - 68.00 Oz. R-134a; 11.00 Oz. PAG-46; w/ Denso Compressor	59007
92	All Eng.; w/o Rear AC - 48.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
	All Eng.; w/ Rear AC - 68.00 Oz. R-12; 11.00 Oz. Mineral Oil	59000 ⁵⁹
91-89	All Eng.; w/o Rear AC - 48.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
	All Eng.; w/ Rear AC - 72.00 Oz. R-12; 11.00 Oz. Mineral Oil	59000 ⁵⁹
88	6 Cyl. 4.3 Eng.; w/o Rear AC - 56.00 Oz. R-12; 8.00 Oz. Mineral Oil; w/ R4 Compressor	59000 ⁵⁹
	6 Cyl. 4.3 Eng.; w/ Rear AC - 72.00 Oz. R-12; 9.00 Oz. Mineral Oil; w/ R4 Compressor	59000 ⁵⁹
	8 Cyl. 5.0 Eng.; w/o Rear AC - 56.00 Oz. R-12; 8.00 Oz. Mineral Oil; w/ R4 Compressor	59000 ⁵⁹
	8 Cyl. 5.0 Eng.; w/ Rear AC - 72.00 Oz. R-12; 9.00 Oz. Mineral Oil; w/ R4 Compressor	59000 ⁵⁹
	8 Cyl. 5.7 Eng.; w/o Rear AC - 56.00 Oz. R-12; 8.00 Oz. Mineral Oil; w/ R4 Compressor	59000 ⁵⁹
	8 Cyl. 5.7 Eng.; w/ Rear AC - 72.00 Oz. R-12; 9.00 Oz. Mineral Oil; w/ R4 Compressor	59000 ⁵⁹
	8 Cyl. 6.2 Eng.; w/o Rear AC - 48.00 Oz. R-12; 8.00 Oz. Mineral Oil; w/ HR6/DA6 Compressor	59000 ⁵⁹
	8 Cyl. 6.2 Eng.; w/ Rear AC - 56.00 Oz. R-12; 10.00 Oz. Mineral Oil; w/ A6 Compressor	59000 ⁵⁹
	8 Cyl. 6.2 Eng.; w/ Rear AC - 72.00 Oz. R-12; 11.00 Oz. Mineral Oil; w/ HR6/DA6 Compressor	59000 ⁵⁹
	8 Cyl. 6.2 Eng.; w/ Rear AC - 72.00 Oz. R-12; 13.00 Oz. Mineral Oil; w/ A6 Compressor	59000 ⁵⁹
	8 Cyl. 7.4 Eng.; w/o Rear AC - 46.00 Oz. R-12; 10.00 Oz. Mineral Oil; w/ A6 Compressor	59000 ⁵⁹
	8 Cyl. 7.4 Eng.; w/o Rear AC - 46.00 Oz. R-12; 8.00 Oz. Mineral Oil; w/ R4 Compressor	59000 ⁵⁹
	8 Cyl. 7.4 Eng.; w/o Rear AC - 48.00 Oz. R-12; 8.00 Oz. Mineral Oil; w/ HR6/DA6 Compressor	59000 ⁵⁹
	8 Cyl. 7.4 Eng.; w/ Rear AC - 64.00 Oz. R-12; 13.00 Oz. Mineral Oil; w/ A6 Compressor	59000 ⁵⁹
	8 Cyl. 7.4 Eng.; w/ Rear AC - 64.00 Oz. R-12; 9.00 Oz. Mineral Oil; w/ R4 Compressor	59000 ⁵⁹
	8 Cyl. 7.4 Eng.; w/ Rear AC - 72.00 Oz. R-12; 11.00 Oz. Mineral Oil; w/ HR6/DA6 Compressor	59000 ⁵⁹
87-85	All Eng.; w/o Rear AC - 56.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
	All Eng.; w/ Rear AC - 72.00 Oz. R-12; 11.00 Oz. Mineral Oil	59000 ⁵⁹
84-83	All Eng.; w/o Rear AC - 48.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
	All Eng.; w/ Rear AC - 72.00 Oz. R-12; 11.00 Oz. Mineral Oil	59000 ⁵⁹
82-81	6 Cyl. 4.1 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.0 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.7 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 6.2 Eng. - See Under Hood Decal	59000 ⁵⁹
80-77	6 Cyl. 4.1 Eng. - See Under Hood Decal	59000 ⁵⁹
	6 Cyl. 4.8 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.0 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.7 Eng. - See Under Hood Decal	59000 ⁵⁹
76-75	6 Cyl. 4.1 Eng. - See Under Hood Decal	59000 ⁵⁹
	6 Cyl. 4.8 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.7 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 6.6 Eng. - See Under Hood Decal	59000 ⁵⁹
74	6 Cyl. 4.1 Eng. - See Under Hood Decal	59000 ⁵⁹
	6 Cyl. 4.8 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.7 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 7.4 Eng. - See Under Hood Decal	59000 ⁵⁹
73	6 Cyl. 4.1 Eng. - See Under Hood Decal	59000 ⁵⁹
	6 Cyl. 4.8 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.0 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.7 Eng. - See Under Hood Decal	59000 ⁵⁹
71	8 Cyl. 7.4 Eng. - See Under Hood Decal	59000 ⁵⁹
	6 Cyl. 4.1 Eng. - See Under Hood Decal	59000 ⁵⁹
	6 Cyl. 4.8 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.0 Eng. - See Under Hood Decal	59000 ⁵⁹
70	8 Cyl. 5.7 Eng. - See Under Hood Decal	59000 ⁵⁹
	6 Cyl. 4.1 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.0 Eng. - See Under Hood Decal	59000 ⁵⁹

Continued on Next Page

⁵⁹ When retrofitting to R134a PAG Oil must be used.

CHEVROLET LIGHT TRUCK

Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that A/C system has been properly cleaned, and new accumulator / filter drier has been installed. Specs are for total system capacities. Always refer to under hood decal as the primary source for refrigerant and lubricant information.

Year	Model	Lubricant	
G SERIES FULLSIZE VAN / EXPRESS (Cont'd)			
70	8 Cyl. 5.7 Eng. - See Under Hood Decal	59000 ⁵⁹	
69-68	6 Cyl. 3.8 Eng. - See Under Hood Decal	59000 ⁵⁹	
	6 Cyl. 4.1 Eng. - See Under Hood Decal	59000 ⁵⁹	
67	8 Cyl. 5.0 Eng. - See Under Hood Decal	59000 ⁵⁹	
	6 Cyl. 3.8 Eng. - See Under Hood Decal	59000 ⁵⁹	
	6 Cyl. 4.1 Eng. - See Under Hood Decal	59000 ⁵⁹	
	8 Cyl. 4.6 Eng. - See Under Hood Decal	59000 ⁵⁹	
HHR			
11	4 Cyl. - 14.40 Oz. R-134a; 5.00 Oz. PAG-46; w/ CVC Compressor	59007	
10-07	4 Cyl. 2.4 Eng. - 14.40 Oz. R-134a; 4.00 Oz. PAG-46; w/ PXV16 Compressor	59007	
	All Eng. - 14.40 Oz. R-134a; 4.00 Oz. PAG-46; w/ PXV16 Compressor	59007	
06	All Eng. - 14.40 Oz. R-134a; 5.00 Oz. PAG-46; w/ CVC Compressor	59007	
	All Eng. - 14.10 Oz. R-134a; 4.00 Oz. PAG-46; w/ PXV16 Compressor	59007	
	All Eng. - 14.10 Oz. R-134a; 5.00 Oz. PAG-46; w/ CVC Compressor	59007	
P SERIES VAN			
99-94	6 Cyl. 4.3 Eng. - w/ Denso Compressor	59007	
	6 Cyl. 4.3 Eng. - w/ OE Harrison Compressor	59003	
	8 Cyl. 5.7 Eng. - w/ Denso Compressor	59007	
	8 Cyl. 5.7 Eng. - w/ OE Harrison Compressor	59003	
	8 Cyl. 6.5 Eng. - w/ Denso Compressor	59007	
	8 Cyl. 6.5 Eng. - w/ OE Harrison Compressor	59003	
	8 Cyl. 7.4 Eng. - w/ Denso Compressor	59007	
	8 Cyl. 7.4 Eng. - w/ OE Harrison Compressor	59003	
93	6 Cyl. 4.3 Eng. - See Under Hood Decal	59003	
	8 Cyl. 5.7 Eng. - w/ R-12	59000 ⁵⁹	
	8 Cyl. 5.7 Eng. - w/ R-134a	59003	
92	8 Cyl. 6.2 Eng. - See Under Hood Decal	59003	
	8 Cyl. 7.4 Eng. - See Under Hood Decal	59003	
	6 Cyl. 4.3 Eng. - See Under Hood Decal	59000 ⁵⁹	
	8 Cyl. 5.7 Eng. - See Under Hood Decal	59000 ⁵⁹	
91-90	8 Cyl. 6.2 Eng. - See Under Hood Decal	59000 ⁵⁹	
	8 Cyl. 7.4 Eng. - See Under Hood Decal	59000 ⁵⁹	
	4 Cyl. 3.9 Eng. - See Under Hood Decal	59000 ⁵⁹	
	6 Cyl. 4.3 Eng. - See Under Hood Decal	59000 ⁵⁹	
89	8 Cyl. 5.7 Eng. - See Under Hood Decal	59000 ⁵⁹	
	8 Cyl. 6.2 Eng. - See Under Hood Decal	59000 ⁵⁹	
	8 Cyl. 7.4 Eng. - See Under Hood Decal	59000 ⁵⁹	
	4 Cyl. 3.9 Eng. - See Under Hood Decal	59000 ⁵⁹	
	6 Cyl. 4.8 Eng. - See Under Hood Decal	59000 ⁵⁹	
	8 Cyl. 5.7 Eng. - See Under Hood Decal	59000 ⁵⁹	
88-85	8 Cyl. 6.2 Eng. - See Under Hood Decal	59000 ⁵⁹	
	8 Cyl. 7.4 Eng. - See Under Hood Decal	59000 ⁵⁹	
	6 Cyl. 4.8 Eng. - See Under Hood Decal	59000 ⁵⁹	
	8 Cyl. 5.7 Eng. - See Under Hood Decal	59000 ⁵⁹	
79	8 Cyl. 6.2 Eng. - See Under Hood Decal	59000 ⁵⁹	
	8 Cyl. 7.4 Eng. - See Under Hood Decal	59000 ⁵⁹	
	6 Cyl. 4.1 Eng. - w/ A6 Compressor	59000 ⁵⁹	
	6 Cyl. 4.8 Eng. - w/ A6 Compressor	59000 ⁵⁹	
	6 Cyl. 4.8 Eng. - w/ R4 Compressor	59000 ⁵⁹	
	8 Cyl. 5.7 Eng. - w/ A6 Compressor	59000 ⁵⁹	
05-01	8 Cyl. 5.7 Eng. - w/ R4 Compressor	59000 ⁵⁹	
	8 Cyl. 7.4 Eng. - w/ A6 Compressor	59000 ⁵⁹	
	8 Cyl. 7.4 Eng. - w/ R4 Compressor	59000 ⁵⁹	
	S10 BLAZER		
	00-99	All Eng. - 28.00 Oz. R-134a; 8.00 Oz. PAG-150; w/ OE Harrison Compressor	59003
		All Eng. - 28.00 Oz. R-134a; 8.00 Oz. PAG-46; w/ Denso Compressor	59007
	98-96	All Eng. - 31.00 Oz. R-134a; 8.50 Oz. PAG-150; w/ OE Harrison Compressor	59003
		All Eng. - 31.00 Oz. R-134a; 8.50 Oz. PAG-46; w/ Denso Compressor	59007
95	All Eng. - 32.00 Oz. R-134a; 8.00 Oz. PAG-150; w/ OE Harrison Compressor	59003	
	All Eng. - 32.00 Oz. R-134a; 8.00 Oz. PAG-46; w/ Denso Compressor	59007	
94	All Eng. - 32.00 Oz. R-134a; 8.00 Oz. PAG-150	59003	
93	All Eng. - 40.00 Oz. R-134a; 8.00 Oz. PAG-150	59003	
	All Eng. - 36.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹	

Continued on Next Page

⁵⁹ When retrofitting to R134a PAG Oil must be used.

CHEVROLET LIGHT TRUCK

Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that A/C system has been properly cleaned, and new accumulator / filter drier has been installed. Specs are for total system capacities. Always refer to under hood decal as the primary source for refrigerant and lubricant information.

Year	Model	Lubricant
S10 BLAZER (Cont'd)		
92-89	All Eng. - 40.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
88	All Eng. - 37.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
87-85	All Eng. - 40.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
84	4 Cyl. 1.9 Eng. - See Under Hood Decal	59000 ⁵⁹
	4 Cyl. 2.0 Eng. - See Under Hood Decal	59000 ⁵⁹
	4 Cyl. 2.2 Eng. - See Under Hood Decal	59000 ⁵⁹
	6 Cyl. 2.8 Eng. - See Under Hood Decal	59000 ⁵⁹
83	4 Cyl. 1.9 Eng. - See Under Hood Decal	59000 ⁵⁹
	4 Cyl. 2.0 Eng. - See Under Hood Decal	59000 ⁵⁹
	6 Cyl. 2.8 Eng. - See Under Hood Decal	59000 ⁵⁹
S10 PICKUP		
04-99	All Eng. - 28.00 Oz. R-134a; 9.00 Oz. PAG-150; w/ V7 Compressor; w/ OE Harrison Compressor	59003
	All Eng. - 28.00 Oz. R-134a; 9.00 Oz. PAG-46; w/ Denso Compressor	59007
	All Eng. - 30.00 Oz. R-134a; 8.00 Oz. PAG-150; w/ HT6 Compressor; w/ OE Harrison Compressor	59003
	All Eng. - 30.00 Oz. R-134a; 8.00 Oz. PAG-46; w/ Denso Compressor	59007
98-96	All Eng. - 32.00 Oz. R-134a; 8.00 Oz. PAG-150; w/ OE Harrison Compressor	59003
	All Eng. - 32.00 Oz. R-134a; 8.00 Oz. PAG-46; w/ Denso Compressor	59007
95-94	All Eng. - 32.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
93-90	All Eng. - 40.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
89	All Eng. - 56.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
88	All Eng. - 37.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
87-85	All Eng. - 40.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
84	4 Cyl. 1.9 Eng. - See Under Hood Decal	59000 ⁵⁹
	4 Cyl. 2.0 Eng. - See Under Hood Decal	59000 ⁵⁹
	4 Cyl. 2.2 Eng. - See Under Hood Decal	59000 ⁵⁹
	6 Cyl. 2.8 Eng. - See Under Hood Decal	59000 ⁵⁹
83-82	6 Cyl. 2.8 Eng. - See Under Hood Decal	59000 ⁵⁹
SSR		
06	All Eng. - 19.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
05-04	All Eng. - 19.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
SUBURBAN / FULLSIZE BLAZER / TAHOE		
12	8 Cyl. 5.3 Eng.; w/o Rear AC - 26.00 Oz. R-134a; 7.10 Oz. PAG-46	59007
	8 Cyl. 5.3 Eng. Suburban; w/ Rear AC - 48.00 Oz. R-134a; 11.00 Oz. PAG-46	59007
	8 Cyl. 6.0 Eng.; w/o Rear AC - 26.00 Oz. R-134a; 7.10 Oz. PAG-46	59007
11	8 Cyl. 6.0 Eng. Suburban; w/ Rear AC - 48.00 Oz. R-134a; 11.00 Oz. PAG-46	59007
	8 Cyl. 4.8 Eng. Tahoe; Hybrid; w/ Rear AC - 40.00 Oz. R-134a; 11.00 Oz. PAG-46	59007
	8 Cyl. 5.3 Eng.; w/o Rear AC - 25.60 Oz. R-134a; 7.10 Oz. PAG-46	59007
	8 Cyl. 5.3 Eng.; w/o Rear AC - 25.60 Oz. R-134a; 7.10 Oz. PAG-46	59007
10	8 Cyl. 5.3 Eng. Tahoe; Hybrid; w/ Rear AC - 40.00 Oz. R-134a; 11.00 Oz. PAG-46	59007
	8 Cyl. 5.3 Eng.; w/ Rear AC - 48.00 Oz. R-134a; 11.00 Oz. PAG-46	59007
	8 Cyl. 6.0 Eng.; w/o Rear AC - 25.60 Oz. R-134a; 7.10 Oz. PAG-46	59007
	8 Cyl. 6.0 Eng.; w/ Rear AC - 48.00 Oz. R-134a; 11.00 Oz. PAG-46	59007
	8 Cyl. 4.8 Eng. Tahoe; Hybrid; w/ Rear AC - 40.00 Oz. R-134a; 11.00 Oz. PAG-46	59007
	8 Cyl. 5.3 Eng.; w/o Rear AC - 25.60 Oz. R-134a; 7.10 Oz. PAG-46	59007
	8 Cyl. 5.3 Eng.; w/ Rear AC - 48.00 Oz. R-134a; 11.00 Oz. PAG-46	59007
	8 Cyl. 6.0 Eng.; w/o Rear AC - 25.60 Oz. R-134a; 7.10 Oz. PAG-46	59007
09	8 Cyl. 6.0 Eng.; w/ Rear AC - 48.00 Oz. R-134a; 11.00 Oz. PAG-46	59007
	8 Cyl. 4.8 Eng. Tahoe; Excl. Hybrid; w/o Rear AC - 25.60 Oz. R-134a; 7.10 Oz. PAG-46	59007
	8 Cyl. 4.8 Eng. Tahoe; Excl. Hybrid; w/ Rear AC - 40.00 Oz. R-134a; 11.00 Oz. PAG-46	59007
	8 Cyl. 5.3 Eng.; Excl. Hybrid; w/o Rear AC - 25.60 Oz. R-134a; 7.10 Oz. PAG-46	59007
	8 Cyl. 5.3 Eng. Tahoe; Hybrid; w/ Rear AC - 40.00 Oz. R-134a; 11.00 Oz. PAG-46	59007
	8 Cyl. 5.3 Eng.; Excl. Hybrid; w/ Rear AC - 48.00 Oz. R-134a; 11.00 Oz. PAG-46	59007
	8 Cyl. 6.0 Eng.; Excl. Hybrid; w/o Rear AC - 25.60 Oz. R-134a; 7.10 Oz. PAG-46	59007
	8 Cyl. 6.0 Eng.; Excl. Hybrid; w/ Rear AC - 48.00 Oz. R-134a; 11.00 Oz. PAG-46	59007
08	8 Cyl. 6.2 Eng. Tahoe; Excl. Hybrid; w/o Rear AC - 25.60 Oz. R-134a; 7.10 Oz. PAG-46	59007
	8 Cyl. 6.2 Eng. Tahoe; Excl. Hybrid; w/ Rear AC - 40.00 Oz. R-134a; 11.00 Oz. PAG-46	59007
	Tahoe; Excl. Hybrid; w/ Rear AC - 40.00 Oz. R-134a; 10.00 Oz. PAG-46	59007
	Suburban; Excl. Hybrid; w/ Rear AC - 48.00 Oz. R-134a; 11.00 Oz. PAG-46	59007
	All Eng.; Excl. Hybrid; w/ Rear AC - 48.00 Oz. R-134a; 11.00 Oz. PAG-46	59007
	All Eng.; Hybrid - See Under Hood Decal	59889
	8 Cyl. 4.8 Eng. Tahoe; Hybrid; w/ Rear AC - 40.00 Oz. R-134a; 11.00 Oz. PAG-46	59007
	8 Cyl. 5.3 Eng. Tahoe; Hybrid; w/ Rear AC - 40.00 Oz. R-134a; 11.00 Oz. PAG-46	59007

Continued on Next Page

⁵⁹ When retrofitting to R134a PAG Oil must be used.

CHEVROLET LIGHT TRUCK

Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that A/C system has been properly cleaned, and new accumulator / filter drier has been installed. Specs are for total system capacities. Always refer to under hood decal as the primary source for refrigerant and lubricant information.

Year	Model	Lubricant
SUBURBAN / FULLSIZE BLAZER / TAHOE (Cont'd)		
07	All Eng.; w/o Rear AC - 25.50 Oz. R-134a; 8.00 Oz. PAG-46	59007
	Tahoe; w/ Rear AC - 40.00 Oz. R-134a; 10.00 Oz. PAG-46	59007
	Suburban; w/ Rear AC - 48.00 Oz. R-134a; 11.00 Oz. PAG-46	59007
06-03	All Eng.; w/o Rear AC - 25.50 Oz. R-134a; 8.00 Oz. PAG-46	59007
	Tahoe; w/ Rear AC - 43.00 Oz. R-134a; 11.00 Oz. PAG-46	59007
	Suburban; w/ Rear AC - 48.00 Oz. R-134a; 11.00 Oz. PAG-46	59007
02	All Eng.; w/o Rear AC - 28.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
	Tahoe; w/ Rear AC - 42.00 Oz. R-134a; 11.00 Oz. PAG-46	59007
	Suburban; w/ Rear AC - 48.00 Oz. R-134a; 11.00 Oz. PAG-46	59007
01	All Eng.; w/o Rear AC - 29.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
	Suburban; w/ Rear AC - 48.00 Oz. R-134a; 11.00 Oz. PAG-46	59007
	Tahoe; w/ Rear AC - 48.00 Oz. R-134a; 11.00 Oz. PAG-46	59007
00-96	All Eng.; w/o Rear AC - 36.00 Oz. R-134a; 8.00 Oz. PAG-150; w/ OE Harrison Compressor	59003
	All Eng.; w/o Rear AC - 36.00 Oz. R-134a; 8.00 Oz. PAG-46; w/ Denso Compressor	59007
	All Eng.; w/ Rear AC - 64.00 Oz. R-134a; 11.00 Oz. PAG-150; w/ OE Harrison Compressor	59003
	All Eng.; w/ Rear AC - 64.00 Oz. R-134a; 11.00 Oz. PAG-46; w/ Denso Compressor	59007
95-94	All Eng.; w/o Rear AC - 36.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
	All Eng.; w/ Rear AC - 64.00 Oz. R-134a; 11.00 Oz. PAG-150	59003
93	All Eng.; w/o Rear AC - 48.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
	All Eng.; w/ Rear AC - 68.00 Oz. R-12; 11.00 Oz. Mineral Oil	59000 ⁵⁹
92	All Eng.; w/o Rear AC - 44.80 Oz. R-12; 6.00 Oz. Mineral Oil	59000 ⁵⁹
91-90	All Eng.; w/o Rear AC - 52.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
	All Eng.; w/ Rear AC - 84.00 Oz. R-12; 11.00 Oz. Mineral Oil	59000 ⁵⁹
89	All Eng.; w/o Rear AC - 36.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
	All Eng.; w/ Rear AC - 60.00 Oz. R-12; 10.00 Oz. Mineral Oil	59000 ⁵⁹
88	All Eng.; w/o Rear AC - 52.00 Oz. R-12; 6.00 Oz. Mineral Oil	59000 ⁵⁹
	All Eng.; w/ Rear AC - 84.00 Oz. R-12; 9.00 Oz. Mineral Oil	59000 ⁵⁹
87-85	8 Cyl. 5.0 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.7 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 6.2 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 7.4 Eng. - See Under Hood Decal	59000 ⁵⁹
84	6 Cyl. 4.8 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.0 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.7 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 6.2 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 7.4 Eng. - See Under Hood Decal	59000 ⁵⁹
72-71	6 Cyl. 4.1 Eng. - See Under Hood Decal	59000 ⁵⁹
	6 Cyl. 4.8 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.0 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.7 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 6.6 Eng. - See Under Hood Decal	59000 ⁵⁹
70	8 Cyl. 5.0 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.7 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 6.6 Eng. - See Under Hood Decal	59000 ⁵⁹
69	8 Cyl. 5.0 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.3 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.7 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 6.5 Eng. - See Under Hood Decal	59000 ⁵⁹
TRACKER		
04-99	All Eng. - 16.00 Oz. R-134a; 3.50 Oz. PAG-46	59007
98-94	All Eng. - 21.00 Oz. R-134a; 3.50 Oz. PAG-100	59002
93-89	All Eng. - 21.00 Oz. R-12; 5.00 Oz. Mineral Oil	59000 ⁵⁹
TRAILBLAZER		
09	All Eng. - 30.40 Oz. R-134a; 6.00 Oz. PAG-46; 2nd Design; w/ Sanden Compressor; w/o Thermal Switch	59007
	All Eng. - 30.40 Oz. R-134a; 8.00 Oz. PAG-46; 1st Design; w/ Sanden Compressor; w/ Thermal Switch	59007
08-05	All Eng.; w/o Rear AC - 30.40 Oz. R-134a; 8.00 Oz. PAG-46	59007
	All Eng.; w/ Rear AC - 42.50 Oz. R-134a; 8.50 Oz. PAG-46	59007
04-02	All Eng.; w/o Rear AC - 29.00 Oz. R-134a; 7.50 Oz. PAG-46	59007
	All Eng.; w/ Rear AC - 48.00 Oz. R-134a; 8.50 Oz. PAG-46	59007
TRAVERSE		
13	6 Cyl. 3.6 Eng. - 39.68 Oz. R-134a; 7.80 Oz. PAG-46	59007
12-09	6 Cyl. 3.6 Eng. - 37.00 Oz. R-134a; 6.50 Oz. PAG-46	59007

Continued on Next Page

⁵⁹ When retrofitting to R134a PAG Oil must be used.

CHEVROLET LIGHT TRUCK

Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that A/C system has been properly cleaned, and new accumulator / filter drier has been installed. Specs are for total system capacities. Always refer to under hood decal as the primary source for refrigerant and lubricant information.

Year	Model	Lubricant
	UPLANDER	
08-07	All Eng.; w/o Rear AC - 22.88 Oz. R-134a; 7.10 Oz. PAG-46	59007
	All Eng.; w/ Rear AC - 31.68 Oz. R-134a; 7.77 Oz. PAG-46	59007
06-05	All Eng.; w/o Rear AC - 27.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
	All Eng.; w/ Rear AC - 35.00 Oz. R-134a; 7.75 Oz. PAG-46	59007

CHRYSLER

Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that A/C system has been properly cleaned, and new accumulator / filter drier has been installed. Specs are for total system capacities. Always refer to under hood decal as the primary source for refrigerant and lubricant information.

Year	Model	Lubricant
	200 SERIES	
13-11	4 Cyl. 2.4 Eng. - 16.00 Oz. R-134a; 3.40 Oz. PAG-46	59007
	6 Cyl. 3.6 Eng. - 16.00 Oz. R-134a; 3.40 Oz. PAG-46	59007
	300 SERIES	
13	8 Cyl. 5.7 Eng. - 24.00 Oz. R-134a; 6.10 Oz. PAG-46	59007
	8 Cyl. 6.4 Eng. - 24.00 Oz. R-134a; 6.10 Oz. PAG-46	59007
12	6 Cyl. 3.6 Eng. - 26.00 Oz. R-134a; 6.10 Oz. PAG-46	59007
	8 Cyl. 5.7 Eng. - 26.00 Oz. R-134a; 6.10 Oz. PAG-46	59007
	8 Cyl. 6.4 Eng. - 26.00 Oz. R-134a; 6.10 Oz. PAG-46	59007
11	6 Cyl. 3.6 Eng. - 26.00 Oz. R-134a; 6.10 Oz. PAG-46	59007
	8 Cyl. 5.7 Eng. - 26.00 Oz. R-134a; 6.10 Oz. PAG-46	59007
10-09	6 Cyl. 2.7 Eng. - 26.00 Oz. R-134a; 6.10 Oz. PAG-46	59007
	6 Cyl. 3.5 Eng. - 26.00 Oz. R-134a; 6.10 Oz. PAG-46	59007
	8 Cyl. 5.7 Eng. - 26.00 Oz. R-134a; 6.10 Oz. PAG-46	59007
	8 Cyl. 6.1 Eng. - 26.00 Oz. R-134a; 6.10 Oz. PAG-46	59007
08-05	All Eng. - 26.00 Oz. R-134a; 5.50 Oz. PAG-46	59007
04-99	All Eng. - 25.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
	ASPEN	
09-07	8 Cyl.; w/o Rear AC - 30.00 Oz. R-134a; 5.07 Oz. PAG-46	59007
	8 Cyl.; w/ Rear AC - 40.00 Oz. R-134a; 7.40 Oz. PAG-46	59007
	CIRRUS	
00	All Eng. - 19.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
99	All Eng. - 20.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
98	All Eng. - 26.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
97-95	All Eng. - 28.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
	CONCORDE	
04-99	All Eng. - 25.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
98-97	All Eng. - 28.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
96	All Eng. - 28.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
95-94	All Eng. - 28.00 Oz. R-134a; 4.75 Oz. PAG-46	59007
93	All Eng. - 28.00 Oz. R-134a; 4.75 Oz. PAG-46	59007
	6 Cyl. 3.3 Eng. - w/ R-12	59000 ⁵⁹
	6 Cyl. 3.5 Eng. - w/ R-12	59000 ⁵⁹
	CONQUEST	
89	All Eng. - 29.00 Oz. R-12; 5.75 Oz. Mineral Oil	59000 ⁵⁹
88-87	4 Cyl. 2.6 Eng. - See Under Hood Decal	59000 ⁵⁹
	CORDOBA	
83-81	6 Cyl. 3.7 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.2 Eng. - See Under Hood Decal	59000 ⁵⁹
80	6 Cyl. 3.7 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.2 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.9 Eng. - See Under Hood Decal	59000 ⁵⁹
79	8 Cyl. 5.2 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.9 Eng. - See Under Hood Decal	59000 ⁵⁹
	CROSSFIRE	
08-07	6 Cyl. 3.2 Eng. - 30.00 Oz. R-134a; 4.50 Oz. PAG-46	59007
06-04	All Eng. - 30.00 Oz. R-134a; 4.50 Oz. PAG-46	59007
	DYNASTY	
93	6 Cyl. 3.3 Eng. - 38.00 Oz. R-12; See Under Hood Decal; Mineral Oil	59000 ⁵⁹
92-91	4 Cyl. 2.5 Eng. - 38.00 Oz. R-12; See Under Hood Decal; Mineral Oil	59000 ⁵⁹
	6 Cyl. 3.3 Eng. - 38.00 Oz. R-12; See Under Hood Decal; Mineral Oil	59000 ⁵⁹

Continued on Next Page

⁵⁹ When retrofitting to R134a PAG Oil must be used.

Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that A/C system has been properly cleaned, and new accumulator / filter drier has been installed. Specs are for total system capacities. Always refer to under hood decal as the primary source for refrigerant and lubricant information.

Year	Model	Lubricant
DYNASTY (Cont'd)		
90	4 Cyl. 2.5 Eng. - 38.00 Oz. R-12; See Under Hood Decal; Mineral Oil	59000 ⁵⁹
	6 Cyl. 3.0 Eng. - 38.00 Oz. R-12; See Under Hood Decal; Mineral Oil	59000 ⁵⁹
	6 Cyl. 3.3 Eng. - 38.00 Oz. R-12; See Under Hood Decal; Mineral Oil	59000 ⁵⁹
89-88	4 Cyl. 2.5 Eng. - 38.00 Oz. R-12; See Under Hood Decal; Mineral Oil	59000 ⁵⁹
	6 Cyl. 3.0 Eng. - 38.00 Oz. R-12; See Under Hood Decal; Mineral Oil	59000 ⁵⁹
E CLASS		
84	4 Cyl. 2.2 Eng. - See Under Hood Decal	59000 ⁵⁹
	4 Cyl. 2.6 Eng. - See Under Hood Decal	59000 ⁵⁹
83	4 Cyl. 2.2 Eng. - See Under Hood Decal	59000 ⁵⁹
EXECUTIVE		
85-84	4 Cyl. 2.6 Eng. - See Under Hood Decal	59000 ⁵⁹
FIFTH AVENUE		
93-91	6 Cyl. 3.3 Eng. - 41.00 Oz. R-12; 7.25 Oz. Mineral Oil	59000 ⁵⁹
	6 Cyl. 3.8 Eng. - 41.00 Oz. R-12; 7.25 Oz. Mineral Oil	59000 ⁵⁹
90	6 Cyl. 3.3 Eng. - 41.00 Oz. R-12; 7.25 Oz. Mineral Oil	59000 ⁵⁹
89-88	All Eng. - 41.00 Oz. R-12; 7.25 Oz. Mineral Oil	59000 ⁵⁹
87-85	All Eng. - 42.00 Oz. R-12; 7.00 Oz. Mineral Oil	59000 ⁵⁹
83	8 Cyl. 5.2 Eng. - See Under Hood Decal	59000 ⁵⁹
IMPERIAL		
93	6 Cyl. 3.8 Eng. - 32.00 Oz. R-12 ;See Under Hood Decal	59000 ⁵⁹
92	6 Cyl. 3.8 Eng. - See Under Hood Decal	59000 ⁵⁹
91	6 Cyl. 3.3 Eng. - See Under Hood Decal	59000 ⁵⁹
	6 Cyl. 3.8 Eng. - See Under Hood Decal	59000 ⁵⁹
90	6 Cyl. 3.3 Eng. - See Under Hood Decal	59000 ⁵⁹
83-81	8 Cyl. 5.2 Eng. - See Under Hood Decal	59000 ⁵⁹
LASER		
86	4 Cyl. 2.2 Eng. - See Under Hood Decal	59000 ⁵⁹
	4 Cyl. 2.5 Eng. - See Under Hood Decal	59000 ⁵⁹
85	4 Cyl. 2.2 Eng. - See Under Hood Decal	59000 ⁵⁹
LEBARON		
95	All Eng. - 24.00 Oz. R-134a; 7.25 Oz. PAG-46	59007
94	All Eng. - 26.00 Oz. R-134a; 7.25 Oz. PAG-46	59007
93	All Eng. - 32.00 Oz. R-12; 7.25 Oz. Mineral Oil	59000 ⁵⁹
92	All Eng. - 32.00 Oz. R-12; 9.00 Oz. Mineral Oil	59000 ⁵⁹
91	All Eng. - 32.00 Oz. R-12; 7.25 Oz. Mineral Oil	59000 ⁵⁹
90-86	All Eng. - 38.00 Oz. R-12; 7.25 Oz. Mineral Oil	59000 ⁵⁹
85	All Eng. - 37.00 Oz. R-12; 7.25 Oz. Mineral Oil	59000 ⁵⁹
84-82	4 Cyl. 2.2 Eng. - See Under Hood Decal	59000 ⁵⁹
	4 Cyl. 2.6 Eng. - See Under Hood Decal	59000 ⁵⁹
81-80	6 Cyl. 3.7 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.2 Eng. - See Under Hood Decal	59000 ⁵⁹
LHS		
01-99	All Eng. - 25.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
97	All Eng. - 28.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
96	All Eng. - 28.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
95-94	All Eng. - 28.00 Oz. R-134a; 4.75 Oz. PAG-46	59007
NEW YORKER		
96	All Eng. - 28.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
95-94	All Eng. - 28.00 Oz. R-134a; 4.75 Oz. PAG-46	59007
93	All Eng. - 32.00 Oz. R-12; 7.25 Oz. Mineral Oil	59000 ⁵⁹
	6 Cyl. 3.3 Eng. - 32.00 Oz. R-12; 7.25 Oz. Mineral Oil	59000 ⁵⁹
92	All Eng. - 32.00 Oz. R-12; 7.25 Oz. Mineral Oil	59000 ⁵⁹
91	All Eng. - 32.00 Oz. R-12; 7.25 Oz. Mineral Oil	59000 ⁵⁹
	All Eng. - 34.00 Oz. R-12; 9.00 Oz. Mineral Oil	59000 ⁵⁹
90-89	All Eng. - 38.00 Oz. R-12; 7.25 Oz. Mineral Oil; w/ Fixed Displacement Compressor	59000 ⁵⁹
	All Eng. - 38.00 Oz. R-12; 8.75 Oz. Mineral Oil; w/ Variable Displacement Compressor	59000 ⁵⁹
88	All Eng. - 38.00 Oz. R-12; 7.25 Oz. Mineral Oil	59000 ⁵⁹
87-86	4 Cyl. 2.2 Eng. - See Under Hood Decal	59000 ⁵⁹
	4 Cyl. 2.5 Eng. - See Under Hood Decal	59000 ⁵⁹
85-83	4 Cyl. 2.2 Eng. - See Under Hood Decal	59000 ⁵⁹
	4 Cyl. 2.6 Eng. - See Under Hood Decal	59000 ⁵⁹
82-81	8 Cyl. 5.2 Eng. - See Under Hood Decal	59000 ⁵⁹
80-79	8 Cyl. 5.2 Eng. - See Under Hood Decal	59000 ⁵⁹

Continued on Next Page

⁵⁹ When retrofitting to R134a PAG Oil must be used.

CHRYSLER

Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that A/C system has been properly cleaned, and new accumulator / filter drier has been installed. Specs are for total system capacities. Always refer to under hood decal as the primary source for refrigerant and lubricant information.

Year	Model	Lubricant
NEW YORKER (Cont'd)		
80-79	8 Cyl. 5.9 Eng. - See Under Hood Decal	59000 ⁵⁹
NEWPORT		
81-80	8 Cyl. 5.2 Eng. - See Under Hood Decal	59000 ⁵⁹
79	8 Cyl. 5.2 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.9 Eng. - See Under Hood Decal	59000 ⁵⁹
PACIFICA		
08-07	All Eng. - 24.00 Oz. R-134a; 5.50 Oz. PAG-46	59007
06-04	All Eng. - 19.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
PROWLER		
02	All Eng.; w/o Rear AC - 21.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
01	6 Cyl. 3.5 Eng.; w/o Rear AC - 21.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
	6 Cyl. 3.5 Eng.; w/ Rear AC - 21.00 Oz. R-134a; 7.40 Oz. PAG-46	59007
PT CRUISER		
10-09	4 Cyl. 2.4 Eng. - 24.00 Oz. R-134a; 6.10 Oz. PAG-46	59007
08	All Eng. - 24.00 Oz. R-134a; 6.10 Oz. PAG-46	59007
07-02	All Eng. - 25.00 Oz. R-134a; 6.00 Oz. PAG-46	59007
01	All Eng. - 25.00 Oz. R-134a; 5.50 Oz. PAG-46	59007
SEBRING		
10-09	4 Cyl. 2.4 Eng. - 16.00 Oz. R-134a; 3.50 Oz. PAG-46	59007
	6 Cyl. 2.7 Eng. - 16.00 Oz. R-134a; 3.50 Oz. PAG-46	59007
	6 Cyl. 3.5 Eng. - 16.00 Oz. R-134a; 3.50 Oz. PAG-46	59007
08	Sedan - 16.00 Oz. R-134a; 3.50 Oz. PAG-46	59007
	Convertible - 16.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
07	Convertible - 16.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
	Sedan - 16.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
06	Sedan - 16.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
	Convertible - See Under Hood Decal; 5.00 Oz. PAG-46	59007
05-04	Sedan / Coupe - 15.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
03	Sedan / Coupe - 15.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
	6 Cyl. 2.7 Eng. - See Under Hood Decal; 5.00 Oz. PAG-46	59007
	6 Cyl. 3.0 Eng. - See Under Hood Decal; 5.00 Oz. PAG-46	59007
02-01	Sedan / Coupe - 15.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
	Convertible - 19.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
00	Convertible - 19.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
	Sedan / Coupe - 26.00 Oz. R-134a; 6.00 Oz. PAG-100	59002
99-97	Convertible - 26.00 Oz. R-134a; 6.50 Oz. PAG-46	59007
	4 Cyl. Sedan / Coupe - 24.00 Oz. R-134a; 4.00 Oz. PAG-46; w/ Denso Compressor	59007
	6 Cyl. Sedan / Coupe - 26.00 Oz. R-134a; 6.00 Oz. PAG-100; w/ Sanden Compressor	59002
96	Convertible - 28.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
	4 Cyl. Sedan / Coupe - 24.00 Oz. R-134a; 4.00 Oz. PAG-46; w/ Denso Compressor	59007
	6 Cyl. Sedan / Coupe - 26.00 Oz. R-134a; 6.00 Oz. PAG-100; w/ Sanden Compressor	59002
95	4 Cyl. Sedan / Coupe - 24.00 Oz. R-134a; 4.00 Oz. PAG-46; w/ Denso Compressor	59007
	6 Cyl. Sedan / Coupe - 26.00 Oz. R-134a; 6.00 Oz. PAG-100; w/ Sanden Compressor	59002
TC MASERATI		
91	6 Cyl. 3.0 Eng. - See Under Hood Decal	59000 ⁵⁹
90	4 Cyl. 2.2 Eng. - See Under Hood Decal	59000 ⁵⁹
	6 Cyl. 3.0 Eng. - See Under Hood Decal	59000 ⁵⁹
89	4 Cyl. 2.2 Eng. - See Under Hood Decal	59000 ⁵⁹
TOWN & COUNTRY		
13-12	All Eng. - 28.96 Oz. R-134a; 4.05 Oz. PAG-46	59007
	All Eng. - 40.48 Oz. R-134a; 5.07 Oz. PAG-46	59007
11	All Eng.; w/o Rear AC - 29.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
	All Eng.; w/ Rear AC - 40.50 Oz. R-134a; 5.00 Oz. PAG-46	59007
10-08	All Eng.; w/o Rear AC - 27.80 Oz. R-134a; 4.00 Oz. PAG-46	59007
	All Eng.; w/ Rear AC - 39.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
07-06	All Eng.; w/o Rear AC - 24.00 Oz. R-134a; 6.10 Oz. PAG-46	59007
	All Eng.; w/ Rear AC - 38.00 Oz. R-134a; 7.40 Oz. PAG-46	59007
05	All Eng.; w/o Rear AC - See Under Hood Decal R-134a; 6.10 Oz. PAG-46	59007
	All Eng.; w/ Rear AC - See Under Hood Decal R-134a; 7.80 Oz. PAG-46	59007
04	All Eng.; w/ Rear AC - See Under Hood Decal R-134a; 10.10 Oz. PAG-46	59007
	All Eng.; w/o Rear AC - See Under Hood Decal R-134a; 6.10 Oz. PAG-46	59007
03	All Eng.; w/o Rear AC - 31.00 Oz. R-134a; 5.00 Oz. PAG-46; w/ Single or Dual Zone	59007
	All Eng.; w/ Rear AC - 31.00 Oz. R-134a; 6.40 Oz. PAG-46; w/ Single or Dual Zone	59007

Continued on Next Page

⁵⁹ When retrofitting to R134a PAG Oil must be used.

Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that A/C system has been properly cleaned, and new accumulator / filter drier has been installed. Specs are for total system capacities. Always refer to under hood decal as the primary source for refrigerant and lubricant information.

Year	Model	Lubricant
TOWN & COUNTRY (Cont'd)		
03	All Eng.; w/ Rear AC - 43.00 Oz. R-134a; 6.40 Oz. PAG-46; w/ 3 Zone	59007
02	All Eng.; w/o Rear AC - See Under Hood Decal R-134a; 5.00 Oz. PAG-46	59007
	All Eng.; w/ Rear AC - See Under Hood Decal R-134a; 7.40 Oz. PAG-46	59007
01-00	All Eng.; w/o Rear AC - 34.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
	All Eng.; w/ Rear AC - 46.00 Oz. R-134a; 7.40 Oz. PAG-46	59007
99-96	All Eng.; w/o Rear AC - 34.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
	All Eng.; w/ Rear AC - 48.00 Oz. R-134a; 7.50 Oz. PAG-46	59007
95-94	All Eng.; w/o Rear AC - 36.00 Oz. R-134a; 4.73 Oz. PAG-46	59007
	All Eng.; w/ Rear AC - 50.00 Oz. R-134a; 7.40 Oz. PAG-46	59007
93	All Eng.; w/o Rear AC - 36.00 Oz. R-134a; 4.73 Oz. PAG-46	59007
	All Eng.; w/ Rear AC - 50.00 Oz. R-134a; 7.40 Oz. PAG-46	59007
	6 Cyl. 3.3 Eng. - w/ R-12	59000 ⁵⁹
92	All Eng.; w/o Rear AC - 33.50 Oz. R-12; 7.25 Oz. Mineral Oil; w/ Fixed Displacement Compressor	59000 ⁵⁹
	All Eng.; w/o Rear AC - 33.50 Oz. R-12; 8.75 Oz. Mineral Oil; w/ Variable Displacement Compressor	59000 ⁵⁹
	All Eng.; w/ Rear AC - 44.00 Oz. R-12; 13.00 Oz. Mineral Oil; w/ Fixed Displacement Compressor	59000 ⁵⁹
	All Eng.; w/ Rear AC - 44.00 Oz. R-12; 13.00 Oz. Mineral Oil; w/ Variable Displacement Compressor	59000 ⁵⁹
91-90	All Eng.; w/o Rear AC - 32.00 Oz. R-12; 7.25 Oz. Mineral Oil; w/ Fixed Displacement Compressor	59000 ⁵⁹
	All Eng.; w/o Rear AC - 32.00 Oz. R-12; 8.75 Oz. Mineral Oil; w/ Variable Displacement Compressor	59000 ⁵⁹
	All Eng.; w/ Rear AC - 43.00 Oz. R-12; 13.00 Oz. Mineral Oil; w/ Fixed Displacement Compressor	59000 ⁵⁹
	All Eng.; w/ Rear AC - 43.00 Oz. R-12; 13.00 Oz. Mineral Oil; w/ Variable Displacement Compressor	59000 ⁵⁹
88-86	4 Cyl. 2.2 Eng. - See Under Hood Decal	59000 ⁵⁹
	4 Cyl. 2.5 Eng. - See Under Hood Decal	59000 ⁵⁹
85-84	4 Cyl. 2.2 Eng. - See Under Hood Decal	59000 ⁵⁹
	4 Cyl. 2.6 Eng. - See Under Hood Decal	59000 ⁵⁹
VOYAGER / GRAND VOYAGER		
03	All Eng.; w/o Rear AC - 31.00 Oz. R-134a; 5.00 Oz. PAG-46; w/ Single or Dual Zone	59007
	All Eng.; w/ Rear AC - 31.00 Oz. R-134a; 6.40 Oz. PAG-46; w/ Single or Dual Zone	59007
	All Eng.; w/ Rear AC - 43.00 Oz. R-134a; 6.40 Oz. PAG-46; w/ 3 Zone	59007
02	All Eng.; w/o Rear AC - See Under Hood Decal R-134a; 5.00 Oz. PAG-46	59007
	All Eng.; w/ Rear AC - See Under Hood Decal R-134a; 7.40 Oz. PAG-46	59007
01-00	All Eng.; w/o Rear AC - 34.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
	All Eng.; w/ Rear AC - 46.00 Oz. R-134a; 7.40 Oz. PAG-46	59007
97	6 Cyl. 3.3 Eng.; w/o Rear AC - 34.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
	6 Cyl. 3.3 Eng.; w/ Rear AC - 46.00 Oz. R-134a; 7.40 Oz. PAG-46	59007
96	6 Cyl. 3.3 Eng. - 36.00 Oz. R-134a; 4.73 Oz. PAG-46	59007
	6 Cyl. 3.3 Eng.; w/ Rear AC - 52.00 Oz. R-134a; 7.40 Oz. PAG-46	59007
	6 Cyl. 3.8 Eng. - 36.00 Oz. R-134a; 4.73 Oz. PAG-46	59007
	6 Cyl. 3.8 Eng.; w/ Rear AC - 52.00 Oz. R-134a; 7.40 Oz. PAG-46	59007
95	6 Cyl. 3.3 Eng.; w/o Rear AC - 36.00 Oz. R-134a; 4.73 Oz. PAG-46	59007
	6 Cyl. 3.3 Eng.; w/ Rear AC - 52.00 Oz. R-134a; 7.40 Oz. PAG-46	59007
	6 Cyl. 3.8 Eng.; w/o Rear AC - 36.00 Oz. R-134a; 4.73 Oz. PAG-46	59007
	6 Cyl. 3.8 Eng.; w/ Rear AC - 52.00 Oz. R-134a; 7.40 Oz. PAG-46	59007

DAEWOO

Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that A/C system has been properly cleaned, and new accumulator / filter drier has been installed. Specs are for total system capacities. Always refer to under hood decal as the primary source for refrigerant and lubricant information.

Year	Model	Lubricant
LANOS		
02-99	All Eng. - 26.00 Oz. R-134a; 8.00 Oz. PAG-100	59002
LEGANZA		
02-99	All Eng. - 26.00 Oz. R-134a; 8.00 Oz. PAG-100	59002
NUBIRA		
02-99	All Eng. - 26.00 Oz. R-134a; 8.00 Oz. PAG-100	59002

⁵⁹ When retrofitting to R134a PAG Oil must be used.

DAIHATSU

Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that A/C system has been properly cleaned, and new accumulator / filter drier has been installed. Specs are for total system capacities. Always refer to under hood decal as the primary source for refrigerant and lubricant information.

Year	Model	Lubricant
	CHARADE	
92-89	All Eng. - 23.00 Oz. R-12; 4.00 Oz. Mineral Oil	59000 ⁵⁹
	ROCKY	
92-90	All Eng. - 26.50 Oz. R-12; 4.00 Oz. Mineral Oil	59000 ⁵⁹

DODGE

Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that A/C system has been properly cleaned, and new accumulator / filter drier has been installed. Specs are for total system capacities. Always refer to under hood decal as the primary source for refrigerant and lubricant information.

Year	Model	Lubricant
	400	
83-82	4 Cyl. 2.2 Eng. - See Under Hood Decal	59000 ⁵⁹
	4 Cyl. 2.6 Eng. - See Under Hood Decal	59000 ⁵⁹
	600	
88-86	4 Cyl. 2.2 Eng. - See Under Hood Decal	59000 ⁵⁹
	4 Cyl. 2.5 Eng. - See Under Hood Decal	59000 ⁵⁹
85-83	4 Cyl. 2.2 Eng. - See Under Hood Decal	59000 ⁵⁹
	4 Cyl. 2.6 Eng. - See Under Hood Decal	59000 ⁵⁹
	ARIES	
89	All Eng. - 38.00 Oz. R-12; 7.25 Oz. Mineral Oil; w/ Fixed Displacement Compressor	59000 ⁵⁹
	All Eng. - 38.00 Oz. R-12; 8.75 Oz. Mineral Oil; w/ Variable Displacement Compressor	59000 ⁵⁹
88-87	All Eng. - 38.00 Oz. R-12; 7.25 Oz. Mineral Oil	59000 ⁵⁹
86	4 Cyl. 2.2 Eng. - See Under Hood Decal	59000 ⁵⁹
	4 Cyl. 2.5 Eng. - See Under Hood Decal	59000 ⁵⁹
85	All Eng. - 37.00 Oz. R-12; 7.25 Oz. Mineral Oil	59000 ⁵⁹
84-81	4 Cyl. 2.2 Eng. - See Under Hood Decal	59000 ⁵⁹
	4 Cyl. 2.6 Eng. - See Under Hood Decal	59000 ⁵⁹
	ASPEN	
80	6 Cyl. 3.7 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.2 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.9 Eng. - See Under Hood Decal	59000 ⁵⁹
	AVENGER	
13-11	4 Cyl. 2.4 Eng. - 16.00 Oz. R-134a; 3.40 Oz. PAG-46	59007
	6 Cyl. 3.6 Eng. - 16.00 Oz. R-134a; 3.40 Oz. PAG-46	59007
10-09	4 Cyl. 2.4 Eng. - 16.00 Oz. R-134a; 3.40 Oz. PAG-46	59007
	6 Cyl. 2.7 Eng. - 16.00 Oz. R-134a; 3.40 Oz. PAG-46	59007
	6 Cyl. 3.5 Eng. - 16.00 Oz. R-134a; 3.40 Oz. PAG-46	59007
08	All Eng. - 16.00 Oz. R-134a; 3.40 Oz. PAG-46	59007
00	All Eng. - 26.00 Oz. R-134a; 6.00 Oz. PAG-100	59002
99-95	4 Cyl. - 26.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
	6 Cyl. - 26.00 Oz. R-134a; 6.00 Oz. PAG-100	59002
	CALIBER	
12-11	4 Cyl. 2.0 Eng. - 20.96 Oz. R-134a; 3.40 Oz. PAG-46	59007
	4 Cyl. 2.4 Eng. - 20.96 Oz. R-134a; 3.40 Oz. PAG-46	59007
10	4 Cyl. 2.0 Eng. - 18.00 Oz. R-134a; 3.40 Oz. PAG-46; w/ 6SEU16C A/C Compressor	59007
	4 Cyl. 2.0 Eng. - 18.00 Oz. R-134a; 4.10 Oz. PAG-46; w/ 5SE12C A/C Compressor	59007
	4 Cyl. 2.4 Eng. - 20.00 Oz. R-134a; 3.40 Oz. PAG-46; w/ 6SEU16C A/C Compressor	59007
	4 Cyl. 2.4 Eng. - 20.00 Oz. R-134a; 4.10 Oz. PAG-46; w/ 5SE12C A/C Compressor	59007
09	4 Cyl. 1.8 Eng. - 18.00 Oz. R-134a; 3.40 Oz. PAG-46; w/ 6SEU16C A/C Compressor	59007
	4 Cyl. 1.8 Eng. - 18.00 Oz. R-134a; 4.10 Oz. PAG-46; w/ 5SE12C A/C Compressor	59007
	4 Cyl. 2.0 Eng. - 18.00 Oz. R-134a; 3.40 Oz. PAG-46; w/ 6SEU16C A/C Compressor	59007
	4 Cyl. 2.0 Eng. - 18.00 Oz. R-134a; 4.10 Oz. PAG-46; w/ 5SE12C A/C Compressor	59007
	4 Cyl. 2.4 Eng. - 20.00 Oz. R-134a; 3.40 Oz. PAG-46; w/ 6SEU16C A/C Compressor	59007
	4 Cyl. 2.4 Eng. - 20.00 Oz. R-134a; 4.10 Oz. PAG-46; w/ 5SE12C A/C Compressor	59007
08-07	All Eng. - 18.00 Oz. R-134a; 4.10 Oz. PAG-46	59007
	CHALLENGER	
13	6 Cyl. 3.6 Eng. - 24.00 Oz. R-134a; 6.10 Oz. PAG-46	59007
	8 Cyl. 5.7 Eng. - 24.00 Oz. R-134a; 6.10 Oz. PAG-46	59007
	8 Cyl. 6.4 Eng. - 24.00 Oz. R-134a; 6.10 Oz. PAG-46	59007
12	6 Cyl. 3.6 Eng. - 24.00 Oz. R-134a; 6.10 Oz. PAG-46	59007
	8 Cyl. 5.7 Eng. - 24.00 Oz. R-134a; 6.10 Oz. PAG-46	59007
	8 Cyl. 6.4 Eng. - 23.00 Oz. R-134a; 6.10 Oz. PAG-46	59007

Continued on Next Page

⁵⁹ When retrofitting to R134a PAG Oil must be used.

Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that A/C system has been properly cleaned, and new accumulator / filter drier has been installed. Specs are for total system capacities. Always refer to under hood decal as the primary source for refrigerant and lubricant information.

Year	Model	Lubricant
CHALLENGER (Cont'd)		
11	6 Cyl. 3.6 Eng. - 23.00 Oz. R-134a; 6.10 Oz. PAG-46	59007
	8 Cyl. 5.7 Eng. - 23.00 Oz. R-134a; 6.10 Oz. PAG-46	59007
	8 Cyl. 6.4 Eng. - 24.00 Oz. R-134a; 6.10 Oz. PAG-46	59007
10	6 Cyl. 3.5 Eng. - 16.00 Oz. R-134a; 6.10 Oz. PAG-46	59007
	8 Cyl. 5.7 Eng. - 16.00 Oz. R-134a; 6.10 Oz. PAG-46	59007
	8 Cyl. 6.1 Eng. - 16.00 Oz. R-134a; 6.10 Oz. PAG-46	59007
09	6 Cyl. 3.5 Eng. - 26.00 Oz. R-134a; 6.10 Oz. PAG-46	59007
	8 Cyl. 5.7 Eng. - 26.00 Oz. R-134a; 6.10 Oz. PAG-46	59007
	8 Cyl. 6.1 Eng. - 26.00 Oz. R-134a; 6.10 Oz. PAG-46	59007
08	8 Cyl. 6.1 Eng. - 26.00 Oz. R-134a; 6.10 Oz. PAG-46	59007
83-81	4 Cyl. 2.6 Eng. - See Under Hood Decal	59000 ⁵⁹
CHARGER		
13	6 Cyl. 3.6 Eng. - 24.00 Oz. R-134a; 6.10 Oz. PAG-46	59007
	8 Cyl. 5.7 Eng. - 24.00 Oz. R-134a; 6.10 Oz. PAG-46	59007
	8 Cyl. 6.4 Eng. - 24.00 Oz. R-134a; 6.10 Oz. PAG-46	59007
12	6 Cyl. 3.6 Eng. - 24.96 Oz. R-134a; 6.10 Oz. PAG-46	59007
	8 Cyl. 5.7 Eng. - 24.96 Oz. R-134a; 6.10 Oz. PAG-46	59007
	8 Cyl. 6.4 Eng. - 24.96 Oz. R-134a; 6.10 Oz. PAG-46	59007
11	6 Cyl. 3.6 Eng. - 24.96 Oz. R-134a; 6.10 Oz. PAG-46	59007
	8 Cyl. 5.7 Eng. - 24.96 Oz. R-134a; 6.10 Oz. PAG-46	59007
	8 Cyl. 6.4 Eng. - 24.96 Oz. R-134a; 6.10 Oz. PAG-46	59007
10-09	6 Cyl. 2.7 Eng. - 26.00 Oz. R-134a; 6.10 Oz. PAG-46	59007
	6 Cyl. 3.5 Eng. - 26.00 Oz. R-134a; 6.10 Oz. PAG-46	59007
	8 Cyl. 5.7 Eng. - 26.00 Oz. R-134a; 6.10 Oz. PAG-46	59007
08-07	8 Cyl. 6.1 Eng. - 26.00 Oz. R-134a; 6.10 Oz. PAG-46	59007
	All Eng. - 26.00 Oz. R-134a; 6.10 Oz. PAG-46	59007
	All Eng. - 26.00 Oz. R-134a; 6.50 Oz. PAG-46	59007
87	4 Cyl. 2.2 Eng. - See Under Hood Decal	59000 ⁵⁹
86-85	4 Cyl. 1.6 Eng. - See Under Hood Decal	59000 ⁵⁹
	4 Cyl. 2.2 Eng. - See Under Hood Decal	59000 ⁵⁹
COLT		
94-93	4 Cyl. 1.5 Eng. - 28.00 Oz. R-134a; 4.40 Oz. PAG-46	59007
	4 Cyl. 1.8 Eng. - 28.00 Oz. R-134a; 4.40 Oz. PAG-46	59007
92	4 Cyl. 1.5 Eng. - See Under Hood Decal	59000 ⁵⁹
91	4 Cyl. 1.5 Eng. - See Under Hood Decal	59000 ⁵⁹
90-89	4 Cyl. 2.0 Eng. - See Under Hood Decal	59000 ⁵⁹
	4 Cyl. 1.5 Eng. - See Under Hood Decal	59000 ⁵⁹
	4 Cyl. 1.6 Eng. - See Under Hood Decal	59000 ⁵⁹
	4 Cyl. 1.8 Eng. - See Under Hood Decal	59000 ⁵⁹
	4 Cyl. 2.0 Eng. - See Under Hood Decal	59000 ⁵⁹
	4 Cyl. 2.0 Eng. - See Under Hood Decal	59000 ⁵⁹
88-87	4 Cyl. 1.5 Eng. - See Under Hood Decal	59000 ⁵⁹
	4 Cyl. 2.0 Eng. - See Under Hood Decal	59000 ⁵⁹
86-85	4 Cyl. 1.5 Eng. - See Under Hood Decal	59000 ⁵⁹
	4 Cyl. 1.6 Eng. - See Under Hood Decal	59000 ⁵⁹
	4 Cyl. 2.0 Eng. - See Under Hood Decal	59000 ⁵⁹
CONQUEST		
86-85	4 Cyl. 2.6 Eng. - See Under Hood Decal	59000 ⁵⁹
DART		
13	4 Cyl. 1.4 Eng. - 20.00 Oz. R-134a; 5.90 Oz. PAG-46	59007
	4 Cyl. 2.0 Eng. - 20.00 Oz. R-134a; 5.90 Oz. PAG-46	59007
	4 Cyl. 2.4 Eng. - 20.00 Oz. R-134a; 5.90 Oz. PAG-46	59007
DAYTONA		
93-91	All Eng. - 32.00 Oz. R-12; 7.25 Oz. Mineral Oil	59000 ⁵⁹
90-89	All Eng. - 38.00 Oz. R-12; 7.25 Oz. Mineral Oil	59000 ⁵⁹
88-86	4 Cyl. 2.2 Eng. - See Under Hood Decal	59000 ⁵⁹
85-84	4 Cyl. 2.5 Eng. - See Under Hood Decal	59000 ⁵⁹
	4 Cyl. 2.2 Eng. - See Under Hood Decal	59000 ⁵⁹
DIPLOMAT		
89-84	8 Cyl. 5.2 Eng. - See Under Hood Decal	59000 ⁵⁹
83-80	6 Cyl. 3.7 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.2 Eng. - See Under Hood Decal	59000 ⁵⁹
79	8 Cyl. 5.2 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.9 Eng. - See Under Hood Decal	59000 ⁵⁹

Continued on Next Page

⁵⁹ When retrofitting to R134a PAG Oil must be used.

DODGE

Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that A/C system has been properly cleaned, and new accumulator / filter drier has been installed. Specs are for total system capacities. Always refer to under hood decal as the primary source for refrigerant and lubricant information.

Year	Model	Lubricant
DYNASTY		
93-91	All Eng. - 32.00 Oz. R-12; 7.25 Oz. Mineral Oil; w/ Fixed Displacement Compressor	59000 ⁵⁹
	All Eng. - 32.00 Oz. R-12; 8.75 Oz. Mineral Oil; w/ Variable Displacement Compressor	59000 ⁵⁹
90-89	All Eng. - 38.00 Oz. R-12; 7.25 Oz. Mineral Oil; w/ Fixed Displacement Compressor	59000 ⁵⁹
	All Eng. - 38.00 Oz. R-12; 8.75 Oz. Mineral Oil; w/ Variable Displacement Compressor	59000 ⁵⁹
88	All Eng. - 38.00 Oz. R-12; 7.25 Oz. Mineral Oil	59000 ⁵⁹
INTREPID		
04-99	All Eng. - 25.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
98-96	All Eng. - 28.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
95-94	All Eng. - 28.00 Oz. R-134a; 4.75 Oz. PAG-46	59007
93	All Eng. - 28.00 Oz. R-134a; 4.75 Oz. PAG-46	59007
	6 Cyl. 3.3 Eng. - w/ R-12	59000 ⁵⁹
	6 Cyl. 3.5 Eng. - w/ R-12	59000 ⁵⁹
LANCER		
89-86	4 Cyl. 2.2 Eng. - See Under Hood Decal	59000 ⁵⁹
	4 Cyl. 2.5 Eng. - See Under Hood Decal	59000 ⁵⁹
85	4 Cyl. 2.2 Eng. - See Under Hood Decal	59000 ⁵⁹
MAGNUM		
08-06	All Eng. - 26.00 Oz. R-134a; 6.50 Oz. PAG-46	59007
05	6 Cyl. 2.7 Eng. - 26.00 Oz. R-134a; 6.10 Oz. PAG-46	59007
	6 Cyl. 3.5 Eng. - 26.00 Oz. R-134a; 6.10 Oz. PAG-46	59007
	8 Cyl. 5.7 Eng. - 26.00 Oz. R-134a; 6.10 Oz. PAG-46	59007
MIRADA		
83-81	6 Cyl. 3.7 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.2 Eng. - See Under Hood Decal	59000 ⁵⁹
80	6 Cyl. 3.7 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.2 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.9 Eng. - See Under Hood Decal	59000 ⁵⁹
MONACO		
92-90	All Eng. - 36.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
NEON		
05-02	All Eng. - 30.00 Oz. R-134a; 6.00 Oz. PAG-46	59007
01-00	All Eng. - 27.00 Oz. R-134a; 6.00 Oz. PAG-46	59007
99	All Eng. - 28.00 Oz. R-134a; 4.75 Oz. PAG-46	59007
98-97	All Eng. - 25.00 Oz. R-134a; 6.75 Oz. PAG-46	59007
96-95	All Eng. - 29.00 Oz. R-134a; 4.75 Oz. PAG-46	59007
OMNI		
90-89	4 Cyl. 2.2 Eng. - See Under Hood Decal	59000 ⁵⁹
88	All Eng. - 38.00 Oz. R-12; 7.25 Oz. Mineral Oil	59000 ⁵⁹
87	All Eng. - 34.00 Oz. R-12; 7.25 Oz. Mineral Oil	59000 ⁵⁹
86-84	4 Cyl. 1.6 Eng. - See Under Hood Decal	59000 ⁵⁹
	4 Cyl. 2.2 Eng. - See Under Hood Decal	59000 ⁵⁹
83-81	4 Cyl. 1.7 Eng. - See Under Hood Decal	59000 ⁵⁹
	4 Cyl. 2.2 Eng. - See Under Hood Decal	59000 ⁵⁹
80-78	4 Cyl. 1.7 Eng. - See Under Hood Decal	59000 ⁵⁹
SHADOW		
94	All Eng. - 26.00 Oz. R-134a; 7.25 Oz. PAG-46	59007
93-91	All Eng. - 32.00 Oz. R-12; 7.25 Oz. Mineral Oil	59000 ⁵⁹
90-87	All Eng. - 38.00 Oz. R-12; 7.25 Oz. Mineral Oil	59000 ⁵⁹
SPIRIT		
95	All Eng. - 24.00 Oz. R-134a; 7.25 Oz. PAG-46	59007
94	All Eng. - 26.00 Oz. R-134a; 7.25 Oz. PAG-46	59007
93-91	All Eng. - 32.00 Oz. R-12; 7.25 Oz. Mineral Oil	59000 ⁵⁹
90-89	All Eng. - 38.00 Oz. R-12; 7.25 Oz. Mineral Oil	59000 ⁵⁹
STEALTH		
96	All Eng. - 30.00 Oz. R-134a; 5.50 Oz. PAG-46	59007
95-94	All Eng. - 28.00 Oz. R-134a; 5.50 Oz. PAG-46	59007
93	All Eng. - 29.00 Oz. R-12; 5.50 Oz. Mineral Oil	59000 ⁵⁹
92-91	All Eng. - 18.00 Oz. R-12; 5.50 Oz. Mineral Oil	59000 ⁵⁹
STRATUS		
06-05	All Eng. - See Under Hood Decal; 5.00 Oz. PAG-46	59007
04-02	All Eng. - 15.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
01-99	All Eng. - 20.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
98	All Eng. - 26.00 Oz. R-134a; 5.00 Oz. PAG-46	59007

Continued on Next Page

⁵⁹ When retrofitting to R134a PAG Oil must be used.

Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that A/C system has been properly cleaned, and new accumulator / filter drier has been installed. Specs are for total system capacities. Always refer to under hood decal as the primary source for refrigerant and lubricant information.

Year	Model	Lubricant
STRATUS (Cont'd)		
97-95	All Eng. - 28.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
VIPER		
10-09	10 Cyl. 8.4 Eng. - 16.00 Oz. R-134a; 6.10 Oz. PAG-46	59007
08-03	All Eng. - 16.00 Oz. R-134a; 6.00 Oz. PAG-46	59007
02-94	All Eng. - 30.00 Oz. R-134a; 4.75 Oz. PAG-46	59007

DODGE LIGHT TRUCK

Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that A/C system has been properly cleaned, and new accumulator / filter drier has been installed. Specs are for total system capacities. Always refer to under hood decal as the primary source for refrigerant and lubricant information.

Year	Model	Lubricant
CARAVAN / GRAND CARAVAN		
14	6 Cyl. 3.6 Eng. - See Under Hood Decal	59007
13	6 Cyl. 3.6 Eng.; w/o Rear AC - 29.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
	6 Cyl. 3.6 Eng.; w/ Rear AC - 40.48 Oz. R-134a; 5.07 Oz. PAG-46	59007
12	6 Cyl. 3.6 Eng.; w/ Rear AC - 29.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
	6 Cyl. 3.6 Eng.; w/ Rear AC - 40.48 Oz. R-134a; 5.07 Oz. PAG-46	59007
11	All Eng.; w/o Rear AC - 29.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
	All Eng.; w/ Rear AC - 40.50 Oz. R-134a; 5.00 Oz. PAG-46	59007
10-08	All Eng.; w/o Rear AC - 27.80 Oz. R-134a; 4.00 Oz. PAG-46	59007
	All Eng.; w/ Rear AC - 39.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
07-06	All Eng.; w/o Rear AC - 24.00 Oz. R-134a; 6.10 Oz. PAG-46	59007
	All Eng.; w/ Rear AC - 38.00 Oz. R-134a; 7.40 Oz. PAG-46	59007
05	All Eng.; w/o Rear AC - See Under Hood Decal R-134a; 6.10 Oz. PAG-46	59007
	All Eng.; w/ Rear AC - See Under Hood Decal R-134a; 7.80 Oz. PAG-46	59007
04	All Eng.; w/ Rear AC - See Under Hood Decal R-134a; 10.10 Oz. PAG-46	59007
	All Eng.; w/o Rear AC - See Under Hood Decal R-134a; 6.10 Oz. PAG-46	59007
03	All Eng.; w/o Rear AC - 31.00 Oz. R-134a; 5.00 Oz. PAG-46; w/ Single or Dual Zone	59007
	All Eng.; w/ Rear AC - 31.00 Oz. R-134a; 6.40 Oz. PAG-46; w/ Single or Dual Zone	59007
	All Eng.; w/o Rear AC - 43.00 Oz. R-134a; 6.40 Oz. PAG-46; w/ 3 Zone	59007
02	All Eng.; w/o Rear AC - See Under Hood Decal R-134a; 5.00 Oz. PAG-46	59007
	All Eng.; w/ Rear AC - See Under Hood Decal R-134a; 7.40 Oz. PAG-46	59007
01-00	All Eng.; w/o Rear AC - 34.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
	All Eng.; w/ Rear AC - 46.00 Oz. R-134a; 7.40 Oz. PAG-46	59007
99-96	All Eng.; w/o Rear AC - 34.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
	All Eng.; w/ Rear AC - 48.00 Oz. R-134a; 7.50 Oz. PAG-46	59007
95-94	All Eng.; w/o Rear AC - 36.00 Oz. R-134a; 4.73 Oz. PAG-46	59007
	All Eng.; w/ Rear AC - 50.00 Oz. R-134a; 7.40 Oz. PAG-46	59007
93	All Eng.; w/o Rear AC - 36.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
	All Eng.; w/ Rear AC - 50.00 Oz. R-134a; 13.00 Oz. PAG-46	59007
	4 Cyl. 2.5 Eng. - w/ R-12	59000 ⁵⁹
	6 Cyl. 3.0 Eng. - w/ R-12	59000 ⁵⁹
	6 Cyl. 3.3 Eng. - w/ R-12	59000 ⁵⁹
92	All Eng.; w/o Rear AC - 33.50 Oz. R-12; 7.25 Oz. Mineral Oil; w/ Fixed Displacement Compressor	59000 ⁵⁹
	All Eng.; w/o Rear AC - 33.50 Oz. R-12; 8.75 Oz. Mineral Oil; w/ Variable Displacement Compressor	59000 ⁵⁹
	All Eng.; w/ Rear AC - 44.00 Oz. R-12; 13.00 Oz. Mineral Oil; w/ Fixed Displacement Compressor	59000 ⁵⁹
	All Eng.; w/ Rear AC - 44.00 Oz. R-12; 13.00 Oz. Mineral Oil; w/ Variable Displacement Compressor	59000 ⁵⁹
91-90	All Eng.; w/o Rear AC - 32.00 Oz. R-12; 7.25 Oz. Mineral Oil; w/ Fixed Displacement Compressor	59000 ⁵⁹
	All Eng.; w/o Rear AC - 32.00 Oz. R-12; 8.75 Oz. Mineral Oil; w/ Variable Displacement Compressor	59000 ⁵⁹
	All Eng.; w/ Rear AC - 43.00 Oz. R-12; 13.00 Oz. Mineral Oil; w/ Fixed Displacement Compressor	59000 ⁵⁹
	All Eng.; w/ Rear AC - 43.00 Oz. R-12; 13.00 Oz. Mineral Oil; w/ Variable Displacement Compressor	59000 ⁵⁹
89	All Eng.; w/o Rear AC - 38.00 Oz. R-12; 7.25 Oz. Mineral Oil; w/ Fixed Displacement Compressor	59000 ⁵⁹
	All Eng.; w/o Rear AC - 38.00 Oz. R-12; 8.75 Oz. Mineral Oil; w/ Variable Displacement Compressor	59000 ⁵⁹
	All Eng.; w/ Rear AC - 43.00 Oz. R-12; 13.00 Oz. Mineral Oil; w/ Fixed Displacement Compressor	59000 ⁵⁹
	All Eng.; w/ Rear AC - 43.00 Oz. R-12; 13.00 Oz. Mineral Oil; w/ Variable Displacement Compressor	59000 ⁵⁹
88	All Eng.; w/o Rear AC - 44.00 Oz. R-12; 7.25 Oz. Mineral Oil	59000 ⁵⁹
87-86	All Eng.; w/o Rear AC - 38.00 Oz. R-12; 7.00 Oz. Mineral Oil	59000 ⁵⁹
85-84	4 Cyl. 2.2 Eng. - See Under Hood Decal	59000 ⁵⁹
	4 Cyl. 2.6 Eng. - See Under Hood Decal	59000 ⁵⁹

Continued on Next Page

⁵⁹ When retrofitting to R134a PAG Oil must be used.

DODGE LIGHT TRUCK

Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that A/C system has been properly cleaned, and new accumulator / filter drier has been installed. Specs are for total system capacities. Always refer to under hood decal as the primary source for refrigerant and lubricant information.

Year	Model	Lubricant
DAKOTA		
11	6 Cyl. 3.7 Eng. - 20.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
	8 Cyl. 4.7 Eng. - 20.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
10-09	All Eng. - 20.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
08	All Eng. - 20.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
07-01	All Eng. - 32.00 Oz. R-134a; 7.00 Oz. PAG-100	59002
00	All Eng. - 32.00 Oz. R-134a; 6.00 Oz. PAG-100	59002
99-98	All Eng. - 32.00 Oz. R-134a; 8.00 Oz. PAG-100	59002
97-94	All Eng. - 32.00 Oz. R-134a; 7.75 Oz. PAG-100	59002
93-92	All Eng. - 40.00 Oz. R-12; 7.25 Oz. Mineral Oil	59000 ⁵⁹
91-87	All Eng. - 44.00 Oz. R-12; 7.25 Oz. Mineral Oil	59000 ⁵⁹
DURANGO		
13	6 Cyl. 3.6 Eng. - 22.08 Oz. R-134a; 4.00 Oz. PAG-46	59007
	8 Cyl. 5.7 Eng. - 22.08 Oz. R-134a; 4.00 Oz. PAG-46	59007
12	6 Cyl. 3.6 Eng.; w/o Rear AC - 22.08 Oz. R-134a; 4.00 Oz. PAG-46	59007
	6 Cyl. 3.6 Eng.; w/ Rear AC - 32.48 Oz. R-134a; 5.00 Oz. PAG-46	59007
	8 Cyl. 5.7 Eng.; w/o Rear AC - 22.08 Oz. R-134a; 4.00 Oz. PAG-46	59007
	8 Cyl. 5.7 Eng.; w/ Rear AC - 32.48 Oz. R-134a; 5.00 Oz. PAG-46	59007
11	6 Cyl. 3.6 Eng.; w/o Rear AC - 31.68 Oz. R-134a; 4.00 Oz. PAG-46	59007
	6 Cyl. 3.6 Eng.; w/ Rear AC - 32.48 Oz. R-134a; 5.00 Oz. PAG-46	59007
	8 Cyl. 5.7 Eng.; w/o Rear AC - 22.08 Oz. R-134a; 4.00 Oz. PAG-46	59007
	8 Cyl. 5.7 Eng.; w/ Rear AC - 32.48 Oz. R-134a; 5.00 Oz. PAG-46	59007
09	6 Cyl. 3.7 Eng.; w/o Rear AC - 30.00 Oz. R-134a; 5.41 Oz. PAG-46	59007
	6 Cyl. 3.7 Eng.; w/ Rear AC - 41.00 Oz. R-134a; 6.90 Oz. PAG-46	59007
	8 Cyl. 4.7 Eng.; w/o Rear AC - 30.00 Oz. R-134a; 5.41 Oz. PAG-46	59007
	8 Cyl. 4.7 Eng.; w/ Rear AC - 41.00 Oz. R-134a; 6.09 Oz. PAG-46	59007
	8 Cyl. 5.7 Eng.; w/o Rear AC - 30.00 Oz. R-134a; 5.41 Oz. PAG-46	59007
	8 Cyl. 5.7 Eng.; w/ Rear AC - 40.00 Oz. R-134a; 7.40 Oz. PAG-46	59007
	8 Cyl. 5.7 Eng.; HEMI; w/ Rear AC - 45.00 Oz. R-134a; 6.25 Oz. PAG-46	59007
08	6 Cyl. 3.7 Eng.; w/o Rear AC - 30.00 Oz. R-134a; 5.41 Oz. PAG-46	59007
	6 Cyl. 3.7 Eng.; w/ Rear AC - 41.00 Oz. R-134a; 6.09 Oz. PAG-46	59007
	8 Cyl. 4.7 Eng.; w/o Rear AC - 30.00 Oz. R-134a; 5.41 Oz. PAG-46	59007
	8 Cyl. 4.7 Eng.; w/ Rear AC - 41.00 Oz. R-134a; 6.09 Oz. PAG-46	59007
	8 Cyl. 5.7 Eng.; w/o Rear AC - 30.00 Oz. R-134a; 5.41 Oz. PAG-46	59007
	8 Cyl. 5.7 Eng.; w/ Rear AC - 40.00 Oz. R-134a; 7.40 Oz. PAG-46	59007
07	All Eng.; w/o Rear AC - 30.00 Oz. R-134a; 5.07 Oz. PAG-46	59007
	All Eng.; w/ Rear AC - 40.00 Oz. R-134a; 7.40 Oz. PAG-46	59007
06-05	All Eng.; w/o Rear AC - w/ R-134a; 5.00 Oz. PAG-100	59002
	All Eng.; w/ Rear AC - w/ R-134a; 7.50 Oz. PAG-100	59002
04-01	All Eng.; w/ Rear AC - w/ R-134a; 10.00 Oz. PAG-100	59002
	All Eng.; w/o Rear AC - w/ R-134a; 7.00 Oz. PAG-100	59002
00	All Eng.; w/o Rear AC - 28.00 Oz. R-134a; 5.50 Oz. PAG-100	59002
	All Eng.; w/ Rear AC - 32.00 Oz. R-134a; 8.00 Oz. PAG-100	59002
99-98	All Eng.; w/o Rear AC - 28.00 Oz. R-134a; 5.50 Oz. PAG-100	59002
	All Eng.; w/ Rear AC - 30.00 Oz. R-134a; 8.00 Oz. PAG-100	59002
JOURNEY		
13-12	4 Cyl. 2.4 Eng.; w/o Rear AC - 22.00 Oz. R-134a; 3.40 Oz. PAG-100	59002
	4 Cyl. 2.4 Eng.; w/ Rear AC - 32.00 Oz. R-134a; 3.40 Oz. PAG-100	59002
	6 Cyl. 3.6 Eng.; w/o Rear AC - 22.00 Oz. R-134a; 3.40 Oz. PAG-100	59002
	6 Cyl. 3.6 Eng.; w/ Rear AC - 32.00 Oz. R-134a; 3.40 Oz. PAG-100	59002
11	4 Cyl. 2.4 Eng.; w/o Rear AC - 22.00 Oz. R-134a; 3.40 Oz. PAG-100	59002
	4 Cyl. 2.4 Eng.; w/ Rear AC - 32.00 Oz. R-134a; 3.40 Oz. PAG-100	59002
	6 Cyl. 3.6 Eng.; w/o Rear AC - 22.00 Oz. R-134a; 3.40 Oz. PAG-100	59002
	6 Cyl. 3.6 Eng.; w/o Rear AC - 22.00 Oz. R-134a; 3.40 Oz. PAG-100	59002
	6 Cyl. 3.6 Eng.; w/ Rear AC - 32.00 Oz. R-134a; 3.40 Oz. PAG-100	59002
10	4 Cyl. 2.4 Eng.; w/o Rear AC - 22.00 Oz. R-134a; 3.40 Oz. PAG-100	59002
	4 Cyl. 2.4 Eng.; w/o Rear AC - 22.00 Oz. R-134a; 3.40 Oz. PAG-100	59002
	4 Cyl. 2.4 Eng.; w/ Rear AC - 32.00 Oz. R-134a; 3.40 Oz. PAG-100	59002
	6 Cyl. 3.5 Eng.; w/o Rear AC - 22.00 Oz. R-134a; 3.40 Oz. PAG-100	59002
	6 Cyl. 3.5 Eng.; w/o Rear AC - 22.00 Oz. R-134a; 3.40 Oz. PAG-100	59002
	6 Cyl. 3.5 Eng.; w/ Rear AC - 32.00 Oz. R-134a; 3.40 Oz. PAG-100	59002
09	4 Cyl. 2.4 Eng.; w/o Rear AC - 22.00 Oz. R-134a; 3.40 Oz. PAG-100	59002
	4 Cyl. 2.4 Eng.; w/o Rear AC - 22.00 Oz. R-134a; 3.40 Oz. PAG-100	59002
	4 Cyl. 2.4 Eng.; w/ Rear AC - 32.00 Oz. R-134a; 3.40 Oz. PAG-100	59002

Continued on Next Page

⁵⁹ When retrofitting to R134a PAG Oil must be used.

DODGE LIGHT TRUCK

Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that A/C system has been properly cleaned, and new accumulator / filter drier has been installed. Specs are for total system capacities. Always refer to under hood decal as the primary source for refrigerant and lubricant information.

Year	Model	Lubricant
JOURNEY (Cont'd)		
09	6 Cyl. 3.5 Eng.; w/o Rear AC - 22.00 Oz. R-134a; 3.40 Oz. PAG-100	59002
	6 Cyl. 3.5 Eng.; w/o Rear AC - 22.00 Oz. R-134a; 3.40 Oz. PAG-100	59002
	6 Cyl. 3.5 Eng.; w/ Rear AC - 32.00 Oz. R-134a; 3.40 Oz. PAG-100	59002
NITRO		
11 10-07	6 Cyl. 3.7 Eng. - 19.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
	6 Cyl. 4.0 Eng. - 19.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
	All Eng. - 19.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
PICKUP - FULLSIZE / RAMCHARGER		
13	6 Cyl. 3.6 Eng. - 22.00 Oz. R-134a; 6.00 Oz. PAG-46	59007
	6 Cyl. 6.7 Eng. - 22.00 Oz. R-134a; 6.00 Oz. PAG-46	59007
	8 Cyl. 4.7 Eng. - 22.00 Oz. R-134a; 6.00 Oz. PAG-46	59007
12	8 Cyl. 5.7 Eng. - 22.00 Oz. R-134a; 6.00 Oz. PAG-46	59007
	6 Cyl. 3.7 Eng. - 22.00 Oz. R-134a; 6.00 Oz. PAG-46	59007
	6 Cyl. 6.7 Eng. - 22.00 Oz. R-134a; 6.00 Oz. PAG-46	59007
11	8 Cyl. 4.7 Eng. - 22.00 Oz. R-134a; 6.00 Oz. PAG-46	59007
	8 Cyl. 5.7 Eng. - 22.00 Oz. R-134a; 6.00 Oz. PAG-46	59007
	6 Cyl. 3.7 Eng. - 22.00 Oz. R-134a; 6.00 Oz. PAG-46	59007
10-09	6 Cyl. 6.7 Eng. - 19.00 Oz. R-134a; 6.00 Oz. PAG-46	59007
	8 Cyl. 4.7 Eng. - 22.00 Oz. R-134a; 6.00 Oz. PAG-46	59007
	8 Cyl. 5.7 Eng. - 22.00 Oz. R-134a; 6.00 Oz. PAG-46	59007
10-09	6 Cyl. 3.7 Eng. - 22.00 Oz. R-134a; 6.00 Oz. PAG-46	59007
	6 Cyl. 5.9 Eng. - 22.00 Oz. R-134a; 6.00 Oz. PAG-46	59007
	6 Cyl. 6.7 Eng. - 22.00 Oz. R-134a; 6.00 Oz. PAG-46	59007
08-07	8 Cyl. 4.7 Eng. - 22.00 Oz. R-134a; 6.00 Oz. PAG-46	59007
	8 Cyl. 5.7 Eng. - 22.00 Oz. R-134a; 6.00 Oz. PAG-46	59007
	6 Cyl. 3.7 Eng. - 22.00 Oz. R-134a; 6.00 Oz. PAG-46	59007
06	6 Cyl. 5.9 Eng. - 22.00 Oz. R-134a; 6.00 Oz. PAG-46	59007
	6 Cyl. 6.7 Eng. - 24.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
	8 Cyl. 4.7 Eng. - 22.00 Oz. R-134a; 6.00 Oz. PAG-46	59007
05-04	8 Cyl. 5.7 Eng. - 22.00 Oz. R-134a; 6.00 Oz. PAG-46	59007
	10 Cyl. 8.3 Eng. - 24.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
	6 Cyl. 3.7 Eng. - 22.00 Oz. R-134a; 6.00 Oz. PAG-46	59007
03-00	6 Cyl. 5.9 Eng. - 24.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
	8 Cyl. 4.7 Eng. - 22.00 Oz. R-134a; 6.00 Oz. PAG-46	59007
	8 Cyl. 5.7 Eng. - 22.00 Oz. R-134a; 6.00 Oz. PAG-46	59007
99-98	All Eng. - 32.00 Oz. R-134a; 6.25 Oz. PAG-100	59002
	All Eng. - 32.00 Oz. R-134a; 8.00 Oz. PAG-100	59002
	All Eng. - 32.00 Oz. R-134a; 7.75 Oz. PAG-100	59002
97-94	All Eng. - 44.00 Oz. R-12; 4.75 Oz. Mineral Oil	59000 ⁵⁹
	All Eng. - 44.00 Oz. R-12; 7.25 Oz. Mineral Oil	59000 ⁵⁹
	All Eng. - 42.00 Oz. R-12; 7.25 Oz. Mineral Oil	59000 ⁵⁹
93	8 Cyl. 5.2 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.9 Eng. - See Under Hood Decal	59000 ⁵⁹
PICKUP - MINI		
93-90	All Eng. - 30.00 Oz. R-12; 8.50 Oz. Mineral Oil	59000 ⁵⁹
	All Eng. - 32.00 Oz. R-12; 6.00 Oz. Mineral Oil	59000 ⁵⁹
	4 Cyl. 2.0 Eng. - See Under Hood Decal	59000 ⁵⁹
88-87	4 Cyl. 2.6 Eng. - See Under Hood Decal	59000 ⁵⁹
	RAIDER	
89	All Eng. - 32.00 Oz. R-12; 6.75 Oz. Mineral Oil	59000 ⁵⁹
	4 Cyl. 2.6 Eng.	59000 ⁵⁹
	6 Cyl. 3.0 Eng.	59000 ⁵⁹
88-87	4 Cyl. 2.6 Eng. - See Under Hood Decal	59000 ⁵⁹
	RAMPAGE	
84-82	4 Cyl. 2.2 Eng. - See Under Hood Decal	59000 ⁵⁹
	SPRINTER	
09	6 Cyl. 3.0 Eng.; w/o Rear AC - 28.16 Oz. R-134a; 6.40 Oz. PAG-46	59007
	6 Cyl. 3.0 Eng.; w/ Rear AC - 32.48 Oz. R-134a; 5.00 Oz. PAG-46	59007

Continued on Next Page

⁵⁹ When retrofitting to R134a PAG Oil must be used.

DODGE LIGHT TRUCK

Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that A/C system has been properly cleaned, and new accumulator / filter drier has been installed. Specs are for total system capacities. Always refer to under hood decal as the primary source for refrigerant and lubricant information.

Year	Model	Lubricant
SPRINTER (Cont'd)		
08	6 Cyl. 3.0 Eng.; w/o Rear AC - 28.16 Oz. R-134a; 6.40 Oz. PAG-46	59007
	6 Cyl. 3.0 Eng.; w/ Rear AC - 32.48 Oz. R-134a; 5.00 Oz. PAG-46	59007
	6 Cyl. 3.5 Eng.; w/o Rear AC - 28.16 Oz. R-134a; 6.40 Oz. PAG-46	59007
	6 Cyl. 3.5 Eng.; w/ Rear AC - 32.48 Oz. R-134a; 5.00 Oz. PAG-46	59007
07	All Eng.; w/o Rear AC - 28.16 Oz. R-134a; 6.40 Oz. PAG-46	59007
	All Eng.; w/ Rear AC - 40.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
06-03	5 Cyl. 2.7 Eng. - See Under Hood Decal R-134a; 13.90 Oz. PAG-46	59007
VAN - FULLSIZE		
03-98	All Eng.; w/o Rear AC - 34.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
	All Eng.; w/ Rear AC - 46.00 Oz. R-134a; 10.00 Oz. PAG-46	59007
97-94	All Eng.; w/o Rear AC - 40.00 Oz. R-134a; 7.25 Oz. PAG-46	59007
	All Eng.; w/ Rear AC - 60.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
93-91	All Eng.; w/o Rear AC - 44.00 Oz. R-12; 7.25 Oz. Mineral Oil	59000 ⁵⁹
	All Eng.; w/ Rear AC - 65.00 Oz. R-12; 9.00 Oz. Mineral Oil	59000 ⁵⁹
90	All Eng.; w/o Rear AC - 44.00 Oz. R-12; 7.25 Oz. Mineral Oil	59000 ⁵⁹
	All Eng.; w/ Rear AC - 65.00 Oz. R-12; 9.00 Oz. Mineral Oil; w/ Fixed Displacement Compressor	59000 ⁵⁹
	All Eng.; w/ Rear AC - 65.00 Oz. R-12; 9.00 Oz. Mineral Oil; w/ Variable Displacement Compressor	59000 ⁵⁹
89	All Eng.; w/o Rear AC - 49.00 Oz. R-12; 7.25 Oz. Mineral Oil; w/ Fixed Displacement Compressor	59000 ⁵⁹
	All Eng.; w/ Rear AC - 65.00 Oz. R-12; 9.00 Oz. Mineral Oil; w/ Fixed Displacement Compressor	59000 ⁵⁹
	All Eng.; w/ Rear AC - 65.00 Oz. R-12; 9.00 Oz. Mineral Oil; w/ Variable Displacement Compressor	59000 ⁵⁹
88	All Eng.; w/o Rear AC - 44.00 Oz. R-12; 5.00 Oz. Mineral Oil	59000 ⁵⁹
	All Eng.; w/ Rear AC - 65.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
87-86	All Eng.; w/o Rear AC - 48.00 Oz. R-12; 5.00 Oz. Mineral Oil	59000 ⁵⁹
	All Eng.; w/ Rear AC - 64.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
85	All Eng.; w/o Rear AC - 48.00 Oz. R-12; 5.00 Oz. Mineral Oil	59000 ⁵⁹
	All Eng.; w/ Front & Rear AC - 64.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
84-81	8 Cyl. 5.2 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.9 Eng. - See Under Hood Decal	59000 ⁵⁹

EAGLE

Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that A/C system has been properly cleaned, and new accumulator / filter drier has been installed. Specs are for total system capacities. Always refer to under hood decal as the primary source for refrigerant and lubricant information.

Year	Model	Lubricant
MEDALLION		
89	All Eng. - 29.00 Oz. R-12; 5.50 Oz. Mineral Oil	59000 ⁵⁹
PREMIER		
92-89	All Eng. - 36.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
88	4 Cyl. 2.5 Eng. - See Under Hood Decal	59000 ⁵⁹
	6 Cyl. 3.0 Eng. - See Under Hood Decal	59000 ⁵⁹
SUMMIT		
96-95	4 Cyl. 1.5 Eng. Coupe - 27.00 Oz. R-134a; 4.40 Oz. PAG-46	59007
	4 Cyl. 1.5 Eng. Sedan - 27.00 Oz. R-134a; 5.10 Oz. PAG-46	59007
	4 Cyl. 1.8 Eng. - 27.00 Oz. R-134a; 4.10 Oz. PAG-46	59007
94	4 Cyl. 2.4 Eng. - 27.00 Oz. R-134a; 2.70 Oz. PAG-46	59007
	4 Cyl. 1.5 Eng. - 27.00 Oz. R-134a; 4.40 Oz. PAG-46	59007
	4 Cyl. 1.8 Eng. - 27.00 Oz. R-134a; 4.10 Oz. PAG-46	59007
93	4 Cyl. 2.4 Eng. - 27.00 Oz. R-134a; 2.70 Oz. PAG-46	59007
	4 Cyl. 1.5 Eng. - 28.00 Oz. R-12; 5.60 Oz. Mineral Oil	59000 ⁵⁹
	4 Cyl. 1.8 Eng. - 28.00 Oz. R-12; 5.60 Oz. Mineral Oil	59000 ⁵⁹
92	4 Cyl. 2.4 Eng. - 28.00 Oz. R-12; 5.60 Oz. Mineral Oil	59000 ⁵⁹
	4 Cyl. 1.5 Eng. - 36.00 Oz. R-12; 5.70 Oz. Mineral Oil	59000 ⁵⁹
	4 Cyl. 1.8 Eng. - 36.00 Oz. R-12; 5.70 Oz. Mineral Oil	59000 ⁵⁹
91	4 Cyl. 2.4 Eng. - 36.00 Oz. R-12; 5.70 Oz. Mineral Oil	59000 ⁵⁹
	4 Cyl. 1.5 Eng. - 36.00 Oz. R-12; 5.70 Oz. Mineral Oil	59000 ⁵⁹
90-89	4 Cyl. 1.5 Eng. - 36.00 Oz. R-12; 5.70 Oz. Mineral Oil	59000 ⁵⁹
	4 Cyl. 1.6 Eng. - 36.00 Oz. R-12; 5.70 Oz. Mineral Oil	59000 ⁵⁹
TALON		
98-95	All Eng. - 25.50 Oz. R-134a; 6.50 Oz. PAG-100	59002
94-90	All Eng. - 33.00 Oz. R-12; 5.00 Oz. Mineral Oil	59000 ⁵⁹

Continued on Next Page

⁵⁹ When retrofitting to R134a PAG Oil must be used.

Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that A/C system has been properly cleaned, and new accumulator / filter drier has been installed. Specs are for total system capacities. Always refer to under hood decal as the primary source for refrigerant and lubricant information.

Year	Model	Lubricant
	VISION	
97-96	All Eng. - 28.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
95	All Eng. - 28.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
94	All Eng. - 28.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
	6 Cyl. 3.3 Eng. - 28.00 Oz. R-134a; 4.80 Oz. PAG-46	59007
	6 Cyl. 3.5 Eng. - 28.00 Oz. R-134a; 4.80 Oz. PAG-46	59007
93	All Eng. - 28.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
	6 Cyl. 3.3 Eng. - 28.00 Oz. R-134a; 4.75 Oz. PAG-46	59007
	6 Cyl. 3.5 Eng. - 28.00 Oz. R-134a; 4.75 Oz. PAG-46	59007

FIAT

Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that A/C system has been properly cleaned, and new accumulator / filter drier has been installed. Specs are for total system capacities. Always refer to under hood decal as the primary source for refrigerant and lubricant information.

Year	Model	Lubricant
	500	
13-12	4 Cyl. 1.4 Eng. - 17.00 Oz. R-134a; 1.70 Oz. PAG-46	59007

FORD

Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that A/C system has been properly cleaned, and new accumulator / filter drier has been installed. Specs are for total system capacities. Always refer to under hood decal as the primary source for refrigerant and lubricant information.

Year	Model	Lubricant
	ASPIRE	
97	All Eng. - 26.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
96-94	All Eng. - 25.00 Oz. R-134a; 6.00 Oz. PAG-46	59007
	CONTOUR	
00-95	All Eng. - 26.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
	COUNTRY SQUIRE	
91-88	8 Cyl. 5.0 Eng. - 54.00 Oz. R-12; 8.00 Oz. Mineral Oil; w/ Denso Compressor	59000 ⁵⁹
87	8 Cyl. 5.0 Eng. - 54.00 Oz. R-12; 10.00 Oz. Ester; w/ FS6 Compressor	59000 ⁵⁹
	CROWN VICTORIA	
11-09	8 Cyl. 4.6 Eng. - 27.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
08-06	All Eng. - 27.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
05-97	All Eng. - 38.00 Oz. R-134a; 7.50 Oz. PAG-46	59007
96-95	All Eng. - 38.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
94	All Eng. - 34.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
93	All Eng. - 38.00 Oz. R-12; 7.00 Oz. Ester	59000 ⁵⁹
	8 Cyl. 4.6 Eng. - 38.00 Oz. R-134a; See Under Hood Decal	59007
92	All Eng. - 36.00 Oz. R-12; 7.00 Oz. Ester	59000 ⁵⁹
91-89	All Eng. - 48.00 Oz. R-12; 8.00 Oz. Ester	59000 ⁵⁹
88	All Eng. - 52.00 Oz. R-12; 13.00 Oz. Ester	59000 ⁵⁹
87	All Eng. To 9/86 - 52.00 Oz. R-12; 10.00 Oz. Ester	59000 ⁵⁹
	All Eng. From 9/86 - 52.00 Oz. R-12; 13.00 Oz. Ester	59000 ⁵⁹
	EDGE	
13	4 Cyl. 2.0 Eng. - 21.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
	6 Cyl. 3.5 Eng. - 21.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
	6 Cyl. 3.7 Eng. - 21.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
12	4 Cyl. 2.0 Eng. - 25.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
	6 Cyl. 3.5 Eng. - 25.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
	6 Cyl. 3.7 Eng. - 25.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
11	6 Cyl. 3.5 Eng. - 25.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
	6 Cyl. 3.7 Eng. - 25.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
10-09	6 Cyl. 3.5 Eng. - 25.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
08	All Eng. - 21.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
07	All Eng. - 19.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
	ESCORT	
03	4 Cyl. 2.0 Eng. - 24.00 Oz. R-134a; 6.60 Oz. PAG-46	59007
02-98	All Eng. - 28.00 Oz. R-134a; 6.75 Oz. PAG-46	59007
	4 Cyl. 2.0 Eng. - 28.00 Oz. R-134a; 6.75 Oz. PAG-46	59007

Continued on Next Page

⁵⁹ When retrofitting to R134a PAG Oil must be used.

FORD

Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that A/C system has been properly cleaned, and new accumulator / filter drier has been installed. Specs are for total system capacities. Always refer to under hood decal as the primary source for refrigerant and lubricant information.

Year	Model	Lubricant
ESCORT (Cont'd)		
97	All Eng. - 28.00 Oz. R-134a; 6.75 Oz. PAG-46	59007
96-94	All Eng. - 28.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
93	All Eng. - 34.08 Oz. R-12; 7.75 Oz. Ester	59000 ⁵⁹
92-91	All Eng. - 33.92 Oz. R-12; 8.00 Oz. Ester	59000 ⁵⁹
90-88	All Eng. - 36.00 Oz. R-12; 8.00 Oz. Ester	59000 ⁵⁹
87	All Eng. - 41.00 Oz. R-12; 8.00 Oz. Ester	59000 ⁵⁹
86	All Eng. - 36.00 Oz. R-12; 10.00 Oz. Ester	59000 ⁵⁹
85	4 Cyl. 1.6 Eng. - See Under Hood Decal	59000 ⁵⁹
	4 Cyl. 1.9 Eng. - See Under Hood Decal	59000 ⁵⁹
	4 Cyl. 2.0 Eng. - See Under Hood Decal	59000 ⁵⁹
84-81	4 Cyl. 1.6 Eng. - See Under Hood Decal	59000 ⁵⁹
EXP		
88-86	4 Cyl. 1.9 Eng. - See Under Hood Decal	59000 ⁵⁹
85-82	4 Cyl. 1.6 Eng. - See Under Hood Decal	59000 ⁵⁹
FAIRMONT		
82-80	8 Cyl. 4.2 Eng. - See Under Hood Decal	59000 ⁵⁹
79-78	8 Cyl. 5.0 Eng. - See Under Hood Decal	59000 ⁵⁹
FESTIVA		
93-88	All Eng. - 25.00 Oz. R-12; 10.00 Oz. Ester	59000 ⁵⁹
FIESTA		
13-11	4 Cyl. 1.6 Eng. - 19.00 Oz. R-134a; 3.40 Oz. PAG-46	59007
FIVE HUNDRED		
07-05	All Eng.; w/o Rear AC - 29.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
	All Eng.; w/ Rear AC - 38.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
FOCUS		
13-09	4 Cyl. 2.0 Eng. - 18.00 Oz. R-134a; 4.10 Oz. PAG-46	59007
08	All Eng. - 18.00 Oz. R-134a; 4.50 Oz. PAG-46	59007
07-00	All Eng. - 26.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
FUSION		
13	4 Cyl. 1.6 Eng. - 20.00 Oz. R-134a; 4.90 Oz. PAG-46	59007
	4 Cyl. 2.0 Eng.; Hybrid - 20.00 Oz. R-134a; 4.90 Oz. Hybrid Oil	59889
	4 Cyl. 2.0 Eng. - 20.00 Oz. R-134a; 4.90 Oz. PAG-46	59007
	4 Cyl. 2.5 Eng. - 24.00 Oz. R-134a; 4.90 Oz. PAG-46	59007
12-11	4 Cyl. 2.5 Eng. - 22.00 Oz. R-134a; 6.00 Oz. PAG-46	59007
	6 Cyl. 3.0 Eng. - 22.00 Oz. R-134a; 6.00 Oz. PAG-46	59007
	6 Cyl. 3.5 Eng. - 22.00 Oz. R-134a; 6.00 Oz. PAG-46	59007
10	4 Cyl. 2.5 Eng.; Hybrid - 22.00 Oz. R-134a; 4.40 Oz. Hybrid Oil	59889
	4 Cyl. 2.5 Eng. - 22.00 Oz. R-134a; 6.00 Oz. PAG-46	59007
	6 Cyl. 3.0 Eng. - 22.00 Oz. R-134a; 6.00 Oz. PAG-46	59007
	6 Cyl. 3.5 Eng. - 22.00 Oz. R-134a; 6.00 Oz. PAG-46	59007
09	4 Cyl. 2.3 Eng. - 21.00 Oz. R-134a; 6.00 Oz. PAG-46	59007
	6 Cyl. 3.0 Eng. - 21.00 Oz. R-134a; 6.00 Oz. PAG-46	59007
08-06	All Eng. - 21.00 Oz. R-134a; 6.00 Oz. PAG-46	59007
GRANADA		
82	6 Cyl. 3.8 Eng. - See Under Hood Decal	59000 ⁵⁹
81	8 Cyl. 4.2 Eng. - See Under Hood Decal	59000 ⁵⁹
80	6 Cyl. 4.1 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 4.2 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.0 Eng. - See Under Hood Decal	59000 ⁵⁹
79-78	6 Cyl. 4.1 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.0 Eng. - See Under Hood Decal	59000 ⁵⁹
77-76	6 Cyl. 3.3 Eng. - See Under Hood Decal	59000 ⁵⁹
	6 Cyl. 4.1 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.0 Eng. - See Under Hood Decal	59000 ⁵⁹
75	8 Cyl. 5.8 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.0 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.8 Eng. - See Under Hood Decal	59000 ⁵⁹
LTD		
86	All Eng. - 40.00 Oz. R-12; 8.00 Oz. Ester	59000 ⁵⁹
85	All Eng. - 40.00 Oz. R-12; 10.00 Oz. Ester	59000 ⁵⁹
	All Eng. - 40.00 Oz. R-12; 8.00 Oz. Ester	59000 ⁵⁹
84	6 Cyl. 3.8 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.0 Eng. - See Under Hood Decal	59000 ⁵⁹

Continued on Next Page

⁵⁹ When retrofitting to R134a PAG Oil must be used.

Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that A/C system has been properly cleaned, and new accumulator / filter drier has been installed. Specs are for total system capacities. Always refer to under hood decal as the primary source for refrigerant and lubricant information.

Year	Model	Lubricant
	LTD II	
79	8 Cyl. 5.0 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.8 Eng. - See Under Hood Decal	59000 ⁵⁹
78-77	8 Cyl. 5.0 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.8 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 6.6 Eng. - See Under Hood Decal	59000 ⁵⁹
	MAVERICK	
77-71	8 Cyl. 5.0 Eng. - See Under Hood Decal	59000 ⁵⁹
	MUSTANG	
13	6 Cyl. 3.7 Eng. - 21.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
	8 Cyl. 5.0 Eng. - 21.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
	8 Cyl. 5.8 Eng. - 21.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
12-11	6 Cyl. 3.7 Eng. - 21.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
	8 Cyl. 5.0 Eng. - 21.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
	8 Cyl. 5.4 Eng. - 21.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
10	6 Cyl. 4.0 Eng. - 21.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
	8 Cyl. 4.6 Eng. - 21.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
	8 Cyl. 5.4 Eng. - 21.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
09	6 Cyl. 4.0 Eng. - 26.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
	8 Cyl. 4.6 Eng. - 26.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
	8 Cyl. 5.4 Eng. - 26.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
08-07	All Eng. - 26.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
06-05	All Eng. - 31.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
04-97	All Eng. - 34.00 Oz. R-134a; 8.50 Oz. PAG-46	59007
96-94	All Eng. - 34.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
93-89	All Eng. - 40.00 Oz. R-12; 8.00 Oz. Ester	59000 ⁵⁹
88-86	All Eng. - 40.00 Oz. R-12; 10.00 Oz. Ester	59000 ⁵⁹
85-83	6 Cyl. 3.8 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.0 Eng. - See Under Hood Decal	59000 ⁵⁹
82	8 Cyl. 5.0 Eng. - See Under Hood Decal	59000 ⁵⁹
73-72	8 Cyl. 5.0 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.8 Eng. - See Under Hood Decal	59000 ⁵⁹
71	8 Cyl. 5.0 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.8 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 7.0 Eng. - See Under Hood Decal	59000 ⁵⁹
	PINTO	
73	4 Cyl. 1.6 Eng. - See Under Hood Decal	59000 ⁵⁹
	4 Cyl. 2.0 Eng. - See Under Hood Decal	59000 ⁵⁹
	PROBE	
97	All Eng. - 28.00 Oz. R-134a; 7.00 Oz. PAG-100	59002
96-94	All Eng. - 28.00 Oz. R-134a; 6.75 Oz. PAG-100	59002
93	All Eng. - 28.00 Oz. R-12; 8.00 Oz. Ester	59000 ⁵⁹
92-89	All Eng. - 40.00 Oz. R-12; 8.00 Oz. Ester	59000 ⁵⁹
	TAURUS	
13	4 Cyl. 2.0 Eng. - 26.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
	6 Cyl. 3.5 Eng. - 26.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
12-11	6 Cyl. 3.5 Eng. - 26.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
10	All Eng. - 26.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
09	All Eng.; w/o Rear AC - 26.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
	All Eng.; w/ Rear AC - 36.00 Oz. R-134a; 9.50 Oz. PAG-46	59007
08	All Eng.; w/o Rear AC - 26.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
	All Eng.; w/ Rear AC - 32.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
07-96	All Eng. - 34.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
95	All Eng. - 32.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
94	Excl. SHO - 33.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
	SHO - 33.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
93	Excl. SHO - 32.00 Oz. R-12; 7.00 Oz. Ester	59000 ⁵⁹
	SHO - 32.00 Oz. R-12; 8.00 Oz. Ester	59000 ⁵⁹
	6 Cyl. 3.0 Eng. - w/ R-12	59000 ⁵⁹
	6 Cyl. 3.0 Eng. - w/ R-134a	59007
92	Excl. SHO - 41.00 Oz. R-12; 7.00 Oz. Ester	59000 ⁵⁹
	SHO - 41.00 Oz. R-12; 8.00 Oz. Ester	59000 ⁵⁹
	6 Cyl. 3.0 Eng. - w/ R-12	59000 ⁵⁹
	6 Cyl. 3.0 Eng. - w/ R-134a	59007

Continued on Next Page

⁵⁹ When retrofitting to R134a PAG Oil must be used.

FORD

Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that A/C system has been properly cleaned, and new accumulator / filter drier has been installed. Specs are for total system capacities. Always refer to under hood decal as the primary source for refrigerant and lubricant information.

Year	Model	Lubricant
TAURUS (Cont'd)		
91	4 Cyl. 2.5 Eng. - 41.00 Oz. R-12; 10.00 Oz. Ester	59000 ⁵⁹
	6 Cyl. Excl. SHO - 41.00 Oz. R-12; 7.00 Oz. Ester	59000 ⁵⁹
	6 Cyl. SHO - 41.00 Oz. R-12; 8.00 Oz. Ester	59000 ⁵⁹
90	4 Cyl. 2.5 Eng. - 41.00 Oz. R-12; 10.00 Oz. Ester	59000 ⁵⁹
	6 Cyl. Excl. SHO - 41.00 Oz. R-12; 8.00 Oz. Ester	59000 ⁵⁹
	6 Cyl. SHO - 41.00 Oz. R-12; 8.00 Oz. Ester	59000 ⁵⁹
89	4 Cyl. 2.5 Eng. - 44.00 Oz. R-12; 10.00 Oz. Ester	59000 ⁵⁹
	6 Cyl. Excl. SHO - 40.00 Oz. R-12; 8.00 Oz. Ester	59000 ⁵⁹
	6 Cyl. SHO - 44.00 Oz. R-12; 8.00 Oz. Ester	59000 ⁵⁹
88	4 Cyl. 2.5 Eng. - 44.00 Oz. R-12; 10.00 Oz. Ester	59000 ⁵⁹
	6 Cyl. 3.0 Eng. - 44.00 Oz. R-12; 8.00 Oz. Ester	59000 ⁵⁹
	6 Cyl. 3.8 Eng. - 40.00 Oz. R-12; 8.00 Oz. Ester	59000 ⁵⁹
87	4 Cyl. 2.5 Eng. - 44.00 Oz. R-12; 10.00 Oz. Ester	59000 ⁵⁹
	6 Cyl. 3.0 Eng. - 44.00 Oz. R-12; 8.00 Oz. Ester	59000 ⁵⁹
86	All Eng. - 44.00 Oz. R-12; 10.00 Oz. Ester	59000 ⁵⁹
TEMPO		
94	4 Cyl. 2.3 Eng. - 33.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
	6 Cyl. 3.0 Eng. - 33.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
93-92	4 Cyl. 2.3 Eng. - 36.00 Oz. R-12; 7.00 Oz. Ester	59000 ⁵⁹
	6 Cyl. 3.0 Eng. - 36.00 Oz. R-12; 8.00 Oz. Ester	59000 ⁵⁹
91-89	All Eng. - 36.00 Oz. R-12; 7.00 Oz. Ester	59000 ⁵⁹
88-87	All Eng. - 36.00 Oz. R-12; 8.00 Oz. Ester	59000 ⁵⁹
86	All Eng. - 36.00 Oz. R-12; 10.00 Oz. Ester	59000 ⁵⁹
85	All Eng. - 41.00 Oz. R-12; 10.00 Oz. Ester	59000 ⁵⁹
84	4 Cyl. 2.3 Eng. - See Under Hood Decal	59000 ⁵⁹
THUNDERBIRD		
05	8 Cyl. 3.9 Eng. - 28.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
04-02	All Eng. - 28.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
97-95	All Eng. - 36.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
94	All Eng. - 36.00 Oz. R-134a; 6.75 Oz. PAG-46	59007
93-89	All Eng. - 40.00 Oz. R-12; 7.00 Oz. Ester	59000 ⁵⁹
88	4 Cyl. - 40.00 Oz. R-12; 8.00 Oz. Ester	59000 ⁵⁹
	6 Cyl. - 40.00 Oz. R-12; 8.00 Oz. Ester	59000 ⁵⁹
87	8 Cyl. - 40.00 Oz. R-12; 10.00 Oz. Ester	59000 ⁵⁹
	All Eng. - 40.00 Oz. R-12; 8.00 Oz. Ester	59000 ⁵⁹
86	All Eng. To 1/86 - 40.00 Oz. R-12; 10.00 Oz. Ester	59000 ⁵⁹
	All Eng. From 1/86 - 40.00 Oz. R-12; 8.00 Oz. Ester	59000 ⁵⁹
85-83	6 Cyl. 3.8 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.0 Eng. - See Under Hood Decal	59000 ⁵⁹
82	6 Cyl. 3.8 Eng. - See Under Hood Decal	59000 ⁵⁹
81	8 Cyl. 5.0 Eng. - See Under Hood Decal	59000 ⁵⁹
79	8 Cyl. 5.0 Eng. - See Under Hood Decal	59000 ⁵⁹
78-77	8 Cyl. 5.8 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.0 Eng. - See Under Hood Decal	59000 ⁵⁹
76-75	8 Cyl. 6.6 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 7.5 Eng. - See Under Hood Decal	59000 ⁵⁹
74	8 Cyl. 6.6 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 7.5 Eng. - See Under Hood Decal	59000 ⁵⁹
73-72	8 Cyl. 6.6 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 7.0 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 7.5 Eng. - See Under Hood Decal	59000 ⁵⁹
TORINO		
76-75	8 Cyl. 5.8 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 6.6 Eng. - See Under Hood Decal	59000 ⁵⁹
74-72	8 Cyl. 5.0 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.8 Eng. - See Under Hood Decal	59000 ⁵⁹
71	8 Cyl. 6.6 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.0 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.8 Eng. - See Under Hood Decal	59000 ⁵⁹
ZX2		
03-01	4 Cyl. 2.0 Eng. - 24.00 Oz. R-134a; 6.60 Oz. PAG-46	59007
00-98	4 Cyl. 2.0 Eng. - 28.00 Oz. R-134a; 7.00 Oz. PAG-46	59007

⁵⁹ When retrofitting to R134a PAG Oil must be used.

FORD LIGHT TRUCK

Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that A/C system has been properly cleaned, and new accumulator / filter drier has been installed. Specs are for total system capacities. Always refer to under hood decal as the primary source for refrigerant and lubricant information.

Year	Model	Lubricant
AEROSTAR		
97	All Eng.; w/o Rear AC - 38.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
	All Eng.; w/ Rear AC - 54.00 Oz. R-134a; 13.00 Oz. PAG-46	59007
96-94	All Eng.; w/o Rear AC - 38.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
	All Eng.; w/ Rear AC - 54.00 Oz. R-134a; 10.00 Oz. PAG-46	59007
93	All Eng.; w/o Rear AC - 46.00 Oz. R-12; 7.00 Oz. Ester	59000 ⁵⁹
	All Eng.; w/ Rear AC - 64.00 Oz. R-12; 10.00 Oz. Ester	59000 ⁵⁹
92-89	All Eng.; w/o Rear AC - 56.00 Oz. R-12; 7.00 Oz. Ester	59000 ⁵⁹
	All Eng.; w/ Rear AC - 68.00 Oz. R-12; 10.00 Oz. Ester	59000 ⁵⁹
88	All Eng.; w/o Rear AC - 56.00 Oz. R-12; 10.00 Oz. Ester; w/ FS6 Compressor	59000 ⁵⁹
	All Eng.; w/o Rear AC - 56.00 Oz. R-12; 13.00 Oz. Ester; w/ 6E171 Compressor	59000 ⁵⁹
	All Eng.; w/ Rear AC - 60.00 Oz. R-12; 10.00 Oz. Ester; w/ FS6 Compressor	59000 ⁵⁹
	All Eng.; w/ Rear AC - 60.00 Oz. R-12; 13.00 Oz. Ester; w/ 6E171 Compressor	59000 ⁵⁹
87	All Eng.; w/o Rear AC To 9/22/86 - 56.00 Oz. R-12; 10.00 Oz. Ester	59000 ⁵⁹
	All Eng.; w/o Rear AC From 9/22/86 - 56.00 Oz. R-12; 13.00 Oz. Ester	59000 ⁵⁹
	All Eng.; w/ Rear AC To 9/22/86 - 60.00 Oz. R-12; 10.00 Oz. Ester	59000 ⁵⁹
	All Eng.; w/ Rear AC From 9/22/86 - 60.00 Oz. R-12; 13.00 Oz. Ester	59000 ⁵⁹
86	4 Cyl. 2.3 Eng. - See Under Hood Decal	59000 ⁵⁹
	6 Cyl. 2.8 Eng. - See Under Hood Decal	59000 ⁵⁹
	6 Cyl. 3.0 Eng. - See Under Hood Decal	59000 ⁵⁹
BRONCO		
96	All Eng. - 38.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
95	All Eng. - 33.00 Oz. R-134a; 11.00 Oz. PAG-46	59007
94	All Eng. - 32.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
93-91	All Eng. - 44.00 Oz. R-12; 7.00 Oz. Ester	59000 ⁵⁹
90-89	All Eng. - 52.00 Oz. R-12; 7.00 Oz. Ester	59000 ⁵⁹
88-80	6 Cyl. 4.9 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.0 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.8 Eng. - See Under Hood Decal	59000 ⁵⁹
79-78	8 Cyl. 5.8 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 6.6 Eng. - See Under Hood Decal	59000 ⁵⁹
77-76	8 Cyl. 5.0 Eng. - See Under Hood Decal	59000 ⁵⁹
BRONCO II		
90	All Eng. - 32.00 Oz. R-12; 10.00 Oz. Ester	59000 ⁵⁹
89-88	All Eng. - 40.00 Oz. R-12; 10.00 Oz. Ester	59000 ⁵⁹
87	All Eng. - 44.00 Oz. R-12; 10.00 Oz. Ester	59000 ⁵⁹
86	All Eng. - 52.00 Oz. R-12; 10.00 Oz. Ester	59000 ⁵⁹
85	All Eng. - 48.00 Oz. R-12; 10.00 Oz. Ester	59000 ⁵⁹
84	6 Cyl. 2.8 Eng. - See Under Hood Decal	59000 ⁵⁹
E SERIES FULLSIZE VAN		
13-11	10 Cyl. 6.8 Eng.; w/o Rear AC - 30.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
	8 Cyl. 4.6 Eng.; w/o Rear AC - 30.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
	8 Cyl. 4.6 Eng.; w/ Rear AC - 54.00 Oz. R-134a; 16.00 Oz. PAG-46	59007
	8 Cyl. 5.4 Eng.; w/o Rear AC - 30.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
	8 Cyl. 5.4 Eng.; w/ Rear AC - 54.00 Oz. R-134a; 16.00 Oz. PAG-46	59007
	8 Cyl. 6.8 Eng.; w/ Rear AC - 54.00 Oz. R-134a; 16.00 Oz. PAG-46	59007
10	All Eng.; Gas; w/o Rear AC - 30.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
	All Eng.; Gas; w/o Rear AC - 36.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
	All Eng.; Diesel; w/ Rear AC - 54.00 Oz. R-134a; 11.00 Oz. PAG-46	59007
	All Eng.; Gas; w/ Rear AC - 54.00 Oz. R-134a; 16.00 Oz. PAG-46	59007
09	All Eng.; Gas; w/o Rear AC - 30.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
	All Eng.; Gas; w/o Rear AC - 36.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
	All Eng.; Gas; w/ Rear AC - 54.00 Oz. R-134a; 11.00 Oz. PAG-46	59007
	All Eng.; Gas; w/ Rear AC - 54.00 Oz. R-134a; 16.00 Oz. PAG-46	59007
08	All Eng.; Gas; w/o Rear AC - 30.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
	All Eng.; Diesel; w/o Rear AC - 36.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
	All Eng.; Diesel; w/ Rear AC - 54.00 Oz. R-134a; 11.00 Oz. PAG-46	59007
	All Eng.; Gas; w/ Rear AC - 54.00 Oz. R-134a; 16.00 Oz. PAG-46	59007
	All Eng.; Diesel; w/ Rear AC - 60.00 Oz. R-134a; 13.00 Oz. PAG-46	59007
07	All Eng.; Gas; w/o Rear AC - 30.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
	All Eng.; Diesel; w/o Rear AC - 40.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
	All Eng.; Gas; w/ Rear AC - 54.00 Oz. R-134a; 14.00 Oz. PAG-46	59007
	All Eng.; Diesel; w/ Rear AC - 60.00 Oz. R-134a; 13.00 Oz. PAG-46	59007
06-02	All Eng.; w/o Rear AC - 40.00 Oz. R-134a; 9.00 Oz. PAG-46	59007

Continued on Next Page

⁵⁹ When retrofitting to R134a PAG Oil must be used.

FORD LIGHT TRUCK

Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that A/C system has been properly cleaned, and new accumulator / filter drier has been installed. Specs are for total system capacities. Always refer to under hood decal as the primary source for refrigerant and lubricant information.

Year	Model	Lubricant
E SERIES FULLSIZE VAN (Cont'd)		
06-02	All Eng.; w/ Rear AC - 60.00 Oz. R-134a; 13.00 Oz. PAG-46	59007
01-97	All Eng.; w/o Rear AC - 44.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
	All Eng.; w/ Rear AC - 64.00 Oz. R-134a; 13.00 Oz. PAG-46	59007
96-95	All Eng.; w/o Rear AC - 44.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
	All Eng.; w/ Rear AC - 64.00 Oz. R-134a; 10.00 Oz. PAG-46	59007
94	All Eng.; w/o Rear AC - 48.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
	All Eng.; w/ Rear AC - 64.00 Oz. R-134a; 10.00 Oz. PAG-46	59007
93-92	All Eng.; w/o Rear AC - 55.00 Oz. R-12; 10.00 Oz. Ester	59000 ⁵⁹
	All Eng.; w/ Rear AC - 72.00 Oz. R-12; 10.00 Oz. Ester	59000 ⁵⁹
91-89	All Eng.; w/o Rear AC - 56.00 Oz. R-12; 10.00 Oz. Ester	59000 ⁵⁹
	All Eng.; w/ Rear AC - 68.00 Oz. R-12; 10.00 Oz. Ester	59000 ⁵⁹
88-85	All Eng.; w/o Rear AC - 56.00 Oz. R-12; 10.00 Oz. Ester	59000 ⁵⁹
	All Eng.; w/ Rear AC - 68.00 Oz. R-12; 13.00 Oz. Ester	59000 ⁵⁹
84-83	6 Cyl. 4.9 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.0 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.8 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 6.9 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 7.5 Eng. - See Under Hood Decal	59000 ⁵⁹
82-80	6 Cyl. 4.9 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.0 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.8 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 6.6 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 7.5 Eng. - See Under Hood Decal	59000 ⁵⁹
79	6 Cyl. 4.9 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.0 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.8 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 7.5 Eng. - See Under Hood Decal	59000 ⁵⁹
78-76	6 Cyl. 4.9 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.8 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 7.5 Eng. - See Under Hood Decal	59000 ⁵⁹
75	6 Cyl. 4.9 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.0 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.8 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 7.5 Eng. - See Under Hood Decal	59000 ⁵⁹
E SERIES MEDIUM DUTY VAN		
10-09	All Eng. - See Under Hood Decal	59007
08	All Eng. - see Under Hood Decal	59007
07	10 Cyl. 6.8 Eng.; w/o Rear AC - 30.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
	10 Cyl. 6.8 Eng.; w/ Rear AC - 54.00 Oz. R-134a; 16.00 Oz. PAG-46	59007
	8 Cyl. 5.4 Eng.; w/o Rear AC - 30.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
	8 Cyl. 5.4 Eng.; w/ Rear AC - 54.00 Oz. R-134a; 16.00 Oz. PAG-46	59007
	8 Cyl. 6.0 Eng.; w/o Rear AC - 32.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
	8 Cyl. 6.0 Eng.; w/ Rear AC - 60.00 Oz. R-134a; 13.00 Oz. PAG-46	59007
06	10 Cyl. 6.8 Eng.; w/o Rear AC - 40.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
	10 Cyl. 6.8 Eng.; w/ Rear AC - 60.00 Oz. R-134a; 13.00 Oz. PAG-46	59007
	8 Cyl. 5.4 Eng.; w/o Rear AC - 44.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
	8 Cyl. 5.4 Eng.; w/ Rear AC - 60.00 Oz. R-134a; 13.00 Oz. PAG-46	59007
	8 Cyl. 6.0 Eng.; w/o Rear AC - 44.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
	8 Cyl. 6.0 Eng.; w/ Rear AC - 60.00 Oz. R-134a; 13.00 Oz. PAG-46	59007
05	10 Cyl. 6.8 Eng.; w/o Rear AC - 40.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
	10 Cyl. 6.8 Eng.; w/ Rear AC - 60.00 Oz. R-134a; 13.00 Oz. PAG-46	59007
	8 Cyl. 6.0 Eng.; w/o Rear AC - 40.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
	8 Cyl. 6.0 Eng.; w/ Rear AC - 60.00 Oz. R-134a; 13.00 Oz. PAG-46	59007
04	10 Cyl. 6.8 Eng.; w/o Rear AC - 40.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
	10 Cyl. 6.8 Eng.; w/ Rear AC - 60.00 Oz. R-134a; 13.00 Oz. PAG-46	59007
	8 Cyl. 5.4 Eng.; w/o Rear AC - 40.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
	8 Cyl. 5.4 Eng.; w/ Rear AC - 60.00 Oz. R-134a; 13.00 Oz. PAG-46	59007
	8 Cyl. 6.0 Eng.; w/o Rear AC - 40.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
	8 Cyl. 6.0 Eng.; w/ Rear AC - 60.00 Oz. R-134a; 13.00 Oz. PAG-46	59007
03	10 Cyl. 6.8 Eng.; w/o Rear AC - 42.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
	10 Cyl. 6.8 Eng.; w/ Rear AC - 64.00 Oz. R-134a; 13.00 Oz. PAG-46	59007
	8 Cyl. 5.4 Eng.; w/o Rear AC - 42.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
	8 Cyl. 5.4 Eng.; w/ Rear AC - 64.00 Oz. R-134a; 13.00 Oz. PAG-46	59007

Continued on Next Page

⁵⁹ When retrofitting to R134a PAG Oil must be used.

FORD LIGHT TRUCK

Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that A/C system has been properly cleaned, and new accumulator / filter drier has been installed. Specs are for total system capacities. Always refer to under hood decal as the primary source for refrigerant and lubricant information.

Year	Model	Lubricant
E SERIES MEDIUM DUTY VAN (Cont'd)		
03	8 Cyl. 7.3 Eng.; w/o Rear AC - 42.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
	8 Cyl. 7.3 Eng.; w/ Rear AC - 64.00 Oz. R-134a; 13.00 Oz. PAG-46	59007
02	8 Cyl. 5.4 Eng.; w/o Rear AC - 44.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
	8 Cyl. 5.4 Eng.; w/ Rear AC - 46.00 Oz. R-134a; 13.00 Oz. PAG-46	59007
ESCAPE		
13	4 Cyl. 1.6 Eng. - 24.00 Oz. R-134a; 4.50 Oz. PAG-46	59007
	4 Cyl. 2.0 Eng. - 24.00 Oz. R-134a; 4.50 Oz. PAG-46	59007
	4 Cyl. 2.0 Eng. - 27.00 Oz. R-134a; 4.50 Oz. PAG-46	59007
	4 Cyl. 2.5 Eng. - 24.00 Oz. R-134a; 4.50 Oz. PAG-46	59007
12-11	All Eng. - 25.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
	4 Cyl. 2.5 Eng.; Hybrid - 32.00 Oz. R-134a; 4.40 Oz. Hybrid Oil	59889
10	All Eng.; Hybrid - 25.00 Oz. R-134a; 11.00 Oz. PAG-46	59007
	All Eng. - 25.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
	4 Cyl. 2.5 Eng.; Hybrid - 32.00 Oz. R-134a; 4.40 Oz. Hybrid Oil	59889
09-08	All Eng.; Excl. Hybrid - 25.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
	All Eng.; Hybrid - 32.00 Oz. R-134a; 4.40 Oz. Hybrid Oil	59889
07	4 Cyl. 2.3 Eng.; Excl. Hybrid - 32.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
	6 Cyl. 3.0 Eng. - 32.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
06-05	4 Cyl. 2.3 Eng. - 16.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
	4 Cyl. 2.3 Eng.; Excl. Hybrid - 32.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
	6 Cyl. 3.0 Eng. - 32.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
04-01	All Eng. - 32.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
EXCURSION		
05-01	All Eng.; w/o Rear AC - 42.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
	All Eng.; w/ Rear AC - 68.00 Oz. R-134a; 14.00 Oz. PAG-46	59007
00	All Eng.; w/o Rear AC - 40.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
	All Eng.; w/ Rear AC - 68.00 Oz. R-134a; 14.00 Oz. PAG-46	59007
EXPEDITION		
13-11	8 Cyl. 5.4 Eng. - 36.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
10	All Eng.; w/o Rear AC - 22.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
09	All Eng.; w/ Rear AC - 33.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
08	All Eng.; w/o Rear AC - 22.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
	All Eng.; w/ Rear AC - 33.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
07	All Eng.; w/o Rear AC - 22.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
	All Eng.; w/ Rear AC - 33.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
06	All Eng.; w/o Rear AC - 40.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
	All Eng.; w/ Rear AC - 58.00 Oz. R-134a; 14.00 Oz. PAG-46	59007
05-03	All Eng.; w/o Rear AC - 32.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
	All Eng.; w/ Rear AC - 54.00 Oz. R-134a; 14.00 Oz. PAG-46	59007
02-98	All Eng.; w/o Rear AC - 37.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
	All Eng.; w/ Rear AC - 62.00 Oz. R-134a; 11.00 Oz. PAG-46	59007
97	All Eng.; w/o Rear AC - 37.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
	All Eng.; w/ Rear AC - 62.00 Oz. R-134a; 13.00 Oz. PAG-46	59007
EXPLORER / SPORT / SPORT TRAC		
13-12	4 Cyl. 2.0 Eng. - 47.00 Oz. R-134a; 8.80 Oz. PAG-46	59007
	6 Cyl. 3.5 Eng. - 47.00 Oz. R-134a; 8.80 Oz. PAG-46	59007
11	6 Cyl. 3.5 Eng. - 47.00 Oz. R-134a; 8.80 Oz. PAG-46	59007
10	All Eng.; w/o Rear AC - 27.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
	All Eng.; w/ Rear AC - 44.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
09	All Eng.; w/o Rear AC - 27.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
	All Eng.; w/ Rear AC - 44.00 Oz. R-134a; 16.00 Oz. PAG-46	59007
08-06	All Eng.; w/o Rear AC - 31.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
	All Eng.; w/ Rear AC - 47.00 Oz. R-134a; 16.00 Oz. PAG-46	59007
05-02	All Eng.; w/o Rear AC - 34.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
	All Eng.; w/ Rear AC - 56.00 Oz. R-134a; 13.00 Oz. PAG-46	59007
01-98	All Eng. - 30.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
97	All Eng. - 22.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
96-95	All Eng. - 26.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
94	All Eng. - 36.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
93-91	All Eng. - 32.00 Oz. R-12; 7.00 Oz. Ester	59000 ⁵⁹
F SERIES FULLSIZE PICKUP		
13	10 Cyl. 6.8 Eng. - 29.00 Oz. R-134a; 4.10 Oz. PAG-46	59007
	6 Cyl. 3.5 Eng. - 24.00 Oz. R-134a; 3.40 Oz. PAG-46	59007

Continued on Next Page

⁵⁹ When retrofitting to R134a PAG Oil must be used.

FORD LIGHT TRUCK

Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that A/C system has been properly cleaned, and new accumulator / filter drier has been installed. Specs are for total system capacities. Always refer to under hood decal as the primary source for refrigerant and lubricant information.

Year	Model	Lubricant
F SERIES FULLSIZE PICKUP (Cont'd)		
13	6 Cyl. 3.7 Eng. - 24.00 Oz. R-134a; 3.40 Oz. PAG-46	59007
	8 Cyl. 5.0 Eng. - 24.00 Oz. R-134a; 3.40 Oz. PAG-46	59007
	8 Cyl. 6.2 Eng. - 29.00 Oz. R-134a; 4.10 Oz. PAG-46	59007
	8 Cyl. 6.7 Eng. - 26.00 Oz. R-134a; 3.40 Oz. PAG-46	59007
12	10 Cyl. 6.8 Eng. - 29.00 Oz. R-134a; 4.10 Oz. PAG-46	59007
	6 Cyl. 3.5 Eng. - 24.00 Oz. R-134a; 6.00 Oz. PAG-46	59007
	6 Cyl. 3.7 Eng. - 24.00 Oz. R-134a; 6.00 Oz. PAG-46	59007
	8 Cyl. 5.0 Eng. - 24.00 Oz. R-134a; 6.00 Oz. PAG-46	59007
	8 Cyl. 6.2 Eng. - 29.00 Oz. R-134a; 4.10 Oz. PAG-46	59007
	8 Cyl. 6.7 Eng. - 26.00 Oz. R-134a; 3.40 Oz. PAG-46	59007
	10 Cyl. 6.8 Eng. - 29.00 Oz. R-134a; 4.10 Oz. PAG-46	59007
	6 Cyl. 3.5 Eng. - 24.00 Oz. R-134a; 6.00 Oz. PAG-46	59007
11	6 Cyl. 3.7 Eng. - 24.00 Oz. R-134a; 6.00 Oz. PAG-46	59007
	8 Cyl. 5.0 Eng. - 24.00 Oz. R-134a; 6.00 Oz. PAG-46	59007
	8 Cyl. 6.2 Eng. - 24.00 Oz. R-134a; 4.10 Oz. PAG-46	59007
	8 Cyl. 6.7 Eng. - 26.00 Oz. R-134a; 3.40 Oz. PAG-46	59007
	10 Cyl. 6.8 Eng. - 29.00 Oz. R-134a; 4.10 Oz. PAG-46	59007
10-09	Lightduty - 24.00 Oz. R-134a; 6.00 Oz. PAG-46	59007
	Superduty - 27.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
08	Superduty - 26.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
	Lightduty - 34.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
07-06	Lightduty - 34.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
	Superduty - 45.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
05-98	Lightduty - 33.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
	Superduty - 42.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
97-96	All Eng. - 38.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
95	All Eng. - 33.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
94	All Eng. - 32.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
93	All Eng. - 44.00 Oz. R-12; 7.00 Oz. Ester	59000 ⁵⁹
92-91	All Eng. - 44.00 Oz. R-12; 10.00 Oz. Ester	59000 ⁵⁹
90-86	All Eng. - 52.00 Oz. R-12; 10.00 Oz. Ester	59000 ⁵⁹
85	All Eng. - 48.00 Oz. R-12; 10.00 Oz. Ester	59000 ⁵⁹
84	6 Cyl. 4.9 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.0 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.8 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 6.9 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 7.5 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 7.5 Eng. - See Under Hood Decal	59000 ⁵⁹
83	6 Cyl. 3.8 Eng. - See Under Hood Decal	59000 ⁵⁹
	6 Cyl. 4.9 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.0 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.8 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 6.9 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 7.5 Eng. - See Under Hood Decal	59000 ⁵⁹
82	6 Cyl. 3.8 Eng. - See Under Hood Decal	59000 ⁵⁹
	6 Cyl. 4.9 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 4.2 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.0 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.8 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 6.6 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 6.6 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 6.6 Eng. - See Under Hood Decal	59000 ⁵⁹
81	6 Cyl. 4.9 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 4.2 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.0 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.8 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 6.6 Eng. - See Under Hood Decal	59000 ⁵⁹
80	6 Cyl. 4.9 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.0 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.8 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 6.6 Eng. - See Under Hood Decal	59000 ⁵⁹
79-78	6 Cyl. 4.9 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.0 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.8 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 6.6 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 7.5 Eng. - See Under Hood Decal	59000 ⁵⁹
77	6 Cyl. 4.9 Eng. - See Under Hood Decal	59000 ⁵⁹

Continued on Next Page

⁵⁹ When retrofitting to R134a PAG Oil must be used.

FORD LIGHT TRUCK

Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that A/C system has been properly cleaned, and new accumulator / filter drier has been installed. Specs are for total system capacities. Always refer to under hood decal as the primary source for refrigerant and lubricant information.

Year	Model	Lubricant
F SERIES FULLSIZE PICKUP (Cont'd)		
77	8 Cyl. 5.0 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.4 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.8 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.9 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 6.4 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 6.6 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 7.5 Eng. - See Under Hood Decal	59000 ⁵⁹
	76	6 Cyl. 3.9 Eng. - See Under Hood Decal
6 Cyl. 4.9 Eng. - See Under Hood Decal		59000 ⁵⁹
8 Cyl. 5.0 Eng. - See Under Hood Decal		59000 ⁵⁹
8 Cyl. 5.4 Eng. - See Under Hood Decal		59000 ⁵⁹
8 Cyl. 5.9 Eng. - See Under Hood Decal		59000 ⁵⁹
8 Cyl. 6.4 Eng. - See Under Hood Decal		59000 ⁵⁹
8 Cyl. 7.5 Eng. - See Under Hood Decal		59000 ⁵⁹
75-73		6 Cyl. 3.9 Eng. - See Under Hood Decal
	6 Cyl. 4.9 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.0 Eng. - See Under Hood Decal	59000 ⁵⁹
72-70	8 Cyl. 5.0 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.9 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 6.4 Eng. - See Under Hood Decal	59000 ⁵⁹
F SERIES MEDIUM DUTY PICKUP		
10	8 Cyl. 6.4 Eng. - 44.00 Oz. R-12; See Under Hood Decal	59007
09	All Eng. - 44.00 Oz. R-12; See Under Hood Decal	59007
08	All Eng. - See Under Hood Decal	59007
07	10 Cyl. 6.8 Eng. - 27.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
	8 Cyl. 6.0 Eng. - 27.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
06	10 Cyl. 6.8 Eng.; w/ Rear AC - 42.00 Oz. R-134a; 14.00 Oz. PAG-46	59007
	10 Cyl. 6.8 Eng.; w/o Rear AC - 42.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
	8 Cyl. 6.0 Eng.; w/ Rear AC - 42.00 Oz. R-134a; 14.00 Oz. PAG-46	59007
05	8 Cyl. 6.0 Eng.; w/o Rear AC - 42.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
	10 Cyl. 6.8 Eng.; w/o Rear AC - 42.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
	10 Cyl. 6.8 Eng.; w/ Rear AC - 68.00 Oz. R-134a; 14.00 Oz. PAG-46	59007
04	8 Cyl. 6.0 Eng. - See Under Hood Decal	59007
	10 Cyl. 6.8 Eng.; w/o Rear AC - 42.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
	10 Cyl. 6.8 Eng.; w/ Rear AC - 68.00 Oz. R-134a; 14.00 Oz. PAG-46	59007
	8 Cyl. 6.0 Eng.; w/o Rear AC - 42.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
03	8 Cyl. 6.0 Eng.; w/ Rear AC - 68.00 Oz. R-134a; 14.00 Oz. PAG-46	59007
	10 Cyl. 6.8 Eng.; w/ Rear AC - 40.00 Oz. R-134a; 14.00 Oz. PAG-46	59007
	10 Cyl. 6.8 Eng.; w/o Rear AC - 40.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
	8 Cyl. 6.0 Eng.; w/ Rear AC - 40.00 Oz. R-134a; 14.00 Oz. PAG-46	59007
02	8 Cyl. 6.0 Eng.; w/o Rear AC - 40.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
	8 Cyl. 7.3 Eng.; w/ Rear AC - 40.00 Oz. R-134a; 14.00 Oz. PAG-46	59007
	8 Cyl. 7.3 Eng.; w/o Rear AC - 40.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
	10 Cyl. 6.8 Eng.; w/ Rear AC - 40.00 Oz. R-134a; 14.00 Oz. PAG-46	59007
01-00	8 Cyl. 7.3 Eng.; w/ Rear AC - 40.00 Oz. R-134a; 14.00 Oz. PAG-46	59007
	8 Cyl. 7.3 Eng.; w/o Rear AC - 40.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
	10 Cyl. 6.8 Eng.; w/ Rear AC - 40.00 Oz. R-134a; 14.00 Oz. PAG-46	59007
	10 Cyl. 6.8 Eng.; w/o Rear AC - 40.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
99	8 Cyl. 7.3 Eng.; w/ Rear AC - 40.00 Oz. R-134a; 14.00 Oz. PAG-46	59007
	8 Cyl. 7.3 Eng.; w/o Rear AC - 40.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
97	10 Cyl. 6.8 Eng. - 32.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
	8 Cyl. 7.3 Eng. - 32.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
96	8 Cyl. 7.3 Eng. - 38.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
	8 Cyl. 7.5 Eng. - 38.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
95	8 Cyl. 7.3 Eng. - 38.00 Oz. R-134a; 11.00 Oz. PAG-46	59007
	8 Cyl. 7.3 Eng. - 33.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
94	8 Cyl. 7.5 Eng. - 33.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
	8 Cyl. 7.3 Eng. - 32.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
93	8 Cyl. 7.5 Eng. - 32.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
	8 Cyl. 7.3 Eng. - 44.00 Oz. R-12; See Under Hood Decal	59000 ⁵⁹
92-90	8 Cyl. 7.5 Eng. - 44.00 Oz. R-12; See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 7.3 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 7.5 Eng. - See Under Hood Decal	59000 ⁵⁹

Continued on Next Page

⁵⁹ When retrofitting to R134a PAG Oil must be used.

FORD LIGHT TRUCK

Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that A/C system has been properly cleaned, and new accumulator / filter drier has been installed. Specs are for total system capacities. Always refer to under hood decal as the primary source for refrigerant and lubricant information.

Year	Model	Lubricant
FLEX		
13-11	6 Cyl. 3.5 Eng. - 36.00 Oz. R-134a; 9.50 Oz. PAG-46	59007
10	All Eng. - 36.00 Oz. R-134a; 9.50 Oz. PAG-46	59007
09	6 Cyl. 3.5 Eng. - 36.00 Oz. R-134a; 11.00 Oz. PAG-46	59007
FREESTAR		
07-04	All Eng.; w/o Rear AC - 36.00 Oz. R-134a; 10.00 Oz. PAG-46	59007
	All Eng.; w/ Rear AC - 53.00 Oz. R-134a; 13.00 Oz. PAG-46	59007
FREESTYLE		
07-05	All Eng.; w/o Rear AC - 29.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
	All Eng.; w/ Rear AC - 38.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
RANGER		
10	4 Cyl. 2.3 Eng. - 28.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
	6 Cyl. 4.0 Eng. - 32.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
09	4 Cyl. 2.3 Eng. - 33.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
	6 Cyl. 4.0 Eng. - 33.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
08-06	All Eng. - 33.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
05-98	All Eng. - 30.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
97-95	All Eng. - 22.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
94	All Eng. - 36.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
93	All Eng. - 32.00 Oz. R-12; 7.00 Oz. Ester	59000⁵⁹
92-91	4 Cyl. 2.3 Eng. - 36.00 Oz. R-12; 7.00 Oz. Ester	59000⁵⁹
	6 Cyl. 2.9 Eng. - 32.00 Oz. R-12; 10.00 Oz. Ester	59000⁵⁹
	6 Cyl. 3.0 Eng. - 36.00 Oz. R-12; 7.00 Oz. Ester	59000⁵⁹
	6 Cyl. 4.0 Eng. - 36.00 Oz. R-12; 7.00 Oz. Ester	59000⁵⁹
90	All Eng. - 32.00 Oz. R-12; 10.00 Oz. Ester	59000⁵⁹
89-88	All Eng. - 40.00 Oz. R-12; 10.00 Oz. Ester	59000⁵⁹
87	All Eng. - 44.00 Oz. R-12; 10.00 Oz. Ester	59000⁵⁹
86-85	All Eng. - 40.00 Oz. R-12; 10.00 Oz. Ester	59000⁵⁹
84-83	4 Cyl. 2.0 Eng. - See Under Hood Decal	59000⁵⁹
	4 Cyl. 2.2 Eng. - See Under Hood Decal	59000⁵⁹
	4 Cyl. 2.3 Eng. - See Under Hood Decal	59000⁵⁹
	6 Cyl. 2.8 Eng. - See Under Hood Decal	59000⁵⁹
TAURUS X		
09-08	All Eng.; w/o Rear AC - 26.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
	All Eng.; w/ Rear AC - 36.00 Oz. R-134a; 9.50 Oz. PAG-46	59007
TRANSIT CONNECT		
12	4 Cyl. 2.0 Eng. - 29.06 Oz. R-134a; 6.09 Oz. PAG-46	59007
	E Cyl. E Eng. - 29.00 Oz. R-134a;	59889
11	4 Cyl. 2.0 Eng. - 29.00 Oz. R-134a; 6.09 Oz. PAG-46	59007
10	4 Cyl. 2.0 Eng. - 29.00 Oz. R-134a; 6.00 Oz. PAG-46	59007
WINDSTAR		
03-01	All Eng.; w/o Rear AC - 44.00 Oz. R-134a; 10.00 Oz. PAG-46	59007
	All Eng.; w/ Rear AC - 56.00 Oz. R-134a; 14.00 Oz. PAG-46	59007
00-99	All Eng.; w/o Rear AC - 44.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
	All Eng.; w/ Rear AC - 56.00 Oz. R-134a; 11.00 Oz. PAG-46	59007
98	All Eng.; w/o Rear AC - 44.00 Oz. R-134a; 10.00 Oz. PAG-46	59007
	All Eng.; w/ Rear AC - 56.00 Oz. R-134a; 11.00 Oz. PAG-46	59007
97	All Eng.; w/o Rear AC - 44.00 Oz. R-134a; 10.00 Oz. PAG-46	59007
	All Eng.; w/ Rear AC - 56.00 Oz. R-134a; 14.00 Oz. PAG-46	59007
96-95	All Eng.; w/o Rear AC - 44.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
	All Eng.; w/ Rear AC - 56.00 Oz. R-134a; 13.00 Oz. PAG-46	59007

GEO

Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that A/C system has been properly cleaned, and new accumulator / filter drier has been installed. Specs are for total system capacities. Always refer to under hood decal as the primary source for refrigerant and lubricant information.

Year	Model	Lubricant
METRO		
97	All Eng. - 21.00 Oz. R-134a; 3.50 Oz. PAG-46	59007
96-95	All Eng. - 18.00 Oz. R-134a; 3.50 Oz. PAG-46	59007
94	All Eng. - 18.00 Oz. R-134a; 3.50 Oz. PAG-46	59007
	3 Cyl. 1.0 Eng. - 18.00 Oz. R-134a; 3.40 Oz. PAG-46	59007

Continued on Next Page

⁵⁹ When retrofitting to R134a PAG Oil must be used.

Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that A/C system has been properly cleaned, and new accumulator / filter drier has been installed. Specs are for total system capacities. Always refer to under hood decal as the primary source for refrigerant and lubricant information.

Year	Model	Lubricant
METRO (Cont'd)		
94	4 Cyl. 1.3 Eng. - 18.00 Oz. R-134a; 3.40 Oz. PAG-46	59007
93-90	All Eng. - 18.00 Oz. R-12; 3.00 Oz. Mineral Oil	59000 ⁵⁹
89	3 Cyl. 1.0 Eng. - 18.00 Oz. R-12; 3.00 Oz. Mineral Oil	59000 ⁵⁹
PRIZM		
97	All Eng. - 26.50 Oz. R-134a; 4.00 Oz. PAG-46	59007
96-95	All Eng. - 24.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
94	All Eng. - 24.00 Oz. R-134a; 5.25 Oz. PAG-46	59007
93	All Eng. - 24.00 Oz. R-12; 6.00 Oz. Mineral Oil	59000 ⁵⁹
92-91	All Eng. - 27.00 Oz. R-12; 6.00 Oz. Mineral Oil	59000 ⁵⁹
90	All Eng. - 18.00 Oz. R-12; 3.00 Oz. Mineral Oil	59000 ⁵⁹
89	4 Cyl. 1.6 Eng. - 24.00 Oz. R-12; 6.00 Oz. Mineral Oil	59000 ⁵⁹
SPECTRUM		
89	All Eng. - 29.00 Oz. R-12; 3.50 Oz. Mineral Oil	59000 ⁵⁹
STORM		
93-92	All Eng. - 21.00 Oz. R-12; 5.25 Oz. Mineral Oil	59000 ⁵⁹
91-90	All Eng. - 24.00 Oz. R-12; 5.25 Oz. Mineral Oil	59000 ⁵⁹

GMC LIGHT TRUCK

Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that A/C system has been properly cleaned, and new accumulator / filter drier has been installed. Specs are for total system capacities. Always refer to under hood decal as the primary source for refrigerant and lubricant information.

Year	Model	Lubricant
ACADIA		
12-08	6 Cyl. 3.6 Eng. - 37.00 Oz. R-134a; 6.50 Oz. PAG-46	59007
07	All Eng. - 37.00 Oz. R-134a; 6.50 Oz. PAG-46	59007
CABALLERO		
87-85	6 Cyl. 4.3 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.0 Eng. - See Under Hood Decal	59000 ⁵⁹
84	6 Cyl. 3.8 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.0 Eng. - See Under Hood Decal	59000 ⁵⁹
CANYON		
12-09	4 Cyl. 2.9 Eng. - 21.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
	5 Cyl. 3.7 Eng. - 21.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
	8 Cyl. 5.3 Eng. - 19.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
08	All Eng. - 19.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
07-06	All Eng. - 25.50 Oz. R-134a; 5.00 Oz. PAG-46	59007
05-04	All Eng. - 24.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
ENVOY		
09	All Eng.; w/o Rear AC - 31.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
	All Eng. - 42.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
08	All Eng.; w/o Rear AC - 31.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
	All Eng.; w/ Rear AC - 42.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
07-06	All Eng.; w/o Rear AC - 30.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
	All Eng.; w/ Rear AC - 42.50 Oz. R-134a; 8.00 Oz. PAG-46	59007
05	All Eng.; w/o Rear AC - 30.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
	All Eng.; w/ Rear AC - 42.50 Oz. R-134a; 8.50 Oz. PAG-46	59007
04-02	All Eng.; w/o Rear AC - 29.00 Oz. R-134a; 7.50 Oz. PAG-46	59007
	All Eng.; w/ Rear AC - 48.00 Oz. R-134a; 8.50 Oz. PAG-46	59007
FULLSIZE PICKUP		
12-09	All Eng.; w/o Rear AC - 25.60 Oz. R-134a; 7.10 Oz. PAG-46	59007
	All Eng.; w/ Rear AC - 48.00 Oz. R-134a; 11.00 Oz. PAG-46	59007
08	All Eng.; w/o Rear AC - 25.60 Oz. R-134a; 7.10 Oz. PAG-46; w/ Denso Compressor	59007
	All Eng.; w/ Rear AC - 48.00 Oz. R-134a; 11.00 Oz. PAG-46	59007
07	All Eng.; w/o Rear AC - 25.60 Oz. R-134a; 7.10 Oz. PAG-46; w/ Denso Compressor	59007
	All Eng.; w/ Rear AC - 48.00 Oz. R-134a; 11.00 Oz. PAG-46	59007
	8 Cyl. 6.8 Eng.; w/o Rear AC - 25.60 Oz. R-134a; 7.10 Oz. PAG-46; w/ Denso Compressor	59007
	8 Cyl. 8.1 Eng.; w/o Rear AC - 25.60 Oz. R-134a; 7.10 Oz. PAG-46; w/ Denso Compressor	59007
06-03	All Eng. - 25.50 Oz. R-134a; 8.00 Oz. PAG-46; w/ Denso Compressor	59007
02	All Eng. - 29.00 Oz. R-134a; 8.00 Oz. PAG-46; w/ Denso Compressor	59007
	All Eng. - 29.00 Oz. R-134a; 8.00 Oz. PAG-46; w/ Denso Compressor	59007
	All Eng. - 32.00 Oz. R-134a; 8.00 Oz. PAG-150; w/ HT6 Compressor; w/ OE Harrison Compressor	59003

Continued on Next Page

⁵⁹ When retrofitting to R134a PAG Oil must be used.

GMC LIGHT TRUCK

Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that A/C system has been properly cleaned, and new accumulator / filter drier has been installed. Specs are for total system capacities. Always refer to under hood decal as the primary source for refrigerant and lubricant information.

Year	Model	Lubricant
FULLSIZE PICKUP (Cont'd)		
02	All Eng. - 32.00 Oz. R-134a; 8.00 Oz. PAG-46; w/ Denso Compressor	59007
01	All Eng. - 29.00 Oz. R-134a; 8.00 Oz. PAG-46; w/ Denso Compressor	59007
	All Eng. - 29.00 Oz. R-134a; 8.00 Oz. PAG-46; w/ Denso Compressor	59007
	All Eng. - 32.00 Oz. R-134a; 8.00 Oz. PAG-150; w/ HT6 Compressor; w/ OE Harrison Compressor	59003
	All Eng. - 32.00 Oz. R-134a; 8.00 Oz. PAG-46; w/ Denso Compressor	59007
00	All Eng. - 29.00 Oz. R-134a; 8.00 Oz. PAG-46; w/ Denso Compressor	59007
	All Eng. - 32.00 Oz. R-134a; 8.00 Oz. PAG-150; w/ HT6 Compressor; w/ OE Harrison Compressor	59003
	All Eng. - 32.00 Oz. R-134a; 8.00 Oz. PAG-46; w/ Denso Compressor	59007
99-96	All Eng. - 32.00 Oz. R-134a; 8.00 Oz. PAG-150; Standard Cab; w/ OE Harrison Compressor	59003
	All Eng. - 32.00 Oz. R-134a; 8.00 Oz. PAG-46; Standard Cab; w/ Denso Compressor	59007
	Crew Cab - 36.00 Oz. R-134a; 8.00 Oz. PAG-150; w/ HT6 Compressor; w/ OE Harrison Compressor	59003
	Crew Cab - 36.00 Oz. R-134a; 8.00 Oz. PAG-46; w/ Denso Compressor	59007
95-94	All Eng. - 32.00 Oz. R-134a; 8.00 Oz. PAG-150; Standard Cab	59003
	Crew Cab - 36.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
93	All Eng. - 40.00 Oz. R-12; 8.00 Oz. Mineral Oil; Standard Cab	59000 ⁵⁹
	All Eng. - 40.00 Oz. R-134a; 8.00 Oz. PAG-150; Standard Cab	59003
	Crew Cab - 48.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
	Crew Cab - 48.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
92-90	All Eng. - 44.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
	All Eng. - 52.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
89	All Eng. - 40.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
	All Eng. - 52.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
88	All Eng. - 40.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
87	All Eng. - 48.00 Oz. R-12; 6.00 Oz. Mineral Oil	59000 ⁵⁹
86-85	All Eng. - 44.00 Oz. R-12; 10.00 Oz. Mineral Oil; w/ A6 Compressor	59000 ⁵⁹
	All Eng. - 44.00 Oz. R-12; 8.00 Oz. Mineral Oil; w/ R4 Compressor	59000 ⁵⁹
84	6 Cyl. 4.1 Eng. - See Under Hood Decal	59000 ⁵⁹
	6 Cyl. 4.8 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.0 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.7 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 6.2 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 7.4 Eng. - See Under Hood Decal	59000 ⁵⁹
72-70	6 Cyl. 4.1 Eng. - See Under Hood Decal	59000 ⁵⁹
	6 Cyl. 4.8 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.0 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.7 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 6.6 Eng. - See Under Hood Decal	59000 ⁵⁹
69	6 Cyl. 3.8 Eng. - See Under Hood Decal	59000 ⁵⁹
	6 Cyl. 4.1 Eng. - See Under Hood Decal	59000 ⁵⁹
	6 Cyl. 4.8 Eng. - See Under Hood Decal	59000 ⁵⁹
	6 Cyl. 5.0 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.0 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.7 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 6.5 Eng. - See Under Hood Decal	59000 ⁵⁹
68	6 Cyl. 3.8 Eng. - See Under Hood Decal	59000 ⁵⁹
	6 Cyl. 4.1 Eng. - See Under Hood Decal	59000 ⁵⁹
	6 Cyl. 4.8 Eng. - See Under Hood Decal	59000 ⁵⁹
	6 Cyl. 5.0 Eng. - See Under Hood Decal	59000 ⁵⁹
	6 Cyl. 5.7 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.0 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.4 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 6.5 Eng. - See Under Hood Decal	59000 ⁵⁹
67	6 Cyl. 3.8 Eng. - See Under Hood Decal	59000 ⁵⁹
	6 Cyl. 4.1 Eng. - See Under Hood Decal	59000 ⁵⁹
	6 Cyl. 4.8 Eng. - See Under Hood Decal	59000 ⁵⁹
	6 Cyl. 5.0 Eng. - See Under Hood Decal	59000 ⁵⁹
	6 Cyl. 5.7 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 4.6 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.4 Eng. - See Under Hood Decal	59000 ⁵⁹
66	6 Cyl. 3.8 Eng. - See Under Hood Decal	59000 ⁵⁹
	6 Cyl. 4.1 Eng. - See Under Hood Decal	59000 ⁵⁹
	6 Cyl. 4.8 Eng. - See Under Hood Decal	59000 ⁵⁹
	6 Cyl. 5.0 Eng. - See Under Hood Decal	59000 ⁵⁹

Continued on Next Page

⁵⁹ When retrofitting to R134a PAG Oil must be used.

Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that A/C system has been properly cleaned, and new accumulator / filter drier has been installed. Specs are for total system capacities. Always refer to under hood decal as the primary source for refrigerant and lubricant information.

Year	Model	Lubricant
FULLSIZE PICKUP (Cont'd)		
66	6 Cyl. 5.7 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 4.6 Eng. - See Under Hood Decal	59000 ⁵⁹
65	8 Cyl. 5.3 Eng. - See Under Hood Decal	59000 ⁵⁹
	6 Cyl. 3.8 Eng. - See Under Hood Decal	59000 ⁵⁹
	6 Cyl. 4.8 Eng. - See Under Hood Decal	59000 ⁵⁹
	6 Cyl. 5.0 Eng. - See Under Hood Decal	59000 ⁵⁹
	6 Cyl. 5.7 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 4.6 Eng. - See Under Hood Decal	59000 ⁵⁹
G SERIES FULLSIZE VAN / SAVANA		
12	6 Cyl. 4.3 Eng. - 31.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
	8 Cyl. 4.8 Eng.; w/o Rear AC - 31.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
	8 Cyl. 4.8 Eng.; w/ Rear AC - 49.00 Oz. R-134a; 11.00 Oz. PAG-46	59007
	8 Cyl. 4.8 Eng.; w/ Rear AC - 49.00 Oz. R-134a; 11.00 Oz. PAG-46	59007
	8 Cyl. 5.3 Eng.; w/o Rear AC - 31.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
	8 Cyl. 5.3 Eng.; w/ Rear AC - 49.00 Oz. R-134a; 11.00 Oz. PAG-46	59007
	8 Cyl. 6.0 Eng.; w/o Rear AC - 31.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
	8 Cyl. 6.0 Eng.; w/ Rear AC - 49.00 Oz. R-134a; 11.00 Oz. PAG-46	59007
	8 Cyl. 6.6 Eng.; w/o Rear AC - 31.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
11	8 Cyl. 6.6 Eng.; w/ Rear AC - 49.00 Oz. R-134a; 11.00 Oz. PAG-46	59007
	All Eng. - 32.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
10	All Eng. - 48.00 Oz. R-134a; 11.00 Oz. PAG-46	59007
	All Eng.; w/o Rear AC - 32.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
09	All Eng.; w/ Rear AC - 48.00 Oz. R-134a; 11.00 Oz. PAG-46	59007
	All Eng.; w/o Rear AC - 32.00 Oz. R-134a; 11.00 Oz. PAG-46	59007
08-06	All Eng.; w/ Rear AC - 48.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
	All Eng.; w/o Rear AC - 28.80 Oz. R-134a; 8.00 Oz. PAG-46	59007
05	All Eng.; w/ Rear AC - 56.00 Oz. R-134a; 11.00 Oz. PAG-46	59007
	All Eng.; w/o Rear AC - 28.80 Oz. R-134a; 8.00 Oz. PAG-46	59007
04-03	All Eng.; w/ Rear AC - 48.00 Oz. R-134a; 11.00 Oz. PAG-46	59007
	All Eng.; w/o Rear AC - 32.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
02	All Eng.; w/ Rear AC - 48.00 Oz. R-134a; 11.00 Oz. PAG-46	59007
	All Eng.; w/o Rear AC - 32.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
01	All Eng.; w/ Rear AC - 56.00 Oz. R-134a; 11.00 Oz. PAG-150	59003
	All Eng.; w/o Rear AC - 48.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
00	All Eng.; w/ Rear AC - 72.00 Oz. R-134a; 11.00 Oz. PAG-150	59003
	All Eng.; w/o Rear AC - 48.00 Oz. R-134a; 8.00 Oz. PAG-150; w/ OE Harrison Compressor	59003
99-97	All Eng.; w/o Rear AC - 48.00 Oz. R-134a; 8.00 Oz. PAG-46; w/ Denso Compressor	59007
	All Eng.; w/ Rear AC - 72.00 Oz. R-134a; 11.00 Oz. PAG-150; w/ OE Harrison Compressor	59003
	All Eng.; w/ Rear AC - 72.00 Oz. R-134a; 11.00 Oz. PAG-46; w/ Denso Compressor	59007
	All Eng.; w/o Rear AC - 48.00 Oz. R-134a; 8.00 Oz. PAG-150; w/ OE Harrison Compressor	59003
96	All Eng.; w/o Rear AC - 48.00 Oz. R-134a; 8.00 Oz. PAG-46; w/ Denso Compressor	59007
	All Eng.; w/ Rear AC - 78.00 Oz. R-134a; 11.00 Oz. PAG-150; w/ OE Harrison Compressor	59003
	All Eng.; w/ Rear AC - 78.00 Oz. R-134a; 11.00 Oz. PAG-46; w/ Denso Compressor	59007
	All Eng.; w/o Rear AC - 48.00 Oz. R-134a; 8.00 Oz. PAG-150; w/ OE Harrison Compressor	59003
95-94	All Eng.; w/ Rear AC - 68.00 Oz. R-134a; 11.00 Oz. PAG-150; w/ OE Harrison Compressor	59003
	All Eng.; w/ Rear AC - 68.00 Oz. R-134a; 11.00 Oz. PAG-46; w/ Denso Compressor	59007
	All Eng.; w/o Rear AC - 48.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
93	All Eng.; w/ Rear AC - 68.00 Oz. R-12; 11.00 Oz. Mineral Oil	59000 ⁵⁹
	All Eng.; w/o Rear AC - 48.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
91-89	All Eng.; w/ Rear AC - 72.00 Oz. R-12; 11.00 Oz. Mineral Oil	59000 ⁵⁹
	6 Cyl. 4.3 Eng.; w/o Rear AC - 56.00 Oz. R-12; 8.00 Oz. Mineral Oil; w/ R4 Compressor	59000 ⁵⁹
	6 Cyl. 4.3 Eng.; w/ Rear AC - 72.00 Oz. R-12; 9.00 Oz. Mineral Oil; w/ R4 Compressor	59000 ⁵⁹
	8 Cyl. 5.0 Eng.; w/o Rear AC - 56.00 Oz. R-12; 8.00 Oz. Mineral Oil; w/ R4 Compressor	59000 ⁵⁹
	8 Cyl. 5.0 Eng.; w/ Rear AC - 72.00 Oz. R-12; 9.00 Oz. Mineral Oil; w/ R4 Compressor	59000 ⁵⁹
	8 Cyl. 5.7 Eng.; w/o Rear AC - 56.00 Oz. R-12; 8.00 Oz. Mineral Oil; w/ R4 Compressor	59000 ⁵⁹
	8 Cyl. 5.7 Eng.; w/ Rear AC - 72.00 Oz. R-12; 9.00 Oz. Mineral Oil; w/ R4 Compressor	59000 ⁵⁹
	8 Cyl. 6.2 Eng.; w/o Rear AC - 48.00 Oz. R-12; 8.00 Oz. Mineral Oil; w/ HR6/DA6 Compressor	59000 ⁵⁹
8 Cyl. 6.2 Eng.; w/o Rear AC - 56.00 Oz. R-12; 10.00 Oz. Mineral Oil; w/ A6 Compressor	59000 ⁵⁹	

Continued on Next Page

⁵⁹ When retrofitting to R134a PAG Oil must be used.

GMC LIGHT TRUCK

Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that A/C system has been properly cleaned, and new accumulator / filter drier has been installed. Specs are for total system capacities. Always refer to under hood decal as the primary source for refrigerant and lubricant information.

Year	Model	Lubricant	
G SERIES FULLSIZE VAN / SAVANA (Cont'd)			
91-89	8 Cyl. 6.2 Eng.; w/ Rear AC - 72.00 Oz. R-12; 11.00 Oz. Mineral Oil; w/ HR6/DA6 Compressor	59000 ⁵⁹	
	8 Cyl. 6.2 Eng.; w/ Rear AC - 72.00 Oz. R-12; 13.00 Oz. Mineral Oil; w/ A6 Compressor	59000 ⁵⁹	
	8 Cyl. 7.4 Eng.; w/o Rear AC - 46.00 Oz. R-12; 10.00 Oz. Mineral Oil; w/ A6 Compressor	59000 ⁵⁹	
	8 Cyl. 7.4 Eng.; w/o Rear AC - 46.00 Oz. R-12; 8.00 Oz. Mineral Oil; w/ R4 Compressor	59000 ⁵⁹	
	8 Cyl. 7.4 Eng.; w/o Rear AC - 48.00 Oz. R-12; 8.00 Oz. Mineral Oil; w/ HR6/DA6 Compressor	59000 ⁵⁹	
	8 Cyl. 7.4 Eng.; w/ Rear AC - 64.00 Oz. R-12; 13.00 Oz. Mineral Oil; w/ A6 Compressor	59000 ⁵⁹	
	8 Cyl. 7.4 Eng.; w/ Rear AC - 64.00 Oz. R-12; 9.00 Oz. Mineral Oil; w/ R4 Compressor	59000 ⁵⁹	
	8 Cyl. 7.4 Eng.; w/ Rear AC - 72.00 Oz. R-12; 11.00 Oz. Mineral Oil; w/ HR6/DA6 Compressor	59000 ⁵⁹	
88	All Eng.; w/o Rear AC - 56.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹	
	All Eng.; w/ Rear AC - 72.00 Oz. R-12; 11.00 Oz. Mineral Oil	59000 ⁵⁹	
87-86	All Eng.; w/o Rear AC - 48.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹	
	All Eng.; w/ Rear AC - 72.00 Oz. R-12; 11.00 Oz. Mineral Oil	59000 ⁵⁹	
85	6 Cyl. 4.3 Eng. - See Under Hood Decal	59000 ⁵⁹	
	8 Cyl. 5.0 Eng. - See Under Hood Decal	59000 ⁵⁹	
	8 Cyl. 5.7 Eng. - See Under Hood Decal	59000 ⁵⁹	
	8 Cyl. 6.2 Eng. - See Under Hood Decal	59000 ⁵⁹	
84-83	6 Cyl. 4.1 Eng. - See Under Hood Decal	59000 ⁵⁹	
	8 Cyl. 5.0 Eng. - See Under Hood Decal	59000 ⁵⁹	
	8 Cyl. 5.7 Eng. - See Under Hood Decal	59000 ⁵⁹	
	8 Cyl. 6.2 Eng. - See Under Hood Decal	59000 ⁵⁹	
82-81	6 Cyl. 4.1 Eng. - See Under Hood Decal	59000 ⁵⁹	
	8 Cyl. 5.0 Eng. - See Under Hood Decal	59000 ⁵⁹	
	8 Cyl. 5.7 Eng. - See Under Hood Decal	59000 ⁵⁹	
80	6 Cyl. 4.1 Eng. - See Under Hood Decal	59000 ⁵⁹	
	8 Cyl. 5.0 Eng. - See Under Hood Decal	59000 ⁵⁹	
	8 Cyl. 5.7 Eng. - See Under Hood Decal	59000 ⁵⁹	
	8 Cyl. 6.6 Eng. - See Under Hood Decal	59000 ⁵⁹	
78-77	6 Cyl. 4.1 Eng. - See Under Hood Decal	59000 ⁵⁹	
	6 Cyl. 4.8 Eng. - See Under Hood Decal	59000 ⁵⁹	
	8 Cyl. 5.0 Eng. - See Under Hood Decal	59000 ⁵⁹	
	8 Cyl. 5.7 Eng. - See Under Hood Decal	59000 ⁵⁹	
76-75	8 Cyl. 6.6 Eng. - See Under Hood Decal	59000 ⁵⁹	
	6 Cyl. 4.1 Eng. - See Under Hood Decal	59000 ⁵⁹	
	6 Cyl. 4.8 Eng. - See Under Hood Decal	59000 ⁵⁹	
	8 Cyl. 5.7 Eng. - See Under Hood Decal	59000 ⁵⁹	
74	8 Cyl. 6.6 Eng. - See Under Hood Decal	59000 ⁵⁹	
	8 Cyl. 7.4 Eng. - See Under Hood Decal	59000 ⁵⁹	
	6 Cyl. 4.1 Eng. - See Under Hood Decal	59000 ⁵⁹	
	6 Cyl. 4.8 Eng. - See Under Hood Decal	59000 ⁵⁹	
73	8 Cyl. 5.7 Eng. - See Under Hood Decal	59000 ⁵⁹	
	8 Cyl. 7.4 Eng. - See Under Hood Decal	59000 ⁵⁹	
	6 Cyl. 4.1 Eng. - See Under Hood Decal	59000 ⁵⁹	
	8 Cyl. 5.0 Eng. - See Under Hood Decal	59000 ⁵⁹	
71-70	8 Cyl. 5.7 Eng. - See Under Hood Decal	59000 ⁵⁹	
	8 Cyl. 7.4 Eng. - See Under Hood Decal	59000 ⁵⁹	
	6 Cyl. 4.1 Eng. - See Under Hood Decal	59000 ⁵⁹	
69-68	8 Cyl. 5.0 Eng. - See Under Hood Decal	59000 ⁵⁹	
	6 Cyl. 3.8 Eng. - See Under Hood Decal	59000 ⁵⁹	
	6 Cyl. 4.1 Eng. - See Under Hood Decal	59000 ⁵⁹	
67	8 Cyl. 5.0 Eng. - See Under Hood Decal	59000 ⁵⁹	
	4 Cyl. 2.5 Eng. - See Under Hood Decal	59000 ⁵⁹	
	6 Cyl. 3.8 Eng. - See Under Hood Decal	59000 ⁵⁹	
	6 Cyl. 4.1 Eng. - See Under Hood Decal	59000 ⁵⁹	
	8 Cyl. 4.6 Eng. - See Under Hood Decal	59000 ⁵⁹	
	8 Cyl. 5.4 Eng. - See Under Hood Decal	59000 ⁵⁹	
	P SERIES VAN		
	99-94	6 Cyl. 4.3 Eng. - w/ Denso Compressor	59007
6 Cyl. 4.3 Eng. - w/ OE Harrison Compressor		59003	
8 Cyl. 5.7 Eng. - w/ Denso Compressor		59007	
8 Cyl. 5.7 Eng. - w/ OE Harrison Compressor		59003	
8 Cyl. 6.5 Eng. - w/ Denso Compressor		59007	
8 Cyl. 6.5 Eng. - w/ OE Harrison Compressor		59003	

Continued on Next Page

⁵⁹ When retrofitting to R134a PAG Oil must be used.

Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that A/C system has been properly cleaned, and new accumulator / filter drier has been installed. Specs are for total system capacities. Always refer to under hood decal as the primary source for refrigerant and lubricant information.

Year	Model	Lubricant
P SERIES VAN (Cont'd)		
99-94	8 Cyl. 7.4 Eng. - w/ Denso Compressor	59007
	8 Cyl. 7.4 Eng. - w/ OE Harrison Compressor	59003
93	6 Cyl. 4.3 Eng. - See Under Hood Decal	59003
	8 Cyl. 5.7 Eng. - w/ R-12	59000⁵⁹
	8 Cyl. 5.7 Eng. - w/ R-134a	59003
	8 Cyl. 6.2 Eng. - See Under Hood Decal	59003
	8 Cyl. 7.4 Eng. - See Under Hood Decal	59003
S15 JIMMY		
05-02	All Eng. - 28.00 Oz. R-134a; 8.00 Oz. PAG-46; w/ Denso Compressor	59007
	6 Cyl. 4.3 Eng. - 28.00 Oz. R-134a; 8.00 Oz. PAG-150; w/ OE Harrison Compressor	59003
01	All Eng. - 28.00 Oz. R-134a; 8.00 Oz. PAG-150; w/ OE Harrison Compressor	59003
	All Eng. - 28.00 Oz. R-134a; 8.00 Oz. PAG-46; w/ Denso Compressor	59007
00-99	All Eng. - 31.00 Oz. R-134a; 8.50 Oz. PAG-150; w/ OE Harrison Compressor	59003
	All Eng. - 31.00 Oz. R-134a; 8.50 Oz. PAG-46; w/ Denso Compressor	59007
98-96	All Eng. - 32.00 Oz. R-134a; 8.00 Oz. PAG-150; w/ OE Harrison Compressor	59003
	All Eng. - 32.00 Oz. R-134a; 8.00 Oz. PAG-46; w/ Denso Compressor	59007
95	All Eng. - 32.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
94	All Eng. - 40.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
93	All Eng. - 36.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000⁵⁹
92-89	All Eng. - 40.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000⁵⁹
88	All Eng. - 37.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000⁵⁹
87-86	All Eng. - 40.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000⁵⁹
85	4 Cyl. 2.5 Eng. - See Under Hood Decal	59000⁵⁹
	6 Cyl. 2.8 Eng. - See Under Hood Decal	59000⁵⁹
84	4 Cyl. 1.9 Eng. - See Under Hood Decal	59000⁵⁹
	4 Cyl. 2.0 Eng. - See Under Hood Decal	59000⁵⁹
	6 Cyl. 2.8 Eng. - See Under Hood Decal	59000⁵⁹
83	6 Cyl. 2.8 Eng. - See Under Hood Decal	59000⁵⁹
S15 PICKUP		
04-99	All Eng. - 28.00 Oz. R-134a; 9.00 Oz. PAG-150; w/ V7 Compressor; w/ OE Harrison Compressor	59003
	All Eng. - 28.00 Oz. R-134a; 9.00 Oz. PAG-46; w/ Denso Compressor	59007
	All Eng. - 30.00 Oz. R-134a; 8.00 Oz. PAG-150; w/ HT6 Compressor; w/ OE Harrison Compressor	59003
	All Eng. - 30.00 Oz. R-134a; 8.00 Oz. PAG-46; w/ Denso Compressor	59007
98-96	All Eng. - 32.00 Oz. R-134a; 8.00 Oz. PAG-150; w/ OE Harrison Compressor	59003
	All Eng. - 32.00 Oz. R-134a; 8.00 Oz. PAG-46; w/ Denso Compressor	59007
95-94	All Eng. - 32.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
93-89	All Eng. - 40.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000⁵⁹
88	4 Cyl. 2.5 Eng. - See Under Hood Decal	59000⁵⁹
	6 Cyl. 2.8 Eng. - See Under Hood Decal	59000⁵⁹
	6 Cyl. 4.3 Eng. - See Under Hood Decal	59000⁵⁹
87-86	4 Cyl. 2.5 Eng. - See Under Hood Decal	59000⁵⁹
	6 Cyl. 2.8 Eng. - See Under Hood Decal	59000⁵⁹
85	4 Cyl. 1.9 Eng. - See Under Hood Decal	59000⁵⁹
	4 Cyl. 2.2 Eng. - See Under Hood Decal	59000⁵⁹
	4 Cyl. 2.5 Eng. - See Under Hood Decal	59000⁵⁹
	6 Cyl. 2.8 Eng. - See Under Hood Decal	59000⁵⁹
84	4 Cyl. 1.9 Eng. - See Under Hood Decal	59000⁵⁹
	4 Cyl. 2.2 Eng. - See Under Hood Decal	59000⁵⁹
	6 Cyl. 2.8 Eng. - See Under Hood Decal	59000⁵⁹
83-82	6 Cyl. 2.8 Eng. - See Under Hood Decal	59000⁵⁹
SAFARI		
05-94	All Eng.; w/o Rear AC - 32.00 Oz. R-134a; 8.00 Oz. PAG-150; w/ OE Harrison Compressor	59003
	All Eng.; w/o Rear AC - 32.00 Oz. R-134a; 8.00 Oz. PAG-46; w/ Denso Compressor	59007
	All Eng.; w/ Rear AC - 48.00 Oz. R-134a; 11.00 Oz. PAG-150; w/ OE Harrison Compressor	59003
	All Eng.; w/ Rear AC - 48.00 Oz. R-134a; 11.00 Oz. PAG-46; w/ Denso Compressor	59007
93-92	All Eng.; w/o Rear AC - 48.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000⁵⁹
	All Eng.; w/ Rear AC - 60.00 Oz. R-12; 10.00 Oz. Mineral Oil	59000⁵⁹
91-90	All Eng.; w/o Rear AC - 36.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000⁵⁹
	All Eng.; w/ Rear AC - 60.00 Oz. R-12; 10.00 Oz. Mineral Oil	59000⁵⁹
89	All Eng.; w/o Rear AC - 32.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000⁵⁹
	All Eng.; w/ Rear AC - 60.00 Oz. R-12; 9.00 Oz. Mineral Oil	59000⁵⁹
88-86	All Eng.; w/o Rear AC - 32.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000⁵⁹
	All Eng.; w/ Rear AC - 48.00 Oz. R-12; 9.00 Oz. Mineral Oil	59000⁵⁹

Continued on Next Page

⁵⁹ When retrofitting to R134a PAG Oil must be used.

GMC LIGHT TRUCK

Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that A/C system has been properly cleaned, and new accumulator / filter drier has been installed. Specs are for total system capacities. Always refer to under hood decal as the primary source for refrigerant and lubricant information.

Year	Model	Lubricant
	SAFARI (Cont'd)	
85	4 Cyl. 2.5 Eng. - See Under Hood Decal	59000 ⁵⁹
	6 Cyl. 4.3 Eng. - See Under Hood Decal	59000 ⁵⁹
	SUBURBAN / FULLSIZE JIMMY / YUKON	
12	8 Cyl. 5.3 Eng. Yukon; w/o Rear AC - 25.60 Oz. R-134a; 7.10 Oz. PAG-46	59007
	8 Cyl. 5.3 Eng. Yukon; w/ Rear AC - 48.00 Oz. R-134a; 11.00 Oz. PAG-46	59007
	8 Cyl. 6.0 Eng. Yukon; Hybrid - 40.00 Oz. R-134a; 5.00 Oz. Hybrid Oil	59889
	8 Cyl. 6.0 Eng. Yukon XL; w/ Rear AC - 48.00 Oz. R-134a; 11.00 Oz. PAG-46	59007
	8 Cyl. 6.2 Eng. Yukon Denali; AWD; w/o Rear AC - 25.60 Oz. R-134a; 7.10 Oz. PAG-46	59007
	8 Cyl. 6.2 Eng. Yukon Denali; AWD; w/ Rear AC - 40.00 Oz. R-134a; 11.00 Oz. PAG-46	59007
11	8 Cyl. 5.3 Eng. Yukon; w/o Rear AC - 25.60 Oz. R-134a; 7.10 Oz. PAG-46	59007
	8 Cyl. 5.3 Eng. Yukon XL; w/ Rear AC - 48.00 Oz. R-134a; 11.00 Oz. PAG-46	59007
	8 Cyl. 6.0 Eng. Yukon XL; w/ Rear AC - 40.00 Oz. R-134a; 11.00 Oz. PAG-46	59007
	8 Cyl. 6.0 Eng. Yukon; Hybrid - 40.00 Oz. R-134a; 5.00 Oz. Hybrid Oil	59889
	8 Cyl. 6.0 Eng. Yukon XL; w/ Rear AC - 48.00 Oz. R-134a; 11.00 Oz. PAG-46	59007
	8 Cyl. 6.2 Eng. Yukon Denali; AWD; w/ Rear AC - 40.00 Oz. R-134a; 11.00 Oz. PAG-46	59007
	8 Cyl. 6.2 Eng. Yukon XL; w/ Rear AC - 48.00 Oz. R-134a; 11.00 Oz. PAG-46	59007
10	8 Cyl. 5.3 Eng. Yukon; w/o Rear AC - 25.60 Oz. R-134a; 7.10 Oz. PAG-46	59007
	8 Cyl. 5.3 Eng. Yukon XL; w/ Rear AC - 48.00 Oz. R-134a; 11.00 Oz. PAG-46	59007
	8 Cyl. 6.0 Eng. Yukon; Hybrid - 40.00 Oz. R-134a; 5.00 Oz. Hybrid Oil	59889
	8 Cyl. 6.0 Eng. Yukon XL; Excl. Hybrid; w/ Rear AC - 48.00 Oz. R-134a; 11.00 Oz. PAG-46	59007
	8 Cyl. 6.2 Eng. Yukon XL; w/ Rear AC - 48.00 Oz. R-134a; 11.00 Oz. PAG-46	59007
09	8 Cyl. 4.8 Eng. Yukon; Excl. Hybrid; w/o Rear AC - 25.60 Oz. R-134a; 7.10 Oz. PAG-46	59007
	8 Cyl. 5.3 Eng. Yukon; Excl. Hybrid; w/o Rear AC - 25.60 Oz. R-134a; 7.10 Oz. PAG-46	59007
	8 Cyl. 5.3 Eng. Yukon; Excl. Hybrid; w/ Rear AC - 40.00 Oz. R-134a; 11.00 Oz. PAG-46	59007
	8 Cyl. 6.0 Eng. Yukon; Hybrid - 40.00 Oz. R-134a; 5.00 Oz. Hybrid Oil	59889
	8 Cyl. 6.0 Eng. Yukon XL; Excl. Hybrid; w/ Rear AC - 48.00 Oz. R-134a; 11.00 Oz. PAG-46	59007
	8 Cyl. 6.2 Eng. Yukon XL; Excl. Hybrid; w/ Rear AC - 48.00 Oz. R-134a; 11.00 Oz. PAG-46	59007
08	All Eng.; Excl. Hybrid; w/o Rear AC - 25.50 Oz. R-134a; 8.00 Oz. PAG-46	59007
	Yukon; Excl. Hybrid; w/ Rear AC - 40.00 Oz. R-134a; 10.00 Oz. PAG-46	59007
	Yukon XL; Excl. Hybrid; w/ Rear AC - 48.00 Oz. R-134a; 11.00 Oz. PAG-46	59007
	All Eng.; Hybrid - See Under Hood Decal	59889
07	All Eng.; w/o Rear AC - 25.50 Oz. R-134a; 8.00 Oz. PAG-46	59007
	Yukon; w/ Rear AC - 40.00 Oz. R-134a; 10.00 Oz. PAG-46	59007
	Yukon XL; w/ Rear AC - 48.00 Oz. R-134a; 11.00 Oz. PAG-46	59007
06	All Eng.; w/o Rear AC - 25.50 Oz. R-134a; 8.00 Oz. PAG-46	59007
	Yukon; w/ Rear AC - 43.00 Oz. R-134a; 11.00 Oz. PAG-46	59007
	Yukon XL; w/ Rear AC - 48.00 Oz. R-134a; 11.00 Oz. PAG-46	59007
05	All Eng.; w/o Rear AC - 25.50 Oz. R-134a; 8.00 Oz. PAG-46	59007
	Yukon; w/ Rear AC - 43.00 Oz. R-134a; 11.00 Oz. PAG-46	59007
	Yukon XL; w/ Rear AC - 48.00 Oz. R-134a; 11.00 Oz. PAG-46	59007
04-03	6 Cyl. 4.3 Eng. Jimmy (Canada) - 28.80 Oz. R-134a; 8.00 Oz. PAG-46	59007
	All Eng.; w/o Rear AC - 25.50 Oz. R-134a; 8.00 Oz. PAG-46	59007
	Yukon; w/ Rear AC - 43.00 Oz. R-134a; 11.00 Oz. PAG-46	59007
	Yukon XL; w/ Rear AC - 48.00 Oz. R-134a; 11.00 Oz. PAG-46	59007
	6 Cyl. 4.3 Eng. Jimmy (Canada) - 28.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
02	All Eng.; w/o Rear AC - 28.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
	Yukon; w/ Rear AC - 42.00 Oz. R-134a; 11.00 Oz. PAG-46	59007
	Yukon XL; w/ Rear AC - 48.00 Oz. R-134a; 11.00 Oz. PAG-46	59007
	6 Cyl. 4.3 Eng. Jimmy - 28.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
01	All Eng.; w/o Rear AC - 29.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
	Yukon; w/ Rear AC - 48.00 Oz. R-134a; 11.00 Oz. PAG-46	59007
	Yukon XL; w/ Rear AC - 48.00 Oz. R-134a; 11.00 Oz. PAG-46	59007
00-96	All Eng.; w/o Rear AC - 36.00 Oz. R-134a; 8.00 Oz. PAG-150; w/ OE Harrison Compressor	59003
	All Eng.; w/o Rear AC - 36.00 Oz. R-134a; 8.00 Oz. PAG-46; w/ Denso Compressor	59007
	All Eng.; w/ Rear AC - 64.00 Oz. R-134a; 11.00 Oz. PAG-150; w/ OE Harrison Compressor	59003
	All Eng.; w/ Rear AC - 64.00 Oz. R-134a; 11.00 Oz. PAG-46; w/ Denso Compressor	59007
95-94	All Eng.; w/o Rear AC - 36.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
	All Eng.; w/ Rear AC - 64.00 Oz. R-134a; 11.00 Oz. PAG-150	59003
93	All Eng.; w/o Rear AC - 48.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
	All Eng.; w/ Rear AC - 68.00 Oz. R-12; 11.00 Oz. Mineral Oil	59000 ⁵⁹
92	All Eng.; w/o Rear AC - 44.80 Oz. R-12; 6.00 Oz. Mineral Oil	59000 ⁵⁹
91-90	All Eng.; w/o Rear AC - 52.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
	All Eng.; w/ Rear AC - 84.00 Oz. R-12; 11.00 Oz. Mineral Oil	59000 ⁵⁹

Continued on Next Page

⁵⁹ When retrofitting to R134a PAG Oil must be used.

Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that A/C system has been properly cleaned, and new accumulator / filter drier has been installed. Specs are for total system capacities. Always refer to under hood decal as the primary source for refrigerant and lubricant information.

Year	Model	Lubricant
SUBURBAN / FULLSIZE JIMMY / YUKON (Cont'd)		
89	All Eng.; w/o Rear AC - 36.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
	All Eng.; w/ Rear AC - 60.00 Oz. R-12; 10.00 Oz. Mineral Oil	59000 ⁵⁹
88	8 Cyl. 5.7 Eng. Suburban; w/o Rear AC - 54.40 Oz. R-12; 6.00 Oz. Mineral Oil; w/ R4 Compressor	59000 ⁵⁹
	8 Cyl. 5.7 Eng. Suburban; w/ Rear AC - 86.40 Oz. R-12; 6.00 Oz. Mineral Oil; w/ R4 Compressor	59000 ⁵⁹
	8 Cyl. 5.7 Eng. Suburban; w/ Rear AC - 86.40 Oz. R-12; 6.00 Oz. Mineral Oil; w/ HR6 Compressor	59000 ⁵⁹
	8 Cyl. 5.7 Eng. Suburban; w/ Rear AC - 86.40 Oz. R-12; 6.00 Oz. Mineral Oil; w/ R4 Compressor	59000 ⁵⁹
	8 Cyl. 6.2 Eng. Suburban; Diesel - 54.40 Oz. R-12; 6.00 Oz. Mineral Oil; w/ R4 Compressor	59000 ⁵⁹
	8 Cyl. 6.2 Eng.; Diesel - 54.40 Oz. R-12; 6.00 Oz. Mineral Oil; w/ HR6 Compressor	59000 ⁵⁹
	8 Cyl. 6.2 Eng. Suburban; Diesel; w/ Rear AC - 86.40 Oz. R-12; 6.00 Oz. Mineral Oil; w/ R4 Compressor	59000 ⁵⁹
	8 Cyl. 7.4 Eng. Suburban - 54.40 Oz. R-12; 6.00 Oz. Mineral Oil; w/ R4 Compressor	59000 ⁵⁹
	8 Cyl. 7.4 Eng. Suburban; Diesel; w/ Rear AC - 86.40 Oz. R-12; 6.00 Oz. Mineral Oil; w/ R4 Compressor	59000 ⁵⁹
87	8 Cyl. 5.0 Eng. Suburban; w/o Rear AC - 56.00 Oz. R-12; 6.00 Oz. Mineral Oil	59000 ⁵⁹
	8 Cyl. 5.0 Eng. Suburban; w/ Rear AC - 88.00 Oz. R-12; 6.00 Oz. Mineral Oil	59000 ⁵⁹
	8 Cyl. 5.7 Eng. Suburban; w/o Rear AC - 56.00 Oz. R-12; 6.00 Oz. Mineral Oil	59000 ⁵⁹
	8 Cyl. 5.7 Eng. Suburban; w/ Rear AC - 88.00 Oz. R-12; 6.00 Oz. Mineral Oil	59000 ⁵⁹
	8 Cyl. 6.2 Eng. Suburban; w/o Rear AC - 56.00 Oz. R-12; 6.00 Oz. Mineral Oil	59000 ⁵⁹
	8 Cyl. 6.2 Eng. Suburban; w/ Rear AC - 88.00 Oz. R-12; 6.00 Oz. Mineral Oil	59000 ⁵⁹
	8 Cyl. 7.4 Eng.; w/o Rear AC - 52.00 Oz. R-12; 11.00 Oz. Mineral Oil; w/ HR6 Compressor	59000 ⁵⁹
	8 Cyl. 7.4 Eng. Suburban; w/o Rear AC - 52.00 Oz. R-12; 9.00 Oz. Mineral Oil; w/ R4 Compressor	59000 ⁵⁹
	8 Cyl. 7.4 Eng.; w/ Rear AC - 84.00 Oz. R-12; 11.00 Oz. Mineral Oil; w/ HR6 Compressor	59000 ⁵⁹
	8 Cyl. 7.4 Eng.; w/ Rear AC - 84.00 Oz. R-12; 11.00 Oz. Mineral Oil; w/ R4 Compressor	59000 ⁵⁹
86-84	6 Cyl. 4.8 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.0 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.7 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 6.2 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 7.4 Eng. - See Under Hood Decal	59000 ⁵⁹
72-71	6 Cyl. 4.1 Eng. - See Under Hood Decal	59000 ⁵⁹
	6 Cyl. 4.8 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.0 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.7 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 6.6 Eng. - See Under Hood Decal	59000 ⁵⁹
TERRAIN		
12-10	4 Cyl. 2.4 Eng. - 23.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
	6 Cyl. 3.0 Eng. - 23.00 Oz. R-134a; 4.00 Oz. PAG-46	59007

HONDA

Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that A/C system has been properly cleaned, and new accumulator / filter drier has been installed. Specs are for total system capacities. Always refer to under hood decal as the primary source for refrigerant and lubricant information.

Year	Model	Lubricant
ACCORD		
13	4 Cyl. 2.4 Eng. - 17.00 Oz. R-134a; 2.37-2.77 Oz. PAG-46	59007
	6 Cyl. 3.5 Eng. - 17.00 Oz. R-134a; 2.37-2.77 Oz. PAG-46	59007
12	4 Cyl. 2.4 Eng. - 16.00 Oz. R-134a; 2.37-2.77 Oz. PAG-46	59007
	6 Cyl. 3.5 Eng. - 16.00 Oz. R-134a; 2.37-2.77 Oz. PAG-46	59007
11	4 Cyl. 2.4 Eng. - 16.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
	6 Cyl. 3.5 Eng. - 16.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
10	4 Cyl. 2.4 Eng. - 16.00 Oz. R-134a; See Under Hood Decal	59007
	6 Cyl. 3.5 Eng. - 16.00 Oz. R-134a; See Under Hood Decal	59007
09-05	All Eng.; Excl. Hybrid - 19.00 Oz. R-134a; 5.50 Oz. PAG-46	59007
	All Eng.; Hybrid - See Under Hood Decal	59889
04-03	All Eng. - 19.00 Oz. R-134a; 5.50 Oz. PAG-46	59007
02-94	All Eng. - 23.00 Oz. R-134a; 5.50 Oz. PAG-46	59007
93	All Eng. - 30.00 Oz. R-12; 4.50 Oz. Mineral Oil	59000 ⁵⁹
92-90	All Eng. - 32.00 Oz. R-12; 4.00 Oz. Mineral Oil	59000 ⁵⁹
89	All Eng. - 30.00 Oz. R-12; 5.75 Oz. Mineral Oil	59000 ⁵⁹
88-87	All Eng. - 26.00 Oz. R-12; 7.50 Oz. Mineral Oil	59000 ⁵⁹
86-85	All Eng. - 26.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
84-79	4 Cyl. 1.8 Eng. - See Under Hood Decal	59000 ⁵⁹
CIVIC		
13-12	4 Cyl. 1.5 Eng.; Hybrid - 15.00 Oz. R-134a; 8.10 Oz. Hybrid Oil	59889
	4 Cyl. 1.8 Eng. - 15.00 Oz. R-134a; 4.00 Oz. PAG-46	59007

Continued on Next Page

⁵⁹ When retrofitting to R134a PAG Oil must be used.

HONDA

Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that A/C system has been properly cleaned, and new accumulator / filter drier has been installed. Specs are for total system capacities. Always refer to under hood decal as the primary source for refrigerant and lubricant information.

Year	Model	Lubricant
CIVIC (Cont'd)		
13-12	4 Cyl. 2.4 Eng. - 15.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
11	4 Cyl. 1.3 Eng.; Hybrid - 16.00 Oz. R-134a; 4.00 Oz. Hybrid Oil	59889
	4 Cyl. 1.8 Eng. - 16.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
	4 Cyl. 2.0 Eng. - 16.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
10	4 Cyl. 1.3 Eng.; Hybrid - 16.00 Oz. R-134a; 8.11-8.45 Oz. Hybrid Oil	59889
	4 Cyl. 1.8 Eng. - 16.00 Oz. R-134a; 14.10-15.90 Oz. PAG-46	59007
	4 Cyl. 2.0 Eng. - 16.00 Oz. R-134a; 14.10-15.90 Oz. PAG-46	59007
09-06	All Eng.; Excl. Hybrid - 15.00 Oz. R-134a; 5.50 Oz. PAG-46	59007
	All Eng.; Hybrid - See Under Hood Decal	59889
05-02	All Eng. - 18.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
01-96	All Eng. - 23.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
95-94	All Eng. - 19.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
93	All Eng. - 22.00 Oz. R-12; 5.00 Oz. Mineral Oil	59000 ⁵⁹
92	All Eng. - 23.00 Oz. R-12; 5.00 Oz. Mineral Oil	59000 ⁵⁹
91	All Eng. - 33.00 Oz. R-12; 4.00 Oz. Mineral Oil; w/ Sanden Compressor	59000 ⁵⁹
	All Eng. - 33.00 Oz. R-12; 5.00 Oz. Mineral Oil; w/ Matsushita Compressor	59000 ⁵⁹
90	All Eng. - 31.00 Oz. R-12; 4.50 Oz. Mineral Oil	59000 ⁵⁹
89	All Eng. - 31.00 Oz. R-12; 5.00 Oz. Mineral Oil	59000 ⁵⁹
88	All Eng. - 24.00 Oz. R-12; 7.50 Oz. Mineral Oil; w/ Sanden Compressor	59000 ⁵⁹
	All Eng. - 34.00 Oz. R-12; 7.50 Oz. Mineral Oil; w/ Matsushita Compressor	59000 ⁵⁹
87	All Eng. - 25.00 Oz. R-12; 7.50 Oz. Mineral Oil	59000 ⁵⁹
86	All Eng. - 30.00 Oz. R-12; 7.50 Oz. Mineral Oil	59000 ⁵⁹
85	All Eng. - 20.00 Oz. R-12; 7.50 Oz. Mineral Oil	59000 ⁵⁹
84	4 Cyl. 1.3 Eng. - See Under Hood Decal	59000 ⁵⁹
CIVIC DEL SOL		
97-94	All Eng. - 19.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
93	All Eng. - 23.00 Oz. R-12; 5.00 Oz. Mineral Oil	59000 ⁵⁹
CR-V		
11	4 Cyl. 2.4 Eng. - 17.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
10	4 Cyl. 2.4 Eng. - 17.00 Oz. R-134a; 6.42-6.76 Oz. PAG-46	59007
09	4 Cyl. 2.4 Eng. - 16.00 Oz. R-134a; See Under Hood Decal	59007
08-05	All Eng. - 18.00 Oz. R-134a; 4.50 Oz. PAG-46	59007
04	4 Cyl. 2.4 Eng. - 18.00 Oz. R-134a; 4.33-5.00 Oz. PAG-46	59007
03-02	All Eng. - 18.00 Oz. R-134a; 4.50 Oz. PAG-46	59007
01-97	All Eng. - 25.00 Oz. R-134a; 4.50 Oz. PAG-46	59007
CR-Z		
13-12	4 Cyl. 1.5 Eng.; Hybrid - 18.00 Oz. R-134a; 2.70 Oz. Hybrid Oil	59889
11	4 Cyl. 1.5 Eng. - 18.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
CROSSTOUR		
13-12	4 Cyl. 2.4 Eng. - 16.00 Oz. R-134a; 2.37-2.77 Oz. PAG-46	59007
	6 Cyl. 3.5 Eng. - 16.00 Oz. R-134a; 2.37-2.77 Oz. PAG-46	59007
CRX		
91-90	All Eng. - 32.00 Oz. R-12; 4.50 Oz. Mineral Oil	59000 ⁵⁹
89-88	All Eng. - 32.00 Oz. R-12; 4.00 Oz. Mineral Oil; w/ Sanden Compressor	59000 ⁵⁹
	All Eng. - 32.00 Oz. R-12; 5.00 Oz. Mineral Oil; w/ Matsushita Compressor	59000 ⁵⁹
87	All Eng. - 30.00 Oz. R-12; 7.50 Oz. Mineral Oil	59000 ⁵⁹
86	All Eng. - 20.00 Oz. R-12; 7.50 Oz. Mineral Oil	59000 ⁵⁹
85	4 Cyl. 1.5 Eng. - See Under Hood Decal	59000 ⁵⁹
84	4 Cyl. 1.3 Eng. - See Under Hood Decal	59000 ⁵⁹
ELEMENT		
11	4 Cyl. 2.4 Eng. - 19.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
10	4 Cyl. 2.4 Eng. - 18.00 Oz. R-134a; 8.11-8.45 Oz. PAG-46	59007
09	4 Cyl. 2.4 Eng. - 17.60-19.40 Oz. R-134a; See Under Hood Decal	59007
08-03	All Eng. - 18.00 Oz. R-134a; 8.50 Oz. PAG-46	59007
FIT		
13-12	4 Cyl. 1.5 Eng. - 15.00 Oz. R-134a; 2.71-3.04 Oz. PAG-46	59007
11	4 Cyl. 1.5 Eng. - 14.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
10-07	All Eng. - 16.00 Oz. R-134a; 4.50 Oz. PAG-46	59007
INSIGHT		
13-12	4 Cyl. 1.3 Eng.; Hybrid - 18.00 Oz. R-134a; 2.71-3.04 Hybrid Oil	59889
11	4 Cyl. 1.3 Eng.; Hybrid - 18.00 Oz. R-134a; 4.00 Oz. Hybrid Oil	59889
10	4 Cyl. 1.3 Eng.; Hybrid - 17.00 Oz. R-134a; 5.41-5.74 Oz. Hybrid Oil	59889
06-00	All Eng. - 19.00 Oz. R-134a; 4.75 Oz. PAG-46	59007

Continued on Next Page

⁵⁹ When retrofitting to R134a PAG Oil must be used.

Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that A/C system has been properly cleaned, and new accumulator / filter drier has been installed. Specs are for total system capacities. Always refer to under hood decal as the primary source for refrigerant and lubricant information.

Year	Model	Lubricant
ODYSSEY		
13-12	6 Cyl. 3.5 Eng. - 27.00 Oz. R-134a; 4.23-4.63 Oz. PAG-46	59007
11	6 Cyl. 3.5 Eng. - 24.70-26.50 Oz. R-134a; 4.00 Oz. PAG-46	59007
10	6 Cyl. 3.5 Eng. - 24.70-26.50 Oz. R-134a; 7.60-8.01 Oz. PAG-46	59007
09	6 Cyl. 3.5 Eng. - 24.70-26.50 Oz. R-134a; See Under Hood Decal PAG-46	59007
08-07	All Eng. - 26.50 Oz. R-134a; 6.00 Oz. PAG-46	59007
06-99	All Eng.; w/o Rear AC - 23.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
	All Eng.; w/ Rear AC - 32.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
98-95	All Eng.; w/o Rear AC - 23.00 Oz. R-134a; 5.50 Oz. PAG-46	59007
	All Eng.; w/ Rear AC - 30.00 Oz. R-134a; 5.50 Oz. PAG-46	59007
PASSPORT		
02-94	All Eng. - 23.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
PILOT		
13-12	6 Cyl. 3.5 Eng. - 23.00 Oz. R-134a; 4.23-4.63 Oz. PAG-46	59007
11	6 Cyl. 3.5 Eng. - 23.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
10	6 Cyl. 3.5 Eng. - 21.10-2.90 Oz. R-134a; 8.62 Oz. PAG-46	59007
09	6 Cyl. 3.5 Eng. - 21.20-22.90 Oz. R-134a; See Under Hood Decal PAG-46	59007
08-03	All Eng. - 24.70-26.50 Oz. R-134a; 9.00 Oz. PAG-46	59007
PRELUDE		
01-97	All Eng. - 26.50 Oz. R-134a; 4.50 Oz. PAG-46	59007
96-95	All Eng. - 23.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
94	All Eng. - 18.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
93	All Eng. - 18.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
	4 Cyl. 2.2 Eng. - w/ R-12	59000 ⁵⁹
	4 Cyl. 2.3 Eng. - w/ R-12	59000 ⁵⁹
92	All Eng. - 26.50 Oz. R-12; 5.00 Oz. Mineral Oil	59000 ⁵⁹
91	All Eng. - 32.00 Oz. R-12; 4.00 Oz. Mineral Oil	59000 ⁵⁹
90	All Eng. - 32.00 Oz. R-12; 5.00 Oz. Mineral Oil	59000 ⁵⁹
89-88	All Eng. - 34.00 Oz. R-12; 5.00 Oz. Mineral Oil	59000 ⁵⁹
87-86	All Eng. - 30.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
85	All Eng. - 25.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
RIDGELINE		
13-11	6 Cyl. 3.5 Eng. - 21.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
10	6 Cyl. 3.5 Eng. - 21.00 Oz. R-134a; 7.60-8.01 Oz. PAG-46	59007
09	6 Cyl. 3.5 Eng. - 20.30-22.00 Oz. R-134a; See Under Hood Decal PAG-46	59007
08	All Eng. - 22.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
07-06	All Eng. - 23.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
S2000		
09	4 Cyl. 2.2 Eng. - 14.10-15.90 Oz. R-134a; 6.90 Oz. PAG-46	59007
08	All Eng. - 21.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
07-06	All Eng. - 23.00 Oz. R-134a; 4.50 Oz. PAG-46	59007
05-00	All Eng. - 22.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
WAGOVAN		
89-86	4 Cyl. 1.5 Eng. - See Under Hood Decal	59000 ⁵⁹

HUMMER

Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that A/C system has been properly cleaned, and new accumulator / filter drier has been installed. Specs are for total system capacities. Always refer to under hood decal as the primary source for refrigerant and lubricant information.

Year	Model	Lubricant
H2		
08-06	All Eng. - 25.50 Oz. R-134a; 7.00 Oz. PAG-46	59007
05-03	All Eng. - 25.50 Oz. R-134a; 8.00 Oz. PAG-46	59007
H3		
09	5 Cyl. 3.7 Eng. - See Under Hood Decal	59007
08-06	All Eng. - 21.00 Oz. R-134a; 4.00 Oz. PAG-46	59007

⁵⁹ When retrofitting to R134a PAG Oil must be used.

HYUNDAI

Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that A/C system has been properly cleaned, and new accumulator / filter drier has been installed. Specs are for total system capacities. Always refer to under hood decal as the primary source for refrigerant and lubricant information.

Year	Model	Lubricant
ACCENT		
12	4 Cyl. 1.6 Eng. - 18.00 Oz. R-134a; 3.70-4.40 Oz. PAG-46	59007
11-08	4 Cyl. 1.6 Eng. - 18.00 Oz. R-134a; 4.73-5.41 Oz. PAG-46	59007
07-06	All Eng. - 18.50 Oz. R-134a; 4.50 Oz. PAG-46	59007
05-02	All Eng. - 20.00 Oz. R-134a; 6.00 Oz. PAG-46	59007
01-96	All Eng. - 24.00 Oz. R-134a; 6.50 Oz. PAG-46	59007
95	All Eng. - 24.00 Oz. R-134a; 5.50 Oz. PAG-46	59007
AZERA		
12	6 Cyl. 3.3 Eng. - 18.00 Oz. R-134a; 4.73-5.41 Oz. PAG-46	59007
11	6 Cyl. 3.3 Eng. - 18.00 Oz. R-134a; 4.70-5.40 Oz. PAG-46	59007
	6 Cyl. 3.8 Eng. - 18.00 Oz. R-134a; 4.70-5.40 Oz. PAG-46	59007
10-08	6 Cyl. 3.3 Eng. - 17.60+/-0.88 Oz. R-134a; 5.70+/-0.33 Oz. PAG-46	59007
	6 Cyl. 3.8 Eng. - 17.60+/-0.88 Oz. R-134a; 5.70+/-0.33 Oz. PAG-46	59007
07	6 Cyl. 3.3 Eng. - 17.60+/-0.88 Oz. R-134a; 5.70+/-0.33 Oz. PAG-46	59007
	6 Cyl. 3.8 Eng. - 18.00 Oz. R-134a; 4.05 Oz. PAG-46	59007
06	All Eng. - 18.50 Oz. R-134a; 4.50 Oz. PAG-46	59007
ELANTRA		
13	4 Cyl. 1.8 Eng. - 18.50 Oz. R-134a; 3.52-4.20 Oz. PAG-46	59007
12-11	4 Cyl. 1.8 Eng. - 18.50 Oz. R-134a; 3.52-4.20 Oz. PAG-46	59007
	4 Cyl. 2.0 Eng. - 18.50 Oz. R-134a; 3.52-4.20 Oz. PAG-46	59007
10-08	4 Cyl. 2.0 Eng. - 17.60+/-0.88 Oz. R-134a; 5.07+/-0.33 Oz. PAG-46	59007
07	All Eng. - 18.50 Oz. R-134a; 4.50 Oz. PAG-46	59007
06-01	All Eng. - 24.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
00-96	All Eng. - 26.00 Oz. R-134a; 6.50 Oz. PAG-46	59007
95-94	All Eng. - 24.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
93-92	All Eng. - 33.00 Oz. R-12; 4.00 Oz. Mineral Oil	59000 ⁵⁹
ENTOURAGE		
08	6 Cyl. 3.8 Eng. - 34.00 Oz. R-134a; 7.10 Oz. PAG-46	59007
07	All Eng. - 18.50 Oz. R-134a; 4.50 Oz. PAG-46	59007
EQUUS		
13-12	8 Cyl. 5.0 Eng. - 23.00 Oz. R-134a; 4.73-5.41 Oz. PAG-46	59007
11	8 Cyl. 4.6 Eng. - 23.00 Oz. R-134a; 4.70-5.40 Oz. PAG-46	59007
EXCEL		
94	All Eng. - 25.00 Oz. R-134a; 7.75 Oz. PAG-46	59007
93	All Eng. - 32.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
92-91	All Eng. - 33.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
90	All Eng. - 30.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
89-88	All Eng. - 35.00 Oz. R-12; 5.00 Oz. Mineral Oil	59000 ⁵⁹
87-86	All Eng. - 30.00 Oz. R-12; 5.00 Oz. Mineral Oil	59000 ⁵⁹
GENESIS		
13	6 Cyl. 3.8 Eng. - 20.10+/-0.88 Oz. R-134a; 5.07 Oz. PAG-46	59007
	8 Cyl. 5.0 Eng. - 22.90+/-0.88 Oz. R-134a; 4.05 Oz. PAG-46	59007
12	6 Cyl. 3.8 Eng. - 24.00 Oz. R-134a; 3.72-4.40 Oz. PAG-46	59007
	8 Cyl. 4.6 Eng. - 24.00 Oz. R-134a; 3.72-4.40 Oz. PAG-46	59007
	8 Cyl. 5.0 Eng. - 24.00 Oz. R-134a; 3.72-4.40 Oz. PAG-46	59007
11	6 Cyl. 3.8 Eng. - 23.00 Oz. R-134a; 4.73-5.41 Oz. PAG-46	59007
	8 Cyl. 4.6 Eng. - 23.00 Oz. R-134a; 4.73-5.41 Oz. PAG-46	59007
10-09	6 Cyl. 3.8 Eng. - 22.00 Oz. R-134a; 4.73-5.41 Oz. PAG-46	59007
	8 Cyl. 4.6 Eng. - 22.00 Oz. R-134a; 4.73-5.41 Oz. PAG-46	59007
GENESIS COUPE		
13-11	4 Cyl. 2.0 Eng. - 20.00 Oz. R-134a; 4.60-5.60 Oz. PAG-46	59007
	6 Cyl. 3.8 Eng. - 20.00 Oz. R-134a; 4.60-5.60 Oz. PAG-46	59007
10	4 Cyl. 2.0 Eng. - 20.00 Oz. R-134a; 4.56-5.78 Oz. PAG-46	59007
	6 Cyl. 3.8 Eng. - 20.00 Oz. R-134a; 3.80 Oz. PAG-46	59007
SANTA FE		
12	4 Cyl. 2.4 Eng. - 23.00 Oz. R-134a; 4.73-5.41 Oz. PAG-46	59007
	6 Cyl. 3.5 Eng. - 23.00 Oz. R-134a; 4.73-5.41 Oz. PAG-46	59007
11	4 Cyl. 2.4 Eng. - 22.00 Oz. R-134a; 4.73-5.41 Oz. PAG-46	59007
	6 Cyl. 3.5 Eng. - 22.00 Oz. R-134a; 4.73-5.41 Oz. PAG-46	59007
10	4 Cyl. 2.4 Eng. - 20.00 Oz. R-134a; 4.73-5.41 Oz. PAG-46	59007
	6 Cyl. 3.5 Eng. - 20.00 Oz. R-134a; 4.73-5.41 Oz. PAG-46	59007
09	6 Cyl. 2.7 Eng.; w/o Rear AC - 22.00 Oz. R-134a; 4.73-5.41 Oz. PAG-46	59007
	6 Cyl. 2.7 Eng.; w/ Rear AC - 30.00 Oz. R-134a; 6.62-7.43 Oz. PAG-46	59007
	6 Cyl. 3.3 Eng. - 22.00 Oz. R-134a; 4.73-5.41 Oz. PAG-46	59007

Continued on Next Page

⁵⁹ When retrofitting to R134a PAG Oil must be used.

Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that A/C system has been properly cleaned, and new accumulator / filter drier has been installed. Specs are for total system capacities. Always refer to under hood decal as the primary source for refrigerant and lubricant information.

Year	Model	Lubricant
SANTA FE (Cont'd)		
09	6 Cyl. 3.3 Eng.; w/ Rear AC - 30.00 Oz. R-134a; 6.62-7.43 Oz. PAG-46	59007
08	6 Cyl. 2.7 Eng.; w/o Rear AC - 22.00 Oz. R-134a; 5.07+/-0.33 Oz. PAG-46	59007
	6 Cyl. 2.7 Eng.; w/ Rear AC - 32.00 Oz. R-134a; 7.10+/-0.33 Oz. PAG-46	59007
	6 Cyl. 3.3 Eng.; w/o Rear AC - 22.00 Oz. R-134a; 5.07+/-0.33 Oz. PAG-46	59007
	6 Cyl. 3.3 Eng.; w/ Rear AC - 32.00 Oz. R-134a; 7.10+/-0.33 Oz. PAG-46	59007
07	All Eng.; w/o Rear AC - 22.00 Oz. R-134a; 5.50 Oz. PAG-46	59007
	All Eng.; w/ Rear AC - 30.50 Oz. R-134a; 7.50 Oz. PAG-46	59007
06-01	All Eng. - 22.00 Oz. R-134a; 5.50 Oz. PAG-46	59007
SCOUPE		
95-94	All Eng. - 25.00 Oz. R-134a; 5.50 Oz. PAG-46	59007
93	All Eng. - 30.00 Oz. R-12; 3.00 Oz. Mineral Oil	59000 ⁵⁹
92-91	All Eng. - 33.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
SONATA		
13	4 Cyl. 2.0 Eng. - 20.00 Oz. R-134a; 4.73-5.41 Oz. PAG-46	59007
	4 Cyl. 2.4 Eng. - 20.00 Oz. R-134a; 4.73-5.41 Oz. PAG-46	59007
12	4 Cyl. 2.0 Eng. - 20.00 Oz. R-134a; 4.73-5.41 Oz. PAG-46	59007
	4 Cyl. 2.4 Eng.; Hybrid - 19.00 Oz. R-134a; 4.73-5.41 Oz. Hybrid Oil	59889
	4 Cyl. 2.4 Eng. - 20.00 Oz. R-134a; 4.73-5.41 Oz. PAG-46	59007
11	4 Cyl. 2.0 Eng. - 19.00 Oz. R-134a; 4.73-5.41 Oz. PAG-46	59007
	4 Cyl. 2.4 Eng. - 19.00 Oz. R-134a; 4.73-5.41 Oz. PAG-46	59007
	4 Cyl. 2.4 Eng.; Hybrid - 19.00 Oz. R-134a; 4.73-5.41 Oz. Hybrid Oil	59889
10-09	4 Cyl. 2.4 Eng. - 19.00 Oz. R-134a; 4.73-5.41 Oz. PAG-46	59007
	6 Cyl. 3.3 Eng. - 19.00 Oz. R-134a; 4.73-5.41 Oz. PAG-46	59007
08	4 Cyl. 2.4 Eng. - 19.00 Oz. R-134a; 5.07 Oz. PAG-46	59007
	6 Cyl. 3.3 Eng. - 19.00 Oz. R-134a; 5.07 Oz. PAG-46	59007
07	6 Cyl. 2.7 Eng. - 19.00 Oz. R-134a; 4.73-5.41 Oz. PAG-46	59007
	6 Cyl. 3.5 Eng. - 19.00 Oz. R-134a; 4.73-5.41 Oz. PAG-46	59007
06	All Eng. - 22.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
05	All Eng. - 25.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
	4 Cyl. 2.4 Eng. - 21.00 Oz. R-134a; 4.73-5.41 Oz. PAG-46	59007
	6 Cyl. 2.7 Eng. - 21.00 Oz. R-134a; 4.73-5.41 Oz. PAG-46	59007
04-01	All Eng. - 25.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
00-99	All Eng. - 25.00 Oz. R-134a; 7.75 Oz. PAG-46	59007
98-96	All Eng. - 27.00 Oz. R-134a; 7.75 Oz. PAG-46	59007
95	All Eng. - 28.00 Oz. R-134a; 7.75 Oz. PAG-46	59007
94-89	All Eng. - 33.00 Oz. R-12; 7.75 Oz. Mineral Oil	59000 ⁵⁹
TIBURON		
08	4 Cyl. 2.0 Eng. - 18.00+/-0.88 Oz. R-134a; 4.73-5.41 Oz. PAG-46	59007
	6 Cyl. 2.7 Eng. - 18.00+/-0.88 Oz. R-134a; 4.73-5.41 Oz. PAG-46	59007
07	All Eng. - 21.00 Oz. R-134a; 4.73-5.41 Oz. PAG-46	59007
06	All Eng. - 22.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
05-01	All Eng. - 26.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
00-99	All Eng. - 26.00 Oz. R-134a; 6.50 Oz. PAG-46	59007
98	4 Cyl. 2.0 Eng. - 25.00 Oz. R-134a; 5.74-6.42 Oz. PAG-46	59007
97	4 Cyl. 1.8 Eng. - 25.00 Oz. R-134a; 5.74-6.42 Oz. PAG-46	59007
	4 Cyl. 2.0 Eng. - 25.00 Oz. R-134a; 5.74-6.42 Oz. PAG-46	59007
TUCSON		
13-12	4 Cyl. 2.0 Eng. - 19.00 Oz. R-134a; 3.72-4.40 Oz. PAG-46	59007
	4 Cyl. 2.4 Eng. - 19.00 Oz. R-134a; 3.72-4.40 Oz. PAG-46	59007
11	4 Cyl. 2.0 Eng. - 18.00 Oz. R-134a; 3.71-4.39 Oz. PAG-46	59007
	4 Cyl. 2.4 Eng. - 18.00 Oz. R-134a; 3.71-4.39 Oz. PAG-46	59007
10	4 Cyl. 2.4 Eng. - 18.00 Oz. R-134a; 3.71-4.39 Oz. PAG-46	59007
09	6 Cyl.; Beta Eng - 17.89+/-0.88 Oz. R-134a; 4.05-4.56 Oz. PAG-46	59007
	6 Cyl.; Delta Eng - 17.89+/-0.88 Oz. R-134a; 6.76-7.27 Oz. PAG-46	59007
08	4 Cyl. 2.0 Eng. - 17.98+/-0.88 Oz. R-134a; 4.05-4.56 Oz. PAG-46	59007
	6 Cyl. 2.7 Eng. - 17.98+/-0.88 Oz. R-134a; 6.76-7.27 Oz. PAG-46	59007
07	All Eng. - 18.00 Oz. R-134a; 4.00-4.56 Oz. PAG-46	59007
	6 Cyl. 2.7 Eng. - 18.00 Oz. R-134a; 6.76-7.27 Oz. PAG-46	59007
06-05	All Eng. - 19.00 Oz. R-134a; 4.50 Oz. PAG-46; w/ 10PA15C Compressor	59007
	All Eng. - 19.00 Oz. R-134a; 7.00 Oz. PAG-46; w/ 10PA17C Compressor	59007
VELOSTER		
13	4 Cyl. 1.6 Eng. - 15.69 Oz. R-134a; 3.71-4.39 Oz. PAG-46	59007
12	4 Cyl. 1.6 Eng. - 16.00 Oz. R-134a; 3.71-4.39 Oz. PAG-46	59007

Continued on Next Page

⁵⁹ When retrofitting to R134a PAG Oil must be used.

HYUNDAI

Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that A/C system has been properly cleaned, and new accumulator / filter drier has been installed. Specs are for total system capacities. Always refer to under hood decal as the primary source for refrigerant and lubricant information.

Year	Model	Lubricant
VERA CRUZ		
12	6 Cyl. 3.8 Eng. - 15.00 Oz. R-134a; 4.70-5.40 Oz. PAG-46	59007
11	6 Cyl. 3.8 Eng. - 24.69+/-0.88 Oz. R-134a; 5.07+/-0.34 Oz. PAG-46	59007
	6 Cyl. 3.8 Eng.; w/ Rear AC - 31.74+/-0.88 Oz. R-134a; 7.10+/-0.34 Oz. PAG-46	59007
10-09	6 Cyl. 3.8 Eng.; w/o Rear AC - 24.69+/-0.88 Oz. R-134a; 5.07+/-0.34 Oz. PAG-46	59007
	6 Cyl. 3.8 Eng.; w/ Rear AC - 31.74+/-0.88 Oz. R-134a; 7.10+/-0.34 Oz. PAG-46	59007
08	6 Cyl. 3.8 Eng.; w/o Rear AC - 24.64+/-0.05 Oz. R-134a; 5.07+/-0.10 Oz. PAG-46	59007
	6 Cyl. 3.8 Eng.; w/ Rear AC - 31.68+/-0.05 Oz. R-134a; 7.10+/-0.10 Oz. PAG-46	59007
07	All Eng.; w/o Rear AC - 25.00 Oz. R-134a; 5.50 Oz. PAG-46	59007
	All Eng.; w/ Rear AC - 33.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
XG300		
01	6 Cyl. 3.0 Eng. - 24.00 Oz. R-134a; 4.70-5.41 Oz. PAG-46	59007
XG350		
05-02	All Eng. - 24.00 Oz. R-134a; 5.00 Oz. PAG-46	59007

INFINITI

Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that A/C system has been properly cleaned, and new accumulator / filter drier has been installed. Specs are for total system capacities. Always refer to under hood decal as the primary source for refrigerant and lubricant information.

Year	Model	Lubricant
EX35		
12-11	6 Cyl. 3.5 Eng. - 19.00 Oz. R-134a; 5.10 Oz. PAG-46	59007
10-08	All Eng. - 19.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
FX35		
12-11	6 Cyl. 3.5 Eng. - 19.00 Oz. R-134a; 5.10 Oz. PAG-46	59007
10-09	6 Cyl. 3.5 Eng. - 19.00 Oz. R-134a; 5.30 Oz. PAG-46	59007
08-03	All Eng. - 19.00 Oz. R-134a; 6.00 Oz. PAG-46	59007
FX45		
08-03	All Eng. - 19.00 Oz. R-134a; 6.00 Oz. PAG-46	59007
FX50		
13-09	8 Cyl. 5.0 Eng. - 19.00 Oz. R-134a; 5.07 Oz. PAG-46	59007
G20		
02-99	All Eng. - 23.00 Oz. R-134a; 6.75 Oz. PAG-100	59002
96-94	All Eng. - 28.00 Oz. R-134a; 6.75 Oz. PAG-100	59002
93-91	All Eng. - 29.00 Oz. R-12; 6.75 Oz. Mineral Oil	59000 ⁵⁹
G25		
12-11	6 Cyl. 2.5 Eng. - 19.00 Oz. R-134a; 5.10 Oz. PAG-46	59007
G35		
08-03	All Eng. - 19.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
G37		
12-11	6 Cyl. 3.7 Eng. - 19.00 Oz. R-134a; 5.10 Oz. PAG-46	59007
10-09	6 Cyl. 3.7 Eng. - 19.00 Oz. R-134a; 5.30 Oz. PAG-46	59007
08	All Eng. - 19.00 Oz. R-134a; 5.30 Oz. PAG-46	59007
I30		
01-98	All Eng. - 25.00 Oz. R-134a; 6.75 Oz. PAG-46	59007
97-96	All Eng. - 25.00 Oz. R-134a; 8.50 Oz. PAG-46	59007
I35		
04-02	All Eng. - 18.00 Oz. R-134a; 6.00 Oz. PAG-46	59007
J30		
97-94	All Eng. - 28.00 Oz. R-134a; 8.50 Oz. PAG-46	59007
93	All Eng. - 26.50 Oz. R-134a; 8.50 Oz. PAG-46	59007
M30		
92-90	All Eng. - 35.00 Oz. R-12; 6.75 Oz. Mineral Oil	59000 ⁵⁹
M35		
13-12	6 Cyl. 3.5 Eng. - 19.00 Oz. R-134a; 5.10 Oz. PAG-46	59007
10-09	6 Cyl. 3.5 Eng. - 19.00 Oz. R-134a; 5.30 Oz. PAG-46	59007
08-06	All Eng. - 19.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
M37		
13-11	6 Cyl. 3.7 Eng. - 19.00 Oz. R-134a; 5.10 Oz. PAG-46	59007
M45		
10-09	8 Cyl. 4.5 Eng. - 19.00 Oz. R-134a; 5.30 Oz. PAG-46	59007
08-03	All Eng. - 19.00 Oz. R-134a; 5.00 Oz. PAG-46	59007

Continued on Next Page

⁵⁹ When retrofitting to R134a PAG Oil must be used.

Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that A/C system has been properly cleaned, and new accumulator / filter drier has been installed. Specs are for total system capacities. Always refer to under hood decal as the primary source for refrigerant and lubricant information.

Year	Model	Lubricant
	M56	
13-11	8 Cyl. 5.6 Eng. - 19.00 Oz. R-134a; 5.10 Oz. PAG-46	59007
	Q45	
06-02	All Eng. - 21.00 Oz. R-134a; 6.00 Oz. PAG-46	59007
01	All Eng. - 23.00 Oz. R-134a; 6.75 Oz. PAG-46	59007
00-97	All Eng. - 25.50 Oz. R-134a; 6.75 Oz. PAG-46	59007
96	All Eng. - 29.00 Oz. R-134a; 6.75 Oz. PAG-46	59007
95-94	All Eng. - 28.00 Oz. R-134a; 8.50 Oz. PAG-46	59007
93	All Eng. - 42.00 Oz. R-12; 10.00 Oz. Mineral Oil	59000 ⁵⁹
92-90	All Eng. - 44.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
	QX4	
03-02	All Eng. - 16.00 Oz. R-134a; 6.00 Oz. PAG-100	59002
01-97	All Eng. - 25.00 Oz. R-134a; 6.75 Oz. PAG-100	59002
	QX56	
13-11	8 Cyl. 5.6 Eng. - 34.00 Oz. R-134a; 7.10 Oz. PAG-46	59007
10-09	8 Cyl. 5.6 Eng. - 38.00 Oz. R-134a; 9.80 Oz. PAG-46	59007
08-04	All Eng. - 40.00 Oz. R-134a; 10.00 Oz. PAG-100	59002

Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that A/C system has been properly cleaned, and new accumulator / filter drier has been installed. Specs are for total system capacities. Always refer to under hood decal as the primary source for refrigerant and lubricant information.

Year	Model	Lubricant
	AMIGO	
00-99	All Eng. - 23.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
98	All Eng. - 21.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
94	All Eng. - 23.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
93-91	All Eng. - 30.00 Oz. R-12; 6.00 Oz. Mineral Oil	59000 ⁵⁹
90-89	All Eng. - 30.00 Oz. R-12; 5.00 Oz. Mineral Oil	59000 ⁵⁹
	ASCENDER	
08-06	All Eng.; w/o Rear AC - 30.50 Oz. R-134a; 7.50 Oz. PAG-46	59007
	All Eng.; w/ Rear AC - 42.50 Oz. R-134a; 8.50 Oz. PAG-46	59007
05-03	All Eng.; w/o Rear AC - 29.00 Oz. R-134a; 7.50 Oz. PAG-46	59007
	All Eng.; w/ Rear AC - 48.00 Oz. R-134a; 8.50 Oz. PAG-46	59007
	AXIOM	
04-02	All Eng. - 24.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
	HOMBRE	
00-99	All Eng. - 30.00 Oz. R-134a; 8.00 Oz. PAG-150; w/ OE Harrison Compressor	59003
	All Eng. - 30.00 Oz. R-134a; 8.00 Oz. PAG-46; w/ Denso Compressor	59007
98-97	All Eng. - 32.00 Oz. R-134a; 8.00 Oz. PAG-150; w/ OE Harrison Compressor	59003
	All Eng. - 32.00 Oz. R-134a; 8.00 Oz. PAG-46; w/ Denso Compressor	59007
96	All Eng. - 32.00 Oz. R-134a; 9.00 Oz. PAG-150	59003
	I-MARK	
89	All Eng. - 28.00 Oz. R-12; 6.50 Oz. Mineral Oil	59000 ⁵⁹
88-86	4 Cyl. 1.5 Eng. - See Under Hood Decal	59000 ⁵⁹
85	4 Cyl. 1.5 Eng. - See Under Hood Decal	59000 ⁵⁹
	4 Cyl. 1.8 Eng. - See Under Hood Decal	59000 ⁵⁹
	IMPULSE	
92	All Eng. - 21.00 Oz. R-12; 5.00 Oz. Mineral Oil	59000 ⁵⁹
91-89	All Eng. - 35.00 Oz. R-12; 6.75 Oz. Mineral Oil	59000 ⁵⁹
88	4 Cyl. 2.0 Eng. - See Under Hood Decal	59000 ⁵⁹
	4 Cyl. 2.3 Eng. - See Under Hood Decal	59000 ⁵⁹
87-85	4 Cyl. 1.9 Eng. - See Under Hood Decal	59000 ⁵⁹
	4 Cyl. 2.0 Eng. - See Under Hood Decal	59000 ⁵⁹
	OASIS	
99-96	All Eng.; w/o Rear AC - 23.00 Oz. R-134a; 5.50 Oz. PAG-46	59007
	All Eng.; w/ Rear AC - 30.00 Oz. R-134a; 6.50 Oz. PAG-46	59007
	PICKUP	
08-06	All Eng. - 25.50 Oz. R-134a; 5.00 Oz. PAG-46	59007
95-94	All Eng. - 23.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
93	All Eng. - 26.50 Oz. R-12; 6.00 Oz. Mineral Oil	59000 ⁵⁹
92-89	All Eng. - 30.00 Oz. R-12; 6.00 Oz. Mineral Oil	59000 ⁵⁹

Continued on Next Page

⁵⁹ When retrofitting to R134a PAG Oil must be used.

ISUZU

Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that A/C system has been properly cleaned, and new accumulator / filter drier has been installed. Specs are for total system capacities. Always refer to under hood decal as the primary source for refrigerant and lubricant information.

Year	Model	Lubricant
PICKUP (Cont'd)		
88	4 Cyl. 2.3 Eng. - See Under Hood Decal	59000 ⁵⁹
	4 Cyl. 2.6 Eng. - See Under Hood Decal	59000 ⁵⁹
87-86	4 Cyl. 1.9 Eng. - See Under Hood Decal	59000 ⁵⁹
	4 Cyl. 2.2 Eng. - See Under Hood Decal	59000 ⁵⁹
	4 Cyl. 2.3 Eng. - See Under Hood Decal	59000 ⁵⁹
RODEO		
04-02	All Eng. - 24.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
01-94	All Eng. - 23.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
93	All Eng. - 26.50 Oz. R-12; 5.00 Oz. Mineral Oil	59000 ⁵⁹
92-91	All Eng. - 35.00 Oz. R-12; 6.00 Oz. Mineral Oil	59000 ⁵⁹
RODEO SPORT		
03	4 Cyl. 2.2 Eng. - 25.00 Oz. R-134a; 5.00 Oz. PAG-100	59002
	6 Cyl. 3.2 Eng. - 25.00 Oz. R-134a; 5.00 Oz. PAG-100	59002
02-01	4 Cyl. 2.2 Eng. - 23.00 Oz. R-134a; 5.00 Oz. PAG-100	59002
	6 Cyl. 3.2 Eng. - 23.00 Oz. R-134a; 5.00 Oz. PAG-100	59002
STYLUS		
93-92	All Eng. - 21.00 Oz. R-12; 5.00 Oz. Mineral Oil	59000 ⁵⁹
91	All Eng. - 26.50 Oz. R-12; 6.75 Oz. Mineral Oil	59000 ⁵⁹
TROOPER		
02	6 Cyl. 3.5 Eng. - 21.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
01	All Eng. - 21.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
00-98	All Eng. - 21.00 Oz. R-134a; 5.00 Oz. PAG-46; w/ Denso Compressor	59007
	All Eng. - 21.00 Oz. R-134a; 5.00 Oz. PAG-46; w/ OE Harrison Compressor	59007
97-94	All Eng. - 26.50 Oz. R-134a; 5.00 Oz. PAG-46	59007
93-92	All Eng. - 30.00 Oz. R-12; 5.00 Oz. Mineral Oil	59000 ⁵⁹
91-89	All Eng. - 33.50 Oz. R-12; 5.00 Oz. Mineral Oil	59000 ⁵⁹
88	All Eng. - 34.00 Oz. R-12; 5.00 Oz. Mineral Oil	59000 ⁵⁹
87	4 Cyl. 2.3 Eng. - See Under Hood Decal	59000 ⁵⁹
86	4 Cyl. 2.2 Eng. - See Under Hood Decal	59000 ⁵⁹
	4 Cyl. 2.3 Eng. - See Under Hood Decal	59000 ⁵⁹
85	4 Cyl. 1.9 Eng. - See Under Hood Decal	59000 ⁵⁹
VEHICROSS		
01	All Eng. - 23.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
00-99	All Eng. - 23.00 Oz. R-134a; 5.00 Oz. PAG-46; w/ Denso Compressor	59007
	All Eng. - 23.00 Oz. R-134a; 5.00 Oz. PAG-46; w/ OE Harrison Compressor	59007

JAGUAR

Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that A/C system has been properly cleaned, and new accumulator / filter drier has been installed. Specs are for total system capacities. Always refer to under hood decal as the primary source for refrigerant and lubricant information.

Year	Model	Lubricant
S-TYPE		
08-03	All Eng. - 26.50 Oz. R-134a; 7.00 Oz. PAG-100	59002
02-00	All Eng. - 28.00 Oz. R-134a; 7.00 Oz. PAG-100	59002
SUPER V8		
09	8 Cyl. 4.2 Eng.; w/ Rear AC - 29.00 Oz. R-134a; 6.10 Oz. PAG-46	59007
08	8 Cyl. 4.2 Eng.; w/o Rear AC - 24.00 Oz. R-134a; 4.90 Oz. PAG-46	59007
	8 Cyl. 4.2 Eng.; w/ Rear AC - 29.00 Oz. R-134a; 6.10 Oz. PAG-46	59007
07-05	8 Cyl. 4.2 Eng. - 28.00 Oz. R-134a; 6.07 Oz. PAG-46	59007
VANDEN PLAS		
09-08	8 Cyl. 4.2 Eng.; w/o Rear AC - 24.00 Oz. R-134a; 4.90 Oz. PAG-46	59007
	8 Cyl. 4.2 Eng.; w/ Rear AC - 29.00 Oz. R-134a; 6.10 Oz. PAG-46	59007
07-04	8 Cyl. 4.2 Eng. - 28.00 Oz. R-134a; 6.07 Oz. PAG-46	59007
03-01	8 Cyl. 4.0 Eng. - 24.00 Oz. R-134a; 5.44-6.76 Oz. PAG-46	59007
00-98	All Eng. - 24.00 Oz. R-134a; 5.44-6.76 Oz. PAG-46	59007
97-95	6 Cyl. 4.0 Eng. - 38.00 Oz. R-134a; 7.50 Oz. PAG-46	59007
94	6 Cyl. 4.0 Eng. - 40.00 Oz. R-134a; 4.06-5.07 PAG-100	59002
93	6 Cyl. 4.0 Eng. - 40.00 Oz. R-134a; 4.06-5.07 PAG-100	59000 ⁵⁹
92-90	6 Cyl. 4.0 Eng. - 40.00 Oz. R-12; 7.00 Oz. Mineral Oil; w/ A6 Compressor	59000 ⁵⁹
	6 Cyl. 4.0 Eng. - 56.00 Oz. R-12; 4.60 Oz. Mineral Oil; w/ Sanden Compressor	59000 ⁵⁹

Continued on Next Page

⁵⁹ When retrofitting to R134a PAG Oil must be used.

Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that A/C system has been properly cleaned, and new accumulator / filter drier has been installed. Specs are for total system capacities. Always refer to under hood decal as the primary source for refrigerant and lubricant information.

Year	Model	Lubricant
X-TYPE		
08	6 Cyl. 3.0 Eng. - 20.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
07	6 Cyl. 3.0 Eng. - See Under Hood Decal R-134a; 5.00 Oz. PAG-46	59007
06	6 Cyl. 3.0 Eng. - 28.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
05-02	All Eng. - 28.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
XF		
13	4 Cyl. 2.0 Eng. - 25.00 Oz. R-134a; 3.70 Oz. PAG-46	59007
	6 Cyl. 3.0 Eng. - 25.00 Oz. R-134a; 3.70 Oz. PAG-46	59007
	8 Cyl. 5.0 Eng. - 25.00 Oz. R-134a; 3.70 Oz. PAG-46	59007
12	8 Cyl. 5.0 Eng. - 27.00 Oz. R-134a; 3.72 Oz. PAG-46	59007
11	8 Cyl. 5.0 Eng. - 26.00 Oz. R-134a; 3.70 Oz. PAG-46	59007
10	8 Cyl. 4.2 Eng. - 27.00 Oz. R-134a; 3.70 Oz. PAG-46	59007
	8 Cyl. 5.0 Eng. - 27.00 Oz. R-134a; 3.70 Oz. PAG-46	59007
09	8 Cyl. 4.2 Eng. - 27.00 Oz. R-134a; 4.60 Oz. PAG-46	59007
XFR		
13	8 Cyl. 5.0 Eng. - 25.00 Oz. R-134a; 3.70 Oz. PAG-46	59007
12	8 Cyl. 5.0 Eng. - 27.00 Oz. R-134a; 3.72 Oz. PAG-46	59007
11	8 Cyl. 5.0 Eng. - 26.00 Oz. R-134a; 3.70 Oz. PAG-46	59007
10	8 Cyl. 5.0 Eng. - 27.00 Oz. R-134a; 3.70 Oz. PAG-46	59007
XJ		
13	6 Cyl. 3.0 Eng. - 25.00 Oz. R-134a; 3.70 Oz. PAG-46	59007
	8 Cyl. 5.0 Eng. - 25.00 Oz. R-134a; 3.70 Oz. PAG-46	59007
12	8 Cyl. 5.0 Eng. - 25.00 Oz. R-134a; 3.72 Oz. PAG-46	59007
11	8 Cyl. 5.0 Eng. - 25.00 Oz. R-134a; 3.70 Oz. PAG-46	59007
XJ12		
96-95	All Eng. - 38.50 Oz. R-134a; 8.00 Oz. PAG-100	59002
94	All Eng. - 44.00 Oz. R-134a; 6.50 Oz. PAG-100	59002
XJ6		
97-95	All Eng. - 38.50 Oz. R-134a; 7.50 Oz. PAG-100	59002
94	All Eng. - 40.00 Oz. R-134a; 5.00 Oz. PAG-100	59002
93	All Eng. - 40.00 Oz. R-134a; 5.00 Oz. PAG-100	59002
	6 Cyl. 4.0 Eng. - w/ R-12	59000 ⁵⁹
92-89	All Eng. - 40.00 Oz. R-12; 7.00 Oz. Mineral Oil	59000 ⁵⁹
88	6 Cyl. 3.6 Eng. - See Under Hood Decal	59000 ⁵⁹
87	6 Cyl. 3.6 Eng. - See Under Hood Decal	59000 ⁵⁹
	6 Cyl. 4.2 Eng. - See Under Hood Decal	59000 ⁵⁹
86-84	6 Cyl. 4.2 Eng. - See Under Hood Decal	59000 ⁵⁹
XJ8		
09-08	8 Cyl. 4.2 Eng.; w/o Rear AC - 24.00 Oz. R-134a; 4.90 Oz. PAG-46	59007
	8 Cyl. 4.2 Eng.; w/ Rear AC - 29.00 Oz. R-134a; 6.10 Oz. PAG-46	59007
07	8 Cyl. 4.2 Eng. - 28.00 Oz. R-134a; 6.07 Oz. PAG-46	59007
06	All Eng. - 28.00 Oz. R-134a; 6.07 Oz. PAG-46	59007
05-04	8 Cyl. 4.2 Eng. - 28.00 Oz. R-134a; 6.07 Oz. PAG-46	59007
03	8 Cyl. 4.0 Eng. - 24.00 Oz. R-134a; 5.41-6.76 Oz. PAG-46	59007
02	All Eng. - 24.00 Oz. R-134a; 5.41-6.576 Oz. PAG-46	59007
01	All Eng. - 24.00 Oz. R-134a; 5.41-6.76 Oz. PAG-46	59007
00-98	All Eng. - 26.50 Oz. R-134a; 6.75 Oz. PAG-46	59007
XJR		
09-08	8 Cyl. 4.2 Eng.; w/o Rear AC - 24.00 Oz. R-134a; 4.90 Oz. PAG-46	59007
	8 Cyl. 4.2 Eng.; w/ Rear AC - 29.00 Oz. R-134a; 6.40 Oz. PAG-46	59007
07-06	All Eng. - 23.00 Oz. R-134a; 6.76 Oz. PAG-46	59007
05-04	8 Cyl. 4.2 Eng. - 23.00 Oz. R-134a; 6.76 Oz. PAG-46	59007
03	8 Cyl. 4.0 Eng. - 22.93-24.70 Oz. R-134a; 5.41-6.76 Oz. PAG-46	59007
02-98	All Eng. - 22.93-24.70 Oz. R-134a; 5.41-6.76 Oz. PAG-46	59007
97-95	6 Cyl. 4.0 Eng. - 37.04-40.56 Oz. R-134a; 6.08-6.76 Oz. PAG-46	59007
XJRS		
93	All Eng. - 40.00 Oz. R-134a; 5.00 Oz. PAG-150	59003
XJS		
96	All Eng. - 39.68-41.28 Oz. R-134a; 4.06-5.07 Oz. PAG-100	59002
95	All Eng. - 39.67-41.28 Oz. R-134a; 4.06-5.07 Oz. PAG-100	59002
94	All Eng. - 39.68-41.28 Oz. R-134a; 4.06-5.07 Oz. PAG-100	59002
93	All Eng. - 40.00 Oz. R-134a; 6.50 Oz. PAG-100	59002
92-90	All Eng. - 40.00 Oz. R-12; 7.00 Oz. Mineral Oil	59000 ⁵⁹
89	All Eng. - 40.00 Oz. R-12; 7.00 Oz. Mineral Oil; w/ Delco Compressor	59000 ⁵⁹

Continued on Next Page

⁵⁹ When retrofitting to R134a PAG Oil must be used.

JAGUAR

Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that A/C system has been properly cleaned, and new accumulator / filter drier has been installed. Specs are for total system capacities. Always refer to under hood decal as the primary source for refrigerant and lubricant information.

Year	Model	Lubricant
XJS (Cont'd)		
89	All Eng. - 56.00 Oz. R-12; 6.50 Oz. Mineral Oil; w/ Sanden Compressor	59000 ⁵⁹
88-84	12 Cyl. 5.3 Eng. - See Under Hood Decal	59000 ⁵⁹
XK		
13	8 Cyl. 5.0 Eng. - 26.00 Oz. R-134a; 3.70 Oz. PAG-46	59007
12-10	8 Cyl. 5.0 Eng. - 25.00 Oz. R-134a; 3.70 Oz. PAG-46	59007
09-08	8 Cyl. 4.2 Eng. - 26.00 Oz. R-134a; 4.40 Oz. PAG-46	59007
07	8 Cyl. 4.2 Eng. - 24.00 Oz. R-134a; 6.76 Oz. PAG-46	59007
XK8		
06	All Eng. - 23.00 Oz. R-134a; 6.76 Oz. PAG-46	59007
05-03	8 Cyl. 4.2 Eng. - 23.00 Oz. R-134a; 6.76 Oz. PAG-46	59007
02	All Eng. - 23.00 Oz. R-134a; 5.41-6.76 Oz. PAG-46	59007
01-99	All Eng. - 23.00 Oz. R-134a; 5.14-6.76 Oz. PAG-46	59007
98-97	All Eng. - 23.00 Oz. R-134a; 5.41-6.76 Oz. PAG-46	59007
XKR		
13-10	8 Cyl. 5.0 Eng. - 25.00 Oz. R-134a; 3.70 Oz. PAG-46	59007
09	8 Cyl. 4.2 Eng. - 26.00 Oz. R-134a; 4.40 Oz. PAG-46	59007
08	8 Cyl. 4.2 Eng. - 24.00 Oz. R-134a; 4.40 Oz. PAG-46	59007
07	8 Cyl. 4.2 Eng. - 25.00 Oz. R-134a; 6.76 Oz. PAG-46	59007
06	All Eng. - 23.00 Oz. R-134a; 6.76 Oz. PAG-46	59007
05-04	8 Cyl. 4.2 Eng. - 23.00 Oz. R-134a; 6.76 Oz. PAG-46	59007
03	8 Cyl. 4.2 Eng. - 23.00 Oz. R-134a; 5.41-6.76 Oz. PAG-46	59007
02-01	All Eng. - 23.00 Oz. R-134a; 5.41-6.76 Oz. PAG-46	59007
00	8 Cyl. 4.0 Eng. - 23.00 Oz. R-134a; 5.41-6.76 Oz. PAG-46	59007

JEEP

Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that A/C system has been properly cleaned, and new accumulator / filter drier has been installed. Specs are for total system capacities. Always refer to under hood decal as the primary source for refrigerant and lubricant information.

Year	Model	Lubricant
CHEROKEE		
01-00	All Eng. - 20.00 Oz. R-134a; 6.00 Oz. PAG-100	59002
99-97	All Eng. - 20.00 Oz. R-134a; 8.00 Oz. PAG-100	59002
96-95	All Eng. - 32.00 Oz. R-134a; 7.75 Oz. PAG-100	59002
94	All Eng. - 38.00 Oz. R-12; 4.50 Oz. Mineral Oil	59000 ⁵⁹
	4 Cyl. 2.5 Eng. - w/ R-134a	59002
	6 Cyl. 4.0 Eng. - w/ R-134a	59002 ⁵⁹
93-90	All Eng. - 38.00 Oz. R-12; 4.50 Oz. Mineral Oil	59000 ⁵⁹
89	All Eng. - 32.00 Oz. R-12; 6.00 Oz. Mineral Oil	59000 ⁵⁹
88-86	All Eng. - 36.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
85	4 Cyl. 2.1 Eng. - 36.00 Oz. R-12; See Under Hood Decal	59000 ⁵⁹
	4 Cyl. 2.5 Eng. - 36.00 Oz. R-12; See Under Hood Decal	59000 ⁵⁹
	6 Cyl. 2.8 Eng. - 36.00 Oz. R-12; See Under Hood Decal	59000 ⁵⁹
84	4 Cyl. 2.5 Eng. - See Under Hood Decal	59000 ⁵⁹
	6 Cyl. 2.8 Eng. - See Under Hood Decal	59000 ⁵⁹
83	6 Cyl. 4.2 Eng. - See Under Hood Decal	59000 ⁵⁹
CJ SERIES		
86-85	4 Cyl. 2.5 Eng. - See Under Hood Decal	59000 ⁵⁹
	6 Cyl. 4.2 Eng. - See Under Hood Decal	59000 ⁵⁹
84-82	6 Cyl. 4.2 Eng. - See Under Hood Decal	59000 ⁵⁹
COMANCHE		
92-90	All Eng. - 38.00 Oz. R-12; 4.50 Oz. Mineral Oil	59000 ⁵⁹
89	All Eng. - 32.00 Oz. R-12; 6.00 Oz. Mineral Oil	59000 ⁵⁹
88	4 Cyl. 2.5 Eng. - 32.00 Oz. R-12; 6.00-6.50 Oz. Mineral Oil	59000 ⁵⁹
	6 Cyl. 4.0 Eng. - 32.00 Oz. R-12; 6.00-6.50 Oz. Mineral Oil	59000 ⁵⁹
87	4 Cyl. 2.1 Eng. - 32.00 Oz. R-12; 6.00-6.50 Oz. Mineral Oil	59000 ⁵⁹
	4 Cyl. 2.5 Eng. - 32.00 Oz. R-12; 6.00-6.50 Oz. Mineral Oil	59000 ⁵⁹
	6 Cyl. 4.0 Eng. - 32.00 Oz. R-12; 6.00-6.50 Oz. Mineral Oil	59000 ⁵⁹
86	4 Cyl. 2.1 Eng. - 32.00 Oz. R-12; 6.00-6.50 Oz. Mineral Oil	59000 ⁵⁹
	4 Cyl. 2.5 Eng. - 32.00 Oz. R-12; 6.00-6.50 Oz. Mineral Oil	59000 ⁵⁹
	6 Cyl. 2.8 Eng. - 32.00 Oz. R-12; 6.00-6.50 Oz. Mineral Oil	59000 ⁵⁹

Continued on Next Page

⁵⁹ When retrofitting to R134a PAG Oil must be used.

Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that A/C system has been properly cleaned, and new accumulator / filter drier has been installed. Specs are for total system capacities. Always refer to under hood decal as the primary source for refrigerant and lubricant information.

Year	Model	Lubricant
COMMANDER		
10	6 Cyl. 3.7 Eng.; w/o Rear AC - 24.00 Oz. R-134a; 5.07 Oz. PAG-46	59007
	6 Cyl. 3.7 Eng.; w/ Rear AC - 34.00 Oz. R-134a; 7.50 Oz. PAG-46	59007
09	8 Cyl. 5.7 Eng.; w/o Rear AC - 24.00 Oz. R-134a; 5.07 Oz. PAG-46	59007
	8 Cyl. 5.7 Eng.; w/ Rear AC - 34.00 Oz. R-134a; 7.50 Oz. PAG-46	59007
	8 Cyl. 4.7 Eng.; w/o Rear AC - 24.00 Oz. R-134a; 5.07 Oz. PAG-46	59007
	8 Cyl. 4.7 Eng.; w/ Rear AC - 34.00 Oz. R-134a; 7.50 Oz. PAG-46	59007
08-06	All Eng.; w/o Rear AC - 24.00 Oz. R-134a; 4.50 Oz. PAG-46	59007
	All Eng.; w/ Rear AC - 34.00 Oz. R-134a; 7.50 Oz. PAG-46	59007
COMPASS		
13-11	4 Cyl. 2.0 Eng. - 21.00 Oz. R-134a; 3.40 Oz. PAG-46	59007
10-09	4 Cyl. 2.4 Eng. - 21.00 Oz. R-134a; 3.40 Oz. PAG-46	59007
	4 Cyl. 2.0 Eng. - 18.00 Oz. R-134a; 3.40 Oz. PAG-46	59007
08-07	4 Cyl. 2.4 Eng. - 18.00 Oz. R-134a; 3.40 Oz. PAG-46	59007
	All Eng. - 18.00 Oz. R-134a; 4.50 Oz. PAG-46	59007
GRAND CHEROKEE		
13-12	6 Cyl. 3.6 Eng. - 22.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
	8 Cyl. 5.7 Eng. - 22.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
11	8 Cyl. 6.4 Eng. - 22.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
	6 Cyl. 3.6 Eng. - 22.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
10	8 Cyl. 5.7 Eng. - 22.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
	6 Cyl. 3.7 Eng. - 24.00 Oz. R-134a; 4.40 Oz. PAG-46	59007
09	8 Cyl. 5.7 Eng. - 24.00 Oz. R-134a; 4.40 Oz. PAG-46	59007
	8 Cyl. 6.1 Eng. - 24.00 Oz. R-134a; 4.40 Oz. PAG-46	59007
	6 Cyl. 3.0 Eng. - 24.00 Oz. R-134a; 4.40 Oz. PAG-46	59007
	6 Cyl. 3.7 Eng. - 24.00 Oz. R-134a; 4.40 Oz. PAG-46	59007
08-05	8 Cyl. 4.7 Eng. - 24.00 Oz. R-134a; 4.40 Oz. PAG-46	59007
	8 Cyl. 5.7 Eng. - 24.00 Oz. R-134a; 4.40 Oz. PAG-46	59007
04-02	8 Cyl. 6.1 Eng. - 24.00 Oz. R-134a; 4.40 Oz. PAG-46	59007
	All Eng. - 24.00 Oz. R-134a; 4.50 Oz. PAG-46	59007
01	All Eng. - 27.00 Oz. R-134a; 4.50 Oz. PAG-46	59007
00	All Eng. - 24.00 Oz. R-134a; 5.75 Oz. PAG-100	59002
99-98	All Eng. - 24.00 Oz. R-134a; 5.75 Oz. PAG-46	59007
97-93	All Eng. - 26.00 Oz. R-134a; 7.50 Oz. PAG-100	59002
	All Eng. - 28.00 Oz. R-134a; 7.75 Oz. PAG-100	59002
GRAND WAGONEER		
93	All Eng. - 28.00 Oz. R-12; 7.75 Oz. Mineral Oil	59000 ⁵⁹
91-89	All Eng. - 32.00 Oz. R-12; 4.50 Oz. Mineral Oil	59000 ⁵⁹
88-87	8 Cyl. 5.9 Eng. - See Under Hood Decal	59000 ⁵⁹
86-84	6 Cyl. 4.2 Eng. - See Under Hood Decal	59000 ⁵⁹
LIBERTY		
12-11	6 Cyl. 3.7 Eng. - 18.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
10-08	All Eng. - 18.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
07	All Eng. - 22.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
06	All Eng. - 22.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
05	All Eng. - See Under Hood Decal; 8.00 Oz. PAG-46	59007
04-02	All Eng. - 26.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
PATRIOT		
13-12	4 Cyl. 2.0 Eng. - 21.00 Oz. R-134a; 3.40 Oz. PAG-46	59007
	4 Cyl. 2.4 Eng. - 21.00 Oz. R-134a; 3.40 Oz. PAG-46	59007
11	4 Cyl. 2.0 Eng. - 21.00 Oz. R-134a; 3.40 Oz. PAG-46	59007
	4 Cyl. 2.4 Eng. - 18.00 Oz. R-134a; 3.40 Oz. PAG-46	59007
10-09	4 Cyl. 2.0 Eng. - 18.00 Oz. R-134a; 3.40 Oz. PAG-46	59007
	4 Cyl. 2.4 Eng. - 18.00 Oz. R-134a; 3.40 Oz. PAG-46	59007
08-07	All Eng. - 18.00 Oz. R-134a; 4.50 Oz. PAG-46	59007
WAGONEER		
90	All Eng. - 38.00 Oz. R-12; 4.50 Oz. Mineral Oil	59000 ⁵⁹
89	All Eng. - 32.00 Oz. R-12; 6.00 Oz. Mineral Oil	59000 ⁵⁹
88	6 Cyl. 4.0 Eng. - See Under Hood Decal	59000 ⁵⁹
87	4 Cyl. 2.5 Eng. - See Under Hood Decal	59000 ⁵⁹

Continued on Next Page

⁵⁹ When retrofitting to R134a PAG Oil must be used.

Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that A/C system has been properly cleaned, and new accumulator / filter drier has been installed. Specs are for total system capacities. Always refer to under hood decal as the primary source for refrigerant and lubricant information.

Year	Model	Lubricant
WAGONEER (Cont'd)		
87	6 Cyl. 4.0 Eng. - See Under Hood Decal	59000 ⁵⁹
86-84	4 Cyl. 2.5 Eng. - See Under Hood Decal	59000 ⁵⁹
	6 Cyl. 2.8 Eng. - See Under Hood Decal	59000 ⁵⁹
83	6 Cyl. 4.2 Eng. - See Under Hood Decal	59000 ⁵⁹
WRANGLER		
13-12	6 Cyl. 3.6 Eng. - 18.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
11	6 Cyl. 3.8 Eng. - 18.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
10-07	All Eng. - 18.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
06-05	4 Cyl. 2.4 Eng. - See Under Hood Decal; 6.10 Oz. PAG-46	59007
	6 Cyl. 4.0 Eng. - See Under Hood Decal; 6.10 Oz. PAG-46	59007
04-01	All Eng. - 20.00 Oz. R-134a; 6.00 Oz. PAG-46	59007
00	All Eng. - 20.00 Oz. R-134a; 6.00 Oz. PAG-100	59002
99-97	All Eng. - 20.00 Oz. R-134a; 8.00 Oz. PAG-100	59002
95-94	All Eng. - 32.00 Oz. R-134a; 4.50 Oz. PAG-100	59002
93-90	All Eng. - 32.00 Oz. R-12; 4.50 Oz. Mineral Oil	59000 ⁵⁹
89	All Eng. - 32.00 Oz. R-12; 6.00 Oz. Mineral Oil	59000 ⁵⁹
88-87	4 Cyl. 2.5 Eng. - 32.00 Oz. R-12; 6.00-6.50 Oz. Mineral Oil	59000 ⁵⁹
	6 Cyl. 4.2 Eng. - 32.00 Oz. R-12; 6.00-6.50 Oz. Mineral Oil	59000 ⁵⁹

KIA

Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that A/C system has been properly cleaned, and new accumulator / filter drier has been installed. Specs are for total system capacities. Always refer to under hood decal as the primary source for refrigerant and lubricant information.

Year	Model	Lubricant
AMANTI		
09	6 Cyl. 3.8 Eng. - 23.00 Oz. R-134a; 5.30 Oz. PAG-46	59007
08-04	All Eng. - 24.00 Oz. R-134a; 5.50 Oz. PAG-46	59007
BORREGO		
09	All Eng. - See Under Hood Decal	59007
FORTE		
13	4 Cyl. 2.0 Eng. - 20.00 Oz. R-134a; 3.70-4.40 Oz. PAG-46	59007
	4 Cyl. 2.4 Eng. - 20.00 Oz. R-134a; 3.70-4.40 Oz. PAG-46	59007
12	4 Cyl. 2.0 Eng. - 18.00 Oz. R-134a; 3.70-4.40 Oz. PAG-46	59007
	4 Cyl. 2.4 Eng. - 18.00 Oz. R-134a; 3.70-4.40 Oz. PAG-46	59007
11	4 Cyl. 2.0 Eng. - 18.00 Oz. R-134a; 3.70-4.40 Oz. PAG-46	59007
	4 Cyl. 2.4 Eng. - 19.00 Oz. R-134a; 3.00-3.70 Oz. PAG-46	59007
10	4 Cyl. 2.0 Eng. - 18.00 Oz. R-134a; 6.80 Oz. PAG-46	59007
	4 Cyl. 2.4 Eng. - 18.00 Oz. R-134a; 6.80 Oz. PAG-46	59007
OPTIMA		
13-11	4 Cyl. 2.0 Eng. - 19.00 Oz. R-134a; 3.00-3.70 Oz. PAG-46	59007
	4 Cyl. 2.4 Eng. - 19.00 Oz. R-134a; 3.00-3.70 Oz. PAG-46	59007
10-09	4 Cyl. 2.4 Eng. - 18.00 Oz. R-134a; 5.10 Oz. PAG-46	59007
	6 Cyl. 2.7 Eng. - 18.00 Oz. R-134a; 5.10 Oz. PAG-46	59007
08-07	All Eng. - 18.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
06	All Eng. - 24.00 Oz. R-134a; 5.50 Oz. PAG-46	59007
05-01	All Eng. - 22.00-24.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
RIO / RIO5		
13-12	4 Cyl. 1.6 Eng. - 16.00 Oz. R-134a; 3.70-4.40 Oz. PAG-46	59007
11	4 Cyl. 1.6 Eng. - 18.00 Oz. R-134a; 3.70-4.40 Oz. PAG-46	59007
10-09	4 Cyl. 1.6 Eng. - 18.00 Oz. R-134a; 4.10 Oz. PAG-46	59007
08-07	All Eng. - 18.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
06	All Eng. - 18.00 Oz. R-134a; 4.50 Oz. PAG-46	59007
05	All Eng. - 17.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
04-01	All Eng. - 22.00-24.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
RONDO		
12-11	4 Cyl. 2.4 Eng. - 15.88+/-0.88 R-134a; 4.05+/-0.34 Oz. PAG-46	59007
	6 Cyl. 2.7 Eng. - 15.88+/-0.88 R-134a; 4.05+/-0.34 Oz. PAG-46	59007
10-08	4 Cyl. 2.4 Eng. - 16.00 Oz. R-134a; 4.10 Oz. PAG-46	59007
	6 Cyl. 2.7 Eng. - 16.00 Oz. R-134a; 4.10 Oz. PAG-46	59007
07	All Eng. - 16.00 Oz. R-134a; 4.50 Oz. PAG-46	59007

Continued on Next Page

⁵⁹ When retrofitting to R134a PAG Oil must be used.

Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that A/C system has been properly cleaned, and new accumulator / filter drier has been installed. Specs are for total system capacities. Always refer to under hood decal as the primary source for refrigerant and lubricant information.

Year	Model	Lubricant
SEDONA		
12-11	6 Cyl. 3.5 Eng. - 32.00 Oz. R-134a; 4.10-7.40 Oz. PAG-46	59007
10-08	6 Cyl. 3.8 Eng. - 32.00 Oz. R-134a; 7.40 Oz. PAG-46	59007
07-06	All Eng. - 32.00 Oz. R-134a; 7.25 Oz. PAG-46	59007
05-02	All Eng. - 34.40-36.10 Oz. R-134a; 7.00 Oz. PAG-46	59007
SEPHIA		
01-98	All Eng. - 26.50 Oz. R-134a; 6.75 Oz. PAG-46	59007
97-94	All Eng. - 24.00 Oz. R-134a	59007
SORENTO		
13	4 Cyl. 2.4 Eng.; w/o Rear AC - 21.10+/-0.88 Oz. R-134a; 5.07 Oz. PAG-46	59007
	4 Cyl. 2.4 Eng.; w/ Rear AC - 26.40+/-0.88 Oz. R-134a; 7.10 Oz. PAG-46	59007
12-11	6 Cyl. 3.5 Eng.; w/o Rear AC - 21.00 Oz. R-134a; 4.70-5.40 Oz. PAG-46	59007
	6 Cyl. 3.5 Eng.; w/ Rear AC - 26.00 Oz. R-134a; 6.70-7.40 Oz. PAG-46	59007
	4 Cyl. 2.4 Eng.; w/o Rear AC - 21.00 Oz. R-134a; 4.70-5.40 Oz. PAG-46	59007
	4 Cyl. 2.4 Eng.; w/ Rear AC - 26.00 Oz. R-134a; 6.70-7.40 Oz. PAG-46	59007
	6 Cyl. 3.5 Eng.; w/o Rear AC - 21.00 Oz. R-134a; 4.70-5.40 Oz. PAG-46	59007
	6 Cyl. 3.5 Eng.; w/ Rear AC - 26.00 Oz. R-134a; 6.70-7.40 Oz. PAG-46	59007
09-08	6 Cyl. 3.3 Eng. - 21.00 Oz. R-134a; 5.30 Oz. PAG-46	59007
	6 Cyl. 3.8 Eng. - 21.00 Oz. R-134a; 5.30 Oz. PAG-46	59007
07	All Eng. - 19.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
06-03	All Eng. - 22.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
SOUL		
13	4 Cyl. 1.6 Eng. - 19.40+/-0.88 Oz. R-134a; 3.38+/-0.16-.33 Oz. PAG-46	59007
	4 Cyl. 2.0 Eng. - 20.00 Oz. R-134a; 3.00-3.70 Oz. PAG-46	59007
12	4 Cyl. 1.6 Eng. - 19.00 Oz. R-134a; 3.00-3.70 Oz. PAG-46	59007
	4 Cyl. 2.0 Eng. - 19.00 Oz. R-134a; 3.00-.370 Oz. PAG-46	59007
11	4 Cyl. 1.6 Eng. - 19.00 Oz. R-134a; 3.00-3.70 Oz. PAG-46	59007
	4 Cyl. 2.0 Eng. - 19.00 Oz. R-134a; 3.00-3.70 Oz. PAG-46	59007
10	4 Cyl. 1.6 Eng. - 20.00 Oz. R-134a; 3.40 Oz. PAG-46	59007
	4 Cyl. 2.0 Eng. - 20.00 Oz. R-134a; 3.40 Oz. PAG-46	59007
SPECTRA / SPECTRA5		
09	4 Cyl. 2.0 Eng. - 18.00 Oz. R-134a; 4.10 Oz. PAG-46	59007
08	All Eng. - 18.00 Oz. R-134a; 4.10 Oz. PAG-46	59007
07	All Eng. - 18.00 Oz. R-134a; 4.05 Oz. PAG-46	59007
06-04	All Eng. - 18.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
03-02	All Eng. - 23.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
01-00	All Eng. - 25.00 Oz. R-134a; 6.08 Oz. PAG-46	59007
SPORTAGE		
13	4 Cyl. 2.0 Eng. - 19.00 Oz. R-134a; 3.70-4.40 Oz. PAG-46	59007
	4 Cyl. 2.4 Eng. - 19.00 Oz. R-134a; 3.70-4.40 Oz. PAG-46	59007
12	4 Cyl. 2.0 Eng. - 18.00 Oz. R-134a; 3.70-4.40 Oz. PAG-46	59007
	4 Cyl. 2.4 Eng. - 18.00 Oz. R-134a; 3.70-4.40 Oz. PAG-46	59007
11	4 Cyl. 2.0 Eng. - 17.90+/-0.88 Oz. R-134a; 4.05+/-0.33 Oz. PAG-46	59007
	4 Cyl. 2.4 Eng. - 18.00 Oz. R-134a; 3.70-4.40 Oz. PAG-46	59007
10	4 Cyl. 2.0 Eng. - 18.00 Oz. R-134a; 4.10-4.60 Oz. PAG-46	59007
	6 Cyl. 2.7 Eng. - 18.00 Oz. R-134a; 6.80-7.30 Oz. PAG-46	59007
09-06	All Eng. - 19.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
05	4 Cyl. 2.0 Eng. - 18.00 Oz. R-134a; 4.30 Oz. PAG-46	59007
	6 Cyl. 2.7 Eng. - 18.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
02	4 Cyl. 2.0 Eng. - 25.00 Oz. R-134a; See Under Hood Decal PAG-46	59007
01-95	All Eng. - 25.00 Oz. R-134a; See Under Hood Decal PAG-46	59007

LAND ROVER

Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that A/C system has been properly cleaned, and new accumulator / filter drier has been installed. Specs are for total system capacities. Always refer to under hood decal as the primary source for refrigerant and lubricant information.

Year	Model	Lubricant
DEFENDER SERIES		
97	All Eng. - 32.00 Oz. R-134a; 6.50 Oz. PAG-46	59007
95	All Eng. - 32.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
94-93	All Eng. - 38.00 Oz. R-12; 5.00 Oz. Mineral Oil	59000⁵⁹

Continued on Next Page

⁵⁹ When retrofitting to R134a PAG Oil must be used.

LAND ROVER

Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that A/C system has been properly cleaned, and new accumulator / filter drier has been installed. Specs are for total system capacities. Always refer to under hood decal as the primary source for refrigerant and lubricant information.

Year	Model	Lubricant
DISCOVERY		
04-00	All Eng.; w/o Rear AC - 25.00 Oz. R-134a; 6.50 Oz. PAG-46	59007
	All Eng.; w/ Rear AC - 32.00 Oz. R-134a; 6.50 Oz. PAG-46	59007
99-94	All Eng.; w/o Rear AC - 32.00 Oz. R-134a; 6.50 Oz. PAG-46	59007
	All Eng.; w/ Rear AC - 41.00 Oz. R-134a; 6.50 Oz. PAG-46	59007
FREELANDER		
05-03	6 Cyl. 2.5 Eng. - 15.00 Oz. R-134a; See Under Hood Decal PAG-46	59007
02	All Eng. - 16.00 Oz. R-134a; See Under Hood Decal PAG-46	59007
LR2		
13	4 Cyl. 2.0 Eng. - 26.00 Oz. R-134a; 6.80 Oz. PAG-46	59007
12-11	6 Cyl. 3.2 Eng. - 26.00 Oz. R-134a; 3.70 Oz. PAG-46	59007
10-08	6 Cyl. 3.2 Eng. - 26.00 Oz. R-134a; 5.10 Oz. PAG-46	59007
LR3		
09	8 Cyl. 4.4 Eng.; w/o Rear AC - 21.00 Oz. R-134a; 4.40 Oz. PAG-46	59007
	8 Cyl. 4.4 Eng.; w/ Rear AC - 32.00 Oz. R-134a; 4.40 Oz. PAG-46	59007
08	All Eng.; w/o Rear AC - 21.00 Oz. R-134a; 4.50 Oz. PAG-46	59007
	All Eng.; w/ Rear AC - 28.00 Oz. R-134a; 6.00 Oz. PAG-46	59007
07	All Eng.; w/o Rear AC - 21.00 Oz. R-134a; 4.50 Oz. PAG-46	59007
	All Eng.; w/ Rear AC - 31.00 Oz. R-134a; 6.00 Oz. PAG-46	59007
06-05	All Eng.; w/o Rear AC - 21.00 Oz. R-134a; 4.50 Oz. PAG-46	59007
	All Eng.; w/ Rear AC - 32.00 Oz. R-134a; 6.00 Oz. PAG-46	59007
LR4		
13	8 Cyl. 5.0 Eng. - 24.00 Oz. R-134a; 3.72 Oz. PAG-46	59007
	8 Cyl. 5.0 Eng.; w/ Rear AC - 33.00 Oz. R-134a; 5.40 Oz. PAG-46	59007
12	8 Cyl. 5.0 Eng.; w/o Rear AC - 24.00 Oz. R-134a; 3.72 Oz. PAG-46	59007
	8 Cyl. 5.0 Eng.; w/ Rear AC - 33.00 Oz. R-134a; 5.40 Oz. PAG-46	59007
11-10	8 Cyl. 5.0 Eng.; w/o Rear AC - 23.00 Oz. R-134a; 3.70 Oz. PAG-46	59007
	8 Cyl. 5.0 Eng.; w/ Rear AC - 32.00 Oz. R-134a; 5.40 Oz. PAG-46	59007
RANGE ROVER		
13	4 Cyl. 2.0 Eng. - 24.00 Oz. R-134a; 5.07 Oz. PAG-46	59007
	8 Cyl. 5.0 Eng.; w/o Rear AC - 25.00 Oz. R-134a; 3.72 Oz. PAG-46	59007
	8 Cyl. 5.0 Eng.; w/ Rear AC - 31.00 Oz. R-134a; 6.80 Oz. PAG-46	59007
12	4 Cyl. 2.0 Eng. - 24.00 Oz. R-134a; 5.07 Oz. PAG-46	59007
	8 Cyl. 5.0 Eng.; w/o Rear AC - 26.00 Oz. R-134a; 3.72 Oz. PAG-46	59007
	8 Cyl. 5.0 Eng.; w/ Rear AC - 31.00 Oz. R-134a; 6.80 Oz. PAG-46	59007
11	8 Cyl. 5.0 Eng.; w/o Rear AC - 25.00 Oz. R-134a; 3.70 Oz. PAG-46	59007
	8 Cyl. 5.0 Eng.; w/ Rear AC - 31.00 Oz. R-134a; 6.80 Oz. PAG-46	59007
10	8 Cyl. 5.0 Eng.; w/o Rear AC - 25.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
	8 Cyl. 5.0 Eng.; w/ Rear AC - 31.00 Oz. R-134a; 6.80 Oz. PAG-46	59007
09	8 Cyl. 4.2 Eng.; w/o Rear AC - 24.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
	8 Cyl. 4.2 Eng.; w/ Rear AC - 31.00 Oz. R-134a; 5.70 Oz. PAG-46	59007
	8 Cyl. 4.4 Eng.; w/o Rear AC - 24.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
	8 Cyl. 4.4 Eng.; w/ Rear AC - 31.00 Oz. R-134a; 5.70 Oz. PAG-46	59007
08-06	All Eng. - 21.00 Oz. R-134a; 4.50 Oz. PAG-46	59007
05-02	All Eng. - 18.00 Oz. R-134a; 3.50 Oz. PAG-46	59007
01-00	All Eng. - 49.00 Oz. R-134a; 6.00 Oz. PAG-46	59007
99	All Eng. - 41.00 Oz. R-134a; 6.00 Oz. PAG-46	59007
98-97	All Eng. - 44.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
96	All Eng. - 32.00 Oz. R-134a; 5.00 Oz. PAG-46; Old Body Style	59007
	All Eng. - 44.00 Oz. R-134a; 5.00 Oz. PAG-46; New Body Style	59007
95	All Eng. - 32.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
94	8 Cyl. 3.9 Eng. - 42.00 Oz. R-134a; 5.06 Oz. PAG-46	59007
	8 Cyl. 4.2 Eng. - 42.00 Oz. R-134a; 5.06 Oz. PAG-46	59007

LEXUS

Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that A/C system has been properly cleaned, and new accumulator / filter drier has been installed. Specs are for total system capacities. Always refer to under hood decal as the primary source for refrigerant and lubricant information.

Year	Model	Lubricant
	CT200	
13-11	4 Cyl. 1.8 Eng. - 17.00 Oz. R-134a; 4.40-4.90 Oz. PAG-46	59007
	ES250	
91-90	All Eng. - 27.00 Oz. R-12; 7.00 Oz. Mineral Oil	59000 ⁵⁹
	ES300	
03-02	All Eng. - 19.00 Oz. R-134a; See Under Hood Decal PAG-46	59007
01-98	All Eng. - 26.50-30.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
97-94	All Eng. - 30.00 Oz. R-134a; 7.75 Oz. PAG-46	59007
93	All Eng. - 33.50 Oz. R-12; 7.00 Oz. Mineral Oil	59000 ⁵⁹
92	All Eng. - 35.00 Oz. R-12; 7.00 Oz. Mineral Oil	59000 ⁵⁹
	ES330	
06	All Eng. - 21.00 Oz. R-134a; 4.50 Oz. PAG-46	59007
05-04	All Eng. - 19.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
	ES350	
13-10	6 Cyl. 3.5 Eng. - 16.60-18.70 Oz. R-134a; See Under Hood Decal PAG-46	59007
09	6 Cyl. 3.5 Eng. - 16.60-18.70 Oz. R-134a; 4.60+/-0.51 Oz. PAG-46	59007
08-07	6 Cyl. 3.5 Eng. - 19.00 Oz. R-134a; 4.50 Oz. PAG-46	59007
	GS300	
06	All Eng. - 17.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
05-02	All Eng. - 22.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
01-98	All Eng. - 21.00-23.0 Oz. R-134a; 7.00 Oz. PAG-46	59007
97-93	All Eng. - 30.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
	GS350	
11	6 Cyl. 3.5 Eng. - 15.87+/-1.76 Oz. R-134a; 4.60+/-0.51 Oz. PAG-46	59007
	6 Cyl. 3.5 Eng.; 1UR-FSE - 19.39+/-1.76 Oz. R-134a; 4.60+/-0.51 Oz. PAG-46	59007
10	6 Cyl. 3.5 Eng.; 2GRFSE Eng Desg. - 15.87+/-1.76 Oz. R-134a; See Under Hood Decal PAG-46	59007
	6 Cyl. 3.5 Eng.; 1UR-FSE - 19.39+/-1.76 Oz. R-134a; 4.60+/-0.51 Oz. PAG-46	59007
09	6 Cyl. 3.5 Eng.; 2GRFSE Eng Desg. - 15.87+/-1.76 Oz. R-134a; 4.60+/-0.51 Oz. PAG-46	59007
	6 Cyl. 3.5 Eng.; 1UR-FSE - 19.39+/-1.76 Oz. R-134a; 4.60+/-0.51 Oz. PAG-46	59007
08	6 Cyl. 3.5 Eng.; 2GRFSE Eng Desg. - 15.87+/-1.76 Oz. R-134a; 4.50 Oz. PAG-46	59007
	6 Cyl. 3.5 Eng.; 1UR-FSE - 19.39+/-1.76 Oz. R-134a; 4.50 Oz. PAG-46	59007
07	6 Cyl. 3.5 Eng. - 15.87+/-1.76 Oz. R-134a; 4.50 Oz. PAG-46	59007
	GS400	
00-98	All Eng. - 21.00-23.0 Oz. R-134a; 7.00 Oz. PAG-46	59007
	GS430	
07-06	All Eng. - 23.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
05-01	All Eng. - 21.00-23.0 Oz. R-134a; 7.00 Oz. PAG-46	59007
	GS450	
14	6 Cyl. 3.5 Eng. - See Under Hood Decal	59889
13-07	6 Cyl. 3.5 Eng.; Hybrid - 15.87+/-1.76 Oz. R-134a; 4.10+/-0.51 Oz. Hybrid Oil	59889
	GS460	
11	8 Cyl. 4.6 Eng. - 19.00 Oz. R-134a; 4.10-5.10 Oz. PAG-46	59007
	8 Cyl. 4.6 Eng.; 1UR-FSE - 19.39+/-1.76 Oz. R-134a; 4.60+/-0.51 Oz. PAG-46	59007
10	8 Cyl. 4.6 Eng.; 2GRFSE Eng Desg. - 15.87+/-1.76 Oz. R-134a; See Under Hood Decal PAG-46	59007
	8 Cyl. 4.6 Eng.; 1UR-FSE - 19.39+/-1.76 Oz. R-134a; See Under Hood Decal PAG-46	59007
09	8 Cyl. 4.6 Eng.; 2GRFSE Eng Desg. - 15.87+/-1.76 Oz. R-134a; 4.60+/-0.51 Oz. PAG-46	59007
	8 Cyl. 4.6 Eng.; 1UR-FSE - 19.39+/-1.76 Oz. R-134a; See Under Hood Decal PAG-46	59007
08	8 Cyl. 4.6 Eng.; 2GRFSE Eng Desg. - 15.87+/-1.76 Oz. R-134a; See Under Hood Decal PAG-46	59007
	8 Cyl. 4.6 Eng.; 1UR-FSE - 19.39+/-1.76 Oz. R-134a; See Under Hood Decal PAG-46	59007
	GX460	
13	8 Cyl. 4.6 Eng.; w/o Rear AC - 19.00 Oz. R-134a; 5.08 Oz. PAG-46	59007
	8 Cyl. 4.6 Eng.; w/o Cool Box - 29.00 Oz. R-134a; 5.08 Oz. PAG-46	59007
	8 Cyl. 4.6 Eng.; w/ Cool Box - 30.00 Oz. R-134a; 5.10 Oz. PAG-46	59007
12-10	8 Cyl. 4.6 Eng.; w/o Rear AC - 19.00 Oz. R-134a; 5.08 Oz. PAG-46	59007
	8 Cyl. 4.6 Eng.; w/o Cool Box - 29.00 Oz. R-134a; 5.08 Oz. PAG-46	59007
	8 Cyl. 4.6 Eng.; w/ Cool Box - 30.00 Oz. R-134a; 5.08 Oz. PAG-46	59007
	GX470	
09	All Eng.; w/o Rear AC - 22.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
	8 Cyl. 4.7 Eng.; w/ Rear AC - 26.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
08-07	All Eng.; w/o Rear AC - 22.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
	All Eng.; w/ Rear AC - 26.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
06-03	All Eng.; w/o Rear AC - 22.40-24.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
	All Eng.; w/ Rear AC - 28.10-28.90 Oz. R-134a; 4.50 Oz. PAG-46	59007

Continued on Next Page

⁵⁹ When retrofitting to R134a PAG Oil must be used.

LEXUS

Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that A/C system has been properly cleaned, and new accumulator / filter drier has been installed. Specs are for total system capacities. Always refer to under hood decal as the primary source for refrigerant and lubricant information.

Year	Model	Lubricant
	HS250	
12-10	4 Cyl. 2.4 Eng.; Hybrid - 17.00 Oz. R-134a; 3.50 Oz. Hybrid Oil	59889
	IS F	
13	8 Cyl. 5.0 Eng. - 18.00 Oz. R-134a; 5.10 Oz. PAG-46	59007
12-08	8 Cyl. 5.0 Eng. - 14.10-17.63 Oz. R-134a; See Under Hood Decal PAG-46	59007
	IS250	
13	6 Cyl. 2.5 Eng. - 15.00 Oz. R-134a; 5.10 Oz. PAG-46	59007
12	6 Cyl. 2.5 Eng. - 15.00 Oz. R-134a; 4.60-5.10 Oz. PAG-46	59007
11-10	6 Cyl. 2.5 Eng. - 15.00 Oz. R-134a; 5.10 Oz. PAG-46	59007
09	6 Cyl. 2.5 Eng. - 15.17+/-1.06 Oz. R-134a; See Under Hood Decal PAG-46	59007
08-06	6 Cyl. 2.5 Eng. - 16.00 Oz. R-134a; See Under Hood Decal PAG-46	59007
	IS300	
05-03	6 Cyl. 3.0 Eng. - 21.00 Oz. R-134a; See Under Hood Decal PAG-46	59007
02-01	All Eng. - 21.00 Oz. R-134a; See Under Hood Decal PAG-46	59007
	IS350	
13-10	6 Cyl. 3.5 Eng. - 15.00 Oz. R-134a; 5.10 Oz. PAG-46	59007
09-06	6 Cyl. 3.5 Eng. - 15.17+/-1.06 Oz. R-134a; See Under Hood Decal PAG-46	59007
	LS400	
00-98	All Eng. - 22.90-26.50 Oz. R-134a; 7.75 Oz. PAG-46	59007
97-94	All Eng. - 30.00 Oz. R-134a; 7.75 Oz. PAG-46	59007
93	All Eng. - 33.50 Oz. R-134a; 5.25 Oz. PAG-46	59007
	8 Cyl. 4.0 Eng. - w/ R-12	59000 ⁵⁹
92-90	All Eng. - 37.00 Oz. R-12; 7.00 Oz. Mineral Oil	59000 ⁵⁹
	LS430	
06-03	All Eng.; w/o Rear AC - 22.00-24.00 Oz. R-134a; 4.50 Oz. PAG-46	59007
	All Eng.; w/ Rear AC - 30.00-33.50 Oz. R-134a; 4.50 Oz. PAG-46	59007
02-01	All Eng.; w/o Rear AC - 22.00-24.00 Oz. R-134a; PAG-46	59007
	All Eng.; w/ Rear AC - 30.00-33.50 Oz. R-134a; PAG-46	59007
	LS460	
13	8 Cyl. 4.6 Eng.; w/o Rear AC - 23.00 Oz. R-134a; 5.10 Oz. PAG-46	59007
	8 Cyl. 4.6 Eng.; w/ Rear AC - 28.00 Oz. R-134a; 5.10 Oz. PAG-46	59007
12	8 Cyl. 4.6 Eng.; w/o Rear AC - 23.00 Oz. R-134a; 5.10 Oz. PAG-46	59007
	8 Cyl. 4.6 Eng. - 28.00 Oz. R-134a; 5.10 Oz. PAG-46	59007
11-10	8 Cyl. 4.6 Eng.; w/o Rear AC - 23.00 Oz. R-134a; 5.10 Oz. PAG-46	59007
	8 Cyl. 4.6 Eng.; w/ Rear AC - 28.00 Oz. R-134a; 5.10 Oz. PAG-46	59007
09-08	8 Cyl. 4.6 Eng.; w/o Rear AC - 23.00 Oz. R-134a; See Under Hood Decal PAG-46	59007
	8 Cyl. 4.6 Eng.; w/ Rear AC - 28.00 Oz. R-134a; See Under Hood Decal PAG-46	59007
07	8 Cyl. 4.6 Eng. - 26.00 Oz. R-134a; 4.60 Oz. PAG-46	59007
	LS600	
13-10	8 Cyl. 5.0 Eng.; Hybrid - See Under Hood Decal; Hybrid Oil	59889
09-08	8 Cyl. 5.0 Eng.; Hybrid; w/o Rear AC - See Under Hood Decal; Hybrid Oil	59889
	8 Cyl. 5.0 Eng.; Hybrid; w/ Rear AC - See Under Hood Decal; Hybrid Oil	59889
	LX450	
97-96	All Eng. - 30.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
	LX470	
07	8 Cyl. 4.7 Eng. - 31.70+/-1.18. R-134a; See Under Hood Decal PAG-46	59007
06-98	All Eng. - 35.30-38.80 Oz. R-134a; 7.75 Oz. PAG-46	59007
	LX570	
13	8 Cyl. 5.7 Eng.; w/o Cool Box - 34.00 Oz. R-134a; See Under Hood Decal PAG-46	59007
	8 Cyl. 5.7 Eng.; w/ Cool Box - 35.00 Oz. R-134a; See Under Hood Decal PAG-46	59007
11-09	8 Cyl. 5.7 Eng.; w/o Cool Box - 32.50+/-1.10 Oz. R-134a; See Under Hood Decal PAG-46	59007
	8 Cyl. 5.7 Eng.; w/ Cool Box - 34.20+/-1.10 Oz. R-134a; See Under Hood Decal PAG-46	59007
08	8 Cyl. 5.7 Eng.; Standard Air - 32.50+/-1.10 Oz. R-134a; See Under Hood Decal PAG-46	59007
	8 Cyl. 5.7 Eng.; w/o Cool Box - 34.20+/-1.10 Oz. R-134a; See Under Hood Decal PAG-46	59007
	RX300	
03	6 Cyl. 3.0 Eng. - 21.00 Oz. R-134a; 6.91 Oz. PAG-46	59007
02	6 Cyl. 3.0 Eng. - 21.00 Oz. R-134a; 4.80 Oz. PAG-46	59007
01-99	All Eng. - 21.00 Oz. R-134a; 4.80 Oz. PAG-46	59007
	RX330	
08-04	All Eng. - 22.00-24.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
	RX350	
13-10	6 Cyl. 3.5 Eng. - 15.90-19.40 Oz. R-134a; See Under Hood Decal PAG-46	59007
09	6 Cyl. 3.5 Eng. - 19.40-22.90 Oz. R-134a; See Under Hood Decal PAG-46	59007
08-07	All Eng. - 19.40-22.90 Oz. R-134a; See Under Hood Decal PAG-46	59007

Continued on Next Page

⁵⁹ When retrofitting to R134a PAG Oil must be used.

Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that A/C system has been properly cleaned, and new accumulator / filter drier has been installed. Specs are for total system capacities. Always refer to under hood decal as the primary source for refrigerant and lubricant information.

Year	Model	Lubricant
	RX400	
09-06	6 Cyl. 3.3 Eng.; Hybrid - 19.40-22.90 Oz. R-134a; See Under Hood Decal; Hybrid Oil	59889
	RX450	
14	6 Cyl. 3.5 Eng. - See Under Hood Decal	59889
13	6 Cyl. 3.5 Eng.; Hybrid - 23.00 Oz. R-134a; See Under Hood Decal; Hybrid Oil	59889
12	6 Cyl. 3.5 Eng.; Hybrid - 21.00 Oz. R-134a; 4.10-4.60 Oz. Hybrid Oil	59889
11-10	6 Cyl. 3.5 Eng.; Hybrid - 21.00 Oz. R-134a; 3.53 Oz. Hybrid Oil	59889
	SC300	
00-97	All Eng. - 32.00-34.0 Oz. R-134a; 7.00 Oz. PAG-46	59007
96	All Eng. - 31.80-35.30 Oz. R-134a; 7.00 Oz. PAG-46	59007
95-94	All Eng. - 30.00 Oz. R-134a; 7.75 Oz. PAG-46	59007
93	All Eng. - 33.50 Oz. R-12; 7.00 Oz. Mineral Oil	59000⁵⁹
92	All Eng. - 35.00 Oz. R-12; 7.00 Oz. Mineral Oil	59000⁵⁹
	SC400	
00-96	All Eng. - 33.50 Oz. R-134a; 7.00 Oz. PAG-46	59007
95-94	All Eng. - 30.00 Oz. R-134a; 7.75 Oz. PAG-46	59007
93	All Eng. - 33.50 Oz. R-12; 7.00 Oz. Mineral Oil	59000⁵⁹
92	All Eng. - 35.00 Oz. R-12; 7.00 Oz. Mineral Oil	59000⁵⁹
	SC430	
10-08	8 Cyl. 4.3 Eng. - See Under Hood Decal	59007
07	8 Cyl. 4.3 Eng. - 21.00 Oz. R-134a; 4.10 Oz. PAG-46	59007
06-02	All Eng. - 21.00 Oz. R-134a; 4.10 Oz. PAG-46	59007

Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that A/C system has been properly cleaned, and new accumulator / filter drier has been installed. Specs are for total system capacities. Always refer to under hood decal as the primary source for refrigerant and lubricant information.

Year	Model	Lubricant
	AVIATOR	
05-03	All Eng.; w/ Rear AC - 56.00 Oz. R-134a; 13.00 Oz. PAG-46	59007
	BLACKWOOD	
02	All Eng. - 37.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
	CONTINENTAL	
02-98	All Eng. - 38.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
97-95	All Eng. - 34.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
94	All Eng. - 40.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
93	All Eng.; w/ Rear AC - 40.00 Oz. R-12; 10.00 Oz. Ester	59000⁵⁹
	All Eng.; w/o Rear AC - 40.00 Oz. R-12; 7.00 Oz. Ester	59000⁵⁹
92	All Eng. - 40.00 Oz. R-12; 7.00 Oz. Ester	59000⁵⁹
91-89	All Eng. - 40.00 Oz. R-12; 8.00 Oz. Ester	59000⁵⁹
88	6 Cyl. 3.8 Eng. - See Under Hood Decal	59000⁵⁹
87-86	8 Cyl. 5.0 Eng. - See Under Hood Decal	59000⁵⁹
85	6 Cyl. 2.4 Eng. - See Under Hood Decal	59000⁵⁹
	8 Cyl. 5.0 Eng. - See Under Hood Decal	59000⁵⁹
82	6 Cyl. 3.8 Eng. - See Under Hood Decal	59000⁵⁹
	8 Cyl. 5.0 Eng. - See Under Hood Decal	59000⁵⁹
81	8 Cyl. 5.0 Eng. - See Under Hood Decal	59000⁵⁹
80	8 Cyl. 5.0 Eng. - See Under Hood Decal	59000⁵⁹
	8 Cyl. 5.8 Eng. - See Under Hood Decal	59000⁵⁹
79	8 Cyl. 6.6 Eng. - See Under Hood Decal	59000⁵⁹
78-77	8 Cyl. 6.6 Eng. - See Under Hood Decal	59000⁵⁹
	8 Cyl. 7.5 Eng. - See Under Hood Decal	59000⁵⁹
76-74	8 Cyl. 7.5 Eng. - See Under Hood Decal	59000⁵⁹
	LS	
06-00	All Eng. - 28.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
	MARK LIGHT TRUCK	
08-06	All Eng. - 34.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
	MARK SERIES	
98-95	All Eng. - 34.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
94	All Eng. - 40.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
93	All Eng.; w/ Rear AC - 34.00 Oz. R-134a; 10.00 Oz. PAG-46	59007
	All Eng.; w/o Rear AC - 34.00 Oz. R-134a; 7.00 Oz. PAG-46	59007

Continued on Next Page

⁵⁹ When retrofitting to R134a PAG Oil must be used.

LINCOLN

Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that A/C system has been properly cleaned, and new accumulator / filter drier has been installed. Specs are for total system capacities. Always refer to under hood decal as the primary source for refrigerant and lubricant information.

Year	Model	Lubricant
MARK SERIES (Cont'd)		
93	All Eng. - w/ R-12	59000 ⁵⁹
92-89	All Eng. - 40.00 Oz. R-12; 8.00 Oz. Ester	59000 ⁵⁹
88	All Eng. - 40.00 Oz. R-12; 10.00 Oz. Ester	59000 ⁵⁹
87-86	8 Cyl. 5.0 Eng. - See Under Hood Decal	59000 ⁵⁹
85	6 Cyl. 2.4 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.0 Eng. - See Under Hood Decal	59000 ⁵⁹
84-81	8 Cyl. 5.0 Eng. - See Under Hood Decal	59000 ⁵⁹
80	8 Cyl. 5.0 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.8 Eng. - See Under Hood Decal	59000 ⁵⁹
79	8 Cyl. 6.6 Eng. - See Under Hood Decal	59000 ⁵⁹
78-77	8 Cyl. 6.6 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 7.5 Eng. - See Under Hood Decal	59000 ⁵⁹
76-72	8 Cyl. 7.5 Eng. - See Under Hood Decal	59000 ⁵⁹
MKS		
13-11	6 Cyl. 3.5 Eng. - 26.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
	6 Cyl. 3.7 Eng. - 26.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
10-09	All Eng. - 26.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
MKT		
13	4 Cyl. 2.0 Eng. - See Under Hood Decal	59007
	6 Cyl. 3.5 Eng. - 36.00 Oz. R-134a; 9.50 Oz. PAG-46	59007
	6 Cyl. 3.7 Eng. - 36.00 Oz. R-134a; 9.50 Oz. PAG-46	59007
12-10	6 Cyl. 3.5 Eng. - 36.00 Oz. R-134a; 9.50 Oz. PAG-46	59007
	6 Cyl. 3.7 Eng. - 36.00 Oz. R-134a; 9.50 Oz. PAG-46	59007
MKX		
13-11	6 Cyl. 3.7 Eng. - 21.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
10-07	6 Cyl. 3.5 Eng. - 21.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
MKZ		
13	4 Cyl. 2.0 Eng. - 20.00 Oz. R-134a; 4.70 Oz. PAG-46	59007
	6 Cyl. 3.7 Eng. - 24.00 Oz. R-134a; 4.70 Oz. PAG-46	59007
12	4 Cyl. 2.5 Eng.; Hybrid - 22.00 Oz. R-134a; 4.40 Oz. Hybrid Oil	59889
	6 Cyl. 3.5 Eng. - 22.00 Oz. R-134a; 6.00 Oz. PAG-46	59007
11	4 Cyl. 2.5 Eng.; Hybrid - 22.00 Oz. R-134a; 6.00 Oz. Hybrid Oil	59889
	6 Cyl. 3.5 Eng. - 22.00 Oz. R-134a; 6.00 Oz. PAG-46	59007
10-07	6 Cyl. 3.5 Eng. - 21.00 Oz. R-134a; 6.00 Oz. PAG-46	59007
NAVIGATOR		
13-12	8 Cyl. 5.4 Eng. - 36.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
11	8 Cyl. 5.4 Eng. - 33.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
10-09	All Eng. - 33.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
	L - 36.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
08	All Eng.; w/o Rear AC - 22.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
07	All Eng.; w/o Rear AC - 22.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
	All Eng.; w/ Rear AC - 33.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
06	All Eng.; w/o Rear AC - 40.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
	All Eng.; w/ Rear AC - 58.00 Oz. R-134a; 14.00 Oz. PAG-46	59007
05-03	All Eng.; w/o Rear AC - 32.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
	All Eng.; w/ Rear AC - 54.00 Oz. R-134a; 14.00 Oz. PAG-46	59007
02-98	All Eng.; w/o Rear AC - 37.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
	All Eng.; w/ Rear AC - 62.00 Oz. R-134a; 14.00 Oz. PAG-46	59007
TOWN CAR		
11-09	8 Cyl. 4.6 Eng. - 23.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
08-06	All Eng. - 23.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
05-03	All Eng. - 32.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
02-98	All Eng. - 38.00 Oz. R-134a; 7.50 Oz. PAG-46	59007
97	All Eng. - 34.00 Oz. R-134a; 7.50 Oz. PAG-46	59007
96-95	All Eng. - 34.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
94	All Eng.; w/o Rear AC - 40.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
	All Eng.; w/ Rear AC - 40.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
93	All Eng.; w/ Rear AC - 36.00 Oz. R-12; 10.00 Oz. Ester	59000 ⁵⁹
	All Eng.; w/o Rear AC - 36.00 Oz. R-12; 7.00 Oz. Ester	59000 ⁵⁹
92-91	All Eng. - 40.00 Oz. R-12; 7.00 Oz. Ester	59000 ⁵⁹
90-89	All Eng. - 48.00 Oz. R-12; 8.00 Oz. Ester	59000 ⁵⁹
88	All Eng. - 52.00 Oz. R-12; 10.00 Oz. Ester	59000 ⁵⁹
87-86	All Eng. - 48.00 Oz. R-12; 10.00 Oz. Ester	59000 ⁵⁹

Continued on Next Page

⁵⁹ When retrofitting to R134a PAG Oil must be used.

Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that A/C system has been properly cleaned, and new accumulator / filter drier has been installed. Specs are for total system capacities. Always refer to under hood decal as the primary source for refrigerant and lubricant information.

Year	Model	Lubricant
TOWN CAR (Cont'd)		
85	All Eng. - 52.00 Oz. R-12; 10.00 Oz. Ester	59000 ⁵⁹
84-82	8 Cyl. 5.0 Eng. - See Under Hood Decal	59000 ⁵⁹
ZEPHYR		
06	All Eng. - 21.00 Oz. R-134a; 6.00 Oz. PAG-46	59007

MAZDA

Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that A/C system has been properly cleaned, and new accumulator / filter drier has been installed. Specs are for total system capacities. Always refer to under hood decal as the primary source for refrigerant and lubricant information.

Year	Model	Lubricant
323		
94-93	All Eng. - 28.00 Oz. R-134a; 7.50 Oz. PAG-46	59007
92-89	All Eng. - 27.00 Oz. R-12; 6.75 Oz. Mineral Oil	59000 ⁵⁹
88	All Eng. - 27.00 Oz. R-12; 7.75 Oz. Mineral Oil	59000 ⁵⁹
87-86	All Eng. - 30.00 Oz. R-12; 7.75 Oz. Mineral Oil	59000 ⁵⁹
626		
02-98	All Eng. - 26.50 Oz. R-134a; 8.00 Oz. PAG-100	59002
97-94	All Eng. - 25.00 Oz. R-134a; 8.00 Oz. PAG-100	59002
93-89	All Eng. - 26.00 Oz. R-12; 6.00 Oz. Mineral Oil	59000 ⁵⁹
88	All Eng. - 37.00 Oz. R-12; 7.75 Oz. Mineral Oil	59000 ⁵⁹
87-86	All Eng. - 32.00 Oz. R-12; 7.75 Oz. Mineral Oil	59000 ⁵⁹
85	All Eng. - w/ R-12; 7.75 Oz. Mineral Oil	59000 ⁵⁹
84-79	4 Cyl. 2.0 Eng. - See Under Hood Decal	59000 ⁵⁹
808		
77-74	4 Cyl. 1.6 Eng. - See Under Hood Decal	59000 ⁵⁹
929		
95-94	All Eng. - 28.00 Oz. R-134a; 7.50 Oz. PAG-100	59002
93-92	All Eng. - 28.00 Oz. R-12; 6.50 Oz. Mineral Oil	59000 ⁵⁹
91-89	All Eng. - 40.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
88	All Eng. - 35.00 Oz. R-12; 5.00 Oz. Mineral Oil	59000 ⁵⁹
COSMO		
78-76	2 Cyl. 1.3 Eng. - See Under Hood Decal	59000 ⁵⁹
CX-7		
12-10	4 Cyl. 2.3 Eng. - 15.70-17.40 Oz. R-134a; 4.06 Oz. PAG-46	59007
	4 Cyl. 2.5 Eng. - 15.70-17.40 Oz. R-134a; 4.06 Oz. PAG-46	59007
09-07	4 Cyl. 2.3 Eng. - 17.70 Oz. R-134a; 4.06 Oz. PAG-46	59007
CX-9		
12-09	6 Cyl. 3.7 Eng. - 23.00-25.00 Oz. R-134a; 5.50 Oz. PAG-46	59007
08	6 Cyl. 3.5 Eng. - 23.00-25.00 Oz. R-134a; 5.50 Oz. PAG-46	59007
	6 Cyl. 3.7 Eng. - 23.00-25.00 Oz. R-134a; 5.41 Oz. PAG-46	59007
07	6 Cyl. 3.5 Eng. - 24.00 Oz. R-134a; 5.50 Oz. PAG-46	59007
GLC		
85-81	4 Cyl. 1.5 Eng. - See Under Hood Decal	59000 ⁵⁹
80-79	4 Cyl. 1.4 Eng. - See Under Hood Decal	59000 ⁵⁹
78-77	4 Cyl. 1.3 Eng. - See Under Hood Decal	59000 ⁵⁹
MAZDA 2		
13-11	4 Cyl. 1.5 Eng. - 15.70-17.40 Oz. R-134a; 3.72 Oz. PAG-46	59007
MAZDA 3		
13-11	4 Cyl. 2.0 Eng. - 18.00 Oz. R-134a; 4.10 Oz. PAG-46	59007
	4 Cyl. 2.3 Eng. - 18.00 Oz. R-134a; 4.10 Oz. PAG-46	59007
	4 Cyl. 2.5 Eng. - 18.00 Oz. R-134a; 4.10 Oz. PAG-46	59007
10	4 Cyl. 2.0 Eng. - 17.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
	4 Cyl. 2.3 Eng. - 17.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
	4 Cyl. 2.5 Eng. - 17.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
09	4 Cyl. 2.0 Eng. - 18.00 Oz. R-134a; 5.08 Oz. PAG-46	59007
	4 Cyl. 2.3 Eng. - 18.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
08-04	All Eng. - 18.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
MAZDA 5		
13-12	4 Cyl. 2.5 Eng. - 18.00 Oz. R-134a; 4.10 Oz. PAG-46	59007
10	4 Cyl. 2.3 Eng. - 18.00 Oz. R-134a; 5.41 Oz. PAG-46	59007
09	4 Cyl. 2.3 Eng. - 18.00 Oz. R-134a; 5.08 Oz. PAG-46	59007

Continued on Next Page

⁵⁹ When retrofitting to R134a PAG Oil must be used.

MAZDA

Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that A/C system has been properly cleaned, and new accumulator / filter drier has been installed. Specs are for total system capacities. Always refer to under hood decal as the primary source for refrigerant and lubricant information.

Year	Model	Lubricant
MAZDA 5 (Cont'd)		
08	All Eng. - 18.00 Oz. R-134a; 5.08 Oz. PAG-46	59007
07-06	All Eng. - 18.00 Oz. R-134a; 5.41 Oz. PAG-46	59007
MAZDA 6		
13	4 Cyl. 2.5 Eng. - 19.00 Oz. R-134a; 4.10 Oz. PAG-46	59007
	6 Cyl. 3.7 Eng. - 19.00 Oz. R-134a; 4.10 Oz. PAG-46	59007
12-11	4 Cyl. 2.5 Eng. - 17.60-19.40 Oz. R-134a; 4.10 Oz. PAG-46	59007
	6 Cyl. 3.7 Eng. - 17.60-19.40 Oz. R-134a; 4.10 Oz. PAG-46	59007
10-09	4 Cyl. 2.5 Eng. - 17.60-19.40 Oz. R-134a; 4.06 Oz. PAG-46	59007
	6 Cyl. 3.7 Eng. - 17.60-19.40 Oz. R-134a; 4.06 Oz. PAG-46	59007
08-05	All Eng. - 16.80 Oz. R-134a; 5.07 Oz. PAG-46	59007
04-03	All Eng. - 17.60 Oz. R-134a; 5.07 Oz. PAG-46	59007
MIATA		
13-10	4 Cyl. 2.0 Eng. - 16.00 Oz. R-134a; 4.40 Oz. PAG-46	59007
09	4 Cyl. 2.0 Eng. - 16.00 Oz. R-134a; 4.39 Oz. PAG-46	59007
08-06	All Eng. - 16.00 Oz. R-134a; 4.39 Oz. PAG-46	59007
05	All Eng. - 14.00 Oz. R-134a; See Under Hood Decal PAG-46	59007
04	All Eng. - 14.00 Oz. R-134a; 5.07 Oz. PAG-46	59007
03-01	All Eng. - 14.00 Oz. R-134a; 5.00 Oz. PAG-100	59002
00-99	All Eng. - 20.00 Oz. R-134a; 8.75 Oz. PAG-100	59002
97-94	All Eng. - 21.00 Oz. R-134a; 8.75 Oz. PAG-100	59002
93	All Eng. - 28.00 Oz. R-12; 6.50 Oz. Mineral Oil	59000 ⁵⁹
92-90	All Eng. - 29.00 Oz. R-12; 6.50 Oz. Mineral Oil	59000 ⁵⁹
MILLENNIA		
02-95	All Eng. - 26.50 Oz. R-134a; 6.00 Oz. PAG-100	59002
MPV		
06-03	All Eng.; w/o Rear AC - 21.00 Oz. R-134a; 6.00 Oz. PAG-46	59007
	All Eng.; w/ Rear AC - 28.00 Oz. R-134a; 8.50 Oz. PAG-46	59007
02-00	All Eng.; w/o Rear AC - 23.00 Oz. R-134a; 8.50 Oz. PAG-46	59007
	All Eng.; w/ Rear AC - 30.00 Oz. R-134a; 8.50 Oz. PAG-46	59007
98-97	All Eng.; w/o Rear AC - 32.00 Oz. R-134a; 6.75 Oz. PAG-46	59007
	All Eng.; w/ Rear AC - 35.00 Oz. R-134a; 6.75 Oz. PAG-46	59007
96-95	All Eng.; w/o Rear AC - 32.00 Oz. R-134a; 7.25 Oz. PAG-46	59007
	All Eng.; w/ Rear AC - 35.00 Oz. R-134a; 8.75 Oz. PAG-46	59007
94	All Eng.; w/o Rear AC - 37.00 Oz. R-134a; 8.75 Oz. PAG-46	59007
	All Eng.; w/ Rear AC - 44.00 Oz. R-134a; 8.75 Oz. PAG-46	59007
93-91	All Eng.; w/o Rear AC - 43.00 Oz. R-12; 6.50 Oz. Mineral Oil	59000 ⁵⁹
	All Eng.; w/ Rear AC - 49.50 Oz. R-12; 6.50 Oz. Mineral Oil	59000 ⁵⁹
90	All Eng.; w/o Rear AC - 42.00 Oz. R-12; 6.50 Oz. Mineral Oil	59000 ⁵⁹
	All Eng.; w/ Rear AC - 49.00 Oz. R-12; 6.50 Oz. Mineral Oil	59000 ⁵⁹
89	4 Cyl. 2.6 Eng. - See Under Hood Decal	59000 ⁵⁹
	6 Cyl. 3.0 Eng. - See Under Hood Decal	59000 ⁵⁹
MX-3		
95-94	All Eng. - 26.50 Oz. R-134a; 6.25 Oz. PAG-100	59002
93-92	All Eng. - 28.00 Oz. R-12; 4.50 Oz. Mineral Oil	59000 ⁵⁹
MX-6		
97	All Eng. - 24.00 Oz. R-134a; 6.00 Oz. PAG-100	59002
96-94	All Eng. - 24.00 Oz. R-134a; 5.25 Oz. PAG-100	59002
93-89	All Eng. - 26.00 Oz. R-12; 6.00 Oz. Mineral Oil	59000 ⁵⁹
88	All Eng. - 37.00 Oz. R-12; 7.75 Oz. Mineral Oil	59000 ⁵⁹
NAVAJO		
94	All Eng.; w/ Rear AC - 28.00 Oz. R-134a; 10.00 Oz. PAG-100	59002
	All Eng.; w/o Rear AC - 28.00 Oz. R-134a; 7.00 Oz. PAG-100	59002
93-91	All Eng. - 28.00 Oz. R-12; 7.00 Oz. Mineral Oil	59000 ⁵⁹
PICKUP		
08-06	All Eng. - 33.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
05-97	All Eng. - 30.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
96-94	All Eng. - 22.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
93-92	4 Cyl. 2.2 Eng. - See Under Hood Decal	59000 ⁵⁹
	4 Cyl. 2.6 Eng. - See Under Hood Decal	59000 ⁵⁹
91-90	B2200 - 26.50 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
	B2600 - See Under Hood Decal	59000 ⁵⁹
89-87	B2200 - 30.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
	B2600 - See Under Hood Decal	59000 ⁵⁹

Continued on Next Page

⁵⁹ When retrofitting to R134a PAG Oil must be used.

Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that A/C system has been properly cleaned, and new accumulator / filter drier has been installed. Specs are for total system capacities. Always refer to under hood decal as the primary source for refrigerant and lubricant information.

Year	Model	Lubricant
PICKUP (Cont'd)		
86	B2000 - 30.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
84-82	4 Cyl. 2.0 Eng. - See Under Hood Decal	59000 ⁵⁹
	4 Cyl. 2.2 Eng. - See Under Hood Decal	59000 ⁵⁹
81-79	4 Cyl. 2.0 Eng. - See Under Hood Decal	59000 ⁵⁹
78	4 Cyl. 1.8 Eng. - See Under Hood Decal	59000 ⁵⁹
77-76	2 Cyl. 1.3 Eng. - See Under Hood Decal	59000 ⁵⁹
PROTEGE		
03-02	4 Cyl. 1.6 Eng. - See Under Hood Decal	59007
	4 Cyl. 2.0 Eng. - 21.00 Oz. R-134a; 5.07 Oz. PAG-46	59007
01	4 Cyl. 1.6 Eng. - 21.00 Oz. R-134a; 5.07 Oz. PAG-46	59007
	4 Cyl. 2.0 Eng. - 21.00 Oz. R-134a; 5.07 Oz. PAG-46	59007
00-99	4 Cyl. 1.6 Eng. - 21.00 Oz. R-134a; 5.07 Oz. PAG-46	59007
	4 Cyl. 1.8 Eng. - 21.00 Oz. R-134a; 5.07 Oz. PAG-46	59007
98-95	4 Cyl. 1.5 Eng. - 21.00 Oz. R-134a; 5.07 Oz. PAG-46	59007
	4 Cyl. 1.8 Eng. - 21.00 Oz. R-134a; 5.07 Oz. PAG-46	59007
94	4 Cyl. 1.8 Eng. - 28.00 Oz. R-12; 3.88-4.56 Oz. Mineral Oil	59000 ⁵⁹
93-90	4 Cyl. 1.8 Eng. - 28.00 Oz. R-12; See Under Hood Decal; Mineral Oil	59000 ⁵⁹
PROTEGE5		
03	4 Cyl. 2.0 Eng. - 19.00 Oz. R-134a; 5.07 Oz. PAG-46	59007
02	All Eng. - 18.50 Oz. R-134a; 5.00 Oz. PAG-46	59007
RX-2		
74-72	2 Cyl. 1.1 Eng. - See Under Hood Decal	59000 ⁵⁹
RX-3		
78-72	2 Cyl. 1.1 Eng. - See Under Hood Decal	59000 ⁵⁹
RX-4		
78-74	2 Cyl. 1.3 Eng. - See Under Hood Decal	59000 ⁵⁹
RX-7		
95-94	All Eng. - 19.00 Oz. R-134a; 5.75 Oz. PAG-100	59002
93	All Eng. - 22.00 Oz. R-12; 5.00 Oz. Mineral Oil	59000 ⁵⁹
91-89	All Eng. - 29.00 Oz. R-12; 6.00 Oz. Mineral Oil; w/ Denso Compressor	59000 ⁵⁹
	All Eng. - 29.00 Oz. R-12; 6.00 Oz. Mineral Oil; w/ Sanden Compressor	59000 ⁵⁹
88-86	2 Cyl. 1.3 Eng. - See Under Hood Decal	59000 ⁵⁹
82-79	2 Cyl. 1.1 Eng. - See Under Hood Decal	59000 ⁵⁹
RX-8		
11-09	2 Cyl. 1.3 Eng. - 15.00 Oz. R-134a; See Under Hood Decal PAG-46	59007
08-04	All Eng. - 16.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
TRIBUTE		
11	4 Cyl. 2.5 Eng. - 25.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
	6 Cyl. 3.0 Eng. - 25.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
10	4 Cyl. 2.5 Eng.; Hybrid - 32.00 Oz. R-134a; 4.40 Oz. Hybrid Oil	59889
	6 Cyl. 3.0 Eng. - 25.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
09	4 Cyl. 2.5 Eng.; Hybrid - 38.00 Oz. R-134a; 5.00 Oz. Hybrid Oil	59889
	6 Cyl. 3.0 Eng. - 25.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
08	All Eng. - 25.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
06-01	All Eng. - 32.00 Oz. R-134a; 7.00 Oz. PAG-46	59007

MERCEDES-BENZ

Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that A/C system has been properly cleaned, and new accumulator / filter drier has been installed. Specs are for total system capacities. Always refer to under hood decal as the primary source for refrigerant and lubricant information.

Year	Model	Lubricant
190 SERIES		
93-90	190E - 35.00 Oz. R-12; 7.75 Oz. Mineral Oil	59000 ⁵⁹
89	190D - 35.00 Oz. R-12; 7.50 Oz. Mineral Oil	59000 ⁵⁹
	190E - 35.00 Oz. R-12; 7.75 Oz. Mineral Oil	59000 ⁵⁹
88	4 Cyl. 2.3 Eng. - See Under Hood Decal	59000 ⁵⁹
	5 Cyl. 2.5 Eng. - See Under Hood Decal	59000 ⁵⁹
	5 Cyl. 2.5 Eng. - See Under Hood Decal	59000 ⁵⁹
	5 Cyl. 2.5 Eng. - See Under Hood Decal	59000 ⁵⁹
	5 Cyl. 2.5 Eng. - See Under Hood Decal	59000 ⁵⁹
	6 Cyl. 2.6 Eng. - See Under Hood Decal	59000 ⁵⁹

Continued on Next Page

⁵⁹ When retrofitting to R134a PAG Oil must be used.

MERCEDES-BENZ

Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that A/C system has been properly cleaned, and new accumulator / filter drier has been installed. Specs are for total system capacities. Always refer to under hood decal as the primary source for refrigerant and lubricant information.

Year	Model	Lubricant	
190 SERIES (Cont'd)			
87	4 Cyl. 2.3 Eng. - See Under Hood Decal	59000 ⁵⁹	
	5 Cyl. 2.5 Eng. - See Under Hood Decal	59000 ⁵⁹	
	5 Cyl. 2.5 Eng. - See Under Hood Decal	59000 ⁵⁹	
	5 Cyl. 2.5 Eng. - See Under Hood Decal	59000 ⁵⁹	
	5 Cyl. 2.5 Eng. - See Under Hood Decal	59000 ⁵⁹	
	6 Cyl. 2.6 Eng. - See Under Hood Decal	59000 ⁵⁹	
86	4 Cyl. 2.3 Eng. - See Under Hood Decal	59000 ⁵⁹	
	5 Cyl. 2.5 Eng. - See Under Hood Decal	59000 ⁵⁹	
	5 Cyl. 2.5 Eng. - See Under Hood Decal	59000 ⁵⁹	
85	4 Cyl. 2.2 Eng. - See Under Hood Decal	59000 ⁵⁹	
	4 Cyl. 2.3 Eng. - See Under Hood Decal	59000 ⁵⁹	
84	4 Cyl. 2.3 Eng. - See Under Hood Decal	59000 ⁵⁹	
220 SERIES			
73-68	4 Cyl. 2.2 Eng. - See Under Hood Decal	59000 ⁵⁹	
230 SERIES			
78-74	4 Cyl. 2.3 Eng. - See Under Hood Decal	59000 ⁵⁹	
68-65	6 Cyl. 2.3 Eng. - See Under Hood Decal	59000 ⁵⁹	
240 SERIES			
83-76	4 Cyl. 2.4 Eng. - See Under Hood Decal	59000 ⁵⁹	
260 SERIES			
89-87	6 Cyl. 2.6 Eng. - See Under Hood Decal	59000 ⁵⁹	
280 SERIES			
81-77	6 Cyl. 2.8 Eng. - See Under Hood Decal	59000 ⁵⁹	
300 SERIES			
93	300CE - 33.50 Oz. R-134a; 8.50 Oz. PAG-46	59007	
	300D - 33.50 Oz. R-134a; 8.50 Oz. PAG-46	59007	
	300E - 33.50 Oz. R-134a; 8.50 Oz. PAG-46	59007	
	300SD; w/o Rear AC - 39.00 Oz. R-134a; 8.50 Oz. PAG-46	59007	
	300SD; w/ Rear AC - 41.50 Oz. R-134a; 8.50 Oz. PAG-46	59007	
	300CE - w/ R-12	59000 ⁵⁹	
	300D - w/ R-12	59000 ⁵⁹	
	300E - w/ R-12	59000 ⁵⁹	
	300SD; w/o Rear AC - w/ R-12	59000 ⁵⁹	
	300SE - w/ R-12	59000 ⁵⁹	
	300SL - w/ R-12	59000 ⁵⁹	
	300TE - w/ R-12	59000 ⁵⁹	
	300SE - w/ R-134a	59007	
	300SL - w/ R-134a	59007	
300TE - w/ R-134a	59007		
92	300CE - 35.00 Oz. R-12; 7.75 Oz. Mineral Oil	59000 ⁵⁹	
	300E - 35.00 Oz. R-12; 7.75 Oz. Mineral Oil	59000 ⁵⁹	
	300SD; w/o Rear AC - 39.00 Oz. R-134a; 8.50 Oz. PAG-46	59007	
	300SD; w/ Rear AC - 41.50 Oz. R-134a; 8.50 Oz. PAG-46	59007	
	300D - 46.00 Oz. R-12; 7.75 Oz. Mineral Oil	59000 ⁵⁹	
	300SL - See Under Hood Decal	59000 ⁵⁹	
	300TE - See Under Hood Decal	59000 ⁵⁹	
6 Cyl. 3.0 Eng. - w/ R-12		59000 ⁵⁹	
	6 Cyl. 3.0 Eng. - w/ R-134a	59007	
91	300CE - 35.00 Oz. R-12; 7.75 Oz. Mineral Oil	59000 ⁵⁹	
	300E - 35.00 Oz. R-12; 7.75 Oz. Mineral Oil	59000 ⁵⁹	
	300D - 46.00 Oz. R-12; 7.75 Oz. Mineral Oil	59000 ⁵⁹	
	300SE - 46.00 Oz. R-12; 7.75 Oz. Mineral Oil	59000 ⁵⁹	
	300SEL - 46.00 Oz. R-12; 7.75 Oz. Mineral Oil	59000 ⁵⁹	
	300SL - See Under Hood Decal	59000 ⁵⁹	
300TE - See Under Hood Decal		59000 ⁵⁹	
	90	300CE - 35.00 Oz. R-12; 7.75 Oz. Mineral Oil	59000 ⁵⁹
		300E - 35.00 Oz. R-12; 7.75 Oz. Mineral Oil	59000 ⁵⁹
		300SE - 46.00 Oz. R-12; 7.75 Oz. Mineral Oil	59000 ⁵⁹
		300SEL - 46.00 Oz. R-12; 7.75 Oz. Mineral Oil	59000 ⁵⁹
300D - See Under Hood Decal		59000 ⁵⁹	
300SL - See Under Hood Decal		59000 ⁵⁹	
	300TE - See Under Hood Decal		59000 ⁵⁹
		89	300CE - 35.00 Oz. R-12; 7.75 Oz. Mineral Oil
			59000 ⁵⁹

Continued on Next Page

⁵⁹ When retrofitting to R134a PAG Oil must be used.

Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that A/C system has been properly cleaned, and new accumulator / filter drier has been installed. Specs are for total system capacities. Always refer to under hood decal as the primary source for refrigerant and lubricant information.

Year	Model	Lubricant
300 SERIES (Cont'd)		
89	300E - 35.00 Oz. R-12; 7.75 Oz. Mineral Oil	59000 ⁵⁹
	300SE - 46.00 Oz. R-12; 7.75 Oz. Mineral Oil	59000 ⁵⁹
	300SEL - 46.00 Oz. R-12; 7.75 Oz. Mineral Oil	59000 ⁵⁹
	300TE - See Under Hood Decal	59000 ⁵⁹
88-86	6 Cyl. 3.0 Eng. - See Under Hood Decal	59000 ⁵⁹
85-77	5 Cyl. 3.0 Eng. - See Under Hood Decal	59000 ⁵⁹
350 SERIES		
91	All Eng. - 46.00 Oz. R-12; 7.75 Oz. Mineral Oil	59000 ⁵⁹
90	350SDL - 46.00 Oz. R-12; 7.75 Oz. Mineral Oil	59000 ⁵⁹
380 SERIES		
85-81	8 Cyl. 3.8 Eng. - See Under Hood Decal	59000 ⁵⁹
400 SERIES		
93	400E - 33.50 Oz. R-134a; 8.50 Oz. PAG-46	59007
	400SEL; w/o Rear AC - 39.00 Oz. R-134a; 8.50 Oz. PAG-46	59007
	400SEL; w/ Rear AC - 41.50 Oz. R-134a; 8.50 Oz. PAG-46	59007
92	400E; w/o Rear AC - 39.00 Oz. R-12; 7.75 Oz. Mineral Oil	59000 ⁵⁹
	400SE; w/o Rear AC - 39.00 Oz. R-134a; 8.50 Oz. PAG-46	59007
	400SE; w/ Rear AC - 41.50 Oz. R-134a; 8.50 Oz. PAG-46	59007
	400E; w/ Rear AC - 44.00 Oz. R-12; 7.75 Oz. Mineral Oil	59000 ⁵⁹
420 SERIES		
91-89	420SEL - 46.00 Oz. R-12; 7.75 Oz. Mineral Oil	59000 ⁵⁹
88-86	8 Cyl. 4.2 Eng. - See Under Hood Decal	59000 ⁵⁹
450 SERIES		
80-73	8 Cyl. 4.5 Eng. - See Under Hood Decal	59000 ⁵⁹
500 SERIES		
93	500E - 33.50 Oz. R-134a; 8.50 Oz. PAG-46	59007
	500SEC; w/o Rear AC - 39.00 Oz. R-134a; 8.50 Oz. PAG-46	59007
	500SEL; w/o Rear AC - 39.00 Oz. R-134a; 8.50 Oz. PAG-46	59007
	500SEC; w/ Rear AC - 41.50 Oz. R-134a; 8.50 Oz. PAG-46	59007
	500SEL; w/ Rear AC - 41.50 Oz. R-134a; 8.50 Oz. PAG-46	59007
	500SL - w/ R-134a	59007
92	500E; w/o Rear AC - 39.00 Oz. R-12; 7.75 Oz. Mineral Oil	59000 ⁵⁹
	500SEL; w/o Rear AC - 39.00 Oz. R-134a; 8.50 Oz. PAG-46	59007
	500SEL; w/ Rear AC - 41.50 Oz. R-134a; 8.50 Oz. PAG-46	59007
	500E; w/ Rear AC - 44.00 Oz. R-12; 7.75 Oz. Mineral Oil	59000 ⁵⁹
	500SL - w/ R-12	59000 ⁵⁹
	8 Cyl. 5.0 Eng. - See Under Hood Decal	59007
91-84	8 Cyl. 5.0 Eng. - See Under Hood Decal	59000 ⁵⁹
560 SERIES		
91-90	560SEC - 46.00 Oz. R-12; 7.75 Oz. Mineral Oil	59000 ⁵⁹
	560SEL - 46.00 Oz. R-12; 7.75 Oz. Mineral Oil	59000 ⁵⁹
89	560SEC - 46.00 Oz. R-12; 7.75 Oz. Mineral Oil	59000 ⁵⁹
	560SEL - 46.00 Oz. R-12; 7.75 Oz. Mineral Oil	59000 ⁵⁹
	560SL - See Under Hood Decal	59000 ⁵⁹
88-86	8 Cyl. 5.6 Eng. - See Under Hood Decal	59000 ⁵⁹
600 SERIES		
93	600SL; w/o Rear AC - 33.50 Oz. R-134a; 5.00 Oz. PAG-46	59007
	600SEC; w/o Rear AC - 39.00 Oz. R-134a; 8.50 Oz. PAG-46	59007
	600SEL; w/o Rear AC - 39.00 Oz. R-134a; 8.50 Oz. PAG-46	59007
	600SEC; w/ Rear AC - 41.50 Oz. R-134a; 8.50 Oz. PAG-46	59007
	600SEL; w/ Rear AC - 41.50 Oz. R-134a; 8.50 Oz. PAG-46	59007
92	600SEL; w/o Rear AC - 39.00 Oz. R-134a; 8.50 Oz. PAG-46	59007
	600SEL; w/ Rear AC - 41.50 Oz. R-134a; 8.50 Oz. PAG-46	59007
B200		
09	8 Cyl. 5.5 Eng. - See Under Hood Decal	59007
C CLASS		
13	4 Cyl. 1.8 Eng. - 21.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
	6 Cyl. 3.5 Eng. - 21.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
	8 Cyl. 6.3 Eng. - 21.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
12	4 Cyl. 1.8 Eng. - 21.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
	6 Cyl. 3.0 Eng. - 21.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
	6 Cyl. 3.5 Eng. - 21.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
	8 Cyl. 6.3 Eng. - 21.00 Oz. R-134a; 4.06 Oz. PAG-46	59007

Continued on Next Page

⁵⁹ When retrofitting to R134a PAG Oil must be used.

MERCEDES-BENZ

Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that A/C system has been properly cleaned, and new accumulator / filter drier has been installed. Specs are for total system capacities. Always refer to under hood decal as the primary source for refrigerant and lubricant information.

Year	Model	Lubricant
C CLASS (Cont'd)		
11	6 Cyl. 3.0 Eng. - 21.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
	6 Cyl. 3.5 Eng. - 21.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
10	8 Cyl. 6.3 Eng. - 34.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
	6 Cyl. 3.0 Eng. - 21.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
	6 Cyl. 3.5 Eng. - 21.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
09	8 Cyl. 6.3 Eng. - 38.00 Oz. R-134a; 3.72 Oz. PAG-46	59007
	6 Cyl. 3.0 Eng. - 21.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
	6 Cyl. 3.5 Eng. - 21.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
08	8 Cyl. 6.3 Eng. - 33.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
	6 Cyl. 3.0 Eng. - 21.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
	6 Cyl. 3.5 Eng. - 21.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
07	8 Cyl. 6.3 Eng. - 27.00 Oz. R-134a; See Under Hood Decal PAG-46	59007
	6 Cyl. 2.5 Eng. - 30.00 Oz. R-134a; 5.20 Oz. PAG-46	59007
	6 Cyl. 3.0 Eng. - 30.00 Oz. R-134a; 5.20 Oz. PAG-46	59007
	6 Cyl. 3.5 Eng. - 30.00 Oz. R-134a; 5.20 Oz. PAG-46	59007
06	6 Cyl. 2.5 Eng. - 30.00 Oz. R-134a; 5.20 Oz. PAG-46	59007
	6 Cyl. 3.0 Eng. - 30.00 Oz. R-134a; 5.20 Oz. PAG-46	59007
	6 Cyl. 3.5 Eng. - 30.00 Oz. R-134a; 5.20 Oz. PAG-46	59007
	8 Cyl. 5.5 Eng. - 33.00 Oz. R-134a; See Under Hood Decal PAG-46	59007
05	4 Cyl. 1.8 Eng. - 30.00 Oz. R-134a; 5.20 Oz. PAG-46	59007
	6 Cyl. 2.6 Eng. - 30.00 Oz. R-134a; 5.20 Oz. PAG-46	59007
	6 Cyl. 3.2 Eng. - 30.00 Oz. R-134a; 5.20 Oz. PAG-46	59007
	8 Cyl. 5.5 Eng. - 30.00 Oz. R-134a; 5.20 Oz. PAG-46	59007
04	4 Cyl. 1.8 Eng. - 30.00 Oz. R-134a; 5.20 Oz. PAG-46	59007
	6 Cyl. 2.6 Eng. - 30.00 Oz. R-134a; 5.20 Oz. PAG-46	59007
	6 Cyl. 3.2 Eng. - 30.00 Oz. R-134a; 5.20 Oz. PAG-46	59007
03-01	All Eng. - 26.50 Oz. R-134a; 4.00 Oz. PAG-46	59007
00-94	All Eng. - 29.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
CL CLASS		
13	12 Cyl. 5.5 Eng. - 38.00 Oz. R-134a; 3.72 Oz. PAG-46	59007
	12 Cyl. 6.0 Eng. - 38.00 Oz. R-134a; 3.72 Oz. PAG-46	59007
	8 Cyl. 4.6 Eng. - 21.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
	8 Cyl. 4.7 Eng. - See Under Hood Decal	59007
12	8 Cyl. 5.5 Eng. - 21.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
	12 Cyl. 5.5 Eng. - 38.00 Oz. R-134a; 3.72 Oz. PAG-46	59007
	12 Cyl. 6.0 Eng. - 38.00 Oz. R-134a; 3.72 Oz. PAG-46	59007
	8 Cyl. 4.6 Eng. - 38.00 Oz. R-134a; 3.72 Oz. PAG-46	59007
11	8 Cyl. 4.7 Eng. - See Under Hood Decal	59007
	8 Cyl. 5.5 Eng. - 38.00 Oz. R-134a; 3.72 Oz. PAG-46	59007
	12 Cyl. 5.5 Eng. - 38.00 Oz. R-134a; 3.72 Oz. PAG-46	59007
	12 Cyl. 6.0 Eng. - 38.00 Oz. R-134a; 3.72 Oz. PAG-46	59007
10	8 Cyl. 4.6 Eng. - 38.00 Oz. R-134a; 3.72 Oz. PAG-46	59007
	8 Cyl. 5.5 Eng. - 34.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
	8 Cyl. 6.2 Eng. - See Under Hood Decal	59007
	12 Cyl. 5.5 Eng. - 38.00 Oz. R-134a; 3.72 Oz. PAG-46	59007
09-08	12 Cyl. 6.0 Eng. - 33.00 Oz. R-134a; 3.72 Oz. PAG-46	59007
	8 Cyl. 5.5 Eng. - 33.00 Oz. R-134a; 3.72 Oz. PAG-46	59007
	8 Cyl. 6.2 Eng. - See Under Hood Decal	59007
	8 Cyl. 6.3 Eng. - 34.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
07	12 Cyl. 5.5 Eng. - 27.00 Oz. R-134a; See Under Hood Decal PAG-46	59007
	12 Cyl. 6.0 Eng. - 38.00 Oz. R-134a; 3.72 Oz. PAG-46	59007
	8 Cyl. 5.5 Eng. - 27.00 Oz. R-134a; See Under Hood Decal PAG-46	59007
06	8 Cyl. 6.3 Eng. - 33.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
	12 Cyl. 5.5 Eng. - 38.00 Oz. R-134a; 3.72 Oz. PAG-46	59007
	8 Cyl. 5.5 Eng. - 33.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
05-01	12 Cyl. 5.5 Eng. - 26.00 Oz. R-134a; See Under Hood Decal PAG-46	59007
	12 Cyl. 6.0 Eng. - 33.00 Oz. R-134a; See Under Hood Decal PAG-46	59007
	8 Cyl. 5.0 Eng. - 33.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
	8 Cyl. 5.5 Eng. - 26.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
00-98	All Eng.; w/ Rear AC - 33.50 Oz. R-134a; 4.00 Oz. PAG-46	59007
	All Eng.; w/o Rear AC - 39.00 Oz. R-134a; 6.00 Oz. PAG-46	59007
	All Eng.; w/ Rear AC - 41.50 Oz. R-134a; 7.00 Oz. PAG-46	59007

Continued on Next Page

Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that A/C system has been properly cleaned, and new accumulator / filter drier has been installed. Specs are for total system capacities. Always refer to under hood decal as the primary source for refrigerant and lubricant information.

Year	Model	Lubricant
CLK CLASS		
09-08	6 Cyl. 3.5 Eng. - 27.00 Oz. R-134a; See Under Hood Decal PAG-46	59007
	8 Cyl. 5.5 Eng. - 33.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
07	8 Cyl. 6.3 Eng. - 33.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
	6 Cyl. 3.5 Eng. - 26.00 Oz. R-134a; See Under Hood Decal PAG-46	59007
	8 Cyl. 5.5 Eng. - 33.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
06	8 Cyl. 6.3 Eng. - 33.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
	6 Cyl. 3.5 Eng. - 26.00 Oz. R-134a; See Under Hood Decal PAG-46	59007
	8 Cyl. 5.0 Eng. - 33.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
05	8 Cyl. 5.5 Eng. - 26.00 Oz. R-134a; See Under Hood Decal PAG-46	59007
	6 Cyl. 3.2 Eng. - 26.00 Oz. R-134a; See Under Hood Decal PAG-46	59007
	8 Cyl. 5.0 Eng. - 26.00 Oz. R-134a; See Under Hood Decal PAG-46	59007
04-01	8 Cyl. 5.5 Eng. - 26.00 Oz. R-134a; See Under Hood Decal PAG-46	59007
00-98	All Eng. - 30.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
	All Eng. - 30.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
CLS CLASS		
13	8 Cyl. 4.6 Eng. - See Under Hood Decal	59007
	8 Cyl. 4.7 Eng. - 21.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
12	8 Cyl. 5.5 Eng. - 21.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
	8 Cyl. 4.6 Eng. - 34.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
11-10	8 Cyl. 4.7 Eng. - See Under Hood Decal	59007
	8 Cyl. 5.5 Eng. - 21.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
	8 Cyl. 5.5 Eng. - 34.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
09-07	8 Cyl. 6.2 Eng. - See Under Hood Decal	59007
	8 Cyl. 6.3 Eng. - 34.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
06	8 Cyl. 5.5 Eng. - 33.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
	8 Cyl. 6.3 Eng. - 33.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
06	8 Cyl. 5.0 Eng. - 33.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
	8 Cyl. 5.5 Eng. - 33.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
E CLASS		
13	6 Cyl. 3.0 Eng. - 21.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
	6 Cyl. 3.5 Eng. - 21.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
	8 Cyl. 4.6 Eng. - 21.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
	8 Cyl. 4.7 Eng. - See Under Hood Decal	59007
12	8 Cyl. 5.5 Eng. - 21.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
	6 Cyl. 3.0 Eng. - 21.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
	6 Cyl. 3.5 Eng. - 21.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
	8 Cyl. 4.6 Eng. - 21.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
11	8 Cyl. 5.5 Eng. - 21.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
	6 Cyl. 3.0 Eng. - See Under Hood Decal	59007
	6 Cyl. 3.5 Eng. - 19.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
	8 Cyl. 5.5 Eng. - 19.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
10	8 Cyl. 6.2 Eng. - See Under Hood Decal	59007
	8 Cyl. 6.3 Eng. - 33.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
	6 Cyl. 3.0 Eng. - 33.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
	6 Cyl. 3.5 Eng. - 19.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
09	8 Cyl. 5.5 Eng. - 21.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
	8 Cyl. 6.2 Eng. - 33.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
	8 Cyl. 6.3 Eng. - 21.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
	6 Cyl. 3.0 Eng. - 21.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
08	6 Cyl. 3.5 Eng. - 21.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
	6 Cyl. 3.5 Eng. - 21.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
	8 Cyl. 5.5 Eng. - 21.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
	8 Cyl. 6.3 Eng. - 21.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
07	6 Cyl. 3.0 Eng. - 21.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
	6 Cyl. 3.5 Eng. - 21.00 Oz. R-134a; See Under Hood Decal PAG-46	59007
06	8 Cyl. 5.5 Eng. - 21.00 Oz. R-134a; See Under Hood Decal PAG-46	59007
	6 Cyl. 3.2 Eng. - 21.00 Oz. R-134a; See Under Hood Decal PAG-46	59007
	6 Cyl. 3.5 Eng. - 21.00 Oz. R-134a; See Under Hood Decal PAG-46	59007
05-01	8 Cyl. 5.0 Eng. - 34.00 Oz. R-134a; See Under Hood Decal PAG-46	59007
	8 Cyl. 5.5 Eng. - 21.00 Oz. R-134a; See Under Hood Decal PAG-46	59007
05-01	All Eng. - 35.00 Oz. R-134a; 7.00 Oz. PAG-46	59007

Continued on Next Page

MERCEDES-BENZ

Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that A/C system has been properly cleaned, and new accumulator / filter drier has been installed. Specs are for total system capacities. Always refer to under hood decal as the primary source for refrigerant and lubricant information.

Year	Model	Lubricant
E CLASS (Cont'd)		
00-96	All Eng. - 33.50 Oz. R-134a; 8.50 Oz. PAG-46	59007
95-94	All Eng. - 33.50 Oz. R-134a; 8.00 Oz. PAG-46	59007
G CLASS		
13	8 Cyl. 5.5 Eng. From 1/1/13 - 31.00 Oz. R-134a; 6.08 Oz. PAG-46	59007
	8 Cyl. 5.5 Eng. To 12/31/13 - 35.00 Oz. R-134a; 6.08 Oz. PAG-46	59007
12	8 Cyl. 5.5 Eng. - 35.00 Oz. R-134a; 5.75 Oz. PAG-46	59007
11	8 Cyl. 5.5 Eng. - 37.00 Oz. R-134a; 5.75 Oz. PAG-46	59007
10	8 Cyl. 5.5 Eng. - 35.00 Oz. R-134a; 5.75 Oz. PAG-46	59007
09	8 Cyl. 5.5 Eng. - 37.00 Oz. R-134a; 5.75 Oz. PAG-46	59007
08	8 Cyl. 5.0 Eng. - 37.00 Oz. R-134a; 5.75 Oz. PAG-46	59007
	8 Cyl. 5.5 Eng. - 37.00 Oz. R-134a; 5.75 Oz. PAG-46	59007
07	8 Cyl. 5.0 Eng. - 37.00 Oz. R-134a; See Under Hood Decal PAG-46	59007
	8 Cyl. 5.5 Eng. - 37.00 Oz. R-134a; See Under Hood Decal PAG-46	59007
06-03	8 Cyl. 5.0 Eng. - 37.00 Oz. R-134a; 4.05 Oz. PAG-46	59007
	8 Cyl. 5.5 Eng. - 37.00 Oz. R-134a; 4.05 Oz. PAG-46	59007
02	8 Cyl. 5.0 Eng. - 37.00 Oz. R-134a; 4.05 Oz. PAG-46	59007
GL CLASS		
13	8 Cyl. 3.0 Eng.; w/ Rear AC - 46.00 Oz. R-134a; 5.40 Oz. PAG-46	59007
	8 Cyl. 4.6 Eng.; w/ Rear AC - 46.00 Oz. R-134a; 5.40 Oz. PAG-46	59007
	8 Cyl. 5.5 Eng.; w/o Rear AC - 37.00 Oz. R-134a; 4.05 Oz. PAG-46	59007
12-08	6 Cyl. 3.0 Eng.; w/o Rear AC - 34.00 Oz. R-134a; 3.72 Oz. PAG-46	59007
	8 Cyl. 3.0 Eng.; w/ Rear AC - 43.00 Oz. R-134a; 3.72 Oz. PAG-46	59007
	8 Cyl. 4.6 Eng.; w/o Rear AC - 34.00 Oz. R-134a; 3.72 Oz. PAG-46	59007
	8 Cyl. 4.6 Eng.; w/ Rear AC - 43.00 Oz. R-134a; 3.72 Oz. PAG-46	59007
	8 Cyl. 5.5 Eng.; w/o Rear AC - 34.00 Oz. R-134a; 3.72 Oz. PAG-46	59007
	8 Cyl. 5.5 Eng.; w/ Rear AC - 43.00 Oz. R-134a; 3.72 Oz. PAG-46	59007
07	6 Cyl. 3.0 Eng. - 43.00 Oz. R-134a; See Under Hood Decal PAG-46	59007
	8 Cyl. 4.6 Eng. - 43.00 Oz. R-134a; See Under Hood Decal PAG-46	59007
GLK CLASS		
13-10	6 Cyl. 3.5 Eng. - 21.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
ML CLASS		
13-12	6 Cyl. 3.0 Eng.; w/o Rear AC - 37.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
	6 Cyl. 3.5 Eng.; w/o Rear AC - 37.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
	8 Cyl. 3.0 Eng.; w/ Rear AC - 46.00 Oz. R-134a; 5.40 Oz. PAG-46	59007
	8 Cyl. 3.5 Eng.; w/ Rear AC - 46.00 Oz. R-134a; 5.40 Oz. PAG-46	59007
	8 Cyl. 4.6 Eng.; w/o Rear AC - 37.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
	8 Cyl. 4.6 Eng.; w/ Rear AC - 46.00 Oz. R-134a; 5.40 Oz. PAG-46	59007
	8 Cyl. 5.5 Eng.; w/o Rear AC - 37.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
	8 Cyl. 5.5 Eng.; w/ Rear AC - 46.00 Oz. R-134a; 5.40 Oz. PAG-46	59007
11	6 Cyl. 3.0 Eng.; w/o Rear AC - 34.00 Oz. R-134a; 3.72 Oz. PAG-46	59007
	6 Cyl. 3.5 Eng.; w/o Rear AC - 34.00 Oz. R-134a; 3.72 Oz. PAG-46	59007
	8 Cyl. 3.5 Eng.; w/ Rear AC - 43.00 Oz. R-134a; 3.72 Oz. PAG-46	59007
	8 Cyl. 5.5 Eng.; w/o Rear AC - 34.00 Oz. R-134a; 3.72 Oz. PAG-46	59007
	8 Cyl. 5.5 Eng.; w/ Rear AC - 43.00 Oz. R-134a; 3.72 Oz. PAG-46	59007
	8 Cyl. 6.2 Eng. - See Under Hood Decal	59007
	8 Cyl. 6.3 Eng.; w/o Rear AC - 34.00 Oz. R-134a; 3.72 Oz. PAG-46	59007
	8 Cyl. 6.3 Eng.; w/ Rear AC - 43.00 Oz. R-134a; 3.72 Oz. PAG-46	59007
10-08	6 Cyl. 3.0 Eng.; w/o Rear AC - 34.00 Oz. R-134a; 3.72 Oz. PAG-46	59007
	6 Cyl. 3.5 Eng.; w/o Rear AC - 34.00 Oz. R-134a; 3.72 Oz. PAG-46	59007
	8 Cyl. 3.0 Eng.; w/ Rear AC - 43.00 Oz. R-134a; 3.72 Oz. PAG-46	59007
	8 Cyl. 3.5 Eng.; w/ Rear AC - 43.00 Oz. R-134a; 3.72 Oz. PAG-46	59007
	8 Cyl. 5.5 Eng.; w/o Rear AC - 34.00 Oz. R-134a; 3.72 Oz. PAG-46	59007
	8 Cyl. 5.5 Eng.; w/ Rear AC - 43.00 Oz. R-134a; 3.72 Oz. PAG-46	59007
	8 Cyl. 6.3 Eng.; w/o Rear AC - 34.00 Oz. R-134a; 3.72 Oz. PAG-46	59007
	8 Cyl. 6.3 Eng.; w/ Rear AC - 43.00 Oz. R-134a; 3.72 Oz. PAG-46	59007
07	6 Cyl. 3.0 Eng. - 21.00 Oz. R-134a; See Under Hood Decal PAG-46	59007
	6 Cyl. 3.5 Eng. - 21.00 Oz. R-134a; See Under Hood Decal PAG-46	59007
	8 Cyl. 5.0 Eng. - 21.00 Oz. R-134a; See Under Hood Decal PAG-46	59007
	8 Cyl. 6.3 Eng. - 21.00 Oz. R-134a; See Under Hood Decal PAG-46	59007
06	6 Cyl. 3.5 Eng. - 21.00 Oz. R-134a; See Under Hood Decal PAG-46	59007
	8 Cyl. 5.0 Eng. - 21.00 Oz. R-134a; See Under Hood Decal PAG-46	59007
05-01	All Eng. - 26.50 Oz. R-134a; 6.00 Oz. PAG-46	59007
00-98	All Eng. - 27.00 Oz. R-134a; 8.00 Oz. PAG-46	59007

Continued on Next Page

Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that A/C system has been properly cleaned, and new accumulator / filter drier has been installed. Specs are for total system capacities. Always refer to under hood decal as the primary source for refrigerant and lubricant information.

Year	Model	Lubricant	
R CLASS			
12	6 Cyl. 3.0 Eng.; w/o Rear AC - 34.00 Oz. R-134a; 3.72 Oz. PAG-46	59007	
	6 Cyl. 3.5 Eng.; w/o Rear AC - 34.00 Oz. R-134a; 3.72 Oz. PAG-46	59007	
11-08	6 Cyl. 3.5 Eng.; w/ Rear AC - 43.00 Oz. R-134a; 3.72 Oz. PAG-46	59007	
	6 Cyl. 3.5 Eng.; w/ Rear AC - 43.00 Oz. R-134a; 3.72 Oz. PAG-46	59007	
	6 Cyl. 3.0 Eng.; w/o Rear AC - 34.00 Oz. R-134a; 3.72 Oz. PAG-46	59007	
	6 Cyl. 3.0 Eng.; w/ Rear AC - 43.00 Oz. R-134a; 3.72 Oz. PAG-46	59007	
07	6 Cyl. 3.5 Eng.; w/o Rear AC - 34.00 Oz. R-134a; 3.72 Oz. PAG-46	59007	
	6 Cyl. 3.5 Eng.; w/ Rear AC - 43.00 Oz. R-134a; 3.72 Oz. PAG-46	59007	
	6 Cyl. 3.0 Eng. - 34.00 Oz. R-134a; 5.91 Oz. PAG-46	59007	
	6 Cyl. 3.5 Eng. - 34.00 Oz. R-134a; 5.91 Oz. PAG-46	59007	
06	8 Cyl. 5.0 Eng. - 34.00 Oz. R-134a; 5.91 Oz. PAG-46	59007	
	8 Cyl. 6.3 Eng. - 43.00 Oz. R-134a; See Under Hood Decal PAG-46	59007	
	8 Cyl. 3.5 Eng. - 34.00 Oz. R-134a; 5.91 Oz. PAG-46	59007	
S CLASS			
13	12 Cyl. 5.5 Eng.; w/o Rear AC - 42.00 Oz. R-134a; 3.72 Oz. PAG-46	59007	
	12 Cyl. 5.5 Eng.; w/ Rear AC - w/ Armored Body	59007	
	12 Cyl. 6.0 Eng.; w/o Rear AC - 38.00 Oz. R-134a; 3.72 Oz. PAG-46	59007	
	12 Cyl. 6.0 Eng.; w/ Rear AC - 42.00 Oz. R-134a; 3.72 Oz. PAG-46	59007	
	6 Cyl. 3.0 Eng.; w/o Rear AC - 38.00 Oz. R-134a; 3.72 Oz. PAG-46	59007	
	6 Cyl. 3.5 Eng.; w/o Rear AC - 38.00 Oz. R-134a; 3.72 Oz. PAG-46	59007	
	8 Cyl. 3.0 Eng.; w/ Rear AC - 42.00 Oz. R-134a; 3.72 Oz. PAG-46	59007	
	8 Cyl. 3.5 Eng.; w/ Rear AC - 42.00 Oz. R-134a; 3.72 Oz. PAG-46	59007	
	8 Cyl. 3.5 Eng.; w/ Rear AC - w/ Armored Body	59007	
	8 Cyl. 4.6 Eng.; w/o Rear AC - 38.00 Oz. R-134a; 3.72 Oz. PAG-46	59007	
	8 Cyl. 4.6 Eng.; w/ Rear AC - 42.00 Oz. R-134a; 3.72 Oz. PAG-46	59007	
	8 Cyl. 4.6 Eng.; w/ Rear AC - w/ Armored Body	59007	
	8 Cyl. 5.5 Eng.; w/o Rear AC - 38.00 Oz. R-134a; 3.72 Oz. PAG-46	59007	
	8 Cyl. 5.5 Eng.; w/ 7SEU17C - 42.00 Oz. R-134a; 3.72 Oz. PAG-46	59007	
	8 Cyl. 5.5 Eng.; w/ Rear AC - w/ Armored Body	59007	
	12	12 Cyl. 5.5 Eng.; w/o Rear AC - 38.00 Oz. R-134a; 3.72 Oz. PAG-46	59007
12 Cyl. 5.5 Eng.; w/o Rear AC - 42.00 Oz. R-134a; 3.72 Oz. PAG-46		59007	
12 Cyl. 6.0 Eng.; w/o Rear AC - 38.00 Oz. R-134a; 3.72 Oz. PAG-46		59007	
12 Cyl. 6.0 Eng.; w/ Rear AC - 42.00 Oz. R-134a; 3.72 Oz. PAG-46		59007	
6 Cyl. 3.5 Eng.; w/o Rear AC - 38.00 Oz. R-134a; 3.72 Oz. PAG-46		59007	
8 Cyl. 3.5 Eng.; w/ Rear AC - 42.00 Oz. R-134a; 3.72 Oz. PAG-46		59007	
8 Cyl. 3.5 Eng.; w/ Rear AC - w/ Armored Body		59007	
8 Cyl. 4.6 Eng.; w/o Rear AC - 38.00 Oz. R-134a; 3.72 Oz. PAG-46		59007	
8 Cyl. 4.6 Eng.; w/ Rear AC - 42.00 Oz. R-134a; 3.72 Oz. PAG-46		59007	
8 Cyl. 4.6 Eng.; w/ Rear AC - w/ Armored Body		59007	
8 Cyl. 5.5 Eng.; w/ 7SEU16C - 33.00 Oz. R-134a; 4.06 Oz. PAG-46		59007	
8 Cyl. 5.5 Eng.; w/ 7SEU17C - 33.00 Oz. R-134a; 4.74 Oz. PAG-46		59007	
11		12 Cyl. 5.5 Eng.; w/o Rear AC - 38.00 Oz. R-134a; 3.72 Oz. PAG-46	59007
		12 Cyl. 5.5 Eng.; w/ Rear AC - 42.00 Oz. R-134a; 3.72 Oz. PAG-46	59007
		12 Cyl. 5.5 Eng.; w/ Rear AC - w/ Armored Body	59007
		12 Cyl. 6.0 Eng.; w/o Rear AC - 38.00 Oz. R-134a; 3.72 Oz. PAG-46	59007
	12 Cyl. 6.0 Eng.; w/ Rear AC - 42.00 Oz. R-134a; 3.72 Oz. PAG-46	59007	
	6 Cyl. 3.5 Eng.; w/o Rear AC - 38.00 Oz. R-134a; 3.72 Oz. PAG-46	59007	
	6 Cyl. 3.5 Eng.; w/ Rear AC - 42.00 Oz. R-134a; 3.72 Oz. PAG-46	59007	
	6 Cyl. 3.5 Eng.; w/ Rear AC - w/ Armored Body	59007	
	8 Cyl. 5.5 Eng.; w/o Rear AC - 38.00 Oz. R-134a; 3.72 Oz. PAG-46	59007	
	8 Cyl. 5.5 Eng.; w/ Rear AC - 42.00 Oz. R-134a; 3.72 Oz. PAG-46	59007	
10	12 Cyl. 5.5 Eng.; w/ Rear AC - 42.00 Oz. R-134a; 3.72 Oz. PAG-46	59007	
	12 Cyl. 6.0 Eng.; w/o Rear AC - 38.00 Oz. R-134a; 3.72 Oz. PAG-46	59007	
	12 Cyl. 6.0 Eng.; w/ Rear AC - 42.00 Oz. R-134a; 3.72 Oz. PAG-46	59007	
	6 Cyl. 3.5 Eng.; w/o Rear AC - 38.00 Oz. R-134a; 3.72 Oz. PAG-46	59007	
	6 Cyl. 3.5 Eng.; w/ Rear AC - 42.00 Oz. R-134a; 3.72 Oz. PAG-46	59007	
	6 Cyl. 3.5 Eng.; w/ Rear AC - w/ Armored Body	59007	
	8 Cyl. 5.5 Eng.; w/o Rear AC - 38.00 Oz. R-134a; 3.72 Oz. PAG-46	59007	
	8 Cyl. 6.3 Eng.; w/o Rear AC - 38.00 Oz. R-134a; 3.72 Oz. PAG-46	59007	
	8 Cyl. 6.3 Eng.; w/ Rear AC - 42.00 Oz. R-134a; 3.72 Oz. PAG-46	59007	
	8 Cyl. 6.3 Eng.; w/ Rear AC - w/ Armored Body	59007	

Continued on Next Page

MERCEDES-BENZ

Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that A/C system has been properly cleaned, and new accumulator / filter drier has been installed. Specs are for total system capacities. Always refer to under hood decal as the primary source for refrigerant and lubricant information.

Year	Model	Lubricant
S CLASS (Cont'd)		
09	12 Cyl. 5.5 Eng.; w/o Rear AC - 38.00 Oz. R-134a; 3.72 Oz. PAG-46	59007
	12 Cyl. 5.5 Eng.; w/ Rear AC - 42.00 Oz. R-134a; 3.72 Oz. PAG-46	59007
	12 Cyl. 6.0 Eng.; w/o Rear AC - 38.00 Oz. R-134a; 3.72 Oz. PAG-46	59007
	12 Cyl. 6.0 Eng.; w/ Rear AC - 42.00 Oz. R-134a; 3.72 Oz. PAG-46	59007
	8 Cyl. 5.5 Eng.; w/o Rear AC - 38.00 Oz. R-134a; 3.72 Oz. PAG-46	59007
	8 Cyl. 5.5 Eng.; w/ Rear AC - 42.00 Oz. R-134a; 3.72 Oz. PAG-46	59007
	8 Cyl. 6.3 Eng.; w/o Rear AC - 38.00 Oz. R-134a; 3.72 Oz. PAG-46	59007
	8 Cyl. 6.3 Eng.; w/ Rear AC - 42.00 Oz. R-134a; 3.72 Oz. PAG-46	59007
08	12 Cyl. 5.5 Eng.; w/o Rear AC - 38.00 Oz. R-134a; 3.72 Oz. PAG-46	59007
	12 Cyl. 6.0 Eng.; w/o Rear AC - 38.00 Oz. R-134a; 3.72 Oz. PAG-46	59007
	8 Cyl. 4.6 Eng.; w/o Rear AC - 38.00 Oz. R-134a; 3.72 Oz. PAG-46	59007
	8 Cyl. 5.5 Eng.; w/o Rear AC - 38.00 Oz. R-134a; 3.72 Oz. PAG-46	59007
	8 Cyl. 5.5 Eng.; w/ Rear AC - 42.00 Oz. R-134a; 3.72 Oz. PAG-46	59007
	8 Cyl. 5.5 Eng.; w/ Rear AC - 42.00 Oz. R-134a; 3.72 Oz. PAG-46	59007
	8 Cyl. 6.0 Eng.; w/ Rear AC - 42.00 Oz. R-134a; 3.72 Oz. PAG-46	59007
	8 Cyl. 6.3 Eng.; w/o Rear AC - 38.00 Oz. R-134a; 3.72 Oz. PAG-46	59007
07	8 Cyl. 6.3 Eng.; w/ Rear AC - 42.00 Oz. R-134a; 3.72 Oz. PAG-46	59007
	12 Cyl. 5.5 Eng. - 41.00 Oz. R-134a; 3.72-5.41 Oz. PAG-46	59007
06	12 Cyl. 6.0 Eng. - 41.00 Oz. R-134a; 3.72-5.41 Oz. PAG-46	59007
	8 Cyl. 5.5 Eng. - 24.00 Oz. R-134a; 4.05 Oz. PAG-46	59007
	12 Cyl. 5.5 Eng. - 37.00 Oz. R-134a; 5.41 Oz. PAG-46	59007
	12 Cyl. 6.0 Eng. - 37.00 Oz. R-134a; 3.72-5.41 Oz. PAG-46	59007
	6 Cyl. 3.7 Eng. - 37.00 Oz. R-134a; 5.41 Oz. PAG-46	59007
05	8 Cyl. 4.3 Eng. - 37.00 Oz. R-134a; 5.41 Oz. PAG-46	59007
	8 Cyl. 5.0 Eng. - 32.00 Oz. R-134a; 4.73 Oz. PAG-46	59007
	8 Cyl. 5.5 Eng. - 24.00 Oz. R-134a; 4.05 Oz. PAG-46	59007
	All Eng.; w/o Rear AC - 33.50 Oz. R-134a; 6.00 Oz. PAG-46	59007
04-01	All Eng.; w/o Rear AC - 37.00 Oz. R-134a; 6.00 Oz. PAG-46	59007
	All Eng.; w/ Rear AC - 33.50 Oz. R-134a; 6.00 Oz. PAG-46	59007
00-94	All Eng.; w/ Rear AC - 37.00 Oz. R-134a; 6.00 Oz. PAG-46	59007
	All Eng.; w/o Rear AC - 39.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
SL CLASS		
13	All Eng.; w/ Rear AC - 41.50 Oz. R-134a; 8.50 Oz. PAG-46	59007
	12 Cyl. 6.0 Eng. - 38.00 Oz. R-134a; 3.72 Oz. PAG-46	59007
	12 Cyl. 6.0 Eng.; w/ Rear AC - 42.00 Oz. R-134a; 3.72 Oz. PAG-46	59007
	12 Cyl. 6.0 Eng.; w/ Rear AC - w/ Armored Body	59007
12	8 Cyl. 4.6 Eng. - 19.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
	8 Cyl. 5.5 Eng. - 19.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
	8 Cyl. 5.5 Eng. - 33.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
	8 Cyl. 5.5 Eng.; w/ 7SEU17C - 33.00 Oz. R-134a; 4.74 Oz. PAG-46	59007
11	8 Cyl. 6.3 Eng.; w/ 7SEU16C - 33.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
	8 Cyl. 6.3 Eng.; w/ 7SEU17C - 33.00 Oz. R-134a; 4.74 Oz. PAG-46	59007
	12 Cyl. 6.0 Eng.; w/ 7SEU16C - 33.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
	8 Cyl. 5.5 Eng.; w/ 7SEU16C - 33.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
09	8 Cyl. 5.5 Eng.; w/ 7SEU17C - 33.00 Oz. R-134a; 4.74 Oz. PAG-46	59007
	8 Cyl. 6.0 Eng.; w/ 7SEU17C - 33.00 Oz. R-134a; 4.74 Oz. PAG-46	59007
	8 Cyl. 6.3 Eng.; w/ 7SEU16C - 33.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
	8 Cyl. 6.3 Eng.; w/ 7SEU17C - 33.00 Oz. R-134a; 4.74 Oz. PAG-46	59007
08	12 Cyl. 5.5 Eng. - 33.00 Oz. R-134a; See Under Hood Decal PAG-46	59007
	8 Cyl. 5.5 Eng.; w/ 7SEU16C - 33.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
	8 Cyl. 5.5 Eng.; w/ 7SEU17C - 33.00 Oz. R-134a; 4.74 Oz. PAG-46	59007
	8 Cyl. 6.3 Eng.; w/ 7SEU16C - 33.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
07	12 Cyl. 5.5 Eng. - 33.00 Oz. R-134a; See Under Hood Decal PAG-46	59007
	12 Cyl. 6.0 Eng.; w/ 7SEU16C - 33.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
	12 Cyl. 6.0 Eng.; w/ 7SEU17C - 33.00 Oz. R-134a; 4.74 Oz. PAG-46	59007
	8 Cyl. 5.5 Eng. - 33.00 Oz. R-134a; 3.72 Oz. PAG-46	59007
06	8 Cyl. 6.3 Eng.; w/ 7SEU17C - 33.00 Oz. R-134a; 4.74 Oz. PAG-46	59007
	12 Cyl. 5.5 Eng. - 32.00 Oz. R-134a; 4.73 Oz. PAG-46	59007
06	12 Cyl. 6.0 Eng. - 32.00 Oz. R-134a; 4.73 Oz. PAG-46	59007
	8 Cyl. 5.0 Eng. - 32.00 Oz. R-134a; 4.73 Oz. PAG-46	59007

Continued on Next Page

Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that A/C system has been properly cleaned, and new accumulator / filter drier has been installed. Specs are for total system capacities. Always refer to under hood decal as the primary source for refrigerant and lubricant information.

Year	Model	Lubricant
SL CLASS (Cont'd)		
06	8 Cyl. 5.5 Eng. - 32.00 Oz. R-134a; 4.73 Oz. PAG-46	59007
05-01	All Eng. - 29.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
00-94	All Eng. - 32.00 Oz. R-134a; 8.50 Oz. PAG-46	59007
SLK CLASS		
13	4 Cyl. 1.8 Eng. - 19.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
	6 Cyl. 3.5 Eng. - 19.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
	6 Cyl. 3.5 Eng. - 24.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
	8 Cyl. 5.5 Eng. - 19.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
12	4 Cyl. 1.8 Eng. - 19.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
	6 Cyl. 3.5 Eng. - 19.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
	6 Cyl. 3.5 Eng. - 23.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
	8 Cyl. 5.5 Eng. - 19.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
11	6 Cyl. 3.0 Eng.; OE:w/o Date Code 809 - 19.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
	6 Cyl. 3.0 Eng.; Code 809 - 23.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
	6 Cyl. 3.5 Eng. - 19.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
	6 Cyl. 3.5 Eng. - 23.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
10	6 Cyl. 3.0 Eng.; OE:w/o Date Code 809 - 19.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
	6 Cyl. 3.0 Eng.; Code 809 - 23.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
	6 Cyl. 3.5 Eng. - 19.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
	6 Cyl. 3.5 Eng. - 23.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
	8 Cyl. 5.5 Eng. - 23.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
09-08	6 Cyl. 3.0 Eng.; OE:w/o Date Code 809 - 19.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
	6 Cyl. 3.0 Eng.; Code 809 - 23.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
	6 Cyl. 3.5 Eng.; OE:w/o Date Code 809 - 19.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
	6 Cyl. 3.5 Eng.; Code 809 - 23.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
	8 Cyl. 5.5 Eng. - 23.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
07	6 Cyl. 3.0 Eng. - 24.00 Oz. R-134a; 4.05 Oz. PAG-46	59007
	6 Cyl. 3.5 Eng. - 24.00 Oz. R-134a; 4.05 Oz. PAG-46	59007
	8 Cyl. 5.5 Eng. - 24.00 Oz. R-134a; 4.05 Oz. PAG-46	59007
06	6 Cyl. 3.0 Eng. - 24.00 Oz. R-134a; 4.05 Oz. PAG-46	59007
	6 Cyl. 3.5 Eng. - 24.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
	8 Cyl. 5.5 Eng. - 24.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
05	6 Cyl. 3.5 Eng. - 24.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
	8 Cyl. 5.5 Eng. - 24.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
04-01	All Eng. - 30.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
00-98	All Eng. - 29.00 Oz. R-134a; 8.50 Oz. PAG-46	59007
SLS CLASS		
13-12	8 Cyl. 6.3 Eng. - See Under Hood Decal	59007
SPRINTER		
13-10	6 Cyl. 3.0 Eng.; Code HH9 - 28.00 Oz. R-134a; 6.40 Oz. PAG-46	59007
	6 Cyl. 3.0 Eng.; Code H08 - 35.00 Oz. R-134a; 6.40 Oz. PAG-46	59007
	6 Cyl. 3.0 Eng.; w/ Option Code HH7 - 42.00 Oz. R-134a; 6.40 Oz. PAG-46	59007
	6 Cyl. 3.0 Eng.; w/ Option Code HK4 - 63.00 Oz. R-134a; 5.40 Oz. PAG-46	59007

MERCURY

Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that A/C system has been properly cleaned, and new accumulator / filter drier has been installed. Specs are for total system capacities. Always refer to under hood decal as the primary source for refrigerant and lubricant information.

Year	Model	Lubricant
CAPRI		
94	All Eng. - 25.00 Oz. R-134a; 10.00 Oz. PAG-46	59007
93-91	All Eng. - 25.00 Oz. R-12; 10.00 Oz. Ester	59000 ⁵⁹
86-83	6 Cyl. 3.8 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.0 Eng. - See Under Hood Decal	59000 ⁵⁹
82	8 Cyl. 5.0 Eng. - See Under Hood Decal	59000 ⁵⁹
COLONY PARK		
91-85	8 Cyl. 5.0 Eng. - See Under Hood Decal	59000 ⁵⁹
COMET		
77-71	8 Cyl. 5.0 Eng. - See Under Hood Decal	59000 ⁵⁹

Continued on Next Page

⁵⁹ When retrofitting to R134a PAG Oil must be used.

MERCURY

Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that A/C system has been properly cleaned, and new accumulator / filter drier has been installed. Specs are for total system capacities. Always refer to under hood decal as the primary source for refrigerant and lubricant information.

Year	Model	Lubricant
COUGAR		
02-00	All Eng. - 26.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
99	All Eng. - 26.00 Oz. R-134a; 6.75 Oz. PAG-46	59007
97-95	All Eng. - 36.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
94	All Eng. - 36.00 Oz. R-134a; 6.75 Oz. PAG-46	59007
93-89	All Eng. - 40.00 Oz. R-12; 7.00 Oz. Ester	59000 ⁵⁹
88-87	All Eng. - 40.00 Oz. R-12; 8.00 Oz. Ester	59000 ⁵⁹
86	All Eng. To 1/86 - 40.00 Oz. R-12; 10.00 Oz. Ester	59000 ⁵⁹
	All Eng. From 1/86 - 40.00 Oz. R-12; 8.00 Oz. Ester	59000 ⁵⁹
85-83	6 Cyl. 3.8 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.0 Eng. - See Under Hood Decal	59000 ⁵⁹
82	6 Cyl. 3.8 Eng. - See Under Hood Decal	59000 ⁵⁹
81	8 Cyl. 4.2 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.0 Eng. - See Under Hood Decal	59000 ⁵⁹
80	6 Cyl. 3.3 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 4.2 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.0 Eng. - See Under Hood Decal	59000 ⁵⁹
79	8 Cyl. 5.0 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.8 Eng. - See Under Hood Decal	59000 ⁵⁹
78-77	8 Cyl. 5.0 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.8 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 6.6 Eng. - See Under Hood Decal	59000 ⁵⁹
76-74	8 Cyl. 5.8 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 6.6 Eng. - See Under Hood Decal	59000 ⁵⁹
73	8 Cyl. 5.8 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 6.6 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 7.5 Eng. - See Under Hood Decal	59000 ⁵⁹
72-71	8 Cyl. 5.8 Eng. - See Under Hood Decal	59000 ⁵⁹
70	8 Cyl. 5.0 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.8 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 6.4 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 7.0 Eng. - See Under Hood Decal	59000 ⁵⁹
GRAND MARQUIS		
11-09	8 Cyl. 4.6 Eng. - 27.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
08-06	All Eng. - 27.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
05-97	All Eng. - 38.00 Oz. R-134a; 7.50 Oz. PAG-46	59007
96-95	All Eng. - 38.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
94	All Eng. - 34.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
93	All Eng. - 38.00 Oz. R-12; 7.00 Oz. Ester	59000 ⁵⁹
	8 Cyl. 4.6 Eng. - 36.00 Oz. R-12; 7.00 Oz. Ester	59007
92	All Eng. - 36.00 Oz. R-12; 7.00 Oz. Ester	59000 ⁵⁹
91-89	All Eng. - 48.00 Oz. R-12; 8.00 Oz. Ester	59000 ⁵⁹
88	All Eng. - 52.00 Oz. R-12; 13.00 Oz. Ester	59000 ⁵⁹
87	All Eng. To 9/86 - 52.00 Oz. R-12; 10.00 Oz. Ester	59000 ⁵⁹
	All Eng. From 9/86 - 52.00 Oz. R-12; 13.00 Oz. Ester	59000 ⁵⁹
86	All Eng. - 52.00 Oz. R-12; 10.00 Oz. Ester	59000 ⁵⁹
	8 Cyl. 5.8 Eng. - 52.00 Oz. R-12; 10.00 Oz. Ester	59000 ⁵⁹
85	All Eng. - 52.00 Oz. R-12; 10.00 Oz. Ester	59000 ⁵⁹
84-83	8 Cyl. 5.0 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.8 Eng. - See Under Hood Decal	59000 ⁵⁹
82	8 Cyl. 4.2 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.0 Eng. - See Under Hood Decal	59000 ⁵⁹
81	8 Cyl. 4.2 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.0 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.8 Eng. - See Under Hood Decal	59000 ⁵⁹
80-79	8 Cyl. 5.0 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.8 Eng. - See Under Hood Decal	59000 ⁵⁹
78	8 Cyl. 5.8 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 6.6 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 7.5 Eng. - See Under Hood Decal	59000 ⁵⁹
77-75	8 Cyl. 6.6 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 7.5 Eng. - See Under Hood Decal	59000 ⁵⁹

Continued on Next Page

⁵⁹ When retrofitting to R134a PAG Oil must be used.

Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that A/C system has been properly cleaned, and new accumulator / filter drier has been installed. Specs are for total system capacities. Always refer to under hood decal as the primary source for refrigerant and lubricant information.

Year	Model	Lubricant
	LN7	
83-82	4 Cyl. 1.6 Eng. - See Under Hood Decal	59000 ⁵⁹
	LYNX	
87-86	4 Cyl. 1.9 Eng. - See Under Hood Decal	59000 ⁵⁹
	4 Cyl. 2.0 Eng. - See Under Hood Decal	59000 ⁵⁹
85	4 Cyl. 1.6 Eng. - See Under Hood Decal	59000 ⁵⁹
	4 Cyl. 1.9 Eng. - See Under Hood Decal	59000 ⁵⁹
	4 Cyl. 2.0 Eng. - See Under Hood Decal	59000 ⁵⁹
84	4 Cyl. 1.6 Eng. - See Under Hood Decal	59000 ⁵⁹
	4 Cyl. 2.0 Eng. - See Under Hood Decal	59000 ⁵⁹
83-81	4 Cyl. 1.6 Eng. - See Under Hood Decal	59000 ⁵⁹
	MARAUDER	
04-03	All Eng. - 38.00 Oz. R-134a; 7.50 Oz. PAG-46	59007
	MARINER	
11	4 Cyl. 2.5 Eng.; Excl. Hybrid - 25.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
	4 Cyl. 2.5 Eng.; Hybrid - 32.00 Oz. R-134a; 4.40 Oz. Hybrid Oil	59889
	6 Cyl. 3.0 Eng. - 25.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
10	All Eng.; Excl. Hybrid - 25.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
	4 Cyl. 2.5 Eng.; Excl. Hybrid - 25.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
	4 Cyl. 2.5 Eng.; Hybrid - 32.00 Oz. R-134a; 4.40 Oz. Hybrid Oil	59889
09-08	All Eng.; Excl. Hybrid - 25.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
	All Eng.; Hybrid - 32.00 Oz. R-134a; 4.40 Oz. Hybrid Oil	59889
07-06	4 Cyl. 2.3 Eng.; Excl. Hybrid - 32.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
	6 Cyl. 3.0 Eng. - 32.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
05	4 Cyl. 2.3 Eng. - 32.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
	6 Cyl. 3.0 Eng. - 32.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
	MARQUIS	
85	8 Cyl. 5.0 Eng. - See Under Hood Decal	59000 ⁵⁹
84-83	6 Cyl. 3.8 Eng. - See Under Hood Decal	59000 ⁵⁹
82-81	8 Cyl. 4.2 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.0 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.8 Eng. - See Under Hood Decal	59000 ⁵⁹
80-79	8 Cyl. 5.0 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.8 Eng. - See Under Hood Decal	59000 ⁵⁹
78	8 Cyl. 5.8 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 6.6 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 7.5 Eng. - See Under Hood Decal	59000 ⁵⁹
77-75	8 Cyl. 6.6 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 7.5 Eng. - See Under Hood Decal	59000 ⁵⁹
	MILAN	
11-10	4 Cyl. 2.5 Eng.; Hybrid - 22.00 Oz. R-134a; 4.40 Oz. Hybrid Oil	59889
	6 Cyl. 3.0 Eng. - 21.00 Oz. R-134a; 6.00 Oz. PAG-46	59007
09	4 Cyl. 2.3 Eng. - 21.00 Oz. R-134a; 6.00 Oz. PAG-46	59007
	6 Cyl. 3.0 Eng. - 21.00 Oz. R-134a; 6.00 Oz. PAG-46	59007
08-06	All Eng. - 21.00 Oz. R-134a; 6.00 Oz. PAG-46	59007
	MONARCH	
80	6 Cyl. 4.1 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 4.2 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.0 Eng. - See Under Hood Decal	59000 ⁵⁹
79-78	6 Cyl. 4.1 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.0 Eng. - See Under Hood Decal	59000 ⁵⁹
75	8 Cyl. 5.0 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.8 Eng. - See Under Hood Decal	59000 ⁵⁹
	MONTEGO	
07-05	All Eng.; w/o Rear AC - 29.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
	All Eng.; w/ Rear AC - 38.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
76-75	8 Cyl. 5.8 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 6.6 Eng. - See Under Hood Decal	59000 ⁵⁹
74	8 Cyl. 5.0 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.8 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 6.6 Eng. - See Under Hood Decal	59000 ⁵⁹
73-71	8 Cyl. 5.0 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.8 Eng. - See Under Hood Decal	59000 ⁵⁹

Continued on Next Page

⁵⁹ When retrofitting to R134a PAG Oil must be used.

MERCURY

Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that A/C system has been properly cleaned, and new accumulator / filter drier has been installed. Specs are for total system capacities. Always refer to under hood decal as the primary source for refrigerant and lubricant information.

Year	Model	Lubricant
MONTEREY		
07-04	All Eng.; w/o Rear AC - 36.00 Oz. R-134a; 10.00 Oz. PAG-46	59007
	All Eng.; w/ Rear AC - 53.00 Oz. R-134a; 12.00 Oz. PAG-46	59007
MOUNTAINEER		
10	6 Cyl. 4.0 Eng.; w/o Rear AC - 31.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
	6 Cyl. 4.0 Eng.; w/ Rear AC - 47.00 Oz. R-134a; 16.00 Oz. PAG-46	59007
	8 Cyl. 4.6 Eng.; w/o Rear AC - 31.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
	8 Cyl. 4.6 Eng.; w/ Rear AC - 47.00 Oz. R-134a; 16.00 Oz. PAG-46	59007
09	6 Cyl. 4.0 Eng.; w/o Rear AC - 31.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
	6 Cyl. 4.0 Eng.; w/ Rear AC - 47.00 Oz. R-134a; 16.00 Oz. PAG-46	59007
	8 Cyl. 4.6 Eng.; w/o Rear AC - 27.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
	8 Cyl. 4.6 Eng.; w/ Rear AC - 44.00 Oz. R-134a; 16.00 Oz. PAG-46	59007
08-06	All Eng.; w/o Rear AC - 31.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
	All Eng.; w/ Rear AC - 47.00 Oz. R-134a; 16.00 Oz. PAG-46	59007
05-02	All Eng.; w/o Rear AC - 34.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
	All Eng.; w/ Rear AC - 56.00 Oz. R-134a; 13.00 Oz. PAG-46	59007
01-98	All Eng. - 30.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
97	All Eng. - 22.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
MYSTIQUE		
00-95	All Eng. - 26.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
SABLE		
09-08	All Eng.; w/ Front AC - 26.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
	All Eng.; w/ Rear AC - 36.00 Oz. R-134a; 9.50 Oz. PAG-46	59007
07-06	All Eng. - See Under Hood Decal	59007
05-96	All Eng. - 34.00 Oz. R-134a; 6.50 Oz. PAG-46	59007
95-94	All Eng. - 32.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
93	All Eng. - 32.00 Oz. R-12; 7.00 Oz. Ester	59000⁵⁹
	6 Cyl. 3.0 Eng. - 19.50 Oz. R-134a; 5.00 Oz. PAG-100	59007
92	All Eng. - 40.00 Oz. R-12; 7.00 Oz. Ester	59000⁵⁹
	6 Cyl. 3.0 Eng. - 19.50 Oz. R-134a; 5.00 Oz. PAG-100	59007
91	All Eng. - 40.00 Oz. R-12; 7.00 Oz. Ester	59000⁵⁹
90-89	All Eng. - 40.00 Oz. R-12; 8.00 Oz. Ester	59000⁵⁹
88-86	All Eng. - 44.00 Oz. R-12; 10.00 Oz. Ester	59000⁵⁹
TOPAZ		
94	All Eng. - 32.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
93	All Eng. - 37.00 Oz. R-12; 8.00 Oz. Ester	59000⁵⁹
92-89	All Eng. - 36.00 Oz. R-12; 7.00 Oz. Ester	59000⁵⁹
88-87	All Eng. - 36.00 Oz. R-12; 8.00 Oz. Ester	59000⁵⁹
86-85	4 Cyl. 2.0 Eng. - See Under Hood Decal	59000⁵⁹
	4 Cyl. 2.3 Eng. - See Under Hood Decal	59000⁵⁹
84	4 Cyl. 2.3 Eng. - See Under Hood Decal	59000⁵⁹
TRACER		
99	All Eng. - 27.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
98	All Eng. - 28.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
97	All Eng. - 28.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
96-94	All Eng. - 28.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
93	All Eng. - 34.00 Oz. R-12; 7.75 Oz. Ester	59000⁵⁹
92-91	All Eng. - 34.00 Oz. R-12; 8.00 Oz. Ester	59000⁵⁹
90-89	All Eng. - 36.00 Oz. R-12; 8.00 Oz. Ester	59000⁵⁹
88	All Eng. - 31.00 Oz. R-12; 10.00 Oz. Ester	59000⁵⁹
87	4 Cyl. 1.6 Eng. - See Under Hood Decal	59000⁵⁹
VILLAGER		
02-00	All Eng.; w/o Rear AC - 32.00 Oz. R-134a; 7.00 Oz. PAG-100	59002
	All Eng.; w/ Rear AC - 52.00 Oz. R-134a; 11.00 Oz. PAG-100	59002
99	All Eng.; w/o Rear AC - 32.00 Oz. R-134a; 10.00 Oz. PAG-100	59002
	All Eng.; w/ Rear AC - 52.00 Oz. R-134a; 11.00 Oz. PAG-100	59002
98	All Eng.; w/o Rear AC - 32.00 Oz. R-134a; 10.00 Oz. PAG-100	59002
	All Eng.; w/ Rear AC - 52.00 Oz. R-134a; 10.00 Oz. PAG-100	59002
97-94	All Eng.; w/o Rear AC - 32.00 Oz. R-134a; 7.00 Oz. PAG-100	59002
	All Eng.; w/ Rear AC - 52.00 Oz. R-134a; 10.00 Oz. PAG-100	59002
93	All Eng.; w/o Rear AC - 36.00 Oz. R-12; 7.00 Oz. Ester	59000⁵⁹
	All Eng.; w/ Rear AC - 56.00 Oz. R-12; 10.00 Oz. Ester	59000⁵⁹

Continued on Next Page

⁵⁹ When retrofitting to R134a PAG Oil must be used.

Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that A/C system has been properly cleaned, and new accumulator / filter drier has been installed. Specs are for total system capacities. Always refer to under hood decal as the primary source for refrigerant and lubricant information.

Year	Model	Lubricant
	ZEPHYR	
82-80	8 Cyl. 4.2 Eng. - See Under Hood Decal	59000 ⁵⁹
79-78	8 Cyl. 5.0 Eng. - See Under Hood Decal	59000 ⁵⁹

MERKUR

Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that A/C system has been properly cleaned, and new accumulator / filter drier has been installed. Specs are for total system capacities. Always refer to under hood decal as the primary source for refrigerant and lubricant information.

Year	Model	Lubricant
	SCORPIO	
89	All Eng. - 40.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
	XR4TI	
89	All Eng. - 40.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹

MITSUBISHI

Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that A/C system has been properly cleaned, and new accumulator / filter drier has been installed. Specs are for total system capacities. Always refer to under hood decal as the primary source for refrigerant and lubricant information.

Year	Model	Lubricant
	3000GT	
99-94	All Eng. - 28.00 Oz. R-134a; 6.50 Oz. PAG-46	59007
93	All Eng. From 10/92 - 29.00 Oz. R-12; 7.00 Oz. Mineral Oil	59000 ⁵⁹
92	All Eng. To 9/92 - 34.00 Oz. R-12; 7.00 Oz. Mineral Oil	59000 ⁵⁹
91	All Eng. - 34.00 Oz. R-12; 8.50 Oz. Mineral Oil	59000 ⁵⁹
	CORDIA	
88-84	4 Cyl. 1.8 Eng. - See Under Hood Decal	59000 ⁵⁹
	4 Cyl. 2.0 Eng. - See Under Hood Decal	59000 ⁵⁹
	DIAMANTE	
04-00	All Eng. - 23.00 Oz. R-134a; 5.50 Oz. PAG-46	59007
99-97	All Eng. - 24.00 Oz. R-134a; 6.50 Oz. PAG-46	59007
96	All Eng. - 28.00 Oz. R-134a; 6.50 Oz. PAG-46	59007
95-94	Sedan - 28.00 Oz. R-134a; 6.50 Oz. PAG-46	59007
	Wagon - 28.00 Oz. R-134a; 8.50 Oz. PAG-46	59007
93	Wagon - 28.00 Oz. R-12; 8.50 Oz. Mineral Oil	59000 ⁵⁹
	Sedan - 38.00 Oz. R-12; 6.00 Oz. Mineral Oil	59000 ⁵⁹
92	All Eng. - 38.00 Oz. R-12; 6.00 Oz. Mineral Oil	59000 ⁵⁹
	ECLIPSE	
12-09	4 Cyl. 2.4 Eng. - 20.00 Oz. R-134a; 4.70 Oz. PAG-46	59007
	6 Cyl. 3.8 Eng. - 20.00 Oz. R-134a; 4.70 Oz. PAG-46	59007
08-06	All Eng. - 20.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
05-00	All Eng. - 15.00 Oz. R-134a; 5.50 Oz. PAG-46	59007
99-95	All Eng. - 26.00 Oz. R-134a; 6.50 Oz. PAG-46	59007
94-90	All Eng. - 33.00 Oz. R-12; 6.50 Oz. Mineral Oil	59000 ⁵⁹
	ENDEAVOR	
11-10	6 Cyl. 3.8 Eng. - 21.00 Oz. R-134a; 4.75 Oz. PAG-46	59007
08-04	All Eng. - 21.00 Oz. R-134a; 4.75 Oz. PAG-46	59007
	EXPO	
95-94	All Eng. - 27.00 Oz. R-134a; 6.50 Oz. PAG-46	59007
93-92	All Eng. - 30.00 Oz. R-12; 6.50 Oz. Mineral Oil	59000 ⁵⁹
	EXPO LRV	
94	4 Cyl. 2.4 Eng. - See Under Hood Decal	59000 ⁵⁹
	GALANT	
12-10	4 Cyl. 2.4 Eng. - 22.00 Oz. R-134a; 4.70 Oz. PAG-46	59007
09	4 Cyl. 2.4 Eng. - 22.00 Oz. R-134a; 4.70 Oz. PAG-46	59007
	6 Cyl. 3.8 Eng. - 22.00 Oz. R-134a; 4.70 Oz. PAG-46	59007
08-06	All Eng. - 22.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
05-00	All Eng. - 23.00 Oz. R-134a; 5.50 Oz. PAG-46	59007
99-97	All Eng. - 24.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
96-94	All Eng. - 24.00 Oz. R-134a; 8.75 Oz. PAG-46	59007
93-89	All Eng. - 33.00 Oz. R-12; 8.75 Oz. Mineral Oil	59000 ⁵⁹

Continued on Next Page

⁵⁹ When retrofitting to R134a PAG Oil must be used.

MITSUBISHI

Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that A/C system has been properly cleaned, and new accumulator / filter drier has been installed. Specs are for total system capacities. Always refer to under hood decal as the primary source for refrigerant and lubricant information.

Year	Model	Lubricant
GALANT (Cont'd)		
87-85	4 Cyl. 2.4 Eng. - See Under Hood Decal	59000 ⁵⁹
LANCER		
13-09	4 Cyl. 2.0 Eng. - 18.00 Oz. R-134a; 3.40 Oz. PAG-46	59007
	4 Cyl. 2.4 Eng. - 18.00 Oz. R-134a; 3.40 Oz. PAG-46	59007
08	All Eng. - 17.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
07-03	All Eng. - 18.00 Oz. R-134a; 4.75 Oz. PAG-46	59007
02	All Eng. - 18.00 Oz. R-134a; 6.50 Oz. PAG-46	59007
MIGHTY MAX		
96-94	All Eng. - 28.00 Oz. R-134a; 7.75 Oz. PAG-46	59007
93-90	All Eng. - 30.00 Oz. R-12; 8.50 Oz. Mineral Oil	59000 ⁵⁹
89-86	4 Cyl. 2.0 Eng. - See Under Hood Decal	59000 ⁵⁹
	4 Cyl. 2.6 Eng. - See Under Hood Decal	59000 ⁵⁹
MIRAGE		
02	All Eng. - 23.00 Oz. R-134a; 4.50 Oz. PAG-46	59007
01-97	All Eng. - 21.00 Oz. R-134a; 4.50 Oz. PAG-46	59007
96-94	All Eng. - 30.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
93	All Eng. - 30.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
92-89	All Eng. - 36.00 Oz. R-12; 8.06 Oz. Mineral Oil	59000 ⁵⁹
88-85	4 Cyl. 1.5 Eng. - See Under Hood Decal	59000 ⁵⁹
	4 Cyl. 1.6 Eng. - See Under Hood Decal	59000 ⁵⁹
MONTERO		
06-02	All Eng.; w/o Rear AC - 21.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
	All Eng.; w/ Rear AC - 27.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
01	All Eng.; w/o Rear AC - 23.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
	All Eng.; w/ Rear AC - 33.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
00-94	All Eng. - 23.00 Oz. R-134a; 5.75 Oz. PAG-46	59007
93-92	All Eng. - 28.00 Oz. R-12; 5.75 Oz. Mineral Oil	59000 ⁵⁹
91-89	All Eng. - 32.00 Oz. R-12; 6.75 Oz. Mineral Oil	59000 ⁵⁹
88-87	4 Cyl. 2.6 Eng. - See Under Hood Decal	59000 ⁵⁹
MONTERO SPORT		
04-97	All Eng. - 24.00 Oz. R-134a; 8.75 Oz. PAG-46	59007
OUTLANDER		
13-11	4 Cyl. 2.0 Eng. - See Under Hood Decal	59007
	4 Cyl. 2.4 Eng. - See Under Hood Decal	59007
	6 Cyl. 3.0 Eng. - See Under Hood Decal	59007
10-08	4 Cyl. 2.4 Eng. - See Under Hood Decal	59007
	6 Cyl. 3.0 Eng. - See Under Hood Decal	59007
07-03	All Eng. - 19.00 Oz. R-134a; 4.75 Oz. PAG-46	59007
PRECIS		
93-90	All Eng. - 30.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
89	All Eng. - 35.00 Oz. R-12; 5.50 Oz. Mineral Oil	59000 ⁵⁹
88-87	4 Cyl. 1.5 Eng. - See Under Hood Decal	59000 ⁵⁹
RAIDER		
09	6 Cyl. 3.7 Eng. - 20.00 Oz. R-134a; 4.10 Oz. PAG-46	59007
08	All Eng. - 20.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
07-06	All Eng. - 28.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
SIGMA		
90	All Eng. - 32.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
89	All Eng. - 32.00 Oz. R-12; 8.75 Oz. Mineral Oil	59000 ⁵⁹
STARION		
89	All Eng. - 29.00 Oz. R-12; 8.75 Oz. Mineral Oil	59000 ⁵⁹
88-85	4 Cyl. 2.6 Eng. - See Under Hood Decal	59000 ⁵⁹
TREDIA		
88-85	4 Cyl. 1.8 Eng. - See Under Hood Decal	59000 ⁵⁹
	4 Cyl. 2.0 Eng. - See Under Hood Decal	59000 ⁵⁹
VAN		
90-87	All Eng.; w/o Rear AC - 32.00 Oz. R-12; 4.00 Oz. Mineral Oil	59000 ⁵⁹
	All Eng.; w/ Rear AC - 52.00 Oz. R-12; 5.00 Oz. Mineral Oil	59000 ⁵⁹

⁵⁹ When retrofitting to R134a PAG Oil must be used.

Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that A/C system has been properly cleaned, and new accumulator / filter drier has been installed. Specs are for total system capacities. Always refer to under hood decal as the primary source for refrigerant and lubricant information.

Year	Model	Lubricant
200 SERIES		
98-95	All Eng. - 25.00 Oz. R-134a; 6.75 Oz. PAG-46	59007
88-87	4 Cyl. 2.0 Eng. - See Under Hood Decal	59000 ⁵⁹
	6 Cyl. 3.0 Eng. - See Under Hood Decal	59000 ⁵⁹
86-85	4 Cyl. 1.8 Eng. - See Under Hood Decal	59000 ⁵⁹
	4 Cyl. 2.0 Eng. - See Under Hood Decal	59000 ⁵⁹
240 SERIES		
98-95	All Eng. - 25.00 Oz. R-134a; 8.50 Oz. PAG-46	59007
94	All Eng. - 28.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
93-91	All Eng. - 32.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
90-89	All Eng. - 35.00 Oz. R-12; 6.75 Oz. Mineral Oil	59000 ⁵⁹
300 SERIES		
96-94	All Eng. - 23.00 Oz. R-134a; 6.75 Oz. PAG-46	59007
93-91	All Eng. - 30.00 Oz. R-12; 6.75 Oz. Mineral Oil	59000 ⁵⁹
90	All Eng. - 34.00 Oz. R-12; 6.75 Oz. Mineral Oil	59000 ⁵⁹
89	All Eng. - 38.50 Oz. R-12; 6.75 Oz. Mineral Oil	59000 ⁵⁹
86-85	All Eng. - 38.00 Oz. R-12; 5.00 Oz. Mineral Oil	59000 ⁵⁹
350Z		
09	6 Cyl. 3.5 Eng. - 19.50 Oz. R-134a; 5.00 Oz. PAG-100	59007
08-07	All Eng. - 19.50 Oz. R-134a; 5.00 Oz. PAG-100	59002
06-03	All Eng. - 19.00 Oz. R-134a; 6.00 Oz. PAG-100	59002
370Z		
13-09	6 Cyl. 3.7 Eng. - 19.00 Oz. R-134a; 5.30 Oz. PAG-46	59007
720 PICKUP		
86	All Eng. To 6/86 - 38.00 Oz. R-12; 8.50 Oz. Mineral Oil	59000 ⁵⁹
85	All Eng. - 38.00 Oz. R-12; 8.50 Oz. Mineral Oil	59000 ⁵⁹
ALTIMA		
13-12	4 Cyl. 2.5 Eng. - 19.00 Oz. R-134a; 5.10 Oz. PAG-46	59007
	6 Cyl. 3.5 Eng. - 19.00 Oz. R-134a; 5.10 Oz. PAG-46	59007
11-10	4 Cyl. 2.5 Eng.; Hybrid - 18.00 Oz. R-134a; 4.20 Oz. Hybrid Oil	59889
	4 Cyl. 2.5 Eng.; Excl. Hybrid - 19.00 Oz. R-134a; 5.10 Oz. PAG-46	59007
	6 Cyl. 3.5 Eng. - 19.00 Oz. R-134a; 5.30 Oz. PAG-46	59007
09	All Eng.; Hybrid - 18.00 Oz. R-134a; 4.20 Oz. Hybrid Oil	59889
	4 Cyl. 2.5 Eng.; Hybrid - 18.00 Oz. R-134a; 4.20 Oz. Hybrid Oil	59889
	4 Cyl. 2.5 Eng.; Excl. Hybrid - 19.00 Oz. R-134a; 5.10 Oz. PAG-46	59007
	6 Cyl. 3.5 Eng. - 19.00 Oz. R-134a; 5.30 Oz. PAG-46	59007
08	All Eng.; Hybrid - 18.00 Oz. R-134a; 4.20 Oz. Hybrid Oil	59889
	All Eng.; Excl. Hybrid - 18.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
07	All Eng.; Hybrid - 18.00 Oz. R-134a; 4.20 Oz. Hybrid Oil	59889
	All Eng.; Excl. Hybrid - 19.00 Oz. R-134a; 5.30 Oz. PAG-46	59007
06-02	All Eng. - 18.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
01	All Eng. - 22.00 Oz. R-134a; 6.75 Oz. PAG-100	59002
00-94	All Eng. - 26.50 Oz. R-134a; 6.75 Oz. PAG-100	59002
93	All Eng. - 26.50 Oz. R-134a; 6.75 Oz. PAG-100	59002
	4 Cyl. 2.4 Eng. - 26.50 Oz. R-12; 6.75 Oz. Mineral Oil	59000 ⁵⁹
ARMADA		
13-09	8 Cyl. 5.6 Eng. - 38.00 Oz. R-134a; 9.80 Oz. PAG-46	59007
08-05	All Eng. - 38.00 Oz. R-134a; 9.80 Oz. PAG-46	59007
AXXESS		
90	All Eng. - 38.50 Oz. R-12; 6.75 Oz. Mineral Oil	59000 ⁵⁹
CUBE		
13-09	4 Cyl. 1.8 Eng. - 16.00 Oz. R-134a; 4.10 Oz. PAG-100	59002
D21 PICKUP		
94	4 Cyl. 2.4 Eng. - See Under Hood Decal	59007
	6 Cyl. 3.0 Eng. - See Under Hood Decal	59007
93	All Eng. - 30.00 Oz. R-134a; 6.75 Oz. PAG-100	59002
	4 Cyl. 2.4 Eng. - w/ R-12	59000 ⁵⁹
	6 Cyl. 3.0 Eng. - w/ R-12	59000 ⁵⁹
92-90	All Eng. - 32.00 Oz. R-12; 6.75 Oz. Mineral Oil	59000 ⁵⁹
89-88	All Eng. - 32.00 Oz. R-12; 7.00 Oz. Mineral Oil	59000 ⁵⁹
87	All Eng. - 38.50 Oz. R-12; 6.75 Oz. Mineral Oil	59000 ⁵⁹
86	All Eng. From 6/86 - 38.00 Oz. R-12; 6.75 Oz. Mineral Oil	59000 ⁵⁹

Continued on Next Page

⁵⁹ When retrofitting to R134a PAG Oil must be used.

NISSAN

Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that A/C system has been properly cleaned, and new accumulator / filter drier has been installed. Specs are for total system capacities. Always refer to under hood decal as the primary source for refrigerant and lubricant information.

Year	Model	Lubricant
FRONTIER		
13	6 Cyl. 4.0 Eng. - 26.50 Oz. R-134a; 6.00 Oz. PAG-100	59002
12-11	4 Cyl. 2.4 Eng. - 26.50 Oz. R-134a; 6.00 Oz. PAG-100	59002
	4 Cyl. 2.5 Eng. - 26.50 Oz. R-134a; 6.00 Oz. PAG-100	59002
	6 Cyl. 4.0 Eng. - 26.50 Oz. R-134a; 6.00 Oz. PAG-100	59002
10-09	4 Cyl. 2.5 Eng. - 26.50 Oz. R-134a; 6.00 Oz. PAG-100	59002
	6 Cyl. 4.0 Eng. - 26.50 Oz. R-134a; 6.00 Oz. PAG-100	59002
08	All Eng. - 26.50 Oz. R-134a; 6.00 Oz. PAG-100	59002
07-98	All Eng. - 25.00 Oz. R-134a; 6.75 Oz. PAG-100	59002
JUKE		
13-11	4 Cyl. 1.6 Eng. - 14.00 Oz. R-134a; 4.10 Oz. PAG 150	59002
LEAF		
13	E Cyl. E Eng.; Hybrid; w/o Heat Pump - 14.00 Oz. R-134a; 5.10 Oz. Hybrid Oil	59889
	E Cyl. E Eng.; Hybrid; w/ Heat Pump - 29.00 Oz. R-134a; 5.10 Oz. Hybrid Oil	59889
12-11	E Cyl. E Eng.; Hybrid - 14.00 Oz. R-134a; 5.10 Oz. Hybrid Oil	59889
MAXIMA		
13-09	6 Cyl. 3.5 Eng. - 19.00 Oz. R-134a; 5.30 Oz. PAG-46	59007
08-04	All Eng. - 19.00 Oz. R-134a; 5.30 Oz. PAG-46	59007
03-02	All Eng. - 18.00 Oz. R-134a; 6.00 Oz. PAG-46	59007
01-97	All Eng. - 23.00 Oz. R-134a; 6.80 Oz. PAG-46	59007
96	All Eng. - 25.00 Oz. R-134a; 8.50 Oz. PAG-46	59007
95	All Eng. - 29.00 Oz. R-134a; 8.50 Oz. PAG-46	59007
94	All Eng. - 33.50 Oz. R-134a; 6.75 Oz. PAG-46	59007
93	All Eng. - 33.50 Oz. R-12; 6.75 Oz. Mineral Oil	59000 ⁵⁹
	All Eng. - 33.50 Oz. R-134a; 6.75 Oz. PAG-46	59007
92-91	All Eng. - 33.50 Oz. R-12; 6.75 Oz. Mineral Oil	59000 ⁵⁹
90-89	All Eng. - 35.00 Oz. R-12; 6.75 Oz. Mineral Oil	59000 ⁵⁹
88-86	All Eng. - 38.00 Oz. R-12; 5.00 Oz. Mineral Oil	59000 ⁵⁹
85	All Eng. - 38.00 Oz. R-12; 9.00 Oz. Mineral Oil	59000 ⁵⁹
MURANO		
14	6 Cyl. 3.5 Eng. - See Under Hood Decal	59007
13-11	6 Cyl. 3.5 Eng. - 21.00 Oz. R-134a; 5.10 Oz. PAG-46	59007
10	All Eng. - 21.00 Oz. R-134a; 5.10 Oz. PAG-46	59007
09	All Eng. - 19.00 Oz. R-134a; 5.25 Oz. PAG-46	59007
08	6 Cyl. 3.5 Eng. - 19.00 Oz. R-134a; 5.25 Oz. PAG-46	59007
07-03	All Eng. - 19.00 Oz. R-134a; 5.25 Oz. PAG-46	59007
NV VAN		
13	6 Cyl. 4.0 Eng.; w/o Rear AC - 30.00 Oz. R-134a; 6.10 Oz. PAG-46	59007
	6 Cyl. 4.0 Eng.; w/ Rear AC - 42.00 Oz. R-134a; 7.80 Oz. PAG-46	59007
	8 Cyl. 5.6 Eng.; w/o Rear AC - 30.00 Oz. R-134a; 6.10 Oz. PAG-46	59007
	8 Cyl. 5.6 Eng.; w/ Rear AC - 42.00 Oz. R-134a; 7.80 Oz. PAG-46	59007
12	6 Cyl. 4.0 Eng. - 30.00 Oz. R-134a; 6.10 Oz. PAG-46	59007
	8 Cyl. 5.6 Eng. - 30.00 Oz. R-134a; 6.10 Oz. PAG-46	59007
PATHFINDER		
13	6 Cyl. 3.5 Eng. - 30.00 Oz. R-134a; 6.10 Oz. PAG-46	59007
12-09	6 Cyl. 4.0 Eng.; w/o Rear AC - 25.00 Oz. R-134a; 6.00 Oz. PAG-46	59007
	6 Cyl. 4.0 Eng.; w/ Rear AC - 28.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
	8 Cyl. 5.6 Eng.; w/o Rear AC - 25.00 Oz. R-134a; 6.00 Oz. PAG-46	59007
	8 Cyl. 5.6 Eng.; w/ Rear AC - 28.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
08	All Eng.; w/o Rear AC - 25.00 Oz. R-134a; 6.00 Oz. PAG-46	59007
	All Eng.; w/ Rear AC - 28.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
07-06	All Eng.; w/o Rear AC - 19.00 Oz. R-134a; 6.00 Oz. PAG-46	59007
	All Eng.; w/ Rear AC - 30.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
05-02	All Eng. - 16.00 Oz. R-134a; 6.00 Oz. PAG-46	59007
01-96	All Eng. - 23.00 Oz. R-134a; 6.80 Oz. PAG-46	59007
95-94	All Eng. - 30.00 Oz. R-134a; 6.75 Oz. PAG-100	59002
93	All Eng. - 30.00 Oz. R-134a; 6.75 Oz. PAG-100	59002
	6 Cyl. 3.0 Eng. - 32.00 Oz. R-12; 6.75 Oz. Mineral Oil	59000 ⁵⁹
92-89	All Eng. - 32.00 Oz. R-12; 6.75 Oz. Mineral Oil	59000 ⁵⁹
88-87	4 Cyl. 2.4 Eng. - See Under Hood Decal	59000 ⁵⁹
	6 Cyl. 3.0 Eng. - See Under Hood Decal	59000 ⁵⁹
PICKUP		
97-94	All Eng. - 30.00 Oz. R-134a; 6.75 Oz. PAG-100	59002

Continued on Next Page

⁵⁹ When retrofitting to R134a PAG Oil must be used.

Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that A/C system has been properly cleaned, and new accumulator / filter drier has been installed. Specs are for total system capacities. Always refer to under hood decal as the primary source for refrigerant and lubricant information.

Year	Model	Lubricant
PULSAR NX / NX		
93-91	All Eng. - 26.50 Oz. R-12; 6.75 Oz. Mineral Oil	59000 ⁵⁹
90	4 Cyl. 1.6 Eng. - See Under Hood Decal	59000 ⁵⁹
89-88	4 Cyl. 1.6 Eng. - See Under Hood Decal	59000 ⁵⁹
	4 Cyl. 1.8 Eng. - See Under Hood Decal	59000 ⁵⁹
87	All Eng. - 38.00 Oz. R-12; 6.75 Oz. Mineral Oil	59000 ⁵⁹
86	4 Cyl. 1.6 Eng. - See Under Hood Decal	59000 ⁵⁹
	4 Cyl. 1.6 Eng. - See Under Hood Decal	59000 ⁵⁹
85	4 Cyl. 1.6 Eng. - See Under Hood Decal	59000 ⁵⁹
QUEST		
13-11	6 Cyl. 3.5 Eng. - 32.00 Oz. R-134a; 8.80 Oz. PAG-46	59007
09	6 Cyl. 3.5 Eng. - 32.00 Oz. R-134a; 7.44 Oz. PAG-46	59007
08	All Eng. - 33.50 Oz. R-134a; 7.50 Oz. PAG-46	59002
07-06	All Eng. - 32.00 Oz. R-134a; 8.00 Oz. PAG-100	59002
05	All Eng. - 32.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
04	All Eng. - 32.00 Oz. R-134a; 8.00 Oz. PAG-100	59002
02-01	All Eng.; w/o Rear AC - 32.00 Oz. R-134a; 7.00 Oz. PAG-100	59002
	All Eng.; w/ Rear AC - 54.00 Oz. R-134a; 11.00 Oz. PAG-100	59002
00-94	All Eng.; w/o Rear AC - 32.00 Oz. R-134a; 7.00 Oz. PAG-100	59002
	All Eng.; w/ Rear AC - 52.00 Oz. R-134a; 11.00 Oz. PAG-100	59002
93	All Eng.; w/o Rear AC - 36.00 Oz. R-12; 7.00 Oz. Ester	59000 ⁵⁹
	All Eng.; w/ Front & Rear AC - 56.00 Oz. R-12; 10.00 Oz. Ester	59000 ⁵⁹
ROGUE		
13-09	4 Cyl. 2.5 Eng. - 18.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
08	All Eng. - 18.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
SENTRA		
13	4 Cyl. 1.8 Eng. - 16.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
12-09	4 Cyl. 2.0 Eng. - 18.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
	4 Cyl. 2.5 Eng. - 18.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
08-07	All Eng. - 19.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
06-02	All Eng. - 19.00 Oz. R-134a; 6.00 Oz. PAG-100	59002
01	All Eng. - 19.00 Oz. R-134a; 6.00 Oz. PAG-150	59002
00	All Eng. - 19.00 Oz. R-134a; 6.00 Oz. PAG-100	59002
99-94	All Eng. - 25.00 Oz. R-134a; 6.75 Oz. PAG-100	59002
93-91	All Eng. - 26.50 Oz. R-12; 6.75 Oz. Mineral Oil	59000 ⁵⁹
90-89	All Eng. - 33.50 Oz. R-12; 6.75 Oz. Mineral Oil	59000 ⁵⁹
88	All Eng. - 38.00 Oz. R-12; 7.00 Oz. Mineral Oil	59000 ⁵⁹
87	All Eng. - 38.00 Oz. R-12; 6.75 Oz. Mineral Oil	59000 ⁵⁹
86	All Eng. - 35.00 Oz. R-12; 5.00 Oz. Mineral Oil	59000 ⁵⁹
85	All Eng. - 35.00 Oz. R-12; 5.10 Oz. Mineral Oil	59000 ⁵⁹
STANZA		
92-91	All Eng. - 30.00 Oz. R-12; 6.75 Oz. Mineral Oil	59000 ⁵⁹
90	All Eng. - 32.00 Oz. R-12; 6.75 Oz. Mineral Oil	59000 ⁵⁹
89	All Eng. - 38.50 Oz. R-12; 6.75 Oz. Mineral Oil	59000 ⁵⁹
88	All Eng. - 38.00 Oz. R-12; 7.00 Oz. Mineral Oil	59000 ⁵⁹
87	Wagon - 38.50 Oz. R-12; 5.00 Oz. Mineral Oil	59000 ⁵⁹
	Sedan / Coupe - 38.50 Oz. R-12; 6.75 Oz. Mineral Oil	59000 ⁵⁹
86-85	4 Cyl. 2.0 Eng. - See Under Hood Decal	59000 ⁵⁹
TITAN		
13-09	8 Cyl. 5.6 Eng. - 26.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
08-04	All Eng. - 26.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
VERSA		
13	4 Cyl. 1.6 Eng. - 18.00 Oz. R-134a; 4.10 Oz. PAG-100	59002
12-11	4 Cyl. 1.6 Eng. - 18.00 Oz. R-134a; 3.40 Oz. PAG-46; w/ CSV511 Compressor	59007
	4 Cyl. 1.6 Eng. - 18.00 Oz. R-134a; 4.10 Oz. PAG-100	59002
	4 Cyl. 1.8 Eng. - 18.00 Oz. R-134a; 3.40 Oz. PAG-46; w/ CSV511 Compressor	59007
	4 Cyl. 1.8 Eng. - 18.00 Oz. R-134a; 4.10 Oz. PAG-100	59002
10-07	All Eng. - 18.00 Oz. R-134a; 3.40 Oz. PAG-46; w/ CSV511 Compressor	59007
	All Eng. - 18.00 Oz. R-134a; 4.10 Oz. PAG-100	59002
XTERRA		
13-09	6 Cyl. 4.0 Eng. - 26.50 Oz. R-134a; 6.00 Oz. PAG-46	59007
08-07	All Eng. - 26.50 Oz. R-134a; 6.00 Oz. PAG-46	59007
06-01	All Eng. - 25.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
00	All Eng. - 25.00 Oz. R-134a; 7.00 Oz. PAG-46	59002

⁵⁹ When retrofitting to R134a PAG Oil must be used.

OLDSMOBILE

Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that A/C system has been properly cleaned, and new accumulator / filter drier has been installed. Specs are for total system capacities. Always refer to under hood decal as the primary source for refrigerant and lubricant information.

Year	Model	Lubricant
98 / 98 REGENCY		
99-96	All Eng. - 32.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
95-94	All Eng. - 39.00 Oz. R-134a; 8.00 Oz. PAG-150; w/ OE Harrison Compressor	59003
	All Eng. - 39.00 Oz. R-134a; 8.00 Oz. PAG-46; w/ Denso Compressor	59007
93-91	All Eng. - 29.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
90-89	All Eng. - 38.50 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
88	All Eng. - 38.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
87-85	All Eng. - 46.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
84	8 Cyl. 5.0 Eng. - See Under Hood Decal	59000 ⁵⁹
73-72	8 Cyl. 5.7 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 7.5 Eng. - See Under Hood Decal	59000 ⁵⁹
71-68	8 Cyl. 7.5 Eng. - See Under Hood Decal	59000 ⁵⁹
67-65	8 Cyl. 7.0 Eng. - See Under Hood Decal	59000 ⁵⁹
64-63	8 Cyl. 6.5 Eng. - See Under Hood Decal	59000 ⁵⁹
ACHIEVA		
98-95	All Eng. - 36.00 Oz. R-134a; 9.00 Oz. PAG-150	59003
94	All Eng. - 36.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
93-92	All Eng. - 42.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
	4 Cyl. 2.3 Eng. - 42.00 Oz. R-12; 8.00 Oz. Mineral Oil	59003
	6 Cyl. 3.3 Eng. - 42.00 Oz. R-12; 8.00 Oz. Mineral Oil	59003
ALERO		
04-02	All Eng. - 22.00 Oz. R-134a; 9.00 Oz. PAG-46	59003
01-99	All Eng. - 28.00 Oz. R-134a; 9.00 Oz. PAG-150	59003
AURORA		
03	All Eng. - 35.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
02-01	All Eng. - 35.00 Oz. R-134a; 9.00 Oz. PAG-150	59003
99-95	All Eng. - 32.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
BRAVADA		
04-02	All Eng.; w/o Rear AC - 29.00 Oz. R-134a; 7.50 Oz. PAG-46	59007
	All Eng.; w/ Rear AC - 48.00 Oz. R-134a; 8.50 Oz. PAG-46	59007
01-99	All Eng. - 31.00 Oz. R-134a; 8.50 Oz. PAG-150; w/ OE Harrison Compressor	59003
	All Eng. - 31.00 Oz. R-134a; 8.50 Oz. PAG-46; w/ Denso Compressor	59007
98-96	All Eng. - 32.00 Oz. R-134a; 8.00 Oz. PAG-150; w/ OE Harrison Compressor	59003
	All Eng. - 32.00 Oz. R-134a; 8.00 Oz. PAG-46; w/ Denso Compressor	59007
94	All Eng. - 32.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
	6 Cyl. 4.3 Eng. - 40.00 Oz. R-134a; 8.00 Oz. PAG-150	59000 ⁵⁹
93	All Eng. - 37.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
92-91	All Eng. - 40.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
CALAIS / CUTLASS CALAIS		
91-87	All Eng. - 36.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
86	All Eng. - 36.00 Oz. R-12; 7.00 Oz. Mineral Oil	59000 ⁵⁹
85	4 Cyl. 2.5 Eng. - See Under Hood Decal	59000 ⁵⁹
	6 Cyl. 3.0 Eng. - See Under Hood Decal	59000 ⁵⁹
	6 Cyl. 3.8 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.0 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.7 Eng. - See Under Hood Decal	59000 ⁵⁹
CIERA / CUTLASS CIERA		
96-94	4 Cyl. 2.2 Eng. - 28.00 Oz. R-134a; 9.00 Oz. PAG-150	59003
	6 Cyl. 3.1 Eng. - 32.00 Oz. R-134a; 9.00 Oz. PAG-150	59003
93	All Eng. - 38.00 Oz. R-12; 9.00 Oz. Mineral Oil	59000 ⁵⁹
92	All Eng. - 38.00 Oz. R-12; 9.00 Oz. Mineral Oil	59000 ⁵⁹
	All Eng. - 38.00 Oz. R-12; 9.00 Oz. Mineral Oil	59000 ⁵⁹
91-85	All Eng. - 44.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
CUTLASS / CUTLASS SUPREME		
99-98	All Eng. - 28.00 Oz. R-134a; 9.00 Oz. PAG-150	59003
97	All Eng. - 30.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
96-94	All Eng. - 32.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
93-92	All Eng. - 36.00 Oz. R-12; 9.00 Oz. Mineral Oil	59000 ⁵⁹
91-89	All Eng. - 36.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
88	All Eng. - 56.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
87-86	All Eng. - 48.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
85	All Eng. - 52.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
84	8 Cyl. 5.0 Eng. - See Under Hood Decal	59000 ⁵⁹
73-72	8 Cyl. 5.7 Eng. - See Under Hood Decal	59000 ⁵⁹

Continued on Next Page

⁵⁹ When retrofitting to R134a PAG Oil must be used.

Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that A/C system has been properly cleaned, and new accumulator / filter drier has been installed. Specs are for total system capacities. Always refer to under hood decal as the primary source for refrigerant and lubricant information.

Year	Model	Lubricant
CUTLASS / CUTLASS SUPREME (Cont'd)		
73-72	8 Cyl. 7.5 Eng. - See Under Hood Decal	59000 ⁵⁹
71-70	6 Cyl. 4.1 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.7 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 7.5 Eng. - See Under Hood Decal	59000 ⁵⁹
69	6 Cyl. 4.1 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.7 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 6.6 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 7.5 Eng. - See Under Hood Decal	59000 ⁵⁹
68	8 Cyl. 5.7 Eng. - See Under Hood Decal	59000 ⁵⁹
CUTLASS CRUISER		
94	6 Cyl. 3.1 Eng. - 32.00 Oz. R-134a; 8.00 Oz. PAG 150	59003
90	4 Cyl. 2.5 Eng. - See Under Hood Decal	59000 ⁵⁹
89	4 Cyl. 2.5 Eng. - See Under Hood Decal	59000 ⁵⁹
	6 Cyl. 2.8 Eng. - See Under Hood Decal	59000 ⁵⁹
	6 Cyl. 3.3 Eng. - See Under Hood Decal	59000 ⁵⁹
88-87	4 Cyl. 2.5 Eng. - See Under Hood Decal	59000 ⁵⁹
	6 Cyl. 2.8 Eng. - See Under Hood Decal	59000 ⁵⁹
	6 Cyl. 3.8 Eng. - See Under Hood Decal	59000 ⁵⁹
CUTLASS CRUISERS		
94	6 Cyl. 3.1 Eng. - 32.00 Oz. R-134a; 8.00 Oz. PAG 150	59003
DELTA 88 CUSTOM CRUISER / CUSTOM CRUISER		
92-91	All Eng. - 49.50 Oz. R-12; 6.00 Oz. Mineral Oil	59000 ⁵⁹
90-89	All Eng. - 56.00 Oz. R-12; 6.00 Oz. Mineral Oil	59000 ⁵⁹
88-86	8 Cyl. 5.0 Eng. - See Under Hood Decal	59000 ⁵⁹
85	8 Cyl. 5.0 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.7 Eng. - See Under Hood Decal	59000 ⁵⁹
73	8 Cyl. 5.7 Eng. - See Under Hood Decal	59000 ⁵⁹
DELTA 88 SEDAN		
99-98	All Eng. - 32.00 Oz. R-134a; 9.00 Oz. PAG-150	59003
97-96	All Eng. - 32.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
95-94	All Eng. - 39.00 Oz. R-134a; 8.00 Oz. PAG-150; w/ OE Harrison Compressor	59003
	All Eng. - 39.00 Oz. R-134a; 8.00 Oz. PAG-46; w/ Denso Compressor	59007
93-92	All Eng. - 36.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
91-90	All Eng. - 38.00 Oz. R-12; 6.00 Oz. Mineral Oil	59000 ⁵⁹
89	All Eng. - 46.00 Oz. R-12; 6.00 Oz. Mineral Oil	59000 ⁵⁹
88	All Eng. - 53.00 Oz. R-12; 6.00 Oz. Mineral Oil	59000 ⁵⁹
87-86	All Eng. - 38.00 Oz. R-12; 7.00 Oz. Mineral Oil	59000 ⁵⁹
85	All Eng. - 46.00 Oz. R-12; 7.00 Oz. Mineral Oil	59000 ⁵⁹
84	6 Cyl. 3.8 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.0 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.7 Eng. - See Under Hood Decal	59000 ⁵⁹
73-68	8 Cyl. 5.7 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 7.5 Eng. - See Under Hood Decal	59000 ⁵⁹
67	8 Cyl. 7.0 Eng. - See Under Hood Decal	59000 ⁵⁹
66-65	8 Cyl. 5.4 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 7.0 Eng. - See Under Hood Decal	59000 ⁵⁹
FIRENZA		
88	4 Cyl. 2.0 Eng. - See Under Hood Decal	59000 ⁵⁹
87	4 Cyl. 2.0 Eng. - See Under Hood Decal	59000 ⁵⁹
	6 Cyl. 2.8 Eng. - See Under Hood Decal	59000 ⁵⁹
86-85	4 Cyl. 1.8 Eng. - See Under Hood Decal	59000 ⁵⁹
	4 Cyl. 2.0 Eng. - See Under Hood Decal	59000 ⁵⁹
	6 Cyl. 2.8 Eng. - See Under Hood Decal	59000 ⁵⁹
84-83	4 Cyl. 1.8 Eng. - See Under Hood Decal	59000 ⁵⁹
	4 Cyl. 2.0 Eng. - See Under Hood Decal	59000 ⁵⁹
82	4 Cyl. 1.8 Eng. - See Under Hood Decal	59000 ⁵⁹
INTRIGUE		
02-98	All Eng. - 36.00 Oz. R-134a; 9.00 Oz. PAG-150	59003
LSS		
99-96	All Eng. - 32.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
OMEGA		
84-82	4 Cyl. 2.5 Eng. - See Under Hood Decal	59000 ⁵⁹
	6 Cyl. 2.8 Eng. - See Under Hood Decal	59000 ⁵⁹

Continued on Next Page

⁵⁹ When retrofitting to R134a PAG Oil must be used.

OLDSMOBILE

Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that A/C system has been properly cleaned, and new accumulator / filter drier has been installed. Specs are for total system capacities. Always refer to under hood decal as the primary source for refrigerant and lubricant information.

Year	Model	Lubricant
OMEGA (Cont'd)		
74	6 Cyl. 4.1 Eng. - See Under Hood Decal	59000 ⁵⁹
73	6 Cyl. 4.1 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.7 Eng. - See Under Hood Decal	59000 ⁵⁹
SILHOUETTE		
04-01	All Eng.; w/o Rear AC - 27.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
	All Eng.; w/ Rear AC - 35.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
00-98	All Eng.; w/o Rear AC - 32.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
	All Eng.; w/ Rear AC - 46.00 Oz. R-134a; 11.00 Oz. PAG-150	59003
97	6 Cyl. 3.4 Eng.; w/o Rear AC - 32.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
	6 Cyl. 3.4 Eng.; w/ Rear AC - 46.00 Oz. R-134a; 11.00 Oz. PAG-150	59003
96	All Eng.; w/o Rear AC - 36.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
	All Eng.; w/ Rear AC - 48.00 Oz. R-134a; 11.00 Oz. PAG-150	59003
95-94	All Eng.; w/o Rear AC - 36.00 Oz. R-134a; 8.00 Oz. PAG-150; w/ OE Harrison Compressor	59003
	All Eng.; w/o Rear AC - 36.00 Oz. R-134a; 8.00 Oz. PAG-46; w/ Denso Compressor	59007
	All Eng.; w/ Rear AC - 48.00 Oz. R-134a; 11.00 Oz. PAG-150; w/ OE Harrison Compressor	59003
	All Eng.; w/ Rear AC - 48.00 Oz. R-134a; 11.00 Oz. PAG-46; w/ Denso Compressor	59007
93	All Eng.; w/o Rear AC - 42.00 Oz. R-134a; 8.00 Oz. PAG-150; w/ OE Harrison Compressor	59003
	All Eng.; w/o Rear AC - 42.00 Oz. R-134a; 8.00 Oz. PAG-46; w/ Denso Compressor	59007
	All Eng.; w/ Rear AC - 56.00 Oz. R-134a; 11.00 Oz. PAG-150; w/ OE Harrison Compressor	59003
	All Eng.; w/ Rear AC - 56.00 Oz. R-134a; 11.00 Oz. PAG-46; w/ Denso Compressor	59007
	6 Cyl. 3.1 Eng. - w/ R-12; w/ OE Harrison Compressor	59000 ⁵⁹
	6 Cyl. 3.8 Eng. - w/ R-12; w/ OE Harrison Compressor	59000 ⁵⁹
92	All Eng.; w/o Rear AC - 51.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
	All Eng.; w/ Rear AC - 67.00 Oz. R-12; 11.00 Oz. Mineral Oil	59000 ⁵⁹
91	All Eng.; w/o Rear AC - 51.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
90	All Eng.; w/o Rear AC - 44.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
TORONADO		
92-89	All Eng. - 38.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
88-86	6 Cyl. 3.8 Eng. - 38.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
85	8 Cyl. 5.0 Eng. - 38.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
	8 Cyl. 5.7 Eng. - 38.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
84	6 Cyl. 4.1 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.0 Eng. - See Under Hood Decal	59000 ⁵⁹
72-71	8 Cyl. 7.5 Eng. - See Under Hood Decal	59000 ⁵⁹

PEUGEOT

Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that A/C system has been properly cleaned, and new accumulator / filter drier has been installed. Specs are for total system capacities. Always refer to under hood decal as the primary source for refrigerant and lubricant information.

Year	Model	Lubricant
405		
91-89	All Eng. - 53.00 Oz. R-12; 6.75 Oz. Mineral Oil	59000 ⁵⁹
505		
91-89	All Eng. - 35.00 Oz. R-12; 6.75 Oz. Mineral Oil	59000 ⁵⁹

PLYMOUTH

Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that A/C system has been properly cleaned, and new accumulator / filter drier has been installed. Specs are for total system capacities. Always refer to under hood decal as the primary source for refrigerant and lubricant information.

Year	Model	Lubricant
ACCLAIM		
95-94	All Eng. - 26.00 Oz. R-134a; 7.25 Oz. PAG-46	59007
93-91	All Eng. - 32.00 Oz. R-12; 7.25 Oz. Mineral Oil	59000 ⁵⁹
90-89	All Eng. - 38.00 Oz. R-12; 7.25 Oz. Mineral Oil	59000 ⁵⁹
BREEZE		
00	All Eng. - 19.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
99	All Eng. - 20.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
98	All Eng. - 26.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
97-96	All Eng. - 28.00 Oz. R-134a; 7.00 Oz. PAG-46	59007

Continued on Next Page

⁵⁹ When retrofitting to R134a PAG Oil must be used.

Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that A/C system has been properly cleaned, and new accumulator / filter drier has been installed. Specs are for total system capacities. Always refer to under hood decal as the primary source for refrigerant and lubricant information.

Year	Model	Lubricant
CARAVELLE		
88-86	All Eng. - 38.00 Oz. R-12; 7.25 Oz. Mineral Oil	59000 ⁵⁹
85	4 Cyl. 2.2 Eng. - See Under Hood Decal	59000 ⁵⁹
	4 Cyl. 2.6 Eng. - See Under Hood Decal	59000 ⁵⁹
COLT		
94	4 Cyl. 1.5 Eng. - 28.00 Oz. R-134a; 4.40 Oz. PAG-46	59007
	4 Cyl. 1.8 Eng. - 28.00 Oz. R-134a; 4.40 Oz. PAG-46	59007
	4 Cyl. 2.4 Eng. - 28.00 Oz. R-134a; 4.40 Oz. PAG-46	59007
93	4 Cyl. 1.5 Eng. - 28.00 Oz. R-12; Mineral See Under Hood Decal	59000 ⁵⁹
	4 Cyl. 1.8 Eng. - 28.00 Oz. R-12; Mineral See Under Hood Decal	59000 ⁵⁹
92	4 Cyl. 1.5 Eng. - See Under Hood Decal	59000 ⁵⁹
91	4 Cyl. 1.5 Eng. - See Under Hood Decal	59000 ⁵⁹
	4 Cyl. 2.0 Eng. - See Under Hood Decal	59000 ⁵⁹
90-89	4 Cyl. 1.5 Eng. - See Under Hood Decal	59000 ⁵⁹
	4 Cyl. 1.6 Eng. - See Under Hood Decal	59000 ⁵⁹
	4 Cyl. 1.8 Eng. - See Under Hood Decal	59000 ⁵⁹
	4 Cyl. 2.0 Eng. - See Under Hood Decal	59000 ⁵⁹
88-87	4 Cyl. 1.5 Eng. - See Under Hood Decal	59000 ⁵⁹
	4 Cyl. 2.0 Eng. - See Under Hood Decal	59000 ⁵⁹
86-85	4 Cyl. 1.5 Eng. - See Under Hood Decal	59000 ⁵⁹
	4 Cyl. 1.6 Eng. - See Under Hood Decal	59000 ⁵⁹
	4 Cyl. 2.0 Eng. - See Under Hood Decal	59000 ⁵⁹
CONQUEST		
86-85	4 Cyl. 2.6 Eng. - See Under Hood Decal	59000 ⁵⁹
GRAN FURY		
89-84	8 Cyl. 5.2 Eng. - See Under Hood Decal	59000 ⁵⁹
83-81	6 Cyl. 3.7 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.2 Eng. - See Under Hood Decal	59000 ⁵⁹
80	6 Cyl. 3.7 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.2 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.9 Eng. - See Under Hood Decal	59000 ⁵⁹
HORIZON		
90-89	4 Cyl. 2.2 Eng. - See Under Hood Decal	59000 ⁵⁹
88	All Eng. - 38.00 Oz. R-12; 7.25 Oz. Mineral Oil	59000 ⁵⁹
87	All Eng. - 34.00 Oz. R-12; 7.25 Oz. Mineral Oil	59000 ⁵⁹
86-84	4 Cyl. 1.6 Eng. - See Under Hood Decal	59000 ⁵⁹
	4 Cyl. 2.2 Eng. - See Under Hood Decal	59000 ⁵⁹
83-81	4 Cyl. 2.2 Eng. - See Under Hood Decal	59000 ⁵⁹
79-78	4 Cyl. 1.7 Eng. - See Under Hood Decal	59000 ⁵⁹
LASER		
94	All Eng. - 26.00 Oz. R-134a; 7.25 Oz. PAG-46	59007
93-91	All Eng. - 32.00 Oz. R-12; 7.25 Oz. Mineral Oil	59000 ⁵⁹
90	All Eng. - 38.00 Oz. R-12; 7.25 Oz. Mineral Oil	59000 ⁵⁹
NEON		
01-00	All Eng. - 27.00 Oz. R-134a; 6.00 Oz. PAG-46	59007
99	All Eng. - 28.00 Oz. R-134a; 4.75 Oz. PAG-46	59007
98-97	All Eng. - 25.00 Oz. R-134a; 6.75 Oz. PAG-46	59007
96-95	All Eng. - 29.00 Oz. R-134a; 4.75 Oz. PAG-46	59007
PROWLER		
01	6 Cyl. 3.5 Eng. - 21.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
00	All Eng. - 21.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
99-97	All Eng. - 24.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
RELIANT		
89	4 Cyl. 2.2 Eng. - 38.00 Oz. R-12; 7.25 Oz. Mineral Oil	59000 ⁵⁹
	4 Cyl. 2.5 Eng. - 38.00 Oz. R-12; 7.25 Oz. Mineral Oil	59000 ⁵⁹
88-86	All Eng. - 38.00 Oz. R-12; 7.25 Oz. Mineral Oil	59000 ⁵⁹
85	All Eng. - 37.00 Oz. R-12; 7.25 Oz. Mineral Oil	59000 ⁵⁹
84-81	4 Cyl. 2.2 Eng. - See Under Hood Decal	59000 ⁵⁹
	4 Cyl. 2.6 Eng. - See Under Hood Decal	59000 ⁵⁹
SAPORO		
83-81	4 Cyl. 2.6 Eng. - See Under Hood Decal	59000 ⁵⁹
SUNDANCE		
94	4 Cyl. 2.2 Eng. - 26.00 Oz. R-134a; 7.25 Oz. PAG-46	59007
	4 Cyl. 2.5 Eng. - 26.00 Oz. R-134a; 7.25 Oz. PAG-46	59007

Continued on Next Page

⁵⁹ When retrofitting to R134a PAG Oil must be used.

PLYMOUTH

Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that A/C system has been properly cleaned, and new accumulator / filter drier has been installed. Specs are for total system capacities. Always refer to under hood decal as the primary source for refrigerant and lubricant information.

Year	Model	Lubricant
SUNDANCE (Cont'd)		
94	6 Cyl. 3.0 Eng. - 26.00 Oz. R-134a; 7.25 Oz. PAG-46	59007
93-91	All Eng. - 32.00 Oz. R-12; 7.25 Oz. Mineral Oil	59000 ⁵⁹
90-89	4 Cyl. 2.2 Eng. - See Under Hood Decal	59000 ⁵⁹
	4 Cyl. 2.5 Eng. - See Under Hood Decal	59000 ⁵⁹
88-87	All Eng. - 38.00 Oz. R-12; 7.25 Oz. Mineral Oil	59000 ⁵⁹
TRAILDUSTER		
81	8 Cyl. 5.2 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.9 Eng. - See Under Hood Decal	59000 ⁵⁹
TURISMO		
85-83	4 Cyl. 1.6 Eng. - See Under Hood Decal	59000 ⁵⁹
VOLARE		
80	6 Cyl. 3.7 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.2 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.9 Eng. - See Under Hood Decal	59000 ⁵⁹
VOYAGER / GRAND VOYAGER		
00	All Eng.; w/o Rear AC - 34.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
	All Eng.; w/ Rear AC - 46.00 Oz. R-134a; 7.40 Oz. PAG-46	59007
99-96	All Eng.; w/o Rear AC - 34.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
	All Eng.; w/ Rear AC - 48.00 Oz. R-134a; 7.50 Oz. PAG-46	59007
95-94	All Eng.; w/o Rear AC - 36.00 Oz. R-134a; 4.73 Oz. PAG-46	59007
	All Eng.; w/ Rear AC - 50.00 Oz. R-134a; 7.40 Oz. PAG-46	59007
93	All Eng.; w/o Rear AC - 36.00 Oz. R-134a; 4.73 Oz. PAG-46	59007
	All Eng.; w/ Rear AC - 50.00 Oz. R-134a; 7.40 Oz. PAG-46	59007
	4 Cyl. 2.5 Eng. - w/ R-12	59000 ⁵⁹
	6 Cyl. 3.0 Eng. - w/ R-12	59000 ⁵⁹
	6 Cyl. 3.3 Eng. - w/ R-12	59000 ⁵⁹
92	All Eng.; w/o Rear AC - 33.50 Oz. R-12; 7.25 Oz. Mineral Oil; w/ Fixed Displacement Compressor	59000 ⁵⁹
	All Eng.; w/o Rear AC - 33.50 Oz. R-12; 8.75 Oz. Mineral Oil; w/ Variable Displacement Compressor	59000 ⁵⁹
	All Eng.; w/ Rear AC - 44.00 Oz. R-12; 13.00 Oz. Mineral Oil; w/ Fixed Displacement Compressor	59000 ⁵⁹
	All Eng.; w/ Rear AC - 44.00 Oz. R-12; 13.00 Oz. Mineral Oil; w/ Variable Displacement Compressor	59000 ⁵⁹
91-90	All Eng.; w/o Rear AC - 32.00 Oz. R-12; 7.25 Oz. Mineral Oil; w/ Fixed Displacement Compressor	59000 ⁵⁹
	All Eng.; w/o Rear AC - 32.00 Oz. R-12; 8.75 Oz. Mineral Oil; w/ Variable Displacement Compressor	59000 ⁵⁹
	All Eng.; w/ Rear AC - 43.00 Oz. R-12; 13.00 Oz. Mineral Oil; w/ Fixed Displacement Compressor	59000 ⁵⁹
	All Eng.; w/ Rear AC - 43.00 Oz. R-12; 13.00 Oz. Mineral Oil; w/ Variable Displacement Compressor	59000 ⁵⁹
89	All Eng.; w/o Rear AC - 38.00 Oz. R-12; 7.25 Oz. Mineral Oil; w/ Fixed Displacement Compressor	59000 ⁵⁹
	All Eng.; w/o Rear AC - 38.00 Oz. R-12; 8.75 Oz. Mineral Oil; w/ Variable Displacement Compressor	59000 ⁵⁹
	All Eng.; w/ Rear AC - 43.00 Oz. R-12; 13.00 Oz. Mineral Oil; w/ Fixed Displacement Compressor	59000 ⁵⁹
	All Eng.; w/ Rear AC - 43.00 Oz. R-12; 13.00 Oz. Mineral Oil; w/ Variable Displacement Compressor	59000 ⁵⁹
88	All Eng.; w/o Rear AC - 44.00 Oz. R-12; 7.25 Oz. Mineral Oil	59000 ⁵⁹
87-86	All Eng.; w/o Rear AC - 38.00 Oz. R-12; 7.00 Oz. Mineral Oil	59000 ⁵⁹
85	4 Cyl. 2.2 Eng. - 38.00 Oz. R-12; 7.00 Oz. Mineral Oil	59000 ⁵⁹
	4 Cyl. 2.6 Eng. - 38.00 Oz. R-12; 7.00 Oz. Mineral Oil	59000 ⁵⁹
84	4 Cyl. 2.2 Eng. - See Under Hood Decal	59000 ⁵⁹
	4 Cyl. 2.6 Eng. - See Under Hood Decal	59000 ⁵⁹

PONTIAC

Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that A/C system has been properly cleaned, and new accumulator / filter drier has been installed. Specs are for total system capacities. Always refer to under hood decal as the primary source for refrigerant and lubricant information.

Year	Model	Lubricant
6000		
91-88	All Eng. - 44.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
87-86	STE - 36.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
	Excl. STE - 44.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
85	All Eng. - 44.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
84-82	4 Cyl. 2.5 Eng. - See Under Hood Decal	59000 ⁵⁹
	6 Cyl. 2.8 Eng. - See Under Hood Decal	59000 ⁵⁹
AZTEK		
05-01	All Eng. - 27.00 Oz. R-134a; 7.50 Oz. PAG-46	59007

Continued on Next Page

⁵⁹ When retrofitting to R134a PAG Oil must be used.

Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that A/C system has been properly cleaned, and new accumulator / filter drier has been installed. Specs are for total system capacities. Always refer to under hood decal as the primary source for refrigerant and lubricant information.

Year	Model	Lubricant
BONNEVILLE		
05-02	All Eng. - 35.00 Oz. R-134a; 9.00 Oz. PAG-150	59003
01-98	All Eng. - 32.00 Oz. R-134a; 9.00 Oz. PAG-150	59003
97-96	All Eng. - 32.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
95-94	All Eng. - 39.00 Oz. R-134a; 8.00 Oz. PAG-150; w/ OE Harrison Compressor	59003
	All Eng. - 39.00 Oz. R-134a; 8.00 Oz. PAG-46; w/ Denso Compressor	59007
93-91	All Eng. - 39.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
90-89	All Eng. - 38.50 Oz. R-12; 8.00 Oz. Mineral Oil	59000
88-87	All Eng. - 53.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
86	6 Cyl. 3.8 Eng. - See Under Hood Decal	59000 ⁵⁹
	6 Cyl. 4.3 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.0 Eng. - See Under Hood Decal	59000 ⁵⁹
85-84	6 Cyl. 3.8 Eng. - See Under Hood Decal	59000
	8 Cyl. 5.0 Eng. - See Under Hood Decal	59000 ⁵⁹
73-70	8 Cyl. 5.7 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 6.6 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 7.5 Eng. - See Under Hood Decal	59000 ⁵⁹
69-68	8 Cyl. 6.6 Eng. - See Under Hood Decal	59000
	8 Cyl. 7.0 Eng. - See Under Hood Decal	59000 ⁵⁹
CATALINA		
73-71	6 Cyl. 4.1 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.7 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 6.6 Eng. - See Under Hood Decal	59000
	8 Cyl. 7.5 Eng. - See Under Hood Decal	59000 ⁵⁹
70	8 Cyl. 5.7 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 6.6 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 7.5 Eng. - See Under Hood Decal	59000 ⁵⁹
69-68	8 Cyl. 6.6 Eng. - See Under Hood Decal	59000
	8 Cyl. 7.0 Eng. - See Under Hood Decal	59000 ⁵⁹
FIERO		
88-86	All Eng. - 40.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
85	4 Cyl. 2.5 Eng. - 40.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
84	6 Cyl. 2.8 Eng. - 40.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
	4 Cyl. 2.5 Eng. - See Under Hood Decal	59000 ⁵⁹
FIREBIRD		
02-98	All Eng. - 24.00 Oz. R-134a; 9.00 Oz. PAG-150	59003
97	6 Cyl. 3.8 Eng. - 26.00 Oz. R-134a; 8.00 Oz. PAG-150; w/ OE Harrison Compressor	59003
	6 Cyl. 3.8 Eng. - 26.00 Oz. R-134a; 8.00 Oz. PAG-46; w/ Denso Compressor	59007
	8 Cyl. 5.7 Eng. - 32.00 Oz. R-134a; 8.00 Oz. PAG-150; w/ OE Harrison Compressor	59003
	8 Cyl. 5.7 Eng. - 32.00 Oz. R-134a; 8.00 Oz. PAG-46; w/ Denso Compressor	59007
96	6 Cyl. 3.8 Eng. - 28.00 Oz. R-134a; 8.00 Oz. PAG-150; w/ OE Harrison Compressor	59003
	6 Cyl. 3.8 Eng. - 28.00 Oz. R-134a; 8.00 Oz. PAG-46; w/ Denso Compressor	59007
	8 Cyl. 5.7 Eng. - 32.00 Oz. R-134a; 8.00 Oz. PAG-150; w/ OE Harrison Compressor	59003
95-94	8 Cyl. 5.7 Eng. - 32.00 Oz. R-134a; 8.00 Oz. PAG-46; w/ Denso Compressor	59007
	All Eng. - 32.00 Oz. R-134a; 8.00 Oz. PAG-150; w/ OE Harrison Compressor	59003
93	All Eng. - 32.00 Oz. R-134a; 8.00 Oz. PAG-46; w/ Denso Compressor	59007
	All Eng. - 32.00 Oz. R-134a; 8.00 Oz. PAG-150; w/ OE Harrison Compressor	59003
92-89	All Eng. - 32.00 Oz. R-134a; 8.00 Oz. PAG-46; w/ Denso Compressor	59007
	6 Cyl. 3.4 Eng. - w/ R-12; w/ OE Harrison Compressor	59000 ⁵⁹
	8 Cyl. 5.7 Eng. - w/ R-12; w/ OE Harrison Compressor	59000 ⁵⁹
88-87	All Eng. - 36.00 Oz. R-12; 6.00 Oz. Mineral Oil	59000 ⁵⁹
86	6 Cyl. 2.8 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.0 Eng. - See Under Hood Decal	59000
	8 Cyl. 5.7 Eng. - See Under Hood Decal	59000 ⁵⁹
85-83	All Eng. - 48.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
	4 Cyl. 2.5 Eng. - See Under Hood Decal	59000 ⁵⁹
	6 Cyl. 2.8 Eng. - See Under Hood Decal	59000 ⁵⁹
82	8 Cyl. 5.0 Eng. - See Under Hood Decal	59000
	4 Cyl. 2.5 Eng. - See Under Hood Decal	59000 ⁵⁹
73-70	6 Cyl. 4.1 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.7 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 6.6 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 7.5 Eng. - See Under Hood Decal	59000 ⁵⁹
69-68	6 Cyl. 4.1 Eng. - See Under Hood Decal	59000 ⁵⁹

Continued on Next Page

⁵⁹ When retrofitting to R134a PAG Oil must be used.

PONTIAC

Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that A/C system has been properly cleaned, and new accumulator / filter drier has been installed. Specs are for total system capacities. Always refer to under hood decal as the primary source for refrigerant and lubricant information.

Year	Model	Lubricant
FIREBIRD (Cont'd)		
69-68	8 Cyl. 5.7 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 6.6 Eng. - See Under Hood Decal	59000 ⁵⁹
67	6 Cyl. 3.8 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.3 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 6.6 Eng. - See Under Hood Decal	59000 ⁵⁹
G3		
09	4 Cyl. 1.6 Eng. - 17.00 Oz. R-134a; 6.80 Oz. PAG-46	59007
G5		
09	4 Cyl. 2.2 Eng. - 14.50 Oz. R-134a; 5.00 Oz. PAG-46	59007
08-07	All Eng. - 14.50 Oz. R-134a; 5.00 Oz. PAG-46	59007
G6		
10	4 Cyl. 2.4 Eng. - 18.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
	6 Cyl. 3.5 Eng. - 18.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
09	4 Cyl. 2.4 Eng. - 18.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
	6 Cyl. 3.5 Eng. - 18.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
	6 Cyl. 3.6 Eng. - 18.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
	6 Cyl. 3.9 Eng. - 18.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
08-05	All Eng. - 18.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
G8		
09	6 Cyl. 3.6 Eng. - 21.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
	8 Cyl. 6.0 Eng. - 21.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
	8 Cyl. 6.2 Eng. - 21.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
08	6 Cyl. 3.6 Eng. - 21.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
	8 Cyl. 6.0 Eng. - 21.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
GRAND AM		
05-02	4 Cyl. 2.2 Eng. - 35.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
	6 Cyl. 3.4 Eng. - 28.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
01-99	All Eng. - 28.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
98-95	All Eng. - 36.00 Oz. R-134a; 9.00 Oz. PAG-150	59003
94	All Eng. - 36.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
93	All Eng. - 42.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
92	All Eng. - 42.50 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
91-88	All Eng. - 36.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
87-86	All Eng. - 44.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
85	4 Cyl. 2.5 Eng. - 44.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
	6 Cyl. 3.0 Eng. - 44.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
GRAND PRIX		
08-06	6 Cyl. 3.8 Eng. - 21.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
	8 Cyl. 5.3 Eng. - 19.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
05	6 Cyl. 3.8 Eng. - 37.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
	8 Cyl. 5.3 Eng. - 19.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
04	All Eng. - 37.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
03-98	All Eng. - 36.00 Oz. R-134a; 9.00 Oz. PAG-150	59003
97	All Eng. - 36.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
96-95	All Eng. - 32.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
94	All Eng. - 32.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
	6 Cyl. 3.1 Eng. - See Under Hood Decal	59000 ⁵⁹
	6 Cyl. 3.4 Eng. - See Under Hood Decal	59000 ⁵⁹
93-92	All Eng. - 36.00 Oz. R-12; 9.00 Oz. Mineral Oil	59000 ⁵⁹
91-88	All Eng. - 36.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
87-86	6 Cyl. 3.8 Eng. - See Under Hood Decal	59000 ⁵⁹
	6 Cyl. 4.3 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.0 Eng. - See Under Hood Decal	59000 ⁵⁹
85	6 Cyl. 3.8 Eng. - 36.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
	8 Cyl. 5.0 Eng. - See Under Hood Decal	59000 ⁵⁹
84	6 Cyl. 3.8 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.0 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.7 Eng. - See Under Hood Decal	59000 ⁵⁹
73-70	8 Cyl. 5.7 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 6.6 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 7.5 Eng. - See Under Hood Decal	59000 ⁵⁹
69-68	8 Cyl. 6.6 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 7.0 Eng. - See Under Hood Decal	59000 ⁵⁹

Continued on Next Page

⁵⁹ When retrofitting to R134a PAG Oil must be used.

Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that A/C system has been properly cleaned, and new accumulator / filter drier has been installed. Specs are for total system capacities. Always refer to under hood decal as the primary source for refrigerant and lubricant information.

Year	Model	Lubricant
	GTO	
06-04	All Eng. - 29.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
	J2000	
84-83	4 Cyl. 1.8 Eng. - See Under Hood Decal	59000 ⁵⁹
	4 Cyl. 2.0 Eng. - See Under Hood Decal	59000 ⁵⁹
82	4 Cyl. 1.8 Eng. - See Under Hood Decal	59000 ⁵⁹
	LEMANS	
93-88	All Eng. - 35.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
73-70	6 Cyl. 4.1 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.7 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 6.6 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 7.5 Eng. - See Under Hood Decal	59000 ⁵⁹
69-68	6 Cyl. 4.1 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.7 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 6.6 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 7.0 Eng. - See Under Hood Decal	59000 ⁵⁹
	MONTANA	
07-01	All Eng.; w/o Rear AC - 27.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
	All Eng.; w/ Rear AC - 35.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
00-99	All Eng.; w/o Rear AC - 32.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
	All Eng.; w/ Rear AC - 46.00 Oz. R-134a; 11.00 Oz. PAG-150	59003
	PARISIENNE	
86-85	All Eng. - 60.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
84	6 Cyl. 3.8 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.0 Eng. - See Under Hood Decal	59000 ⁵⁹
	PHOENIX	
84-82	4 Cyl. 2.5 Eng. - See Under Hood Decal	59000 ⁵⁹
	6 Cyl. 2.8 Eng. - See Under Hood Decal	59000 ⁵⁹
	SAFARI	
89-87	8 Cyl. 5.0 Eng. - See Under Hood Decal	59000 ⁵⁹
	SOLSTICE	
09	4 Cyl. 2.0 Eng. - 16.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
	4 Cyl. 2.4 Eng. - 16.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
08	All Eng. - 16.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
07-06	All Eng. - 26.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
	SUNBIRD	
94	All Eng. - 36.00 Oz. R-134a; 9.00 Oz. PAG-150	59003
93-88	All Eng. - 36.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
87	All Eng. - 44.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
86	4 Cyl. 1.8 Eng. - 44.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
	4 Cyl. 2.0 Eng. - 44.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
85	4 Cyl. 1.8 Eng. - 44.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
	4 Cyl. 2.0 Eng. - See Under Hood Decal	59000 ⁵⁹
	SUNFIRE	
05-03	All Eng. - 24.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
02	4 Cyl. 2.2 Eng. - 21.00 Oz. R-134a; 5.00 Oz. PAG-46; w/ CVC Compressor	59007
	4 Cyl. 2.2 Eng. - 24.00 Oz. R-134a; 9.00 Oz. PAG-150; w/ V5 Compressor	59003
	4 Cyl. 2.4 Eng. - 21.00 Oz. R-134a; 9.00 Oz. PAG-150	59003
01-95	All Eng. - 24.00 Oz. R-134a; 9.00 Oz. PAG-150	59003
	TEMPEST	
70	6 Cyl. 4.1 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.7 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 6.6 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 7.5 Eng. - See Under Hood Decal	59000 ⁵⁹
69	6 Cyl. 4.1 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 6.6 Eng. - See Under Hood Decal	59000 ⁵⁹
68	6 Cyl. 4.1 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.7 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 6.6 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 7.0 Eng. - See Under Hood Decal	59000 ⁵⁹
	TORRENT	
09	6 Cyl. 3.4 Eng. - 21.00 Oz. R-134a; 4.50 Oz. PAG-46	59007
	6 Cyl. 3.6 Eng. - 21.00 Oz. R-134a; 4.50 Oz. PAG-46	59007
08-06	All Eng. - 21.00 Oz. R-134a; 4.50 Oz. PAG-46	59007

Continued on Next Page

⁵⁹ When retrofitting to R134a PAG Oil must be used.

PONTIAC

Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that A/C system has been properly cleaned, and new accumulator / filter drier has been installed. Specs are for total system capacities. Always refer to under hood decal as the primary source for refrigerant and lubricant information.

Year	Model	Lubricant
TRANS SPORT		
98-97	All Eng.; w/o Rear AC - 32.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
	All Eng.; w/ Rear AC - 46.00 Oz. R-134a; 11.00 Oz. PAG-150	59003
96	6 Cyl. 3.4 Eng.; w/o Rear AC - 36.00 Oz. R-134a; 8.00 Oz. PAG-150; w/ OE Harrison Compressor	59003
	6 Cyl. 3.4 Eng.; w/ Rear AC - 48.00 Oz. R-134a; 11.00 Oz. PAG-150; w/ OE Harrison Compressor	59003
95	All Eng.; w/o Rear AC - 36.00 Oz. R-134a; 8.00 Oz. PAG-150; w/ OE Harrison Compressor	59003
	All Eng.; w/o Rear AC - 36.00 Oz. R-134a; 8.00 Oz. PAG-46; w/ Denso Compressor	59007
	All Eng.; w/ Rear AC - 48.00 Oz. R-134a; 11.00 Oz. PAG-150; w/ OE Harrison Compressor	59003
	All Eng.; w/ Rear AC - 48.00 Oz. R-134a; 11.00 Oz. PAG-46; w/ Denso Compressor	59007
94	6 Cyl. 3.1 Eng. - See Under Hood Decal	59003
	6 Cyl. 3.1 Eng. - See Under Hood Decal; w/ Denso Compressor	59007
	6 Cyl. 3.8 Eng. - See Under Hood Decal	59003
	6 Cyl. 3.8 Eng. - See Under Hood Decal; w/ Denso Compressor	59007
93-92	6 Cyl. 3.1 Eng. - See Under Hood Decal	59000 ⁵⁹
	6 Cyl. 3.8 Eng. - See Under Hood Decal	59000 ⁵⁹
91-90	6 Cyl. 3.1 Eng. - See Under Hood Decal	59000 ⁵⁹
VENTURA		
73-71	6 Cyl. 4.1 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.0 Eng. - See Under Hood Decal	59000 ⁵⁹
	8 Cyl. 5.7 Eng. - See Under Hood Decal	59000 ⁵⁹
VIBE		
10-09	4 Cyl. 1.8 Eng. - 23.00 Oz. R-134a; 8.50 Oz. PAG-46	59007
	4 Cyl. 2.4 Eng. - 23.00 Oz. R-134a; 8.50 Oz. PAG-46	59007
08-04	All Eng. - 23.00 Oz. R-134a; 8.50 Oz. PAG-46	59007
03	All Eng. - 23.00 Oz. R-134a; 4.00 Oz. PAG-46	59007

PORSCHE

Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that A/C system has been properly cleaned, and new accumulator / filter drier has been installed. Specs are for total system capacities. Always refer to under hood decal as the primary source for refrigerant and lubricant information.

Year	Model	Lubricant
911 SERIES		
13	6 Cyl. 3.4 Eng. - 30.00 Oz. R-134a; See Under Hood Decal	59007
	6 Cyl. 3.8 Eng. - 30.00 Oz. R-134a; See Under Hood Decal	59007
12	6 Cyl. 3.4 Eng. - 30.00 Oz. R-134a; See Under Hood Decal	59007
	6 Cyl. 3.6 Eng. - 30.00 Oz. R-134a; See Under Hood Decal	59007
	6 Cyl. 3.8 Eng. - 30.00 Oz. R-134a; See Under Hood Decal	59007
11-08	6 Cyl. 3.6 Eng. - 30.00 Oz. R-134a; See Under Hood Decal	59007
	6 Cyl. 3.8 Eng. - 30.00 Oz. R-134a; See Under Hood Decal	59007
07-05	All Eng.; AWD - 30.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
	All Eng.; RWD - 32.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
04-01	All Eng. - 31.00 Oz. R-134a; 6.50 Oz. PAG-46	59007
00-99	All Eng. - 28.00 Oz. R-134a; 6.50 Oz. PAG-46	59007
98-93	All Eng. - 29.50 Oz. R-134a; 4.75 Oz. PAG-46	59007
92-90	All Eng. - 33.00 Oz. R-12; 3.50 Oz. Mineral Oil	59000 ⁵⁹
89	All Eng. - 33.00 Oz. R-12; 4.00 Oz. Mineral Oil	59000 ⁵⁹
88-86	6 Cyl. 3.2 Eng. - See Under Hood Decal	59000 ⁵⁹
	6 Cyl. 3.3 Eng. - See Under Hood Decal	59000 ⁵⁹
85	6 Cyl. 3.2 Eng. - See Under Hood Decal	59000 ⁵⁹
924 SERIES		
88-87	All Eng. - 30.00 Oz. R-12; 7.25 Oz. Mineral Oil	59000 ⁵⁹
78	4 Cyl. 2.0 Eng. - See Under Hood Decal	59000 ⁵⁹
928 SERIES		
95-93	All Eng. - 30.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
91-89	All Eng. - 33.50 Oz. R-12; 9.00 Oz. Mineral Oil	59000 ⁵⁹
88-85	8 Cyl. 5.0 Eng. - 33.50 Oz. R-12; 9.00 Oz. Mineral Oil	59000 ⁵⁹
944 SERIES		
91-89	All Eng. - 33.50 Oz. R-12; 5.75 Oz. Mineral Oil	59000 ⁵⁹
88-85	4 Cyl. 2.5 Eng. - 33.50 Oz. R-12; 5.75 Oz. Mineral Oil	59000 ⁵⁹
968 SERIES		
95-93	All Eng. - 30.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
92	All Eng. - 33.50 Oz. R-12; 5.75 Oz. Mineral Oil	59000 ⁵⁹

Continued on Next Page

⁵⁹ When retrofitting to R134a PAG Oil must be used.

Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that A/C system has been properly cleaned, and new accumulator / filter drier has been installed. Specs are for total system capacities. Always refer to under hood decal as the primary source for refrigerant and lubricant information.

Year	Model	Lubricant
BOXSTER		
13	6 Cyl. 2.7 Eng. - 30.00 Oz. R-134a; 6.10-7.10 Oz. PAG-46	59007
	6 Cyl. 3.4 Eng. - 30.00 Oz. R-134a; See Under Hood Decal	59007
12-09	6 Cyl. 2.9 Eng. - 30.00 Oz. R-134a; 6.10-7.10 Oz. PAG-46	59007
	6 Cyl. 3.4 Eng. - 30.00 Oz. R-134a; See Under Hood Decal	59007
08	6 Cyl. 2.7 Eng. - 30.00 Oz. R-134a; 6.10-7.10 Oz. PAG-46	59007
	6 Cyl. 3.4 Eng. - 30.00 Oz. R-134a; See Under Hood Decal	59007
07-06	All Eng. - 32.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
05-97	All Eng. - 30.00 Oz. R-134a; 6.50 Oz. PAG-46	59007
CAYENNE		
06	All Eng.; w/o Rear AC - 25.00 Oz. R-134a; 6.50 Oz. PAG-46	59007
	All Eng.; w/ Rear AC - 37.00 Oz. R-134a; 10.00 Oz. PAG-46	59007
05-04	All Eng.; w/o Rear AC - 27.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
	All Eng.; w/ Rear AC - 39.00 Oz. R-134a; 12.00 Oz. PAG-46	59007
CAYMAN		
14	6 Cyl. 3.4 Eng. - See Under Hood Decal	59007
12-09	6 Cyl. 2.9 Eng. - 30.00 Oz. R-134a; 6.10-7.10 Oz. PAG-46	59007
	6 Cyl. 3.4 Eng. - 30.00 Oz. R-134a; See Under Hood Decal	59007
08	6 Cyl. 2.7 Eng. - 30.00 Oz. R-134a; See Under Hood Decal	59007
	6 Cyl. 3.4 Eng. - 30.00 Oz. R-134a; See Under Hood Decal	59007
07	6 Cyl. 2.7 Eng. - 30.00 Oz. R-134a; See Under Hood Decal	59007
	6 Cyl. 3.4 Eng. - 30.00 Oz. R-134a; 6.60 Oz. PAG-46	59007
06	6 Cyl. 3.4 Eng. - 30.00 Oz. R-134a; 6.60 Oz. PAG-46	59007

RENAULT

Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that A/C system has been properly cleaned, and new accumulator / filter drier has been installed. Specs are for total system capacities. Always refer to under hood decal as the primary source for refrigerant and lubricant information.

Year	Model	Lubricant
ALLIANCE		
87	4 Cyl. 1.4 Eng. - See Under Hood Decal	59000 ⁵⁹
	4 Cyl. 1.7 Eng. - See Under Hood Decal	59000 ⁵⁹
	4 Cyl. 2.0 Eng. - See Under Hood Decal	59000 ⁵⁹
86-85	4 Cyl. 1.4 Eng. - See Under Hood Decal	59000 ⁵⁹
	4 Cyl. 1.7 Eng. - See Under Hood Decal	59000 ⁵⁹
ENCORE		
86-85	4 Cyl. 1.4 Eng. - See Under Hood Decal	59000 ⁵⁹
	4 Cyl. 1.7 Eng. - See Under Hood Decal	59000 ⁵⁹

SAAB

Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that A/C system has been properly cleaned, and new accumulator / filter drier has been installed. Specs are for total system capacities. Always refer to under hood decal as the primary source for refrigerant and lubricant information.

Year	Model	Lubricant
9-2		
06	4 Cyl. 2.5 Eng. - 16.00 Oz. R-134a; 4.90 Oz. PAG-100	59002
05	4 Cyl. 2.0 Eng. - 16.00 Oz. R-134a; 4.90 Oz. PAG-100	59002
	4 Cyl. 2.5 Eng. - 16.00 Oz. R-134a; 4.90 Oz. PAG-100	59002
9-3		
11-10	4 Cyl. 2.0 Eng. - 24.00 Oz. R-134a; 4.56 Oz. PAG-46	59007
09	4 Cyl. 2.0 Eng. - 24.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
	6 Cyl. 2.8 Eng. - 24.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
08-03	All Eng. - 24.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
02-99	All Eng. - 28.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
9-5		
11	4 Cyl. 2.0 Eng. - 24.00 Oz. R-134a; 3.70 Oz. PAG-46; w/ Sanden Compressor	59007
	4 Cyl. 2.0 Eng. - 24.00 Oz. R-134a; 5.00 Oz. PAG-46; w/ Delphi Compressor	59007
	6 Cyl. 2.8 Eng. - 24.00 Oz. R-134a; 3.70 Oz. PAG-46; w/ Sanden Compressor	59007
	6 Cyl. 2.8 Eng. - 24.00 Oz. R-134a; 5.00 Oz. PAG-46; w/ Delphi Compressor	59007
10	6 Cyl. 2.8 Eng. - 24.00 Oz. R-134a; 3.70 Oz. PAG-46; w/ Sanden Compressor	59007

Continued on Next Page

⁵⁹ When retrofitting to R134a PAG Oil must be used.

SAAB

Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that A/C system has been properly cleaned, and new accumulator / filter drier has been installed. Specs are for total system capacities. Always refer to under hood decal as the primary source for refrigerant and lubricant information.

Year	Model	Lubricant
9-5 (Cont'd)		
10	6 Cyl. 2.8 Eng. - 24.00 Oz. R-134a; 5.00 Oz. PAG-46; w/ Delphi Compressor	59007
09	4 Cyl. 2.3 Eng. - 29.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
08-04	All Eng. - 29.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
03-00	All Eng. - 31.00 Oz. R-134a; 4.90 Oz. PAG-46	59007
99	All Eng. - 29.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
9-7		
09	6 Cyl. 4.2 Eng. - 30.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
	8 Cyl. 5.3 Eng. - 30.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
	8 Cyl. 6.0 Eng. - 30.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
08-05	All Eng. - 30.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
900 SERIES		
98-97	All Eng. - 25.50 Oz. R-134a; 5.00 Oz. PAG-100; w/ Sanden Compressor	59002
	All Eng. - 25.50 Oz. R-134a; 6.75 Oz. PAG-100; w/ Seiko Seiki Compressor	59002
96-94	All Eng. - 25.50 Oz. R-134a; 6.75 Oz. PAG-100	59002
93	4 Cyl. 2.0 Eng. - See Under Hood Decal	59000 ⁵⁹
	4 Cyl. 2.1 Eng. - See Under Hood Decal	59000 ⁵⁹
92-89	All Eng. - 35.00 Oz. R-12; 5.75 Oz. Mineral Oil	59000 ⁵⁹
88-86	4 Cyl. 2.0 Eng. - See Under Hood Decal	59000 ⁵⁹
9000 SERIES		
98	4 Cyl. 2.3 Eng. - 33.00 Oz. R-134a; 6.76 Oz. PAG-100	59002
97-95	4 Cyl. 2.3 Eng. - 33.00 Oz. R-134a; 6.76 Oz. PAG-100	59002
	6 Cyl. 3.0 Eng. - 33.00 Oz. R-134a; 6.76 Oz. PAG-100	59002
94	4 Cyl. 2.3 Eng. - 33.00 Oz. R-134a; 6.76 Oz. PAG-100	59002
93	4 Cyl. 2.3 Eng. - 33.00 Oz. R-134a; 6.76 Oz. Mineral Oil	59000 ⁵⁹
92	All Eng.; w/o Rear AC - 39.00 Oz. R-12; 5.50 Oz. Mineral Oil	59000 ⁵⁹
	All Eng.; w/ Rear AC - 39.00 Oz. R-12; 5.50 Oz. Mineral Oil	59000 ⁵⁹
91-89	All Eng. - 39.00 Oz. R-12; 5.50 Oz. Mineral Oil	59000 ⁵⁹
88-86	4 Cyl. 2.0 Eng. - 39.00 Oz. R-12; 5.50 Oz. Mineral Oil	59000 ⁵⁹

SATURN

Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that A/C system has been properly cleaned, and new accumulator / filter drier has been installed. Specs are for total system capacities. Always refer to under hood decal as the primary source for refrigerant and lubricant information.

Year	Model	Lubricant
ASTRA		
08	4 Cyl. 1.8 Eng. - 14.00 Oz. R-134a; See Under Hood Decal	59007
AURA		
09	4 Cyl. 2.4 Eng.; Hybrid - 18.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
	6 Cyl. 3.6 Eng.; Excl. Hybrid - 18.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
08-07	All Eng.; Excl. Hybrid - 18.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
	All Eng.; Hybrid - 18.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
ION		
07-03	All Eng. - 14.50 Oz. R-134a; 5.00 Oz. PAG-46	59007
L SERIES		
05-02	All Eng. - 33.50 Oz. R-134a; 7.50 Oz. PAG-100	59002
01	4 Cyl. 2.2 Eng. - 33.50 Oz. R-134a; 7.50 Oz. PAG-100	59002
	6 Cyl. 3.0 Eng. - 33.50 Oz. R-134a; 7.50 Oz. PAG-100	59002
LS SERIES		
01-00	All Eng. - 33.50 Oz. R-134a; 7.50 Oz. PAG-100	59002
LW SERIES		
04-01	All Eng. - 33.50 Oz. R-134a; 7.50 Oz. PAG-100	59002
00	4 Cyl. 2.2 Eng. - 33.50 Oz. R-134a; 7.50 Oz. PAG-100	59002
	6 Cyl. 3.0 Eng. - 33.50 Oz. R-134a; 7.50 Oz. PAG-100	59002
OUTLOOK		
10-09	6 Cyl. 3.6 Eng. - 37.00 Oz. R-134a; 6.50 Oz. PAG-46	59007
08-07	All Eng. - 37.00 Oz. R-134a; 6.50 Oz. PAG-46	59007
RELAY		
07	All Eng.; w/o Rear AC - 23.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
	All Eng.; w/ Rear AC - 32.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
06-05	All Eng.; w/o Rear AC - 27.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
	All Eng.; w/ Rear AC - 35.00 Oz. R-134a; 7.75 Oz. PAG-46	59007

Continued on Next Page

⁵⁹ When retrofitting to R134a PAG Oil must be used.

Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that A/C system has been properly cleaned, and new accumulator / filter drier has been installed. Specs are for total system capacities. Always refer to under hood decal as the primary source for refrigerant and lubricant information.

Year	Model	Lubricant
SC SERIES		
02-01	All Eng. - 24.00 Oz. R-134a; 5.00 Oz. PAG-100	59002
00	4 Cyl. 1.9 Eng. - 24.00 Oz. R-134a; 5.00 Oz. PAG-100	59002
99-97	All Eng. - 24.00 Oz. R-134a; 5.00 Oz. PAG-100	59002
96-94	All Eng. - 24.00 Oz. R-134a; 6.75 Oz. PAG-100	59002
93-91	All Eng. - 36.00 Oz. R-12; 6.75 Oz. Mineral Oil	59000 ⁵⁹
SKY		
10	4 Cyl. 2.4 Eng. - See Under Hood Decal	59007
09	4 Cyl. 2.0 Eng. - 16.00 Oz. R-134a; 4.50 Oz. PAG-46	59007
	4 Cyl. 2.4 Eng. - 16.00 Oz. R-134a; 4.50 Oz. PAG-46	59007
08-07	All Eng. - 16.00 Oz. R-134a; 4.50 Oz. PAG-46	59007
SL SERIES		
02-97	All Eng. - 24.00 Oz. R-134a; 5.00 Oz. PAG-100	59002
96-94	All Eng. - 24.00 Oz. R-134a; 6.75 Oz. PAG-100	59002
93-91	All Eng. - 36.00 Oz. R-12; 6.75 Oz. Mineral Oil	59000 ⁵⁹
SW SERIES		
01-97	All Eng. - 24.00 Oz. R-134a; 5.00 Oz. PAG-100	59002
96-94	All Eng. - 24.00 Oz. R-134a; 6.75 Oz. PAG-100	59002
93	All Eng. - 36.00 Oz. R-12; 6.75 Oz. Mineral Oil	59000 ⁵⁹
VUE		
10	6 Cyl. 3.6 Eng. - See Under Hood Decal	59007
09	4 Cyl. 2.4 Eng. - See Under Hood Decal	59007
	6 Cyl. 3.5 Eng. - 20.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
	6 Cyl. 3.6 Eng. - 20.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
08	4 Cyl. 2.4 Eng. - 20.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
	6 Cyl. 3.5 Eng. - 20.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
	6 Cyl. 3.6 Eng. - 20.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
07	4 Cyl. 2.2 Eng. - 24.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
	4 Cyl. 2.4 Eng. - 27.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
	6 Cyl. 3.5 Eng.; w/o Rear AC - 27.00 Oz. R-134a; 7.00 Oz. PAG-46	59002
	6 Cyl. 3.5 Eng.; w/ Rear AC - 38.00 Oz. R-134a; 8.00 Oz. PAG-46	59002
06-04	4 Cyl. 2.2 Eng. - 24.00 Oz. R-134a; 7.00 Oz. PAG-100	59002
	6 Cyl. 3.5 Eng. - 28.00 Oz. R-134a; 7.00 Oz. PAG-100	59002
03-02	4 Cyl. 2.2 Eng. - 24.00 Oz. R-134a; 7.00 Oz. PAG-100	59002
	6 Cyl. 3.0 Eng. - 28.00 Oz. R-134a; 7.00 Oz. PAG-100	59002

SCION

Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that A/C system has been properly cleaned, and new accumulator / filter drier has been installed. Specs are for total system capacities. Always refer to under hood decal as the primary source for refrigerant and lubricant information.

Year	Model	Lubricant
TC		
13-11	4 Cyl. 2.5 Eng. - 15.00 Oz. R-134a; See Under Hood Decal	59007
10	4 Cyl. 2.4 Eng. - 15.00 Oz. R-134a; See Under Hood Decal	59007
09	4 Cyl. 2.4 Eng. - 17.00 Oz. R-134a; See Under Hood Decal	59007
08-05	All Eng. - 17.00 Oz. R-134a; 3.50 Oz. PAG-46	59007
XA		
06-04	All Eng. - 17.00 Oz. R-134a; 3.50 Oz. PAG-46	59007
XB		
13-09	4 Cyl. 2.4 Eng. - 17.00 Oz. R-134a; 3.50 Oz. PAG-46	59007
08-04	All Eng. - 17.00 Oz. R-134a; 3.50 Oz. PAG-46	59007
XD		
13-11	4 Cyl. 1.8 Eng. - 14.00 Oz. R-134a; See Under Hood Decal	59007
10-08	4 Cyl. 1.8 Eng. - 13.00 Oz. R-134a; See Under Hood Decal	59007

⁵⁹ When retrofitting to R134a PAG Oil must be used.

SMART

Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that A/C system has been properly cleaned, and new accumulator / filter drier has been installed. Specs are for total system capacities. Always refer to under hood decal as the primary source for refrigerant and lubricant information.

Year	Model	Lubricant
	FORTWO	
11	3 Cyl. 1.0 Eng. - See Under Hood Decal	59002
	E Cyl. E Eng. - See Under Hood Decal	59002
10-08	3 Cyl. 1.0 Eng. - See Under Hood Decal	59002

STERLING

Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that A/C system has been properly cleaned, and new accumulator / filter drier has been installed. Specs are for total system capacities. Always refer to under hood decal as the primary source for refrigerant and lubricant information.

Year	Model	Lubricant
	827	
91-90	All Eng. - 36.00 Oz. R-12; 5.00 Oz. Mineral Oil	59000 ⁵⁹

SUBARU

Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that A/C system has been properly cleaned, and new accumulator / filter drier has been installed. Specs are for total system capacities. Always refer to under hood decal as the primary source for refrigerant and lubricant information.

Year	Model	Lubricant
	BAJA	
06-03	All Eng. - 24.00 Oz. R-134a; 5.00 Oz. PAG-100	59002
	BRAT	
87-86	All Eng. - 28.00 Oz. R-12; 5.50 Oz. Mineral Oil; w/ Matsushita Compressor	59000 ⁵⁹
	All Eng. - 28.00 Oz. R-12; 6.50 Oz. Mineral Oil; w/ Hitachi Compressor	59000 ⁵⁹
85	4 Cyl. 1.8 Eng. - 28.00 Oz. R-12; 6.50 Oz. Mineral Oil	59000 ⁵⁹
	FORESTER	
13-09	4 Cyl. 2.5 Eng. - 18.00 Oz. R-134a; See Under Hood Decal	59002
08	4 Cyl. 2.5 Eng. - 23.00 Oz. R-134a; 3.50 Oz. PAG-100	59002
07-02	All Eng. - 23.00 Oz. R-134a; 6.00 Oz. PAG-100	59002
01-98	All Eng. - 23.00 Oz. R-134a; 5.25 Oz. PAG-100	59002
	IMPREZA	
13-10	4 Cyl. 2.0 Eng. - 18.00 Oz. R-134a; See Under Hood Decal	59002
	4 Cyl. 2.5 Eng. - 18.00 Oz. R-134a; See Under Hood Decal	59002
09	4 Cyl. 2.5 Eng. - 18.00 Oz. R-134a; See Under Hood Decal	59002
08	4 Cyl. 2.5 Eng. - 18.00 Oz. R-134a; 4.90 Oz. PAG-100	59002
07	4 Cyl. 2.5 Eng. - 21.00 Oz. R-134a; 5.20 Oz. PAG-100	59002
06-02	All Eng. - 21.00 Oz. R-134a; 5.20 Oz. PAG-100	59002
01-97	All Eng. - 21.00 Oz. R-134a; 5.00 Oz. PAG-100	59002
96-94	All Eng. - 24.00 Oz. R-134a; 4.00 Oz. PAG-100	59002
93	All Eng. - 26.50 Oz. R-12; 6.00 Oz. Mineral Oil	59000 ⁵⁹
	IMPREZA OUTBACK	
13-10	4 Cyl. 2.0 Eng. - 18.00 Oz. R-134a; See Under Hood Decal	59002
	4 Cyl. 2.5 Eng. - 18.00 Oz. R-134a; See Under Hood Decal	59002
09	4 Cyl. 2.5 Eng. - 18.00 Oz. R-134a; See Under Hood Decal	59002
08	4 Cyl. 2.5 Eng. - 18.00 Oz. R-134a; 4.90 Oz. PAG-100	59002
07-02	4 Cyl. 2.5 Eng. - 21.00 Oz. R-134a; 5.20 Oz. PAG-100	59002
01	4 Cyl. 2.2 Eng. - 21.00 Oz. R-134a; 5.20 Oz. PAG-100	59002
00	All Eng. - 21.00 Oz. R-134a; 5.20 Oz. PAG-100	59002
99-97	4 Cyl. 2.2 Eng. - 21.00 Oz. R-134a; 5.20 Oz. PAG-100	59002
96	4 Cyl. 2.2 Eng. - 24.00 Oz. R-134a; See Under Hood Decal	59002
95	4 Cyl. 1.8 Eng. - 24.00 Oz. R-134a; See Under Hood Decal	59003
	JUSTY	
94-87	3 Cyl. 1.2 Eng. - 27.00 Oz. R-12; See Under Hood Decal	59000 ⁵⁹
	LEGACY	
13-10	4 Cyl. 2.5 Eng. - See Under Hood Decal	59002
	6 Cyl. 3.6 Eng. - See Under Hood Decal	59002
09-08	4 Cyl. 2.5 Eng. - See Under Hood Decal	59002
	6 Cyl. 3.0 Eng. - See Under Hood Decal	59002
07-05	4 Cyl. 2.5 Eng. - See Under Hood Decal	59002
04-01	All Eng. - 23.00 Oz. R-134a; 4.50 Oz. PAG-100	59002
00-99	All Eng. - 23.00 Oz. R-134a; 5.50 Oz. PAG-100	59002

Continued on Next Page

⁵⁹ When retrofitting to R134a PAG Oil must be used.

Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that A/C system has been properly cleaned, and new accumulator / filter drier has been installed. Specs are for total system capacities. Always refer to under hood decal as the primary source for refrigerant and lubricant information.

Year	Model	Lubricant
LEGACY (Cont'd)		
98-94	All Eng. - 26.50 Oz. R-134a; 5.50 Oz. PAG-100	59002
93-92	All Eng. - 24.00 Oz. R-12; 5.00 Oz. Mineral Oil; w/ Zexel Compressor	59000 ⁵⁹
	All Eng. - 24.00 Oz. R-12; 8.00 Oz. Mineral Oil; w/ Calsonic Compressor	59000 ⁵⁹
91-90	All Eng. - 24.00 Oz. R-12; 5.00 Oz. Mineral Oil; w/ Diesel Kiki Compressor	59000 ⁵⁹
	All Eng. - 24.00 Oz. R-12; 8.00 Oz. Mineral Oil; w/ Calsonic Compressor	59000 ⁵⁹
LEGACY OUTBACK		
13	4 Cyl. 2.5 Eng. - 16.00 Oz. R-134a; See Under Hood Decal	59002
	6 Cyl. 3.6 Eng. - 16.00 Oz. R-134a; See Under Hood Decal	59002
12-10	4 Cyl. 2.5 Eng. - 15.00 Oz. R-134a; See Under Hood Decal	59002
	6 Cyl. 3.6 Eng. - 15.00 Oz. R-134a; See Under Hood Decal	59002
09-08	4 Cyl. 2.5 Eng. - 14.00 Oz. R-134a; See Under Hood Decal	59002
	6 Cyl. 3.0 Eng. - 14.00 Oz. R-134a; See Under Hood Decal	59002
07-05	4 Cyl. 2.5 Eng. - 14.00 Oz. R-134a; See Under Hood Decal	59007
99	4 Cyl. 2.5 Eng. - 23.00 Oz. R-134a; 5.30 Oz. PAG-46	59007
98-96	All Eng. - 24.00 Oz. R-134a; 5.25 Oz. PAG-100	59002
95	All Eng. - 24.00 Oz. R-134a; 6.00 Oz. PAG-100	59002
LOYALE		
94	4 Cyl. 1.8 Eng. - 25.00 Oz. R-12; 4.72 Oz. Mineral Oil	59000 ⁵⁹
93-90	All Eng. To 3/92 - 28.00 Oz. R-12; 5.00 Oz. Mineral Oil	59000 ⁵⁹
	All Eng. From 3/92 - 30.00 Oz. R-12; 4.75 Oz. Mineral Oil	59000 ⁵⁹
OUTBACK		
13-10	4 Cyl. 2.5 Eng. - 16.00 Oz. R-134a; See Under Hood Decal	59007
	6 Cyl. 3.6 Eng. - 16.00 Oz. R-134a; See Under Hood Decal	59007
09-05	4 Cyl. 2.5 Eng. - 14.00 Oz. R-134a; See Under Hood Decal	59007
	6 Cyl. 3.0 Eng. - 14.00 Oz. R-134a; See Under Hood Decal	59007
04-01	All Eng. - 23.00 Oz. R-134a; 4.50 Oz. PAG-100	59002
00	4 Cyl. 2.5 Eng. - 21.00 Oz. R-134a; 5.20 Oz. PAG-100	59002
SEDAN, COUPE, WAGON		
89	HL/GL/GL10 - 28.00 Oz. R-12; 5.00 Oz. Mineral Oil; w/ Hitachi Compressor	59000 ⁵⁹
	HL/GL/GL10 - 30.00 Oz. R-12; 4.75 Oz. Mineral Oil; w/ Panasonic Compressor	59000 ⁵⁹
	All Eng. - See Under Hood Decal	59000 ⁵⁹
88-85	All Eng. - 28.00 Oz. R-12; 4.00 Oz. Mineral Oil	59000 ⁵⁹
SVX		
97	6 Cyl. 3.3 Eng. - 23.00 Oz. R-134a; 5.00 Oz. PAG-100	59002
96-93	All Eng. - 23.00 Oz. R-134a; 5.00 Oz. PAG-100	59002
92	All Eng. - 23.00 Oz. R-12; 5.00 Oz. Mineral Oil	59000 ⁵⁹
TRIBECA		
13-08	6 Cyl. 3.6 Eng. - See Under Hood Decal	59007
07-06	6 Cyl. 3.0 Eng. - See Under Hood Decal	59007
XT		
91-89	All Eng. - 28.00 Oz. R-12; 5.00 Oz. Mineral Oil	59000 ⁵⁹
88	4 Cyl. 1.8 Eng. - See Under Hood Decal	59000 ⁵⁹
	6 Cyl. 2.7 Eng. - See Under Hood Decal	59000 ⁵⁹
87-85	4 Cyl. 1.8 Eng. - See Under Hood Decal	59000 ⁵⁹

Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that A/C system has been properly cleaned, and new accumulator / filter drier has been installed. Specs are for total system capacities. Always refer to under hood decal as the primary source for refrigerant and lubricant information.

Year	Model	Lubricant
AERIO		
07-02	All Eng. - 19.00 Oz. R-134a; 6.00 Oz. PAG-46	59007
EQUATOR		
12-10	4 Cyl. 2.5 Eng. - 25.00 Oz. R-134a; 6.10 Oz. PAG-46	59007
	6 Cyl. 4.0 Eng. - 25.00 Oz. R-134a; 6.10 Oz. PAG-46	59007
09	4 Cyl. 2.5 Eng. - 16.54 Oz. R-134a; 6.10 Oz. PAG-46	59007
	6 Cyl. 4.0 Eng. - 16.54 Oz. R-134a; 6.10 Oz. PAG-46	59007
ESTEEM		
02-96	All Eng. - 21.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
95	4 Cyl. 1.6 Eng. - 21.00 Oz. R-134a; 5.00 Oz. PAG-46	59007

Continued on Next Page

⁵⁹ When retrofitting to R134a PAG Oil must be used.

SUZUKI

Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that A/C system has been properly cleaned, and new accumulator / filter drier has been installed. Specs are for total system capacities. Always refer to under hood decal as the primary source for refrigerant and lubricant information.

Year	Model	Lubricant
FORENZA		
08	All Eng. - 23.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
07-04	All Eng. - 22.00 Oz. R-134a; 7.50 Oz. PAG-100	59002
GRAND VITARA		
13-11	4 Cyl. 2.4 Eng. - 20.00 Oz. R-134a; 4.70-5.40 Oz. PAG-46	59007
10-09	4 Cyl. 2.4 Eng. - 20.00 Oz. R-134a; 5.10 Oz. PAG-46	59007
	6 Cyl. 3.2 Eng. - 20.00 Oz. R-134a; 5.10 Oz. PAG-46	59007
08-06	6 Cyl. 2.7 Eng. - 21.00 Oz. R-134a; 8.50 Oz. PAG-46	59007
05	6 Cyl. 2.5 Eng.; w/o Rear AC - 16.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
04	6 Cyl. 2.5 Eng.; w/o Rear AC - 16.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
	6 Cyl. 2.7 Eng.; w/o Rear AC - 23.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
	6 Cyl. 2.7 Eng.; w/ Rear AC - 30.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
03	All Eng.; w/o Rear AC - 17.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
	All Eng.; w/ Rear AC - 28.00 Oz. R-134a; 12.00 Oz. PAG-46	59007
02-01	All Eng.; w/o Rear AC - 17.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
	All Eng.; w/ Rear AC - 28.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
00-99	All Eng. - 21.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
KIZASHI		
13-12	4 Cyl. 2.4 Eng. - 16.00 Oz. R-134a; 2.71 3.38 Oz. PAG-46	59007
11	4 Cyl. 2.4 Eng. - 15.00 Oz. R-134a; 3.40 Oz. PAG-46	59007
10	4 Cyl. 2.4 Eng. - 19.00 Oz. R-134a; 4.40 Oz. PAG-46	59007
RENO		
08-05	All Eng. - 23.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
SAMURAI		
95-94	All Eng. - 18.00 Oz. R-134a; 3.50 Oz. PAG-46	59007
93-89	All Eng. - 18.00 Oz. R-12; 5.00 Oz. Mineral Oil	59000 ⁵⁹
88-87	All Eng. - 28.00 Oz. R-12; 4.00 Oz. Mineral Oil	59000 ⁵⁹
86	4 Cyl. 1.3 Eng. - See Under Hood Decal	59000 ⁵⁹
SIDEKICK		
98-94	All Eng. - 21.00 Oz. R-134a; 6.00 Oz. PAG-46	59007
93-89	All Eng. - 21.00 Oz. R-12; 5.00 Oz. Mineral Oil	59000 ⁵⁹
SWIFT		
01-94	All Eng. - 18.00 Oz. R-134a; 3.50 Oz. PAG-46	59007
93-89	All Eng. - 18.00 Oz. R-12; 5.00 Oz. Mineral Oil	59000 ⁵⁹
SX4		
13-12	4 Cyl. 2.0 Eng. - 16.00 Oz. R-134a; 2.71-3.38 Oz. PAG-46	59007
11	4 Cyl. 2.0 Eng. - 15.00 Oz. R-134a; 3.40 Oz. PAG-46	59007
10-08	4 Cyl. 2.0 Eng. - 15.00 Oz. R-134a; 2.50 Oz. PAG-46	59007
07	4 Cyl. 2.0 Eng. - 21.00 Oz. R-134a; See Under Hood Decal	59007
VERONA		
06-04	All Eng. - 25.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
VITARA		
04	6 Cyl. 2.5 Eng. - 14.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
03	4 Cyl. 2.0 Eng. - 14.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
02-99	All Eng. - 16.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
X-90		
98-96	All Eng. - 21.00 Oz. R-134a; 6.00 Oz. PAG-46	59007
XL-7		
09-08	6 Cyl. 3.6 Eng.; w/o Rear AC - 21.00 Oz. R-134a; 4.40 Oz. PAG-46	59007
	6 Cyl. 3.6 Eng.; w/ Rear AC - 29.00 Oz. R-134a; 6.75 Oz. PAG-46	59007
07	6 Cyl. 3.6 Eng.; w/o Rear AC - 21.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
	6 Cyl. 3.6 Eng.; w/ Rear AC - 29.00 Oz. R-134a; 6.75 Oz. PAG-46	59007
06-03	6 Cyl. 2.7 Eng.; w/o Rear AC - 21.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
	6 Cyl. 2.7 Eng.; w/ Rear AC - 29.00 Oz. R-134a; 6.75 Oz. PAG-46	59007
02	6 Cyl. 2.7 Eng.; w/o Rear AC - 21.00 Oz. R-134a; 3.38 Oz. PAG-46	59007
	6 Cyl. 2.7 Eng.; w/ Rear AC - 26.00 Oz. R-134a; 4.73 Oz. PAG-46	59007

⁵⁹ When retrofitting to R134a PAG Oil must be used.

Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that A/C system has been properly cleaned, and new accumulator / filter drier has been installed. Specs are for total system capacities. Always refer to under hood decal as the primary source for refrigerant and lubricant information.

Year	Model	Lubricant
4RUNNER		
13-12	6 Cyl. 4.0 Eng. - 20.00 Oz. R-134a; 4.61 Oz. PAG-46	59007
11	6 Cyl. 4.0 Eng. - 20.00 Oz. R-134a; 3.51 Oz. PAG-46	59007
10	4 Cyl. 2.7 Eng. - 19.50 Oz. R-134a; 6.80 Oz. PAG-46	59007
	6 Cyl. 4.0 Eng. - 19.50 Oz. R-134a; 6.80 Oz. PAG-46	59007
09	6 Cyl. 4.0 Eng. - 22.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
	8 Cyl. 4.7 Eng. - 22.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
08-06	All Eng. - 22.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
05-03	All Eng. - 24.00 Oz. R-134a; 4.50 Oz. PAG-46	59007
02-01	All Eng. - 25.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
00-96	All Eng. - 23.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
95-94	All Eng. - 25.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
93-91	All Eng. - 30.00 Oz. R-12; 7.00 Oz. Mineral Oil	59000 ⁵⁹
90-89	All Eng. - 29.00 Oz. R-12; 7.75 Oz. Mineral Oil	59000 ⁵⁹
88	4 Cyl. 2.4 Eng. - See Under Hood Decal	59000 ⁵⁹
	6 Cyl. 3.0 Eng. - See Under Hood Decal	59000 ⁵⁹
87-84	4 Cyl. 2.4 Eng. - See Under Hood Decal	59000 ⁵⁹
AVALON		
13	4 Cyl. 2.5 Eng. - 19.50 Oz. R-134a; 5.00 Oz. PAG-46	59007
	6 Cyl. 3.5 Eng. - 19.50 Oz. R-134a; 5.00 Oz. PAG-46	59007
12-09	6 Cyl. 3.5 Eng. - 19.50 Oz. R-134a; 5.00 Oz. PAG-46	59007
08-05	All Eng. - 19.50 Oz. R-134a; 4.50 Oz. PAG-46	59007
04-01	All Eng. - 23.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
00-95	All Eng. - 30.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
CAMRY		
13	4 Cyl. 2.5 Eng.; Excl. Hybrid - 19.00 Oz. R-134a; 3.88 Oz. PAG-46	59007
	6 Cyl. 3.5 Eng.; Excl. Hybrid - 19.00 Oz. R-134a; 3.88 Oz. PAG-46	59007
12	4 Cyl. 2.5 Eng.; Excl. Hybrid - 19.00 Oz. R-134a; 6.10-6.90 Oz. PAG-46	59007
	6 Cyl. 3.5 Eng.; Excl. Hybrid - 19.00 Oz. R-134a; 6.10-6.90 Oz. PAG-46	59007
11-10	4 Cyl. 2.4 Eng.; Hybrid - 17.00-20.00 Oz. R-134a; 4.50 Oz. Hybrid Oil	59889
	4 Cyl. 2.5 Eng.; Excl. Hybrid - 19.00 Oz. R-134a; 6.00 Oz. PAG-46	59007
	6 Cyl. 3.5 Eng.; Excl. Hybrid - 19.00 Oz. R-134a; 6.00 Oz. PAG-46	59007
09	All Eng.; Hybrid - 17.00-20.00 Oz. R-134a; 4.50 Oz. Hybrid Oil	59889
	4 Cyl. 2.4 Eng.; Excl. Hybrid - 19.00 Oz. R-134a; 6.00 Oz. PAG-46	59007
	6 Cyl. 3.5 Eng.; Excl. Hybrid - 19.00 Oz. R-134a; 6.00 Oz. PAG-46	59007
08-07	All Eng.; Hybrid - 17.00-20.00 Oz. R-134a; 4.50 Oz. Hybrid Oil	59889
	All Eng.; Excl. Hybrid - 18.00 Oz. R-134a; 6.00 Oz. PAG-46	59007
06-04	All Eng. - 21.00 Oz. R-134a; 4.50 Oz. PAG-46	59007
03-02	All Eng. - 19.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
01	All Eng. - 30.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
00-97	All Eng. - 28.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
96-94	All Eng. - 30.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
93	All Eng. - 33.50 Oz. R-12; 7.25 Oz. Mineral Oil	59000 ⁵⁹
92	All Eng. - 35.00 Oz. R-12; 7.25 Oz. Mineral Oil	59000 ⁵⁹
91	All Eng. - 27.00 Oz. R-12; 7.00 Oz. Mineral Oil	59000 ⁵⁹
90-89	All Eng. - 27.00 Oz. R-12; 7.50 Oz. Mineral Oil	59000 ⁵⁹
88-87	All Eng. - 27.00 Oz. R-12; 8.75 Oz. Mineral Oil	59000 ⁵⁹
86-85	All Eng. - 26.00 Oz. R-12; 8.75 Oz. Mineral Oil	59000 ⁵⁹
84	4 Cyl. 1.8 Eng. - 26.00 Oz. R-12; 8.75 Oz. Mineral Oil	59000 ⁵⁹
	4 Cyl. 2.0 Eng. - See Under Hood Decal	59000 ⁵⁹
83	4 Cyl. 2.0 Eng. - See Under Hood Decal	59000 ⁵⁹
CELICA		
05-00	All Eng. - 16.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
99-94	All Eng. - 23.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
93	All Eng. - 25.50 Oz. R-12; 7.00 Oz. Mineral Oil	59000 ⁵⁹
92-91	All Eng. - 27.00 Oz. R-12; 7.00 Oz. Mineral Oil	59000 ⁵⁹
90-89	All Eng. - 27.00 Oz. R-12; 7.75 Oz. Mineral Oil	59000 ⁵⁹
88-87	All Eng. - 27.00 Oz. R-12; 8.75 Oz. Mineral Oil	59000 ⁵⁹
86	4 Cyl. 2.0 Eng. - 26.00 Oz. R-12; 8.75 Oz. Mineral Oil	59000 ⁵⁹
	6 Cyl. 2.8 Eng. - 26.00 Oz. R-12; 8.75 Oz. Mineral Oil	59000 ⁵⁹
85	All Eng. - 26.00 Oz. R-12; 8.75 Oz. Mineral Oil	59000 ⁵⁹
COROLLA		
13-11	4 Cyl. 1.8 Eng. - 16.00 Oz. R-134a; 3.89 Oz. PAG-46	59007
	4 Cyl. 2.4 Eng. - See Under Hood Decal	59007

Continued on Next Page

⁵⁹ When retrofitting to R134a PAG Oil must be used.

TOYOTA

Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that A/C system has been properly cleaned, and new accumulator / filter drier has been installed. Specs are for total system capacities. Always refer to under hood decal as the primary source for refrigerant and lubricant information.

Year	Model	Lubricant
COROLLA (Cont'd)		
10-09	4 Cyl. 1.8 Eng. - 16.00 Oz. R-134a; 3.51 Oz. PAG-46	59007
	4 Cyl. 2.4 Eng. - 16.00 Oz. R-134a; 3.51 Oz. PAG-46	59007
08	4 Cyl. 1.8 Eng. - 18.00 Oz. R-134a; 4.50 Oz. PAG-46	59007
07-05	All Eng. - 18.00 Oz. R-134a; 4.50 Oz. PAG-46	59007
04-03	All Eng. - 18.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
02-01	All Eng. - 24.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
00-99	All Eng. - 23.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
98-96	All Eng. - 24.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
95-94	All Eng. - 26.50 Oz. R-134a; 7.00 Oz. PAG-46	59007
93	All Eng. - 26.50 Oz. R-12; 7.00 Oz. Mineral Oil	59000 ⁵⁹
92-91	All Eng. - 27.00 Oz. R-12; 7.00 Oz. Mineral Oil	59000 ⁵⁹
90-89	All Eng. - 27.00 Oz. R-12; 7.75 Oz. Mineral Oil	59000 ⁵⁹
88	All Eng. - 27.00 Oz. R-12; 7.50 Oz. Mineral Oil	59000 ⁵⁹
87	All Eng. - 26.00 Oz. R-12; 8.75 Oz. Mineral Oil	59000 ⁵⁹
86	All Eng. - 27.00 Oz. R-12; 8.75 Oz. Mineral Oil	59000 ⁵⁹
85	All Eng. - 26.00 Oz. R-12; 8.75 Oz. Mineral Oil	59000 ⁵⁹
84-83	4 Cyl. 1.6 Eng. - See Under Hood Decal	59000 ⁵⁹
CRESSIDA		
92-89	All Eng. - 30.00 Oz. R-12; 7.00 Oz. Mineral Oil	59000 ⁵⁹
88-87	6 Cyl. 2.8 Eng. - 26.00 Oz. R-12; 8.75 Oz. Mineral Oil	59000 ⁵⁹
86	All Eng. - 26.00 Oz. R-12; 8.75 Oz. Mineral Oil	59000 ⁵⁹
85	6 Cyl. 2.8 Eng. - 26.00 Oz. R-12; 8.75 Oz. Mineral Oil	59000 ⁵⁹
84-82	6 Cyl. 2.8 Eng. - See Under Hood Decal	59000 ⁵⁹
ECHO		
05-00	All Eng. - 16.00 Oz. R-134a; 7.75 Oz. PAG-46	59007
FJ CRUISER		
13-11	6 Cyl. 4.0 Eng. - See Under Hood Decal	59007
10-09	6 Cyl. 4.0 Eng. - 22.00 Oz. R-134a; 4.50 Oz. PAG-46	59007
08-07	6 Cyl. 4.0 Eng. - 22.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
HIGHLANDER		
12-11	4 Cyl. 2.7 Eng.; Excl. Hybrid; w/o Rear AC - 19.40-22.90 Oz. R-134a; 3.38 Oz. PAG-46	59007
	4 Cyl. 2.7 Eng.; Excl. Hybrid; w/ Rear AC - 25.40-28.90 Oz. R-134a; 4.73 Oz. PAG-46	59007
	6 Cyl. 3.5 Eng.; Excl. Hybrid; w/o Rear AC - 19.40-22.90 Oz. R-134a; 3.38 Oz. PAG-46	59007
	6 Cyl. 3.5 Eng.; Excl. Hybrid; w/ Rear AC - 25.40-28.90 Oz. R-134a; 4.73 Oz. PAG-46	59007
10-09	4 Cyl. 2.7 Eng.; Excl. Hybrid; w/o Rear AC - 19.40-22.90 Oz. R-134a; 4.50 Oz. PAG-46	59007
	4 Cyl. 2.7 Eng.; Excl. Hybrid; w/ Rear AC - 25.40-28.90 Oz. R-134a; 7.70 Oz. PAG-46	59007
	6 Cyl. 3.3 Eng.; Hybrid; w/o Rear AC - 21.00 Oz. R-134a; 4.20-4.80 Oz. Hybrid Oil	59889
	6 Cyl. 3.3 Eng.; Hybrid; w/ Rear AC - 27.00 Oz. R-134a; 4.20-4.80 Oz. Hybrid Oil	59889
	6 Cyl. 3.5 Eng.; Excl. Hybrid; w/o Rear AC - 19.40-22.90 Oz. R-134a; 4.50 Oz. PAG-46	59007
	6 Cyl. 3.5 Eng.; Excl. Hybrid; w/ Rear AC - 25.40-28.90 Oz. R-134a; 7.70 Oz. PAG-46	59007
08	6 Cyl. 3.3 Eng.; Hybrid; w/o Rear AC - 21.00 Oz. R-134a; 4.20-4.80 Oz. Hybrid Oil	59889
	6 Cyl. 3.3 Eng.; Hybrid; w/ Rear AC - 27.00 Oz. R-134a; 4.20-4.80 Oz. Hybrid Oil	59889
	6 Cyl. 3.5 Eng.; Excl. Hybrid; w/o Rear AC - 19.40-22.90 Oz. R-134a; 4.50 Oz. PAG-46	59007
	6 Cyl. 3.5 Eng.; Excl. Hybrid; w/ Rear AC - 25.40-28.90 Oz. R-134a; 7.70 Oz. PAG-46	59007
07-06	All Eng.; Excl. Hybrid - 23.00 Oz. R-134a; 4.50 Oz. PAG-46	59007
	All Eng.; Hybrid - See Under Hood Decal	59889
05	All Eng. - 24.00 Oz. R-134a; 4.50 Oz. PAG-46	59007
04-01	All Eng. - 24.00 Oz. R-134a; 7.75 Oz. PAG-46	59007
LAND CRUISER		
13-10	8 Cyl. 5.7 Eng.; w/o Cool Box - 33.50 Oz. R-134a; 4.75 Oz. PAG-46	59007
	8 Cyl. 5.7 Eng.; w/ Cool Box - 35.00 Oz. R-134a; 4.75 Oz. PAG-46	59007
09	8 Cyl. 5.7 Eng.; w/ Cool Box - 33.50 Oz. R-134a; 4.75 Oz. PAG-46	59007
	8 Cyl. 5.7 Eng.; w/o Cool Box - 35.00 Oz. R-134a; 4.75 Oz. PAG-46	59007
08	8 Cyl. 5.7 Eng.; w/o Cool Box - 33.50 Oz. R-134a; 4.75 Oz. PAG-46	59007
	8 Cyl. 5.7 Eng.; w/ Cool Box - 35.00 Oz. R-134a; 4.75 Oz. PAG-46	59007
07	8 Cyl. 4.7 Eng. - 38.00 Oz. R-134a; 4.50 Oz. PAG-46	59007
06-01	All Eng.; w/o Rear AC - 24.00 Oz. R-134a; See Under Hood Decal PAG-46	59007
	All Eng.; w/ Rear AC - 38.00 Oz. R-134a; See Under Hood Decal PAG-46	59007
00-98	All Eng.; w/o Rear AC - 28.00 Oz. R-134a; 7.25 Oz. PAG-46	59007
	All Eng.; w/ Rear AC - 39.00 Oz. R-134a; 8.50 Oz. PAG-46	59007
97-94	All Eng. - 30.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
93	All Eng. - 32.00 Oz. R-12; 7.00 Oz. Mineral Oil	59000 ⁵⁹
92-91	All Eng. - 33.50 Oz. R-12; 7.00 Oz. Mineral Oil	59000 ⁵⁹

Continued on Next Page

⁵⁹ When retrofitting to R134a PAG Oil must be used.

Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that A/C system has been properly cleaned, and new accumulator / filter drier has been installed. Specs are for total system capacities. Always refer to under hood decal as the primary source for refrigerant and lubricant information.

Year	Model	Lubricant
LAND CRUISER (Cont'd)		
90-89	All Eng. - 32.00 Oz. R-12; 7.75 Oz. Mineral Oil	59000 ⁵⁹
87-85	6 Cyl. 4.2 Eng. - 32.00 Oz. R-12; 7.75 Oz. Mineral Oil	59000 ⁵⁹
84-83	6 Cyl. 4.2 Eng. - See Under Hood Decal	59000 ⁵⁹
MATRIX		
13-09	4 Cyl. 1.8 Eng. - 15.00 Oz. R-134a; 4.50 Oz. PAG-46	59007
	4 Cyl. 2.4 Eng. - 15.00 Oz. R-134a; 4.50 Oz. PAG-46	59007
08-05	All Eng. - 18.00 Oz. R-134a; 4.50 Oz. PAG-46	59007
04-03	All Eng. - 18.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
MR2		
05-00	All Eng. - 18.00 Oz. R-134a; PAG-46	59007
95-94	All Eng. - 25.50 Oz. R-134a; 7.00 Oz. PAG-46	59007
93	All Eng. - 30.00 Oz. R-12; 7.25 Oz. Mineral Oil	59000 ⁵⁹
92-91	All Eng. - 32.00 Oz. R-12; 7.25 Oz. Mineral Oil	59000 ⁵⁹
89	All Eng. - 29.00 Oz. R-12; 8.75 Oz. Mineral Oil	59000 ⁵⁹
88-85	4 Cyl. 1.6 Eng. - 25.00 Oz. R-12; See Under Hood Decal	59000 ⁵⁹
MR2 SPYDER		
88-85	4 Cyl. 1.6 Eng. - 25.00 Oz. R-12; See Under Hood Decal	59000 ⁵⁹
PASEO		
98-96	All Eng. - 21.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
95-94	All Eng. - 25.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
93	All Eng. - 26.50 Oz. R-12; 7.00 Oz. Mineral Oil	59000 ⁵⁹
	4 Cyl. 1.5 Eng. - See Under Hood Decal	59007
92	All Eng. - 28.00 Oz. R-12; 7.00 Oz. Mineral Oil	59000 ⁵⁹
PICKUP - STANDARD		
95	All Eng. - 20.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
94	All Eng. - 26.50 Oz. R-134a; 7.00 Oz. PAG-46	59007
	4 Cyl. 2.4 Eng. - w/ R-12	59000 ⁵⁹
	6 Cyl. 3.0 Eng. - w/ R-12	59000 ⁵⁹
93	All Eng. - 29.00 Oz. R-12; 7.00 Oz. Mineral Oil	59000 ⁵⁹
92-91	All Eng. - 27.00 Oz. R-12; 7.00 Oz. Mineral Oil	59000 ⁵⁹
90-89	All Eng. - 29.00 Oz. R-12; 7.00 Oz. Mineral Oil	59000 ⁵⁹
88-87	All Eng. - 27.00 Oz. R-12; 7.50 Oz. Mineral Oil	59000 ⁵⁹
86-85	All Eng. - 26.00 Oz. R-12; 7.50 Oz. Mineral Oil	59000 ⁵⁹
84	4 Cyl. 2.4 Eng. - See Under Hood Decal	59000 ⁵⁹
PREVIA		
97-94	All Eng.; w/o Rear AC - 32.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
	All Eng.; w/ Rear AC - 41.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
93	All Eng.; w/o Rear AC - 33.50 Oz. R-12; 7.75 Oz. Mineral Oil	59000 ⁵⁹
	All Eng.; w/ Rear AC - 42.50 Oz. R-12; 7.75 Oz. Mineral Oil	59000 ⁵⁹
92-91	All Eng.; w/o Rear AC - 35.00 Oz. R-12; 7.75 Oz. Mineral Oil	59000 ⁵⁹
	All Eng.; w/ Rear AC - 44.00 Oz. R-12; 7.75 Oz. Mineral Oil	59000 ⁵⁹
PRIUS		
13-12	4 Cyl. 1.5 Eng.; Hybrid - 16.50 Oz. R-134a; 4.40-4.90 Oz. Hybrid Oil	59889
	4 Cyl. 1.8 Eng.; Hybrid - 16.50 Oz. R-134a; 4.40-4.90 Oz. Hybrid Oil	59889
11-10	4 Cyl. 1.8 Eng.; Hybrid - 16.50 Oz. R-134a; 4.40-4.90 Oz. Hybrid Oil	59889
09-04	4 Cyl. 1.5 Eng.; Hybrid - 17.00 Oz. R-134a; 4.00 Oz. Hybrid Oil	59889
03-01	4 Cyl. 1.5 Eng.; Hybrid - 19.00 Oz. R-134a; 4.00 Oz. Hybrid Oil	59889
RAV4		
13	4 Cyl. 2.5 Eng. - 16.00 Oz. R-134a; See Under Hood Decal	59007
12	4 Cyl. 2.5 Eng. - 16.00 Oz. R-134a; 4.35-4.86 Oz. PAG-46	59007
	6 Cyl. 3.5 Eng. - 16.00 Oz. R-134a; 4.35-4.86 Oz. PAG-46	59007
11-09	4 Cyl. 2.5 Eng. - 16.00 Oz. R-134a; 4.50 Oz. PAG-46	59007
	6 Cyl. 3.5 Eng. - 16.00 Oz. R-134a; 4.50 Oz. PAG-46	59007
08-07	All Eng. - 16.00 Oz. R-134a; 4.50 Oz. PAG-46	59007
06-01	All Eng. - 19.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
00-96	All Eng. - 25.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
SEQUOIA		
13	8 Cyl. 5.7 Eng. - 33.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
12-11	8 Cyl. 4.6 Eng. - 33.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
	8 Cyl. 5.7 Eng. - 33.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
10	8 Cyl. 4.6 Eng. - 30.00-32.50 Oz. R-134a; 7.00 Oz. PAG-46	59007
	8 Cyl. 5.7 Eng. - 30.00-32.50 Oz. R-134a; 7.00 Oz. PAG-46	59007
09-08	8 Cyl. 4.7 Eng. - 30.00-32.50 Oz. R-134a; 7.00 Oz. PAG-46	59007

Continued on Next Page

⁵⁹ When retrofitting to R134a PAG Oil must be used.

TOYOTA

Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that A/C system has been properly cleaned, and new accumulator / filter drier has been installed. Specs are for total system capacities. Always refer to under hood decal as the primary source for refrigerant and lubricant information.

Year	Model	Lubricant
SEQUOIA (Cont'd)		
09-08	8 Cyl. 5.7 Eng. - 30.00-32.50 Oz. R-134a; 7.00 Oz. PAG-46	59007
07	8 Cyl. 4.7 Eng. - 28.00 Oz. R-134a; See Under Hood Decal	59007
06-01	All Eng.; w/o Rear AC - 28.00 Oz. R-134a; See Under Hood Decal	59007
	All Eng.; w/ Rear AC - 39.00 Oz. R-134a; See Under Hood Decal	59007
SIENNA		
13	6 Cyl. 3.5 Eng. - 29.00 Oz. R-134a; 5.31 Oz. PAG-46	59007
12	4 Cyl. 2.7 Eng. - 29.00 Oz. R-134a; 5.31 Oz. PAG-46	59007
11	6 Cyl. 3.5 Eng. - 29.00 Oz. R-134a; 5.31 Oz. PAG-46	59007
	4 Cyl. 2.7 Eng. - 26.50 Oz. R-134a; 5.50 Oz. PAG-46	59007
10-07	6 Cyl. 3.5 Eng. - 26.50 Oz. R-134a; 5.50 Oz. PAG-46	59007
	All Eng. - 28.50 Oz. R-134a; 5.50 Oz. PAG-46	59007
06-05	All Eng. - 28.50 Oz. R-134a; 4.50 Oz. PAG-46	59007
04-01	All Eng. - 38.00 Oz. R-134a; 7.50 Oz. PAG-46	59007
00-98	All Eng. - 28.00 Oz. R-134a; 7.25 Oz. PAG-46	59007
SOLARA		
08	4 Cyl. 2.4 Eng. - 21.00 Oz. R-134a; See Under Hood Decal	59007
07-04	6 Cyl. 3.3 Eng. - 21.00 Oz. R-134a; See Under Hood Decal	59007
	All Eng. - 21.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
03-01	All Eng. - 28.00 Oz. R-134a; 7.50 Oz. PAG-46	59007
00-99	All Eng. - 28.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
SUPRA		
98-96	All Eng. - 25.00 Oz. R-134a; 7.75 Oz. PAG-46	59007
95-94	All Eng. - 25.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
93	6 Cyl. 3.0 Eng. - See Under Hood Decal	59007
92-89	All Eng. - 27.00 Oz. R-12; 7.00 Oz. Mineral Oil	59000⁵⁹
88	6 Cyl. 3.0 Eng. - See Under Hood Decal	59000⁵⁹
87	All Eng. - 26.00 Oz. R-12; 8.80 Oz. Mineral Oil	59000⁵⁹
86	6 Cyl. 3.0 Eng. - See Under Hood Decal	59000⁵⁹
80-79	6 Cyl. 2.6 Eng. - See Under Hood Decal	59000⁵⁹
T100		
98-93	All Eng. - 23.00 Oz. R-134a; 7.75 Oz. PAG-46	59007
TACOMA		
13	4 Cyl. 2.7 Eng. - 22.00 Oz. R-134a; 5.61 Oz. PAG-46	59007
12-09	6 Cyl. 4.0 Eng. - 22.00 Oz. R-134a; 5.61 Oz. PAG-46	59007
	4 Cyl. 2.7 Eng. - 22.00 Oz. R-134a; 5.50 Oz. PAG-46	59007
08-05	6 Cyl. 4.0 Eng. - 22.00 Oz. R-134a; 5.50 Oz. PAG-46	59007
	All Eng. - 22.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
04-01	All Eng. - 23.00 Oz. R-134a; 7.75 Oz. PAG-46	59007
00-97	All Eng. - 21.00 Oz. R-134a; 7.75 Oz. PAG-46	59007
96-95	All Eng. - 21.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
TERCEL		
98	All Eng. - 16.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
97-95	All Eng. - 23.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
94	All Eng. - 24.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
93	All Eng. - 26.50 Oz. R-12; 7.00 Oz. Mineral Oil	59000⁵⁹
92	All Eng. - 28.00 Oz. R-12; 7.00 Oz. Mineral Oil	59000⁵⁹
91	All Eng. - 26.50 Oz. R-12; 7.00 Oz. Mineral Oil	59000⁵⁹
90-89	All Eng. - 27.00 Oz. R-12; 7.75 Oz. Mineral Oil	59000⁵⁹
88-87	All Eng. - 27.00 Oz. R-12; 8.50 Oz. Mineral Oil	59000⁵⁹
86-85	All Eng. - 26.00 Oz. R-12; 8.50 Oz. Mineral Oil	59000⁵⁹
84	4 Cyl. 1.5 Eng. - See Under Hood Decal	59000⁵⁹
TUNDRA		
13-10	6 Cyl. 4.0 Eng. - 22.00 Oz. R-134a; 4.50 Oz. PAG-46	59007
09-08	8 Cyl. 4.6 Eng. - 22.00 Oz. R-134a; 4.50 Oz. PAG-46	59007
	8 Cyl. 5.7 Eng. - 22.00 Oz. R-134a; 4.50 Oz. PAG-46	59007
	6 Cyl. 4.0 Eng. - 22.00 Oz. R-134a; 4.50 Oz. PAG-46	59007
07-06	8 Cyl. 4.7 Eng. - 22.00 Oz. R-134a; 4.50 Oz. PAG-46	59007
	8 Cyl. 5.7 Eng. - 22.00 Oz. R-134a; 4.50 Oz. PAG-46	59007
	4 Door - 21.00 Oz. R-134a; 7.75 Oz. PAG-46	59007
05-04	2 Door - 23.00 Oz. R-134a; 7.75 Oz. PAG-46	59007
	4 Door - 20.00 Oz. R-134a; 7.75 Oz. PAG-46	59007
03-00	2 Door - 27.00 Oz. R-134a; 7.75 Oz. PAG-46	59007
	All Eng. - 22.00 Oz. R-134a; 7.75 Oz. PAG-46	59007

Continued on Next Page

⁵⁹ When retrofitting to R134a PAG Oil must be used.

Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that A/C system has been properly cleaned, and new accumulator / filter drier has been installed. Specs are for total system capacities. Always refer to under hood decal as the primary source for refrigerant and lubricant information.

Year	Model	Lubricant
VAN / VAN WAGON		
89-86	All Eng.; w/o Rear AC - 25.00 Oz. R-12; 5.00 Oz. Mineral Oil	59000 ⁵⁹
	All Eng.; w/ Rear AC - 50.00 Oz. R-12; 6.00 Oz. Mineral Oil	59000 ⁵⁹
85-84	4 Cyl. 2.0 Eng. - See Under Hood Decal	59000 ⁵⁹
VENZA		
14	6 Cyl. 3.5 Eng. - 19.00 Oz. R-134a; See Under Hood Decal	59007
13-10	4 Cyl. 2.7 Eng. - 19.00 Oz. R-134a; See Under Hood Decal	59007
	6 Cyl. 3.5 Eng. - 19.00 Oz. R-134a; See Under Hood Decal	59007
09	4 Cyl. 2.7 Eng. - 18.00 Oz. R-134a; See Under Hood Decal	59007
	6 Cyl. 3.5 Eng. - 18.00 Oz. R-134a; See Under Hood Decal	59007
YARIS		
13-10	4 Cyl. 1.5 Eng. - 14.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
09	4 Cyl. 1.5 Eng. - 13.00 Oz. R-134a; 3.00 Oz. PAG-46	59007
08-07	All Eng. - 13.00 Oz. R-134a; 3.00 Oz. PAG-46	59007

VOLKSWAGEN

Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that A/C system has been properly cleaned, and new accumulator / filter drier has been installed. Specs are for total system capacities. Always refer to under hood decal as the primary source for refrigerant and lubricant information.

Year	Model	Lubricant
BEETLE		
13	4 Cyl. 2.0 Eng. - 19.00 Oz. R-134a; 2.70-3.30 Oz. PAG-46; w/ Denso Compressor	59007
	4 Cyl. 2.0 Eng. - 19.00 Oz. R-134a; 3.40-4.00 Oz. PAG-46; w/ Denso Compressor	59007
	5 Cyl. 2.5 Eng. - 19.00 Oz. R-134a; 2.70-3.30 Oz. PAG-46; w/ Denso Compressor	59007
	5 Cyl. 2.5 Eng. - 19.00 Oz. R-134a; 3.40-4.00 Oz. PAG-46; w/ Denso Compressor	59007
12	4 Cyl. 2.0 Eng. - 27.00 Oz. R-134a; 4.60 Oz. PAG-46	59007
	5 Cyl. 2.5 Eng. - 27.00 Oz. R-134a; 4.60 Oz. PAG-46	59007
10	5 Cyl. 2.5 Eng. - 27.00 Oz. R-134a; 4.60 Oz. PAG-46	59007
09	5 Cyl. 2.5 Eng. - 25.00 Oz. R-134a; 4.60 Oz. PAG-46	59007
08-01	All Eng. - 26.00 Oz. R-134a; 4.50 Oz. PAG-46	59007
00-98	All Eng. - 24.00 Oz. R-134a; 4.50 Oz. PAG-46	59007
CABRIO		
02-01	All Eng. - 27.00 Oz. R-134a; 4.50 Oz. PAG-46	59007
00-95	All Eng. - 28.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
CABRIOLET		
93-86	All Eng. - 32.00 Oz. R-12; 4.75 Oz. Mineral Oil	59000 ⁵⁹
85	4 Cyl. 1.8 Eng. - See Under Hood Decal	59000 ⁵⁹
CORRADO		
94	All Eng. - 35.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
93	All Eng. - 30.00 Oz. R-12; 5.00 Oz. Mineral Oil	59000 ⁵⁹
	All Eng. - 35.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
92-90	All Eng. - 30.00 Oz. R-12; 5.00 Oz. Mineral Oil	59000 ⁵⁹
EOS		
13-10	4 Cyl. 2.0 Eng. - 19.00 Oz. R-134a; 3.40-4.00 Oz. PAG-46; w/ Sanden Compressor	59007
	4 Cyl. 2.0 Eng. - 19.00 Oz. R-134a; 3.50-4.50 Oz. PAG-46; w/ Zexel Compressor	59007
	4 Cyl. 2.0 Eng. - 19.00 Oz. R-134a; 4.40-5.00 Oz. PAG-46; w/ Denso Compressor	59007
09	4 Cyl. 2.0 Eng. - 18.00 Oz. R-134a; 4.10 Oz. PAG-46	59007
08-07	All Eng. - 19.50 Oz. R-134a; 4.50 Oz. PAG-46	59007
EUROVAN		
03-02	All Eng.; w/o Rear AC - 40.00 Oz. R-134a; 4.50 Oz. PAG-100	59002
	All Eng.; w/ Rear AC - 48.00 Oz. R-134a; 8.00 Oz. PAG-100	59002
01-93	All Eng.; w/o Rear AC - 33.50 Oz. R-134a; 4.50 Oz. PAG-100	59002
	All Eng.; w/ Rear AC - 48.00 Oz. R-134a; 8.00 Oz. PAG-100	59002
FOX		
93-89	All Eng. - 38.00 Oz. R-12; 6.00 Oz. Mineral Oil	59000 ⁵⁹
88	All Eng. - 40.00 Oz. R-12; Mineral Oil	59000 ⁵⁹
87	4 Cyl. 1.8 Eng. - See Under Hood Decal	59000 ⁵⁹
GOLF / GTI		
13	4 Cyl. 2.0 Eng. - 18.00 Oz. R-134a; 3.20 Oz. PAG-46; w/ Denso 6SEU14 Compressor	59007
	4 Cyl. 2.0 Eng. - 18.00 Oz. R-134a; 3.70 Oz. PAG-46; w/ Delphi Compressor	59007
	4 Cyl. 2.0 Eng. - 18.00 Oz. R-134a; 3.70 Oz. PAG-46; w/ Delphi Compressor; w/ Sanden Compressor	59007
	4 Cyl. 2.0 Eng. - 18.00 Oz. R-134a; 4.90 Oz. PAG-46; w/ Denso 7SEU17C Compressor	59007

Continued on Next Page

⁵⁹ When retrofitting to R134a PAG Oil must be used.

VOLKSWAGEN

Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that A/C system has been properly cleaned, and new accumulator / filter drier has been installed. Specs are for total system capacities. Always refer to under hood decal as the primary source for refrigerant and lubricant information.

Year	Model	Lubricant
GOLF / GTI (Cont'd)		
13	4 Cyl. 2.0 Eng. - 19.00 Oz. R-134a; 3.40-4.00 Oz. PAG-46	59007
	4 Cyl. 2.5 Eng. - 18.00 Oz. R-134a; 3.20 Oz. PAG-46; w/ Denso 6SEU14 Compressor	59007
	4 Cyl. 2.5 Eng. - 18.00 Oz. R-134a; 3.70 Oz. PAG-46; w/ Delphi Compressor; w/ Sanden Compressor	59007
	4 Cyl. 2.5 Eng. - 18.00 Oz. R-134a; 4.90 Oz. PAG-46; w/ Denso 7SEU17C Compressor	59007
	5 Cyl. 2.5 Eng. - 18.00 Oz. R-134a; 3.70 Oz. PAG-46; w/ Delphi Compressor	59007
12	5 Cyl. 2.5 Eng. - 19.00 Oz. R-134a; 3.40-4.00 Oz. PAG-46	59007
	4 Cyl. 2.0 Eng. - 18.00 Oz. R-134a; 3.20 Oz. PAG-46; w/ Denso 6SEU14 Compressor	59007
	4 Cyl. 2.0 Eng. - 18.00 Oz. R-134a; 3.70 Oz. PAG-46; w/ Delphi Compressor	59007
	4 Cyl. 2.0 Eng. - 18.00 Oz. R-134a; 3.70 Oz. PAG-46; w/ Delphi Compressor; w/ Sanden Compressor	59007
	4 Cyl. 2.0 Eng. - 18.00 Oz. R-134a; 4.90 Oz. PAG-46; w/ Denso 7SEU17C Compressor	59007
	4 Cyl. 2.0 Eng. - 19.00 Oz. R-134a; 3.40-4.00 Oz. PAG-46	59007
	5 Cyl. 2.5 Eng. - 18.00 Oz. R-134a; 3.20 Oz. PAG-46; w/ Denso 6SEU14 Compressor	59007
	5 Cyl. 2.5 Eng. - 18.00 Oz. R-134a; 3.70 Oz. PAG-46; w/ Delphi Compressor	59007
	5 Cyl. 2.5 Eng. - 18.00 Oz. R-134a; 3.70 Oz. PAG-46; w/ Delphi Compressor; w/ Sanden Compressor	59007
	5 Cyl. 2.5 Eng. - 18.00 Oz. R-134a; 4.90 Oz. PAG-46; w/ Denso 7SEU17C Compressor	59007
11	5 Cyl. 2.5 Eng. - 19.00 Oz. R-134a; 3.40-4.00 Oz. PAG-46	59007
	4 Cyl. 2.0 Eng. - 18.00 Oz. R-134a; 3.20 Oz. PAG-46; w/ Denso 6SEU14 Compressor	59007
	4 Cyl. 2.0 Eng. - 18.00 Oz. R-134a; 3.70 Oz. PAG-46; w/ Delphi Compressor	59007
	4 Cyl. 2.0 Eng. - 18.00 Oz. R-134a; 3.70 Oz. PAG-46	59007
	4 Cyl. 2.0 Eng. - 18.00 Oz. R-134a; 3.70 Oz. PAG-46; w/ Delphi Compressor; w/ Sanden Compressor	59007
	4 Cyl. 2.0 Eng. - 18.00 Oz. R-134a; 4.90 Oz. PAG-46; w/ Denso 7SEU17C Compressor	59007
	5 Cyl. 2.5 Eng. - 18.00 Oz. R-134a; 3.20 Oz. PAG-46; w/ Denso 6SEU14 Compressor	59007
	5 Cyl. 2.5 Eng. - 18.00 Oz. R-134a; 3.70 Oz. PAG-46; w/ Delphi Compressor	59007
	5 Cyl. 2.5 Eng. - 18.00 Oz. R-134a; 3.70 Oz. PAG-46	59007
	5 Cyl. 2.5 Eng. - 18.00 Oz. R-134a; 3.70 Oz. PAG-46; w/ Delphi Compressor; w/ Sanden Compressor	59007
10	5 Cyl. 2.5 Eng. - 18.00 Oz. R-134a; 4.90 Oz. PAG-46; w/ Denso 7SEU17C Compressor	59007
	4 Cyl. 2.0 Eng. - 18.00 Oz. R-134a; 3.20 Oz. PAG-46; w/ Denso 6SEU14 Compressor	59007
	4 Cyl. 2.0 Eng. - 18.00 Oz. R-134a; 3.20 Oz. PAG-46; w/ Denso 6SEU14 Compressor	59007
	4 Cyl. 2.0 Eng. - 18.00 Oz. R-134a; 3.70 Oz. PAG-46; w/ Delphi Compressor	59007
	4 Cyl. 2.0 Eng. - 18.00 Oz. R-134a; 3.70 Oz. PAG-46; w/ Delphi Compressor; w/ Sanden Compressor	59007
	4 Cyl. 2.0 Eng. - 18.00 Oz. R-134a; 3.70 Oz. PAG-46; w/ Delphi Compressor; w/ Sanden Compressor	59007
	4 Cyl. 2.0 Eng. - 18.00 Oz. R-134a; 4.90 Oz. PAG-46; w/ Denso 7SEU17C Compressor	59007
	4 Cyl. 2.0 Eng. - 18.00 Oz. R-134a; 4.90 Oz. PAG-46; w/ Denso 7SEU17C Compressor	59007
	5 Cyl. 2.0 Eng. - 18.00 Oz. R-134a; 3.20 Oz. PAG-46; w/ Denso 6SEU14 Compressor	59007
	5 Cyl. 2.0 Eng. - 18.00 Oz. R-134a; 3.70 Oz. PAG-46; w/ Delphi Compressor	59007
	5 Cyl. 2.0 Eng. - 18.00 Oz. R-134a; 3.70 Oz. PAG-46; w/ Delphi Compressor; w/ Sanden Compressor	59007
	5 Cyl. 2.0 Eng. - 18.00 Oz. R-134a; 4.90 Oz. PAG-46; w/ Denso 7SEU17C Compressor	59007
	5 Cyl. 2.5 Eng. - 18.00 Oz. R-134a; 3.20 Oz. PAG-46; w/ Denso 6SEU14 Compressor	59007
	5 Cyl. 2.5 Eng. - 18.00 Oz. R-134a; 3.20 Oz. PAG-46; w/ Denso 6SEU14 Compressor	59007
	5 Cyl. 2.5 Eng. - 18.00 Oz. R-134a; 3.70 Oz. PAG-46; w/ Delphi Compressor	59007
	5 Cyl. 2.5 Eng. - 18.00 Oz. R-134a; 3.70 Oz. PAG-46; w/ Delphi Compressor	59007
	5 Cyl. 2.5 Eng. - 18.00 Oz. R-134a; 3.70 Oz. PAG-46; w/ Delphi Compressor; w/ Sanden Compressor	59007
	5 Cyl. 2.5 Eng. - 18.00 Oz. R-134a; 3.70 Oz. PAG-46; w/ Delphi Compressor; w/ Sanden Compressor	59007
	5 Cyl. 2.5 Eng. - 18.00 Oz. R-134a; 4.90 Oz. PAG-46; w/ Denso 7SEU17C Compressor	59007
	5 Cyl. 2.5 Eng. - 18.00 Oz. R-134a; 4.90 Oz. PAG-46; w/ Denso 7SEU17C Compressor	59007
09	4 Cyl. 2.0 Eng. - 19.00 Oz. R-134a; 6.10 Oz. PAG-46	59007
08-07	4 Cyl. 2.0 Eng. - 26.00 Oz. R-134a; 3.71 Oz. PAG-46	59007
06-05	All Eng. - 28.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
04-01	All Eng. - 27.00 Oz. R-134a; 4.50 Oz. PAG-46	59007
00-99	All Eng. - 26.00 Oz. R-134a; 4.50 Oz. PAG-46	59007
98-94	All Eng. - 28.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
93	All Eng. - 28.00 Oz. R-12; 4.00 Oz. Mineral Oil	59000 ⁵⁹
	All Eng. - 28.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
92-89	All Eng. - 39.00 Oz. R-12; 4.50 Oz. Mineral Oil	59000 ⁵⁹
88	4 Cyl. 1.6 Eng. - See Under Hood Decal	59000 ⁵⁹
	4 Cyl. 1.8 Eng. - See Under Hood Decal	59000 ⁵⁹
87-86	4 Cyl. 1.6 Eng. - See Under Hood Decal	59000 ⁵⁹
	4 Cyl. 1.8 Eng. - 40.00 Oz. R-12; 4.50 Oz. Mineral Oil	59000 ⁵⁹
85	4 Cyl. 1.6 Eng. - See Under Hood Decal	59000 ⁵⁹
	4 Cyl. 1.8 Eng. - See Under Hood Decal	59000 ⁵⁹
JETTA		
13-10	4 Cyl. 2.0 Eng. - 19.00 Oz. R-134a; 3.40-4.00 Oz. PAG-46	59007
	5 Cyl. 2.5 Eng. - 19.00 Oz. R-134a; 3.40-4.00 Oz. PAG-46	59007

Continued on Next Page

⁵⁹ When retrofitting to R134a PAG Oil must be used.

Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that A/C system has been properly cleaned, and new accumulator / filter drier has been installed. Specs are for total system capacities. Always refer to under hood decal as the primary source for refrigerant and lubricant information.

Year	Model	Lubricant
JETTA (Cont'd)		
09	4 Cyl. 2.0 Eng. - 19.00 Oz. R-134a; 3.70 Oz. PAG-46	59007
	5 Cyl. 2.5 Eng. - 19.00 Oz. R-134a; 3.70 Oz. PAG-46	59007
08-06	All Eng. - 19.50 Oz. R-134a; 4.00 Oz. PAG-46	59007
05	Excl. Wagon - 19.50 Oz. R-134a; 4.00 Oz. PAG-46	59007
	Wagon - 28.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
04-01	All Eng. - 27.00 Oz. R-134a; 4.50 Oz. PAG-46	59007
00-99	All Eng. - 26.00 Oz. R-134a; 4.50 Oz. PAG-46	59007
98-94	All Eng. - 28.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
93	All Eng. - 28.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
	4 Cyl. 2.0 Eng. - w/ R-12	59000 ⁵⁹
92-89	All Eng. - 39.00 Oz. R-12; 4.50 Oz. Mineral Oil	59000 ⁵⁹
88-85	4 Cyl. 1.6 Eng. - See Under Hood Decal	59000 ⁵⁹
	4 Cyl. 1.8 Eng. - 40.00 Oz. R-12; 4.50 Oz. Mineral Oil	59000 ⁵⁹
PASSAT		
13-12	4 Cyl. 2.0 Eng. - 20.00 Oz. R-134a; 3.40-4.50 Oz. PAG-46	59007
	5 Cyl. 2.5 Eng. - 20.00 Oz. R-134a; 3.40-4.10 Oz. PAG-46	59007
	6 Cyl. 3.6 Eng. - 20.00 Oz. R-134a; 3.40-4.50 Oz. PAG-46	59007
11-09	4 Cyl. 2.0 Eng. - 20.00 Oz. R-134a; 3.40-4.50 Oz. PAG-46	59007
	6 Cyl. 3.6 Eng. - 20.00 Oz. R-134a; 3.40-4.50 Oz. PAG-46	59007
08-05	All Eng. - 22.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
04	All Eng. - 20.00 Oz. R-134a; 8.50 Oz. PAG-46	59007
03-98	All Eng. - 23.00 Oz. R-134a; 8.50 Oz. PAG-46	59007
97-95	All Eng. - 33.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
94	All Eng. - 40.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
93	All Eng. - 40.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
	6 Cyl. 2.8 Eng. - w/ R-12	59000 ⁵⁹
92-90	All Eng. - 40.00 Oz. R-12; 4.00 Oz. Mineral Oil	59000 ⁵⁹
PHAETON		
06-04	All Eng. - 22.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
R32		
08	6 Cyl. 3.2 Eng. - 18.00 Oz. R-134a; 6.30 Oz. PAG-46	59007
RABBIT		
09	5 Cyl. 2.5 Eng. - 19.00 Oz. R-134a; 6.10 Oz. PAG-46	59007
08-06	All Eng. - 23.00 Oz. R-134a; 4.50 Oz. PAG-46	59007
ROUTAN		
12-11	6 Cyl. 3.6 Eng.; w/o Rear AC - 28.00 Oz. R-134a; 4.10 Oz. PAG-46	59007
	6 Cyl. 3.6 Eng.; w/ Rear AC - 40.00 Oz. R-134a; 5.10 Oz. PAG-46	59007
10-09	All Eng.; w/o Rear AC - 28.00 Oz. R-134a; 4.10 Oz. PAG-46	59007
	All Eng.; w/ Rear AC - 40.00 Oz. R-134a; 5.10 Oz. PAG-46	59007
SCIROCCO		
89	All Eng. - 40.00 Oz. R-12; 4.75 Oz. Mineral Oil	59000 ⁵⁹
88-85	4 Cyl. 1.8 Eng. - 40.00 Oz. R-12; 4.75 Oz. Mineral Oil	59000 ⁵⁹
TIGUAN		
13-09	4 Cyl. 2.0 Eng. - 23.00 Oz. R-134a; 3.70 Oz. PAG-46; w/ Sanden Compressor	59007
	4 Cyl. 2.0 Eng. - 23.00 Oz. R-134a; 4.70 Oz. PAG-46; w/ Denso Compressor	59007
TOUAREG		
13	6 Cyl. 3.0 Eng.; w/ Rear AC - 32.00 Oz. R-134a; 4.40 Oz. To 5.00 Oz. PAG-46	59007
	6 Cyl. 3.0 Eng.; w/ Rear AC - 39.00 Oz. R-134a; 4.40 Oz. To 5.00 Oz. PAG-46	59007
	6 Cyl. 3.6 Eng.; w/o Rear AC - 32.00 Oz. R-134a; 4.40 Oz. To 5.00 Oz. PAG-46	59007
	6 Cyl. 3.6 Eng.; w/ Rear AC - 39.00 Oz. R-134a; 4.40 Oz. To 5.00 Oz. PAG-46	59007
12	6 Cyl. 3.0 Eng.; w/o Rear AC - 30.00 Oz. R-134a; 6.70 Oz. PAG-46	59007
	6 Cyl. 3.0 Eng.; w/ Rear AC - 39.00 Oz. R-134a; 6.70 Oz. PAG-46	59007
	6 Cyl. 3.0 Eng.; Hybrid - See Under Hood Decal	59889
	6 Cyl. 3.6 Eng.; w/o Rear AC - 27.00 Oz. R-134a; 4.60 Oz. To 5.30 Oz. PAG-46	59007
	6 Cyl. 3.6 Eng.; w/ Rear AC - 39.00 Oz. R-134a; 4.60 Oz. To 5.30 Oz. PAG-46	59007
11	6 Cyl. 3.0 Eng.; w/o Rear AC - 30.00 Oz. R-134a; 6.70 Oz. PAG-46	59007
	6 Cyl. 3.0 Eng.; w/ Rear AC - 39.00 Oz. R-134a; 6.70 Oz. PAG-46	59007
	6 Cyl. 3.0 Eng.; Hybrid - See Under Hood Decal	59889
	6 Cyl. 3.6 Eng.; w/o Rear AC - 25.00 Oz. R-134a; 4.90 Oz. PAG-46	59007
	6 Cyl. 3.6 Eng.; w/ Rear AC - 37.00 Oz. R-134a; 4.70 Oz. PAG-46	59007
10	6 Cyl. 3.0 Eng.; w/o Rear AC - 24-26.00 Oz. R-134a; 4.73 Oz. PAG-46; w/ Denso 7SEU17C Compressor	59007
	6 Cyl. 3.0 Eng.; w/o Rear AC - 24-26.00 Oz. R-134a; 6.70 Oz. PAG-46; w/ Denso 7SEU16C Compressor	59007
	6 Cyl. 3.0 Eng.; w/ Rear AC - 37.00-38.00 Oz. R-134a; 4.73 Oz. PAG-46; w/ Denso 7SEU17C Compressor	59007

Continued on Next Page

⁵⁹ When retrofitting to R134a PAG Oil must be used.

VOLKSWAGEN

Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that A/C system has been properly cleaned, and new accumulator / filter drier has been installed. Specs are for total system capacities. Always refer to under hood decal as the primary source for refrigerant and lubricant information.

Year	Model	Lubricant
TOUAREG (Cont'd)		
10	6 Cyl. 3.0 Eng.; w/ Rear AC - 37.00-38.00 Oz. R-134a; 6.70 Oz. PAG-46; w/ Denso 7SEU16C Compressor	59007
	6 Cyl. 3.6 Eng.; w/o Rear AC - 25.00 Oz. R-134a; 4.90 Oz. PAG-46	59007
09	6 Cyl. 3.6 Eng.; w/ Rear AC - 37.00 Oz. R-134a; 4.40 Oz. PAG-46	59007
	6 Cyl. 3.0 Eng.; w/o Rear AC - 24-26.00 Oz. R-134a; 6.70 Oz. PAG-46; w/ Denso 7SEU16C Compressor	59007
	6 Cyl. 3.0 Eng.; w/o Rear AC - 24-26.00 Oz. R-134a; 6.70 Oz. PAG-46; w/ Denso 7SEU16C Compressor	59007
	6 Cyl. 3.0 Eng.; w/ Rear AC - 37.00-38.00 Oz. R-134a; 4.73 Oz. PAG-46; w/ Denso 7SEU17C Compressor	59007
	6 Cyl. 3.0 Eng.; w/ Rear AC - 37.00-38.00 Oz. R-134a; 6.70 Oz. PAG-46; w/ Denso 7SEU16C Compressor	59007
	6 Cyl. 3.6 Eng.; Dual Zone - 25.00 Oz. R-134a; 4.90 Oz. PAG-46	59007
	6 Cyl. 3.6 Eng.; w/ 4 Zone - 37.00 Oz. R-134a; 8.50 Oz. PAG-46	59007
	8 Cyl. 4.2 Eng.; Dual Zone - 25.00 Oz. R-134a; 4.90 Oz. PAG-46	59007
08-04	8 Cyl. 4.2 Eng.; w/ 4 Zone - 37.00 Oz. R-134a; 8.50 Oz. PAG-46	59007
	All Eng.; w/o Rear AC - 26.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
	All Eng.; w/ Rear AC - 39.00 Oz. R-134a; 10.00 Oz. PAG-46	59007
VANAGON		
91-89	All Eng. - 51.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
88-86	4 Cyl. 2.1 Eng. - 51.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹
85	4 Cyl. 1.9 Eng. - 51.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 ⁵⁹

VOLVO

Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that A/C system has been properly cleaned, and new accumulator / filter drier has been installed. Specs are for total system capacities. Always refer to under hood decal as the primary source for refrigerant and lubricant information.

Year	Model	Lubricant
240 SERIES		
93	All Eng. - 26.50 Oz. R-134a; 7.50 Oz. PAG-46	59007
92-91	All Eng. - 39.00 Oz. R-12; 6.75 Oz. Mineral Oil	59000 ⁵⁹
90-87	All Eng. - 46.00 Oz. R-12; 6.75 Oz. Mineral Oil	59000 ⁵⁹
86	All Eng. - 46.00 Oz. R-12; 10.00 Oz. Mineral Oil; w/ York Compressor	59000 ⁵⁹
	All Eng. - 46.00 Oz. R-12; 6.75 Oz. Mineral Oil; w/ Diesel Kiki Compressor	59000 ⁵⁹
85	4 Cyl. 2.1 Eng. - 38.00 Oz. R-12; 6.75 Oz. Mineral Oil	59000 ⁵⁹
	4 Cyl. 2.3 Eng. - 46.00 Oz. R-12; 10.00 Oz. Mineral Oil	59000 ⁵⁹
260 SERIES		
79-76	6 Cyl. 2.7 Eng. - See Under Hood Decal	59000 ⁵⁹
740 SERIES		
92	All Eng. - 40.00 Oz. R-12; 4.50 Oz. Mineral Oil; w/ SD5 Compressor	59000 ⁵⁹
	All Eng. - 40.00 Oz. R-12; 6.75 Oz. Mineral Oil; w/ Zexel Compressor	59000 ⁵⁹
	All Eng. - 40.00 Oz. R-12; 8.00 Oz. Mineral Oil; w/ SD7 Compressor	59000 ⁵⁹
91	All Eng. - 39.00 Oz. R-12; 4.50 Oz. Mineral Oil; w/ SD5 Compressor	59000 ⁵⁹
	All Eng. - 39.00 Oz. R-12; 6.75 Oz. Mineral Oil; w/ Zexel Compressor	59000 ⁵⁹
	All Eng. - 39.00 Oz. R-12; 8.00 Oz. Mineral Oil; w/ SD7 Compressor	59000 ⁵⁹
90-89	All Eng. - 41.50 Oz. R-12; 10.00 Oz. Mineral Oil; w/ York Compressor	59000 ⁵⁹
	All Eng. - 41.50 Oz. R-12; 4.50 Oz. Mineral Oil; w/ SD5 Compressor	59000 ⁵⁹
	All Eng. - 41.50 Oz. R-12; 4.50 Oz. Mineral Oil; w/ SD7 Compressor	59000 ⁵⁹
	All Eng. - 41.50 Oz. R-12; 6.00 Oz. Mineral Oil; w/ R4 Compressor	59000 ⁵⁹
88-87	All Eng. - 41.50 Oz. R-12; 6.75 Oz. Mineral Oil; w/ Diesel Kiki Compressor	59000 ⁵⁹
	All Eng. - 46.00 Oz. R-12; 6.75 Oz. Mineral Oil	59000 ⁵⁹
86	4 Cyl. 2.3 Eng. - 46.00 Oz. R-12; 10.00 Oz. Mineral Oil; w/ York Compressor	59000 ⁵⁹
	4 Cyl. 2.3 Eng. - 46.00 Oz. R-12; 6.75 Oz. Mineral Oil; w/ Diesel Kiki Compressor	59000 ⁵⁹
	6 Cyl. 2.4 Eng. - 40.00 Oz. R-12; 6.75 Oz. Mineral Oil	59000 ⁵⁹
85	4 Cyl. 2.3 Eng. - 40.00 Oz. R-12; 6.75 Oz. Mineral Oil	59000 ⁵⁹
	6 Cyl. 2.4 Eng. - 40.00 Oz. R-12; 6.75 Oz. Mineral Oil	59000 ⁵⁹
760 SERIES		
90-89	All Eng. - 41.50 Oz. R-12; 10.00 Oz. Mineral Oil; w/ York Compressor	59000 ⁵⁹
	All Eng. - 41.50 Oz. R-12; 4.50 Oz. Mineral Oil; w/ SD5 Compressor	59000 ⁵⁹
	All Eng. - 41.50 Oz. R-12; 4.50 Oz. Mineral Oil; w/ SD7 Compressor	59000 ⁵⁹
	All Eng. - 41.50 Oz. R-12; 6.00 Oz. Mineral Oil; w/ R4 Compressor	59000 ⁵⁹
	All Eng. - 41.50 Oz. R-12; 6.75 Oz. Mineral Oil; w/ Diesel Kiki Compressor	59000 ⁵⁹
88	4 Cyl. 2.3 Eng. - 41.50 Oz. R-12; 6.75 Oz. Mineral Oil	59000 ⁵⁹
	6 Cyl. 2.8 Eng. - 40.00 Oz. R-12; 6.75 Oz. Mineral Oil	59000 ⁵⁹
87-86	4 Cyl. 2.3 Eng. - 40.00 Oz. R-12; 6.75 Oz. Mineral Oil	59000 ⁵⁹
	6 Cyl. 2.8 Eng. - 40.00 Oz. R-12; 6.75 Oz. Mineral Oil	59000 ⁵⁹

Continued on Next Page

⁵⁹ When retrofitting to R134a PAG Oil must be used.

Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that A/C system has been properly cleaned, and new accumulator / filter drier has been installed. Specs are for total system capacities. Always refer to under hood decal as the primary source for refrigerant and lubricant information.

Year	Model	Lubricant
760 SERIES (Cont'd)		
85	4 Cyl. 2.3 Eng. - 40.00 Oz. R-12; 6.75 Oz. Mineral Oil	59000 ⁵⁹
	6 Cyl. 2.4 Eng. - 40.00 Oz. R-12; 6.75 Oz. Mineral Oil	59000 ⁵⁹
	6 Cyl. 2.8 Eng. - 40.00 Oz. R-12; 6.75 Oz. Mineral Oil	59000 ⁵⁹
84	6 Cyl. 2.4 Eng. - See Under Hood Decal	59000 ⁵⁹
780 SERIES		
91	All Eng. - 39.00 Oz. R-12; 4.50 Oz. Mineral Oil; w/ SD5 Compressor	59000 ⁵⁹
	All Eng. - 39.00 Oz. R-12; 6.75 Oz. Mineral Oil; w/ Zexel Compressor	59000 ⁵⁹
90-89	All Eng. - 39.00 Oz. R-12; 8.00 Oz. Mineral Oil; w/ SD7 Compressor	59000 ⁵⁹
	All Eng. - 41.50 Oz. R-12; 10.00 Oz. Mineral Oil; w/ York Compressor	59000 ⁵⁹
	All Eng. - 41.50 Oz. R-12; 4.50 Oz. Mineral Oil; w/ SD5 Compressor	59000 ⁵⁹
	All Eng. - 41.50 Oz. R-12; 4.50 Oz. Mineral Oil; w/ SD7 Compressor	59000 ⁵⁹
	All Eng. - 41.50 Oz. R-12; 6.00 Oz. Mineral Oil; w/ R4 Compressor	59000 ⁵⁹
88-87	All Eng. - 41.50 Oz. R-12; 6.75 Oz. Mineral Oil; w/ Diesel Kiki Compressor	59000 ⁵⁹
	6 Cyl. 2.8 Eng. - 40.00 Oz. R-12; 6.75 Oz. Mineral Oil	59000 ⁵⁹
850 SERIES		
97-96	All Eng. - 32.00 Oz. R-134a; 5.50 Oz. PAG-46; w/ Seiko Seiki Compressor	59002
95-93	All Eng. - 36.00 Oz. R-134a; 6.75 Oz. PAG-100	59002
940 SERIES		
95	All Eng. - 33.50 Oz. R-134a; 4.50 Oz. PAG-100; w/ SD5 Compressor	59002
	All Eng. - 33.50 Oz. R-134a; 7.50 Oz. PAG-100; w/ Seiko Seiki Compressor	59007
	All Eng. - 33.50 Oz. R-134a; 8.00 Oz. PAG-100; w/ SD7 Compressor	59002
94	All Eng. - 33.50 Oz. R-134a; 4.50 Oz. PAG-100; w/ SD5 Compressor	59002
	All Eng. - 33.50 Oz. R-134a; 7.50 Oz. PAG-150; w/ Seiko Seiki Compressor	59002
93	All Eng. - 33.50 Oz. R-134a; 8.00 Oz. PAG-100; w/ SD7 Compressor	59002
	All Eng. - 33.50 Oz. R-134a; 4.50 Oz. PAG-100; w/ SD5 Compressor	59002
	All Eng. - 33.50 Oz. R-134a; 7.50 Oz. PAG-100; w/ Seiko Seiki Compressor	59007
92	All Eng. - 33.50 Oz. R-134a; 8.00 Oz. PAG-100; w/ SD7 Compressor	59002
	4 Cyl. 2.3 Eng. - w/ R-12	59000 ⁵⁹
	All Eng. - 40.00 Oz. R-12; 4.50 Oz. Mineral Oil; w/ SD5 Compressor	59000 ⁵⁹
91	All Eng. - 40.00 Oz. R-12; 6.75 Oz. Mineral Oil; w/ Zexel Compressor	59000 ⁵⁹
	All Eng. - 40.00 Oz. R-12; 8.00 Oz. Mineral Oil; w/ SD7 Compressor	59000 ⁵⁹
	All Eng. - 39.00 Oz. R-12; 4.50 Oz. Mineral Oil; w/ SD5 Compressor	59000 ⁵⁹
91	All Eng. - 39.00 Oz. R-12; 6.75 Oz. Mineral Oil; w/ Zexel Compressor	59000 ⁵⁹
	All Eng. - 39.00 Oz. R-12; 8.00 Oz. Mineral Oil; w/ SD7 Compressor	59000 ⁵⁹
	960 SERIES	
97-96	All Eng. - 32.00 Oz. R-134a; 8.50 Oz. PAG-100; w/ SD7 Compressor	59002
95-93	All Eng. - 32.00 Oz. R-134a; 4.50 Oz. PAG-100; w/ SD5 Compressor	59002
	All Eng. - 32.00 Oz. R-134a; 6.75 Oz. PAG-100; w/ Seiko Seiki Compressor	59007
92	All Eng. - 32.00 Oz. R-134a; 8.00 Oz. PAG-100; w/ SD7 Compressor	59002
	All Eng. - 39.00 Oz. R-12; 4.50 Oz. Mineral Oil; w/ SD5 Compressor	59000 ⁵⁹
	All Eng. - 39.00 Oz. R-12; 6.75 Oz. Mineral Oil; w/ Zexel Compressor	59000 ⁵⁹
	All Eng. - 39.00 Oz. R-12; 8.00 Oz. Mineral Oil; w/ SD7 Compressor	59000 ⁵⁹
C30		
13-08	5 Cyl. 2.5 Eng. - 19.00 Oz. R-134a; 6.76 Oz. PAG-46	59007
C70		
13-08	5 Cyl. 2.5 Eng. - 19.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
06	All Eng. - 19.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
04-02	All Eng. - 35.00 Oz. R-134a; 6.75 Oz. PAG-46	59007
01-98	All Eng. - 29.00 Oz. R-134a; 6.75 Oz. PAG-46	59007
S40		
11	5 Cyl. 2.5 Eng. - 19.00 Oz. R-134a; 6.09 Oz. PAG-46	59007
10-09	5 Cyl. 2.4 Eng. - 19.00 Oz. R-134a; 6.76 Oz. PAG-46	59007
	5 Cyl. 2.5 Eng. - 19.00 Oz. R-134a; 6.09 Oz. PAG-46	59007
08-07	5 Cyl. 2.4 Eng. - 19.00 Oz. R-134a; 6.76 Oz. PAG-46	59007
	5 Cyl. 2.5 Eng. - 19.00 Oz. R-134a; 6.76 Oz. PAG-46	59007
06-05	All Eng. - 19.00 Oz. R-134a; 7.00 Oz. PAG-100	59002
04-01	All Eng. - 30.00 Oz. R-134a; 6.00 Oz. PAG-100	59002
00	All Eng. - 31.00 Oz. R-134a; 6.00 Oz. PAG-100	59002
S60		
11	6 Cyl. 3.0 Eng. - 35.00 Oz. R-134a; See Under Hood Decal	59007
09	5 Cyl. 2.4 Eng. - 35.00 Oz. R-134a; 6.00 Oz. PAG-46	59007
08-07	5 Cyl. 2.5 Eng. - 27.00 Oz. R-134a; See Under Hood Decal	59007
	5 Cyl. 2.4 Eng. - 35.00 Oz. R-134a; 6.00 Oz. PAG-46	59007

Continued on Next Page

⁵⁹ When retrofitting to R134a PAG Oil must be used.

VOLVO

Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that A/C system has been properly cleaned, and new accumulator / filter drier has been installed. Specs are for total system capacities. Always refer to under hood decal as the primary source for refrigerant and lubricant information.

Year	Model	Lubricant
S60 (Cont'd)		
08-07	5 Cyl. 2.5 Eng. - 35.00 Oz. R-134a; 6.00 Oz. PAG-46	59007
06-01	All Eng. - 35.00 Oz. R-134a; 6.00 Oz. PAG-46	59007
S70		
00-98	All Eng. - 29.00 Oz. R-134a; 6.75 Oz. PAG-46	59007
S80		
13-11	6 Cyl. 3.0 Eng. - See Under Hood Decal	59007
	6 Cyl. 3.2 Eng. - See Under Hood Decal	59007
10	6 Cyl. 3.0 Eng. - See Under Hood Decal	59007
	6 Cyl. 3.2 Eng. - See Under Hood Decal	59007
	8 Cyl. 4.4 Eng. - 28.00 Oz. R-134a; 3.70 Oz. PAG-46	59007
09-08	6 Cyl. 3.0 Eng. - See Under Hood Decal	59007
	6 Cyl. 3.2 Eng. - See Under Hood Decal	59007
	8 Cyl. 4.4 Eng. - 25.00 Oz. R-134a; 2.40 Oz. PAG-46	59007
07	6 Cyl. 3.2 Eng. - 21.86 Oz. R-134a; 6.08 Oz. PAG-46	59007
	8 Cyl. 4.4 Eng. - 24.69 Oz. R-134a; 6.08 Oz. PAG-46	59007
06-00	All Eng. - 35.00 Oz. R-134a; 6.75 Oz. PAG-46	59007
99	All Eng. - 35.00 Oz. R-134a; 6.00 Oz. PAG-46	59007
S90		
98	All Eng. - 32.00 Oz. R-134a; 6.75 Oz. PAG-100; w/ Sanden Compressor	59002
	6 Cyl. 2.9 Eng. - 32.00 Oz. R-134a; 6.75 Oz. PAG-46; w/ Zexel Compressor	59007
97	6 Cyl. 2.9 Eng. - 32.00 Oz. R-134a; 6.75 Oz. PAG-100; w/ Sanden Compressor	59002
	6 Cyl. 2.9 Eng. - 32.00 Oz. R-134a; 6.75 Oz. PAG-46; w/ Zexel Compressor	59007
V40		
04-00	All Eng. - 32.00 Oz. R-134a; 6.00 Oz. PAG-46	59007
V50		
11	5 Cyl. 2.5 Eng. - 19.00 Oz. R-134a; 6.76 Oz. PAG-46	59007
10-08	5 Cyl. 2.4 Eng. - 19.00 Oz. R-134a; 6.76 Oz. PAG-46	59007
	5 Cyl. 2.5 Eng. - 19.00 Oz. R-134a; 6.76 Oz. PAG-46	59007
07	5 Cyl. 2.4 Eng. - 19.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
	5 Cyl. 2.5 Eng. - 19.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
06-05	All Eng. - 19.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
V70		
10-08	6 Cyl. 3.2 Eng. - 22.00 Oz. R-134a; 3.70 Oz. PAG-46	59007
07	5 Cyl. 2.4 Eng. - 35.00 Oz. R-134a; 6.75 Oz. PAG-46	59007
	5 Cyl. 2.5 Eng. - 35.00 Oz. R-134a; 6.75 Oz. PAG-46	59007
06-98	All Eng. - 35.00 Oz. R-134a; 6.75 Oz. PAG-46	59007
V90		
98	All Eng. - 32.00 Oz. R-134a; 6.75 Oz. PAG-100	59002
97	6 Cyl. 2.9 Eng. - 32.00 Oz. R-134a; 6.75 Oz. PAG-100	59002
XC60		
13	6 Cyl. 3.0 Eng. - See Under Hood Decal	59007
	6 Cyl. 3.2 Eng. - See Under Hood Decal	59007
12	4 Cyl. 2.0 Eng. - See Under Hood Decal	59007
	6 Cyl. 3.0 Eng. - See Under Hood Decal	59007
	6 Cyl. 3.2 Eng. - See Under Hood Decal	59007
11-10	6 Cyl. 3.0 Eng. - See Under Hood Decal	59007
	6 Cyl. 3.2 Eng. - See Under Hood Decal	59007
XC70		
13-09	6 Cyl. 3.0 Eng. - See Under Hood Decal	59007
	6 Cyl. 3.2 Eng. - See Under Hood Decal	59007
08	6 Cyl. 3.2 Eng. - 45.00 Oz. R-134a; 3.70 Oz. PAG-46	59007
07	5 Cyl. 2.5 Eng. - 46.00 Oz. R-134a; 6.08 Oz. PAG-46	59007
06-03	All Eng. - 35.00 Oz. R-134a; 6.00 Oz. PAG-46	59007
XC90		
13	6 Cyl. 3.2 Eng.; w/o Rear AC - 25.00 Oz. R-134a; 6.70 Oz. PAG-46	59007
	6 Cyl. 3.2 Eng.; w/ Rear AC - 35.00 Oz. R-134a; 6.70 Oz. PAG-46	59007
12	6 Cyl. 3.2 Eng.; w/ Front AC - 22.00 Oz. R-134a; 6.08 Oz. PAG-46	59007
	6 Cyl. 3.2 Eng.; w/ Dual AC - 35.00 Oz. R-134a; 6.08 Oz. PAG-46	59007
11	6 Cyl. 3.2 Eng.; w/ Front AC - 22.00 Oz. R-134a; 6.08 Oz. PAG-46	59007
	6 Cyl. 3.2 Eng.; w/ Dual AC - 35.00 Oz. R-134a; 6.08 Oz. PAG-46	59007
	8 Cyl. 4.4 Eng.; w/o Dual AC - 24.00 Oz. R-134a; 6.08 Oz. PAG-46	59007
	8 Cyl. 4.4 Eng.; w/ Dual AC - 36.00 Oz. R-134a; 6.08 Oz. PAG-46	59007
10-09	6 Cyl. 3.2 Eng.; w/ Front AC - 25.00 Oz. R-134a; 4.40 Oz. PAG-46	59007

Continued on Next Page

Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that A/C system has been properly cleaned, and new accumulator / filter drier has been installed. Specs are for total system capacities. Always refer to under hood decal as the primary source for refrigerant and lubricant information.

Year	Model	Lubricant
XC90 (Cont'd)		
10-09	6 Cyl. 3.2 Eng.; w/ Dual AC - 35.00 Oz. R-134a; 4.40 Oz. PAG-46	59007
	8 Cyl. 4.4 Eng.; w/o Dual AC - 25.00 Oz. R-134a; 4.40 Oz. PAG-46	59007
	8 Cyl. 4.4 Eng.; w/ Dual AC - 37.00 Oz. R-134a; 4.40 Oz. PAG-46	59007
08	6 Cyl. 3.2 Eng.; w/ Front AC - 35.00 Oz. R-134a; 6.10 Oz. PAG-46	59007
	6 Cyl. 3.2 Eng.; w/ Dual AC - 46.00 Oz. R-134a; 6.10 Oz. PAG-46	59007
	8 Cyl. 4.4 Eng.; w/o Dual AC - 35.00 Oz. R-134a; 6.10 Oz. PAG-46	59007
	8 Cyl. 4.4 Eng.; w/ Dual AC - 46.00 Oz. R-134a; 6.10 Oz. PAG-46	59007
07	6 Cyl. 3.2 Eng.; w/ Front AC - 32.20 Oz. R-134a; 6.08 Oz. PAG-46	59007
	6 Cyl. 3.2 Eng.; w/ Dual AC - 32.90 Oz. R-134a; 6.08 Oz. PAG-46	59007
	8 Cyl. 4.4 Eng. - 32.20 Oz. R-134a; 6.08 Oz. PAG-46	59007
06-03	All Eng.; w/o Rear AC - 35.00 Oz. R-134a; 6.00 Oz. PAG-46	59007
	All Eng.; w/ Rear AC - 46.00 Oz. R-134a; 7.00 Oz. PAG-46	59007

Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that A/C system has been properly cleaned, and new accumulator / filter drier has been installed. Specs are for total system capacities. Always refer to under hood decal as the primary source for refrigerant and lubricant information.

Year	Model	Lubricant
GV		
91-89	All Eng. - 32.00 Oz. R-12; 6.00 Oz. Mineral Oil	59000 ⁵⁹
GVX		
89	All Eng. - 32.00 Oz. R-12; 6.00 Oz. Mineral Oil	59000 ⁵⁹

⁵⁹ When retrofitting to R134a PAG Oil must be used.